

Swarm and Evolutionary Computation

Volume 18, October 2014, Pages 38–53



Regular Paper

mNAFSA: A novel approach for optimization in dynamic environments with global changes

Danial Yazdani^a, Babak Nasiri^b, Alireza Sepas-Moghaddam^c, Mohammadreza Meybodi^d, Mohammadreza Akbarzadeh-Totonchi^e

^a Young Researchers and Elite Club, Mashhad Branch, Islamic Azad University, Mashhad, Iran


^b Department of Computer Engineering, Islamic Azad University of Qazvin, Qazvin, Iran

^c Young Researchers and Elite Club, Science and Research Branch, Islamic Azad University, Tehran, Iran

^d Department of IT and Computer Engineering, Amirkabir University of Tehran, Tehran, Iran

^e Department of Computer and Electronic Engineering, Ferdowsi University, Mashhad, Iran

Received 10 January 2013, Revised 30 March 2014, Accepted 21 May 2014, Available online 29 May 2014



Show less

Choose an option to locate/access this article:

Check if you have access
through your login credentials
or your institution

Check access

Purchase

Get Full Text Elsewhere

doi:10.1016/j.swevo.2014.05.002

[Get rights and content](#)

Abstract

Artificial fish swarm algorithm (AFSA) is one of the state-of-the-art swarm intelligence algorithms that is widely used for optimization purposes in static environments. However, numerous real-world problems are dynamic and uncertain, which could not be solved using static approaches. The contribution of this paper is twofold. First, a novel AFSA algorithm, so called NAFSA, has been proposed in order to eliminate weak points of standard AFSA and increase convergence speed of the algorithm. Second, a multi-swarm algorithm based on NAFSA (mNAFSA) was presented to conquer particular challenges of dynamic environment by proposing several novel mechanisms including particularly modified multi-swarm mechanism for finding and covering potential optimum peaks and diversity increase mechanism which is applied after detecting an environment change. The proposed approaches have been evaluated on moving peak benchmark, which is the most prominent benchmark in this domain. This benchmark involves several parameters in order to simulate different configurations of dynamic environments. Extensive experiments show that the proposed algorithm significantly outperforms previous algorithms in most of the tested dynamic environments modeled by moving peaks benchmark.

Keywords

Artificial fish swarm algorithm; Swarm intelligence; Optimization in dynamic environments; Moving peak benchmark; Evolutionary algorithms; Meta-heuristic algorithms

Corresponding author. Tel.: +98 935 1185556.

Copyright © 2014 Elsevier B.V. All rights reserved.