Use Case: Forget Password

Iteration: 1

Primary Actor: User

Goal in Context: Allow users that have forgotten their passwords to reset their account password. Users must be able to prove they own and are authenticated into the account, by entering details that were used when signing up. This can include but not limited to: Name, location of account creation, security questions, and the pertaining username of the account.

Preconditions:

1. User must have an account in the database to recover
2. User must be authenticated to recover the password, be the original owner and have full access to their data
3. Users must have relevant details which are needed to authenticate if the owner of the account is the individual attempting to recover the password.
4. Reset password meets the criteria, and is valid to be renewed for the account that is being recovered.
5. All details of the account must not change during password recovery, which may create conflicts when verifying data.

Trigger:

1. **Signing Up**: User has entered a name and username that already exists on the database, user is redirected to forget-password to recover their account.
2. **Login:** Users cannot authenticate into their account and must recover their account by correctly entering partial details.

Scenario:

1. User executes the program using the integrated development environment or through an executable.
2. User selects login option from the landing page
    a. User cannot login to their account and enters the forget-password option
    b. User enters the name, username, and necessary details to recovery account (note based on account familiarity)
3. User selects signup and enters an username that exists on the database

a. User enters the name, username, and necessary details to recovery account (note based on account familiarity)