Use Case: Login

Iteration: 1

Primary Actor: User

Goal in Context: Allows the user to create a profile that enables customer customization, save states, and personalized experience within the program. Login will take a username and password, which will be authenticated on a server and verified, before allowing the user to login. Enables quick access to game library and leaderboard stats that otherwise would not be saved/accessible.

Preconditions:

1. Users must have previously created a unique username and password before attempting to login.
2. User attempts to login with a valid username and password which they are authenticated to/own.
3. User has correctly entered the unique username and password that pertains to them.
4. If a user is unable to login into their existing account, they utilize the forget-password function [see use case].
5. Username and password is entered using an input device that enables full compatibility.

Trigger: User enters an unique username and password into the required text fields before proceeding to the landing page.

Scenario:

1. User executes the program using the integrated development environment or through an executable.
2. User selects login option from the landing page
3. User enters their unique username and password in the correct text fields, user proceeds to login
4. User is authenticated and proceeds to the player profile.

Post Conditions:

1. User is logged into their selected player profile
2. User is able to personalize their experience through the program tools
3. Users are able access the game library and save their progress/stats.
4. Users are able to see the leaderboards and their rankings, which are tied to their unique username and saved states.

Exceptions:

1. User is not able to login into their account, and must be redirected to the forget-password page [see use case]
2. User does not fill text fields for username and password, and/or uses incompatible characters, the program will prompt the user to retry.
3. Network may be timed out through multiple attempts at password verification, the user must restart the program and retry.

Priority: High, cannot access other features without logging in.

When available: First-second iteration

Frequency of Use: Once during the program lifecycle, unless requiring a restart.

Channel to Actor: Program landing page.

Secondary Actor: None.

Channel to Secondary Actor: N/A

Open Issues:

1. Need to address password attempting in a way that limits unauthorized access to the system, while allowing enough attempts for user convenience
2. Allow the password-forget option to appear when the username is valid, otherwise the user cannot tell if the username is correct.
3. Before the username and the password are authenticated, must make sure that the text fields are filled in to let the user know the mistakes in their entry.