Use case: Resign Game

iteration: 1

primary actor: Player

Goal in context: The player resigns, resulting in a loss and concluding the game.

Precondition: The player is currently in an active game.

Trigger: The player wishes to conclude the game immediately.

Scenario:
1. Player wishes to end the current game
2. Player pressed the resign game button
3. game ends and player loses

Post conditions: The game ends and the player loses

Exceptions:
1. The resignation button malfunctions
2. network issue or player disconnects prior to resigning
3. player attempts to end game after game has already ended

Priority: High

When available: 1 iteration

Frequency of use: infrequent - Expected when players want to end the game prematurely and lose.

Channel to actor: Player's finger has physical interaction with the resign game button

Open issues:

- **How to handle user misinput:** Should we consider adding a confirmation pop-up to avoid unintended resignations?

Use case: Choose a Side

iteration: 1

primary actor: Player

Goal in context: The player chooses a side.

Precondition: The player started a game.

Trigger: The player starts a game and wants to pick a side.

Scenario:

4. Player starts a game
5. player selects colour or shape from available colours or shapes
6. game begins and other player moves

Post conditions: The game begins and other player moves

Exceptions:

1. The colour or shape malfunctions
2. The game times out

Priority: High

When available: 1 iteration

Frequency of use: Frequent - Every time a new game is started

Channel to actor: Player's finger has physical interaction with the screen to select their side

Open issues:

- First move advantage: How can we ensure an equal share of first moves after players choose their sides?