Use Case: Tic Tac Toe Home Menu

Iteration: 1

Primary Actor: Player

Goal In Context: Player wants to access Tic Tac Toe options from their profile menu (such as joining a game queue or viewing the leaderboard.

Preconditions: Player is logged into the system and is currently on the Player Profile Home Menu.

Trigger: The player selects Tic Tac Toe from the main profile menu.

Scenario:

- The player clicks on the "Tic Tac Toe" button from the Player Profile Home Menu
- The Tic Tac Toe Home Menu is visible and shows options to join a game, view the leaderboard or return to the home menu.

Post Conditions: The player returns to the Tic Tac Toe Home Menu.

Exceptions:

- If an error occurs, the player receives the message "Returning back to home. Please try again later." and is sent back to the Player Profile Home Menu.

Priority: High

When Available: After the player is logged in and is on the Player Profile Home Menu.

Frequency of Use: Frequently.

Channel to Actor: Web interface.

Use Case: Tic Tac Toe Game Queue

Iteration: 1

Primary Actor: Player

Goal In Context: Player looks for an opponent to play against on Tic Tac Toe.

Preconditions: The player is on the Tic Tac Toe Home Menu.

Trigger: The player clicks on “Join Queue” from the Tic Tac Toe Home Menu.

Scenario:

- The player selects “Join Queue”
- The system searches for an available opponent.
- If a match is found, the player is taken to the game instance.
- If no match is found, the player receives a “No match found” message and can try again or return to the home menu.

Post Conditions: The player is either in a Tic Tac Toe game or redirected back to the home menu if no match is found.

Exceptions:

- If an error occurs, player is notified and returned to the Menu.

Priority: High

When Available: Anytime the player is on Home Menu.

Frequency of Use: Frequently.

Channel to Actor: User Interface.