Use Case: Launch Program

Iteration: 1

Primary Actor: User

Goal in Context: Executes the program for the user, opens up the framework for the user to access the profile. This use case will set up and allocate all necessary data and utilities to enable full functionality for the user. Necessary checks will be done to analyze all requirements before launching the program, otherwise will alert the user for any exceptions that may occur within the system.

Preconditions:

1. Users must have necessary files to be able to access the program, either by running the program through an integrated development environment, or through an executable.
2. Users must have an input medium such as a physical or virtual keyboard to be able to interact and enter necessary details.
3. Users must have an output medium such a monitor or screen to be able to see results created by the program.
4. Users must have a running machine, that means program requirements. **[Will be updated as the program is developed and published].**
5. Users must not change the contents of files, unless told otherwise by system prompts.
6. Users must make sure the machine is connected to the necessary connections, i.e. hosted network.

Trigger: Using an input medium the user launches the program either by running it through the integrated development environment, or through an executable.

Scenario:

1. Users download the necessary files through a verified shared domain platform (Gitlab or other sharing website).
2. Users read the README content to familiarize themselves with the program and its various functionality.
3. User ensures the current machine has met the specifications as laid out in the introduction documentation.

4. User launches the program either by running it through the integrated development environment at the program file location, or through an executable.
5. User successfully launches the program and is greeted by the launching page which will carry forward the user experience.

Post Conditions:

1. Users have allocated the necessary resources and connections to enable a full experience, from which they can browse games and see their profile.
2. User is greeted by the login/sign up page.
3. Users are able to close the program if chosen, and states are saved.

Exceptions:

1. User has not downloaded the necessary files to enable them full access to the program, and thus is unable to proceed. Program will terminate and deallocate any resources and connections hosted.
2. User has launched the program, but does not have the input device to continue further. Users may connect to an input device, or restart the program with an appropriate input device.
3. Users cannot execute the files because system requirements are not met, the program will not execute and alert users.
4. User has corrupt or missing files, the program will terminate or will fetch resources online when possible.

Priority: High, cannot access other features without being able to execute a program.

When available: First-second iteration

Frequency of Use: Once during the program lifecycle, unless requiring a restart.

Channel to Actor: Executable or through program files executed in an integrated development environment.

Secondary Actor: None.

Channel to Secondary Actor: N/A

Open Issues:

1. Verifying the files that the user has requires system privileges, which need to be considered carefully as to not impede on the user's privacy and security.
2. Program may require an update, and version mismatch can prevent the user from executing the program, and need to consider ways of devising version control.
3. Program may need logging of system prompts to track any issues that user may be experiencing, and potentially setting up an error code system.
4. If the correct files are not downloaded, the program may not execute to the initial state to alert users that files are corrupted, how can the system alert users without relying on the initial program startup.
5. New executing errors may arise, needing to enable a functionality so that users are able to (by permission) send error reports for code improvement.