Use Case: Establish connection

Iteration: 1

Primary Actor: Player

Goal in Context: To establish a secure and stable connection with the network to access game services

Preconditions: Player has launched the game, Network Services are online and available

Trigger: Player initiates a connection attempt when starting the game

Scenario:

1. Player launches the game and reaches the main menu
2. Player selects an option that requires an online connection (all three of our games need it)
3. `NetworkManager` receives the player's request to connect
4. `NetworkManager` verifies player credentials and initiates a secure session (token? authentication method?)
5. `NetworkManager` checks the network quality and stable connection
6. Player is now connected to the network

Post Conditions: Player is successfully connected and ready to access online features (leaderboard, SBMM, chat)

Exceptions: Network is down and unavailable. Connection timeout: the network takes too long to respond.Poor connection quality.

Priority: High

When Available: 2nd iteration

Frequency of use: Every time a player initiates a connection or re-connects

Channel to Actor: GUI

Secondary Actor: Network (mostly `NetworkManager`)

Channels to Secondary Actor: Stub? (realistically an API call)

Open Issues: Say a player keeps having to reconnect, should there be a timer to stage intervals?

Use Case: Send Message

Iteration: 1

Actor: Player

Goal in Context: To allow a player to send a message to their opponent during a game session

Preconditions: Both players are connected to the same game session chat functionality is enabled for the game session

Trigger: Player initiates a message by typing into the in-game chat interface

Scenario:

1. Player opens the in-game chat interface
2. Player types a message in a text input box
3. Players send their message by clicking the "Send" button or pressing "Enter" on their keyboard.
4. `Network Manager` receives the message and forwards it to `ChatManager.`
5. `ChatManager` routes the message to the opponent
6. The message appears in the opponent's chat interface

Post Conditions: The message is received and displayed in the opponent's chat interface/window both players can see the updated chat log with the new message

Exceptions: A player disconnecting while in the process of sending their message. Network failure. Message blocking (inappropriate language).

Priority: High

When Available: 2nd iteration

Frequency of use: It varies as it depends on a player's communication preferences

Channel to Actor: In-game chat interface/window

Secondary Actor: Network - `NetworkManager` and `ChatManager`

Channels to Secondary Actor: N/A

Open Issues: Filtering chat which can be a long and heavy process

Use Case: Queue Entry

Iteration: 1

Actor: Player

Goal in Context: To allow a player to enter a matchmaking queue and wait for a compatible opponent to begin a game session

Preconditions: Both players are connected to the network. Matchmaking services are active and available

Trigger: Player selects an option to queue up matchmaking

Scenario:

1. Player navigates to the three different games they want to play in the GUI
2. Player chooses a game by selecting one
3. Player chooses to join matchmaking queue by clicking "find game" button in the GUI
4. `NetworkManager` sends a request to `MatchmakingService` to add the player to the queue
5. `MatchmakingService` places the player in a queue and begins searching for the right opponent based on SBMM criteria
6. Player receives a notification/status update to notify that they have found an opponent
7. The player is transitioned to the game session with their matched opponent

Post Conditions: Player is currently in an active match with their opponent or still remains in the queue if no match is available

Exceptions: Network failure. Timeout connection - if a player can't find a match within a certain amount of time. One of the players disconnects or leaves the matchmaking queue. Too many players in the matchmaking queue - a capacity limit

Priority: High

When Available: 2nd iteration

Frequency of use: Frequent as our games are all based on multiplayer

Channel to Actor: GUI interface

Secondary Actor: Network - `MatchmakingService`

Channels to Secondary Actor: Stub (API if we're being serious) calls and notifies from `NetworkManager` to `MatchmakingService`

Open Issues: We should define a time limit when waiting in queue before a timeout

Use Case: Status Update

Actor: Player

Goal in Context: To provide a player with updates regarding their current status within the game. For example, connection quality and matchmaking queue position

Preconditions: player is connected to the network and using the network features - SBMM, game chat, etc... `NetworkManager` or `MatchmakingService` is actively tracking player status

Trigger: A change in a player's status or an update from the network that needs to be communicated to the player

Scenario:

1. Player initiates an action that requires a status update - entering matchmaking queue or sending a message
2. `NetworkManager` detects a change in the payer's current activity - moving up a spot in matchmaking queue
3. `NetworkManager` sends a status update to the player's GUI/interface regarding their current activity - estimated wait time, current queue position, network status etc...
4. Player receives and views the update on their screen
5. Player may adjust their actions - exit queue if it's taking too long, latency issues / connection status

Post Conditions: The player is aware of their current status and makes a decision or not based on the updated information

Exceptions: Network failure. A player may disconnect before the status update is

received. Network latency might cause delay to status updates - potentially giving outdated or slow feedback.

Priority: Medium - it gives a nice experience for the players to know what their status is, but not as important as gameplay functionality

When Available: 3rd iteration

Frequency of use: It varies as it'll be based on network events or player actions

Channel to Actor: GUI - notification or a status window

Secondary Actor: Network - `NetworkManager` and `MatchmakingService`

Channels to Secondary Actor: Stub (API) calls for status changes

Open Issues: We have to determine which relevant statuses to update the player on the frequency and method of update delivery

Use Case: Game Move

Iteration: 1

Primary Actor: Player

Goal in Context: Enables the user to execute their move in the game and also maintains the proper game state synchronization between the two players.

Preconditions:

Player is matched with their suitable opponent.

The game starts and it is the player's turn to make their move.

The game state is properly synchronized and reflects the same at the other end on the player's side. Both the players are active and there is no disruption of connection between them.

Trigger: Player registers their move in the game and plays the turn.

Scenario:

1. The player has started the game
2. The game notifies the player it's their turn and is waiting for the player's move.
3. Player plays their and register's its move.

4. The system then checks if the move made was valid or not.
5. After the check is done, the move is then registered and made visible to both the players. The game state is updated and synchronized properly.

Postconditions:

The game state is updated and maintained

After the move:

If the move made by the player results in a win/loss/draw, the game is over and the state is updated accordingly.

Otherwise the turn then shifts to the opponent.

Exceptions:

Invalid/Not accepted move is played.

Delay in response thereby affecting the game state and synchronization.

Either of the players gets disconnected while playing their move.

Priority: High

When Available: 3rd Iteration

Frequency of Use: Very frequent (as this will allow the users to play eventually)

Channel to actor: Player plays the game with just simple mouse clicks/keys as per the game functionality.

Use Case: End game

Iteration: 1

Primary Actor: Network

Goal in Context: Terminates a game session, whenever a winning move is played thereby resulting the game to end and then notifies both the players about the results.

Preconditions:

Both the players are in an active game session.

Either of the players have played a winning move resulting in game termination.

Either of the players have played a move that resulted in a draw, the game also terminates in that case and notifies the player.

Either of the players have forfeited. A forfeit will terminate the game and the player who forfeited will automatically lose.

Trigger: The system detects that either of the players has played a winning/losing/drawing move.

Scenario:

1. The system receives the last move from the player.
2. The move is then verified and checked.
3. The game state is updated and synchronized for both the players.
4. The system then does all the calculations and detects that it is a winning move played by either of the players.
5. The system then displays the game results to both the players and indicates that the game is over. The system then updates the leaderboard as per the game results and player's stats.

Postconditions:

The game session is terminated properly.

Player rankings are updated accordingly in the leaderboard after every game played.

Exceptions:

Connection disruption may occur due to which even after playing a winning move, the system couldn't detect that and the game doesn't end.

The move played that wasn't checked properly might also lead to end the game abruptly.

The game stats for the players weren't updated properly.

Priority: High

When Available: 3rd Iteration

Frequency of Use: Very frequent (after every game session)

Channel to actor: The system coordinates the game ending process automatically after it detects the move played.

Use Case: View Leaderboard

Iteration: 1

Primary Actor: Player

Goal in Context: Allows players to check the leaderboard in order to view their current standings and rankings for other players.

Preconditions:

- The player is logged in and has played a sufficient number of games in order to be visible on the leaderboard.

- Leaderboard is available to retrieve the rankings for all players as per their gaming history and stats.

Trigger: Whenever the player requests to view the leaderboard.

Scenario:

1. The player has finished their game session.
2. The player then requests to view the leaderboard.
3. The request is received by the system and thereby it fetches all the current top rankings from the database.
4. The GUI interface receives the requested data and displays it as a leaderboard.
5. The players therefore can then view their current standings and compare it with their opponents too.

Postconditions:

- The player is able to successfully retrieve the leaderboard data and view their rankings. The rankings calculated are correct and that it was updated as per the latest game played by the player.

Exceptions:

- There was a disruption in connection which caused miscalculation in rankings thereby the ranking displayed was incorrect.
- The leaderboard rankings were not updated after each game played.

Priority: High

When Available: 3rd iteration

Frequency of Use: Quite a few sometimes.(Depends on the player)

Channel to actor: Player interacts with the GUI just normally using the mouse in order to navigate and view the leaderboard.

Use Case: Initialize Connection

Iteration: 1

Primary Actor: Network

Goal in Context: Establish the connection between the player and the server, which allows for access to matchmaking and chat services

Preconditions: The application has been launched and the network manager is ready to accept connections

Trigger: The player starts the connection by logging in to the application

Scenario:

1. Player requests a connection to the network by trying to log in
2. NetworkManager verifies the players log in information
3. If successful NetworkManager creates a connection for the player
4. Player is notified that the connection was successful, and now has access to online services

Post Conditions:

- There is a stable connection between the network and the player

Exceptions:

- UserID or password is incorrect

- NetworkManager fails to establish a connection

Priority: Essential

When Available: 1st Iteration

Frequency of Use: Very high

Channel to Actor: User interface, network connection

Use Case: Maintain Connection

Iteration: 1

Primary Actor: Network

Goal in Context: Ensure the connection between the player and the server remains active and stable for access to online services

Preconditions:

- The player has initially connected to the network successfully
- NetworkManager is actively monitoring the connection

Trigger: The player is actively using the online services within the application

Scenario:

1. Player successfully initiates a connection
2. NetworkManager periodically checks the status of the connection
3. If the connection is stable, NetworkManager continues communication between the player and the network
4. If the connection is unstable NetworkManager attempts to reestablish a stable connection
5. Player will receive a notification if their connection experiences any issues

Post Conditions:

- The connection remains active and stable

Exceptions:

- Connection is completely lost
- Reconnection fails after several attempts to reconnect

Priority: Essential

When Available: 1st iteration

Frequency of Use: Very high

Channel to Actor: User interface, network connection, connection notifications

Use Case: Manage Network

Iteration: 1

Primary Actor: Network

Goal in Context: To Ensure that all connections are being managed. Which includes initialization, maintenance, and termination of player connections to maintain a stable connection to the network

Preconditions:

- The servers are active, and NetworkManager is functioning
- Online services (Matchmaking, chat, game sessions) are enabled, and accessible to players

Trigger: The player initiates any kind of network activity

Scenario:

1. The NetworkManager is active and listening for network requests from players
2. A request is received and NetworkManager checks for network availability
3. NetworkManager fulfills the players request
4. NetworkManager continues to monitor for requests and routing to different services

Post Conditions:

- All active connections are monitored, maintained, and closed as needed
- Network resources are efficiently allocated and released
- Players experience minimal interruptions in their connection to network services

Exceptions:

- NetworkManager fails to establish a connection insufficient resources
- NetworkManager encounters unexpected latency during an active session
- Disconnection occurs due to a network error

Priority: Essential

When Available: 1st iteration

Frequency of Use: Very high

Channel to Actor: Network connection, server logs, graphical interface

Use Case: Session Timeout/Inactive

Iteration: 2

Primary Actor: Network

Goal in Context: End inactive sessions to free up network resources

Preconditions:

- The player is connected to the network and their session has been idle for 10 minutes

- NetworkManager is functioning

Trigger: The current players session has been idle (no activity) for 10 minutes

Scenario:

1. A players session has been idle for 10 minutes
2. An inactivity warning is displayed to the player
3. If the player remains inactive NetworkManager terminates their session
4. A notification that their session has been terminated is displayed to the player

Post Conditions:

- Player status is updated to offline

Exceptions:

- Player resumes activity during the warning period, cancelling the timeout.

- NetworkManager fails to terminate the session due to a network error.

Priority: Medium

When Available: 2nd iteration

Frequency of Use: Low to medium

Channel to actor: Graphical interface and server logs

Use Case: Accept Match

Iteration: 1

Primary Actor: Player

Goal in Context: Allows players to accept the match found by the matchmaking service based on rankings of the players and start their game.

Preconditions:

- Player has started the game and is already in the queue for matchmaking.
- The matchmaking service finds a suitable opponent for the player.
- No disruption of connection between the player and the game.

Trigger: Player is notified about the suitable match found and is then selects the option to Accept the match.

Scenario:

1. The player is on the queue for matchmaking.
2. The matchmaking service finds a suitable opponent for the player.
3. The system notifies the player about the match found and displays the ranking and stats for the opponent.
4. The system then prompts the player if the player wants to accept the match or not.
5. If both the players accept their respective matches then, a game session is created and both the players are transitioned to the game screen.

Post Conditions:

- Both the players start their game session.

Exceptions:

- The matchmaking times out before the player accepts it.

- There's a network connection disruption and the players get disconnected.

- The opponent rejects the match.

Priority: High as this will actually start the game.

When Available: 3rd iteration

Frequency of Use: Very frequent depending on the number of players in queue.

Channel to actor: The player interacts by just clicking on the accept button with the mouse.

Use Case: Reject Match

Iteration: 1

Primary Actor: Player

Goal in Context: Allows players to reject the match found by the matchmaking service based on rankings of the players and start their game.

Preconditions:

- Player has started the game and is already in the queue for matchmaking.

- The matchmaking service finds a suitable opponent for the player.

- No disruption of connection between the player and the game.

Trigger: Player is notified about the suitable match found and then selects the option to reject the match.

Scenario:

1. The player is on the queue for matchmaking.
2. The matchmaking service finds a suitable opponent for the player.
3. The system notifies the player about the match found and displays the ranking and stats for the opponent.
4. The system then prompts the player if the player wants to accept the match or not.

5. If both the players reject their respective matches then, no game session is created and both the players return back to the matchmaking queue.

Post Conditions:

- No game session is created.

- Both the players are notified about the same and they both return back to the matchmaking queue.

Exceptions:

- There’s a network connection disruption and the players get disconnected.

- The system fails to detect match rejection by the player and starts the game instead.

Priority: High

When Available: 3rd iteration

Frequency of Use: Very frequent depending on the number of players in queue.

Channel to actor: The player interacts by just clicking on the reject button with the mouse.