

# Genetic Programming

## Chapter 6

A.E. Eiben and J.E. Smith, Introduction to Evolutionary Computing  
Genetic Programming

### GP quick overview

- Developed: USA in the 1990's
- Early names: J. Koza
- Typically applied to:
  - machine learning tasks (prediction, classification...)
- Attributed features:
  - competes with neural nets and alike
  - needs huge populations (thousands)
  - slow
- Special:
  - non-linear chromosomes: trees, graphs
  - mutation possible but not necessary (disputed!)

A.E. Eiben and J.E. Smith, Introduction to Evolutionary Computing  
Genetic Programming

### GP technical summary tableau

Representation	Tree structures
Recombination	Exchange of subtrees
Mutation	Random change in trees
Parent selection	Fitness proportional
Survivor selection	Generational replacement

A.E. Eiben and J.E. Smith, Introduction to Evolutionary Computing  
Genetic Programming

### Introductory example: credit scoring

- Bank wants to distinguish good from bad loan applicants
- Model needed that matches historical data


ID	No of children	Salary	Marital status	OK?
ID-1	2	45000	Married	0
ID-2	0	30000	Single	1
ID-3	1	40000	Divorced	1
...				

## Introductory example: credit scoring

- A possible model:  
IF (NOC = 2) AND (S > 80000) THEN good ELSE bad
- In general:  
IF formula THEN good ELSE bad
- Only unknown is the right formula, hence
- Our search space (phenotypes) is the set of formulas
- Natural fitness of a formula: percentage of well classified cases of the model it stands for
- Natural representation of formulas (genotypes) is: parse trees

## Introductory example: credit scoring

IF (NOC = 2) AND (S > 80000) THEN good ELSE bad  
can be represented by the following tree




## Tree based representation

- Trees are a universal form, e.g. consider
- Arithmetic formula  $2 \cdot \pi + \left( (x+3) - \frac{y}{5+1} \right)$
- Logical formula  $(x \wedge \text{true}) \rightarrow ((x \vee y) \vee (z \leftrightarrow (x \wedge y)))$
- Program
 

```


i = 1;
while (i < 20)
{
    i = i + 1
}
      
```

## Tree based representation




$$2 \cdot \pi + \left( (x+3) - \frac{y}{5+1} \right)$$

## Tree based representation



## Tree based representation



## Tree based representation

- In GA, ES, EP chromosomes are linear structures (bit strings, integer string, real-valued vectors, permutations)
- Tree shaped chromosomes are non-linear structures
- In GA, ES, EP the size of the chromosomes is fixed
- Trees in GP may vary in depth and width


## Tree based representation

- Symbolic expressions can be defined by
  - Terminal set  $T$
  - Function set  $F$  (with the arities of function symbols)
- Adopting the following general recursive definition:
  1. Every  $t \in T$  is a correct expression
  2.  $f(e_1, \dots, e_n)$  is a correct expression if  $f \in F$ ,  $\text{arity}(f)=n$  and  $e_1, \dots, e_n$  are correct expressions
  3. There are no other forms of correct expressions
- In general, expressions in GP are not typed (closure property: any  $f \in F$  can take any  $g \in F$  as argument)

## Offspring creation scheme


Compare

- GA scheme using crossover AND mutation sequentially (be it probabilistically)
- GP scheme using crossover OR mutation (chosen probabilistically)



## Mutation

- Most common mutation: replace randomly chosen subtree by randomly generated tree




## Mutation cont'd

- Mutation has two parameters:
  - Probability  $p_m$  to choose mutation vs. recombination
  - Probability to choose an internal point as the root of the subtree to be replaced
- Remarkably  $p_m$  is advised to be 0 (Koza'92) or very small, like 0.05 (Banzhaf et al. '98)
- The size of the child can exceed the size of the parent

## Recombination

- Most common recombination: exchange two randomly chosen subtrees among the parents
- Recombination has two parameters:
  - Probability  $p_c$  to choose recombination vs. mutation
  - Probability to choose an internal point within each parent as crossover point
- The size of offspring can exceed that of the parents



## Selection

- Parent selection typically fitness proportionate
- Over-selection in very large populations
  - rank population by fitness and divide it into two groups:
  - group 1: best  $x\%$  of population, group 2 other  $(100-x)\%$
  - 80% of selection operations chooses from group 1, 20% from group 2
  - for pop. size = 1000, 2000, 4000, 8000  $x = 32\%, 16\%, 8\%, 4\%$
  - motivation: to increase efficiency, %'s come from rule of thumb
- Survivor selection:
  - Typical: generational scheme (thus none)
  - Recently steady-state (keep part of parent pool) is becoming popular for its elitism

## Initialisation

- Maximum initial depth of trees  $D_{max}$  is set
- Full method (each branch has depth  $= D_{max}$ ):
  - nodes at depth  $d < D_{max}$  randomly chosen from function set  $F$
  - nodes at depth  $d = D_{max}$  randomly chosen from terminal set  $T$
- Grow method (each branch has depth  $\leq D_{max}$ ):
  - nodes at depth  $d < D_{max}$  randomly chosen from  $F \cup T$
  - nodes at depth  $d = D_{max}$  randomly chosen from  $T$
- Common GP initialisation: ramped half-and-half, where grow & full method each deliver half of initial population

## Bloat

- Bloat = “survival of the fattest”, i.e., the tree sizes in the population are increasing over time
- Ongoing research and debate about the reasons
- Needs countermeasures, e.g.
  - Prohibiting variation operators that would deliver “too big” children
  - Parsimony pressure: penalty for being oversized

## Problems involving “physical” environments

- Trees for data fitting vs. trees (programs) that are “really” executable
- Execution can change the environment → the calculation of fitness
- Example: robot controller
- Fitness calculations mostly by simulation, ranging from expensive to extremely expensive (in time)
- But evolved controllers are often to very good

## Example application: symbolic regression

- Given some points in  $\mathbf{R}^2$ ,  $(x_1, y_1), \dots, (x_n, y_n)$
- Find function  $f(x)$  s.t.  $\forall i = 1, \dots, n : f(x_i) = y_i$
- Possible GP solution:
  - Representation by  $F = \{+, -, /, \sin, \cos\}$ ,  $T = \mathbf{R} \cup \{x\}$
  - Fitness is the error  $err(f) = \sum_{i=1}^n (f(x_i) - y_i)^2$
  - All operators standard
  - pop.size = 1000, ramped half-half initialisation
  - Termination: n “hits” or 50000 fitness evaluations reached (where “hit” is if  $|f(x_i) - y_i| < 0.0001$ )

## Discussion

Is GP:

The art of evolving computer programs ?

Means to automated programming of computers?

GA with another representation?