```
No.        Time         Source               Destination           Protocol Length Info
     1 0.000000     Dell 5b:b4:3b        Broadcast             ARP      42      Gratuitous ARP for 192

Frame 1: 42 bytes on wire (336 bits), 42 bytes captured (336 bits)
    WTAP ENCAP: 1
    Arrival Time: Jan  5, 2009 21:36:06.407900000 ora solare Europa occidentale
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1231187766.407900000 seconds
    [Time delta from previous captured frame: 0.000000000 seconds]
    [Time delta from previous displayed frame: 0.000000000 seconds]
    [Time since reference or first frame: 0.000000000 seconds]
    Frame Number: 1
    Frame Length: 42 bytes (336 bits)
    Capture Length: 42 bytes (336 bits)
    [Frame is marked: True]
    [Frame is ignored: False]
    [Protocols in frame: eth:arp]
    [Coloring Rule Name: ARP]
    [Coloring Rule String: arp]
Ethernet II, Src: Dell 5b:b4:3b (00:15:c5:5b:b4:3b), Dst: Broadcast (ff:ff:ff:ff:ff:ff)
    Destination: Broadcast (ff:ff:ff:ff:ff:ff)
        Address: Broadcast (ff:ff:ff:ff:ff:ff)
        .... ..1. .... .... .... .... = LG bit: Locally administered address (this is NOT the factory
        .... ...1 .... .... .... .... = IG bit: Group address (multicast/broadcast)
    Source: Dell 5b:b4:3b (00:15:c5:5b:b4:3b)
        Address: Dell 5b:b4:3b (00:15:c5:5b:b4:3b)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: ARP (0x0806)
Address Resolution Protocol (request/gratuitous ARP)
    Hardware type: Ethernet (1)
    Protocol type: IP (0x0800)
    Hardware size: 6
    Protocol size: 4
    Opcode: request (1)
    [Is gratuitous: True]
    Sender MAC address: Dell 5b:b4:3b (00:15:c5:5b:b4:3b)
    Sender IP address: 192.168.1.2 (192.168.1.2)
    Target MAC address: 00:00:00 00:00:00 (00:00:00:00:00:00)
    Target IP address: 192.168.1.2 (192.168.1.2)

No.        Time         Source               Destination           Protocol Length Info
     2 1.078970     Dell 5b:b4:3b        Broadcast             ARP      42      Who has 192.168.1.1?

Frame 2: 42 bytes on wire (336 bits), 42 bytes captured (336 bits)
    WTAP ENCAP: 1
    Arrival Time: Jan  5, 2009 21:36:07.486870000 ora solare Europa occidentale
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1231187767.486870000 seconds
    [Time delta from previous captured frame: 1.078970000 seconds]
    [Time delta from previous displayed frame: 1.078970000 seconds]
    [Time since reference or first frame: 1.078970000 seconds]
    Frame Number: 2
    Frame Length: 42 bytes (336 bits)
    Capture Length: 42 bytes (336 bits)
    [Frame is marked: True]
    [Frame is ignored: False]
    [Protocols in frame: eth:arp]
    [Coloring Rule Name: ARP]
    [Coloring Rule String: arp]
Ethernet II, Src: Dell_5b:b4:3b (00:15:c5:5b:b4:3b), Dst: Broadcast (ff:ff:ff:ff:ff:ff)
    Destination: Broadcast (ff:ff:ff:ff:ff:ff)
        Address: Broadcast (ff:ff:ff:ff:ff:ff)
        .... ..1. .... .... .... .... = LG bit: Locally administered address (this is NOT the factory
        .... ...1 .... .... .... .... = IG bit: Group address (multicast/broadcast)
    Source: Dell_5b:b4:3b (00:15:c5:5b:b4:3b)
```

```
          Address: Dell 5b:b4:3b (00:15:c5:5b:b4:3b)
          .... ..0. .... .... .... .... .... = LG bit: Globally unique address (factory default)
          .... ...0 .... .... .... .... .... = IG bit: Individual address (unicast)
      Type: ARP (0x0806)
Address Resolution Protocol (request)
      Hardware type: Ethernet (1)
      Protocol type: IP (0x0800)
      Hardware size: 6
      Protocol size: 4
      Opcode: request (1)
      Sender MAC address: Dell_5b:b4:3b (00:15:c5:5b:b4:3b)
      Sender IP address: 192.168.1.2 (192.168.1.2)
      Target MAC address: 00:00:00 00:00:00 (00:00:00:00:00:00)
      Target IP address: 192.168.1.1 (192.168.1.1)

No.     Time            Source                  Destination             Protocol Length Info
      3 1.079391     USRoboti 1f:f9:5d        Dell 5b:b4:3b           ARP      60      192.168.1.1 is at 00:1

Frame 3: 60 bytes on wire (480 bits), 60 bytes captured (480 bits)
      WTAP ENCAP: 1
      Arrival Time: Jan  5, 2009 21:36:07.487291000 ora solare Europa occidentale
      [Time shift for this packet: 0.000000000 seconds]
      Epoch Time: 1231187767.487291000 seconds
      [Time delta from previous captured frame: 0.000421000 seconds]
      [Time delta from previous displayed frame: 0.000421000 seconds]
      [Time since reference or first frame: 1.079391000 seconds]
      Frame Number: 3
      Frame Length: 60 bytes (480 bits)
      Capture Length: 60 bytes (480 bits)
      [Frame is marked: True]
      [Frame is ignored: False]
      [Protocols in frame: eth:arp]
      [Coloring Rule Name: ARP]
      [Coloring Rule String: arp]
Ethernet II, Src: USRoboti 1f:f9:5d (00:14:c1:1f:f9:5d), Dst: Dell_5b:b4:3b (00:15:c5:5b:b4:3b)
      Destination: Dell_5b:b4:3b (00:15:c5:5b:b4:3b)
          Address: Dell 5b:b4:3b (00:15:c5:5b:b4:3b)
          .... ..0. .... .... .... .... .... = LG bit: Globally unique address (factory default)
          .... ...0 .... .... .... .... .... = IG bit: Individual address (unicast)
      Source: USRoboti 1f:f9:5d (00:14:c1:1f:f9:5d)
          Address: USRoboti 1f:f9:5d (00:14:c1:1f:f9:5d)
          .... ..0. .... .... .... .... .... = LG bit: Globally unique address (factory default)
          .... ...0 .... .... .... .... .... = IG bit: Individual address (unicast)
      Type: ARP (0x0806)
      Padding: 000000000000000000000000000000000000
Address Resolution Protocol (reply)
      Hardware type: Ethernet (1)
      Protocol type: IP (0x0800)
      Hardware size: 6
      Protocol size: 4
      Opcode: reply (2)
      Sender MAC address: USRoboti 1f:f9:5d (00:14:c1:1f:f9:5d)
      Sender IP address: 192.168.1.1 (192.168.1.1)
      Target MAC address: Dell_5b:b4:3b (00:15:c5:5b:b4:3b)
      Target IP address: 192.168.1.2 (192.168.1.2)
```