

```

+ Frame 1: 42 bytes on wire (336 bits), 42 bytes captured (336 bits)
- Ethernet II, Src: DellEsgP_5b:b4:3b (00:15:c5:5b:b4:3b), Dst: Broadcast (ff:ff:ff:ff:ff:ff)
  - Destination: Broadcast (ff:ff:ff:ff:ff:ff)
    Address: Broadcast (ff:ff:ff:ff:ff:ff)
    .... ..1. .... = LG bit: Locally administered address (this is NOT the factory default)
    .... ..1 .... = IG bit: Group address (multicast/broadcast)
  - Source: DellEsgP_5b:b4:3b (00:15:c5:5b:b4:3b)
    Address: DellEsgP_5b:b4:3b (00:15:c5:5b:b4:3b)
    .... ..0. .... = LG bit: Globally unique address (factory default)
    .... ..0 .... = IG bit: Individual address (unicast)
    Type: ARP (0x0806)
- Address Resolution Protocol (request/gratuitous ARP)
  Hardware type: Ethernet (1)
  Protocol type: IP (0x0800)
  Hardware size: 6
  Protocol size: 4
  Opcode: request (1)
  [Is gratuitous: True]
  Sender MAC address: DellEsgP_5b:b4:3b (00:15:c5:5b:b4:3b)
  Sender IP address: 192.168.1.2 (192.168.1.2)
  Target MAC address: 00:00:00_00:00:00 (00:00:00:00:00:00)
  Target IP address: 192.168.1.2 (192.168.1.2)

```