

POST /v2/transactions/simulate → 200 OK

```
{
  "last-round": 41528301,
  "txn-groups": [
    {
      "failed-at": [2],
      "failure-message":
        "transaction H6BX...2NQ4: logic eval error:
        assert failed pc=142. Details: app=8842, pc=142,
        opcodes=...",
      "txn-results": [
        { "txn-result": { ... } },
        { "txn-result": { ... } },
        { "app-budget-consumed": 683,
          "exec-trace": {
            "approval-program-trace": [ ... ]
          }
        }
      ]
    }
  ],
  "eval-overrides": {
    "allow-empty-signatures": true
  }
}
```

- 1 Which transaction in the group failed. Zero-indexed, so this is the third one.
- 2 Where the error text lives — the assert that fired, wrapper and all, as one long string.
- 3 The program counter — how far the program got before the assert fired. Feed it to the source map PuyaPy wrote beside the TEAL, and it becomes a line number in your own file.
- 4 Opcode budget actually consumed: 683 of 700. One more loop iteration and this call fails for an entirely different reason.
- 5 Why simulate could run it at all — it takes unsigned transactions. That is exactly what makes it usable for negative tests.

The request succeeded. The group did not. A test that asserts on the status code and stops there can never fail, no matter what the contract does — read failure-message, or assert nothing at all.