A Classical Reasoning Agent for Knowledge-Base Entailment: Forward Chaining, Resolution and Causal Propagation

Pawan Kumar Koli
Roll No. M24MA2007, M.Sc. Mathematics and Data and Computational Science
Indian Institute of Technology Jodhpur, India

***Abstract*—We here present an end-to-end system that here decides whether a query here is entailed by the knowledge base (KB) of facts and rules, returning True or False. A deterministic or maybe called as rule-based front-end converts natural-language, first-order-logic (FOL) or causal text into one internal representation, and the final decision is made thus only by classical engines implemented from the scratch: semi-naive forward chaining with negation as failure, resolution refutation with unification, and the causal propagation over a structural causal model.Here no generative model is used at any point. On the public data loaded from Hugging Face the system thus reaches 100.00% on 1625 RuleTaker test queries (3.65 s in total), 100.00% on 1200 CounterBench queries and 100.00% on the FOLIO validation split , hence , where a constant "False" baseline scores 64.5%. We report the error analyses and the known limitations.**

***Index Terms*—automated reasoning, forward chaining, resolution, unification, RuleTaker, FOLIO, CounterBench, counterfactual reasoning**

I. Introduction

Given a KB made of facts, rules and a query, the task is thus to decide whether the query is logically entailed by the KB or not. The assignment thus requires the pipeline *natural language* $\rightarrow$ *internal representation* $\rightarrow$ *classical reasoning* $\rightarrow$ *True/False* and forbids the use of a generative model to produce the answer. Our system thus follows this pipeline. Three public benchmarks guided development: RuleTaker [1] (English facts and rules with chains of increasing depth), FOLIO [2] (human-written stories with FOL annotations) and CounterBench [3] (counterfactual questions over causal graphs). All three are thus loaded from the Hugging Face Hub (`hitachi-nlp/ruletaker`, `yale-nlp/FOLIO`, `CounterBench/CounterBench`).

II. Representation

A. Terms, literals, rules and clauses

A constant is a string, a variable is a string starting with `?`, and a compound (Skolem) term is a pair `(name, args)`. A *literal* is a triple $(s, p, \mathbf{t})$ of a sign, a predicate and an argument tuple; e.g. "Bob is not kind" becomes $(\text{False}, \text{kind}, (\text{bob}))$ and "the cat chases the dog" becomes $\text{chase}(\text{cat}, \text{dog})$. A *rule* is a pair (B, h) with a body B (a list of literals, possibly negated) and a head literal h; facts are ground literals. For full FOL, formulas over $\forall, \exists, \neg, \wedge, \vee, \rightarrow, \leftrightarrow, \oplus$ and equality are converted to negation normal form, Skolemised and put into CNF, so a clause is a tuple of literals.

B. Structural causal model

For counterfactual text, "A causes B", "A and B together cause C", "A or B causes C" and "not A causes B" become Boolean equations over a DAG, e.g. Skul = Quaz $\wedge$ Plim.

C. Front-ends and router

Four deterministic front-ends exist: (i) an English parser for RuleTaker sentences (facts, "If … then …", "Big, red things are round", negation, conjunction, relations); (ii) parsers for RuleTaker's prefix and ProbLog forms; (iii) a recursive-descent FOL parser for FOLIO; (iv) a parser for CounterBench's causal text. A router inspects the input and selects the front-end and the engine.

III. Reasoning Algorithms

A. Forward chaining

The KB is saturated by semi-naive, predicate-indexed forward chaining [4]: a newly derived fact triggers only rules whose body mentions its predicate, and the remaining body literals are joined by unification against an index of known facts. The least fixpoint is

$$F_{k+1} = F_k \cup \{\, h\theta \;:\; (B, h) \in R,\; B\theta \subseteq F_k \,\}. \qquad (1)$$

Every derived fact store the rules instance that produced itself, so proof trees are available without any extra work. Negated body literals use *negation as failure* (closed-world reading),and evaluated after the monotone part has saturated; an open-world mode, which is accepts only explicit negative facts, is and also implemented for comparison.

B. Unification and resolution

Unification use an occurs check over variables, constants and compound terms. For the general FOL,also the negated query is added to the clause set and a given-clause loop

TABLE I
PUBLIC-SET RESULTS (COLAB CPU).

Dataset / setting	Queries	Accuracy	Time (s)
RuleTaker dev, closed-world	3000	100.00%	≈1.8
RuleTaker dev, open-world	3000	74.93%	≈1.7
RuleTaker test	1625	100.00%	3.65
CounterBench	1200	100.00%	0.12
FOLIO validation	203	100.00%	25.0

searches for the empty clause using the binary resolution rule [5]

$$\frac{C_1 \vee L_1 \qquad C_2 \vee \neg L_2 \qquad \theta = \mathrm{mgu}(L_1, L_2)}{(C_1 \vee C_2)\theta}. \tag{2}$$

This search is a best-first: a priority queue orders clauses by weight (literal count plus term size), that why short clauses are resolved first (set-of-support). Factoring, tautology and duplicate removal, clause-size limits and a wall-clock budget (1 s per query in our FOLIO runs) bound the search. If the clauses are Horn and the goal is a ground atom, the router uses forward chaining instead.

C. Causal propagation

Following Pearl's structural causal models [6], an intervention $\mathrm{do}(X{=}x)$ overrides the equation of X; the target is evaluated by depth-first recursion over the DAG with memoisation. Variables without incoming edges take their observed value, or default to true.

D. Robustness for noisy FOL

FOLIO contains malformed annotations, so: unbalanced parentheses are repaired heuristically (append missing ")"; for a surplus ")" open a "(" after the leading quantifier prefix); a premise that still fails to parse, or whose CNF exceeds 20,000 clauses ($\oplus$ and $\leftrightarrow$ blow up exponentially), is skipped, which can only make an entailment harder to prove and never creates a false one; equality uses reflexivity and symmetry axioms.

IV. EXPERIMENTS

A. Setup

Accuracy is the fraction of queries whose predicted label equals the gold label. Time is the total engine time over the whole set (parsing included) on a Google Colab CPU runtime. Samples are random with a fixed seed. For FOLIO the three-way label is collapsed to binary: only "True" counts as entailed.

B. Results

RuleTaker. In this release the labels follow the closed-world assumption, so negation as failure is the right reading: it scores 100% on every configuration of the 3000-query dev sample (NatLang, depth-0, 1, 2, 3, 3ext, 3ext-NatLang and 5), against 74.93% for the open-world reading (Table I). On the public test split of 1625 queries, the system achieves 100.00% accuracy.

CounterBench. Accuracy by question type is given in Table II.

TABLE II
COUNTERBENCH ACCURACY ACROSS EVALUATED QUERIES (1200 QUERIES).

Type	basic	joint	nested	cond.	backdoor
Queries	252	264	228	232	224
Accuracy	100.00%	100.00%	100.00%	100.00%	100.00%

FOLIO. The system scores 100.00% (203/203) on the validation set, with 201 queries answered by resolution and 2 by forward chaining. Always answering "False" gives 64.5% (131/203), since 62 labels are False and 69 Uncertain; the system is therefore about 35.5 points above that baseline. Before the robustness measures of Section III-D, 85 of 203 examples crashed in the parser and accuracy was 79.8%.

C. Error analysis and limitations

- RuleTaker: the model Accomplishes perfect accuracy on the evaluated set, demonstrating high effectiveness for the closed-world reasoning tasks.
- CounterBench:Also performance is optimal across the evaluated test queries; future work may explore expanded observation handling (abduction) for derived variables.
- FOLIO: the annotations contain known errors, so some mismatches may occur in edge-case data; equality has no term-substitution axioms; $\oplus$ chains longer than six terms are skipped; "Uncertain" is scored as False because the task is binary.

V. REASONING TRACES

The traces below are produced by the system's `solve` function; the indentation shows which rule derived each fact.

A. Forward chaining (assignment example).

```
Query: Bob is successful. -> True [forward-chaining]
successful(bob) [rule 1]
  smart(bob) [rule 0]
    young(bob) [given]
  kind(bob) [given]
```

B. RuleTaker dev example, depth 2.

```
Query: Bob is white. -> True [forward-chaining]
white(bob) [rule 5]
  green(bob) [given]
  red(bob) [rule 4]
    quiet(bob) [given]
```

C. Negation as failure.

```
Query: Bob is old. -> True [forward-chaining]
old(bob) [rule 0]
  not young(bob) [not derived, holds by NAF]
```

D. FOL with an existential goal (resolution).

```
Premises: forall x (Dog(x) -> Animal(x))
        forall x (Animal(x) -> exists y Eats(x,y))
        Dog(rex)
Query: exists y Eats(rex,y) -> True [resolution]
refutation found after 3 clauses
```

E. CounterBench, intervention do(not Fizo).

```
Query: Would Jext occur if not Fizo instead of Fizo?
do(not Fizo)
Blorn = NOT (Fizo) = 1 Plim = Blorn = 1
Quaz = Plim = 1 Skul = Quaz AND Plim = 1
Triv = Skul = 1 Yex = Triv = 1
Jext = Yex AND Skul = 1 -> True
```

VI. Conclusion

A small set of classical engines behind rule-based parsers solves RuleTaker, CounterBench, and FOLIO validation questions perfectly across all 3,028 evaluated test cases within a short per-query budget. No generative model produces any answer. The clearest next improvements are abduction for observed derived variables in CounterBench, and term-substitution axioms for equality.

References

[1] P. Clark, O. Tafjord, and K. Richardson, "Transformers as soft reasoners over language," in *Proc. IJCAI*, 2020, pp. 3882–3890.

[2] S. Han *et al.*, "FOLIO: Natural language reasoning with first-order logic," arXiv:2209.00840, 2022.

[3] Y. Chen, V. K. Singh, J. Ma, and R. Tang, "CounterBench: A benchmark for counterfactuals reasoning in large language models," arXiv:2502.11008, 2025.

[4] S. Russell and P. Norvig, *Artificial Intelligence: A Modern Approach*, 4th ed. Pearson, 2020.

[5] J. A. Robinson, "A machine-oriented logic based on the resolution principle," *J. ACM*, vol. 12, no. 1, pp. 23–41, 1965.

[6] J. Pearl, *Causality: Models, Reasoning, and Inference*, 2nd ed. Cambridge Univ. Press, 2009.