

# **RED-Health Test Report**

For

**MAXIIOT LTD** 

LoRaWAN

Model No.: DL7612-EX

Prepared For : MAXIIOT LTD

Address : No.60, Zhongshan Rd., Tucheng Dist, New Taipei, Taiwan 23680

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited

Address : 1/F, Building D, Sogood Science and Technology Park, Sanwei

community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong,

China.518102

Tel: (86) 755-26066440 Fax: (86) 755-26014772

Report Number : SZAWW180622001-03H

Date of Receipt : Jun. 22, 2018

Date of Test : Jun. 22~Nov. 06, 2018

Date of Report : Nov. 06, 2018



# **CONTENTS**

CONTENTS	•••••				2
1. GENERAL INFORMATION	hotek	Anbo	P. Watek	, abo	4
1.1. Client Information	notek	Allpote	A.r.		note <sup>lk</sup>
1.2. Description of Device (EUT)	Yur.		ite <sub>K</sub>	. br	
1.3. Auxiliary Equipment Used During Test	More	Yu.		ootek	Anbo. 2
1.4. Description of Test Facility		rek	upor Ai	······································	bote
1.5. Measurement Uncertainty	Anv		wote <sub>k</sub>	Vupor.	
2. GENERAL PRODUCT INFORMATION	tek N	<sup>ipore</sup>	VII.	Motek	6
2.1. Product Function and Intended Use	Yay	hotek	Anbo		e <sup>k</sup>
2.2. Ratings and System Detail	100	, tek	"Upote,	Anu	6
3. EN 62479 REQUIREMENT	Moter	Anbe		ek M	7
3.1. General Description of Applied Standards	, otek	Anbo	bu.	404	boter
3.2. Human exposure to the Electromagnetic fields	Anv		hotek An	bo.	P.,
3.3. RF Exposure Evaluation	Anbo	to. VI		hotek	Anbo



## **TEST REPORT**

Applicant : MAXIIOT LTD

Manufacturer : MAXIIOT LTD

Product Name : LoRaWAN

Model No. : DL7612-EX

Trade Mark : MAXIIOT

Rating(s) : Input: DC 3.3V, 1A

Test Standard(s) : EN 62479: 2010

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report shows the EUT to be technically compliant with the EN 62479: 2010 requirements. The test results are contained in this report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full responsibility for the accuracy and completeness of these tests.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test	Jun. 22~Nov. 06, 2018
	ek Lotek Anbore Anborek Anb
Anbotek	object object and large and Amount
Prepared By	Anbotek Joseph Anboten
THE PART OF THE PA	(Engineer / Oliay Yang)
	Anbotek Anbotek Anbotek Anbote
	Snavy Meng
Reviewer	potek Anbotek Anbotek Anbotek A
	(Supervisor / Snowy Meng)
	Ambotek Anbotek Anbotek Anbotek
	Sally Zhoung
	Anbotek Anbotek Anbo
Approved & Authorized Signer	otek Anbott An tek motek Al
	(Manager / Sally Zhang)



# 1. General Information

# 1.1. Client Information

Applicant	:	MAXIIOT LTD
Address	:	No.60, Zhongshan Rd., Tucheng Dist, New Taipei, Taiwan 23680
Manufacturer	lek	MAXIIOT LTD
Address	pot	No.60, Zhongshan Rd., Tucheng Dist, New Taipei, Taiwan 23680
Factory	An'	MAXIIOT LTD
Address	:	No.60, Zhongshan Rd., Tucheng Dist, New Taipei, Taiwan 23680

# **1.2. Description of Device (EUT)**

Product Name	pote	LoRaWAN	Anbotek Anbo
Model No.	Ank	DL7612-EX	Anbotek Anbotek Anbotek Ar
Trade Mark	:	MAXIIOT	ek Anbotek Anbotek Anbotek
Test Power Supply		TX & RX: DC 3.3V	botek Anbotek Anbotek Anbotek
Test Sample No.		S1(Normal Sample), S2(Engineer	ring Sample)
Anbotek An	000	Operation Frequency:	868-868.6MHz
	Anb	Number of Channel:	6 Channels
Product	P	Modulation Type:	OOK
Description	8.K	Antenna Type:	Cylindrical Antenna
	otel	Antenna Gain(Peak):	5 dBi
	Anb	Max. Transmitting Power:	7.88 dBm Max.

**Remark:** 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

## 1.3. Auxiliary Equipment Used During Test

k hotek Anbo	Manufacturer: FUJITSU LIMITED
ek hotek An	M/N: LH531
Notebook	S/N: 518127-01R2300775
hotek Anbotek	DC Rating: DC 19V, 4.22A CE, FCC DOC, CCC
And otek anbotek	Adapter:
Anbo tek nbot	M/N: ADP-602HA
Aupor K	Input: 100V-240V~ 50/60Hz, 1.5A
Jek Phojer bu	Output: DC 19V, 3.16A



#### 1.4. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registed and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, July 31, 2017.

#### ISED-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A-1, June 13, 2016.

#### **Test Location**

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

#### 1.5. Measurement Uncertainty

Parameter	Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1,5 dB
Power Spectral Density, conducted	±3 dB
Unwanted Emissions, conducted	±3 dB
All emissions, radiated	±6 dB
Temperature	±1 °C
Humidity	±5 %
DC and low frequency voltages	±3 %
Time	±5 %
Duty Cycle	±5 %



## 2. GENERAL PRODUCT INFORMATION

# 2.1. Product Function and Intended Use

The submitted sample is wireless transceiver includes transmitter and receiver.

### 2.2. Ratings and System Detail

	Anbotek Anbo	rok.	Ann	Transmitter	Anbor	Annotek	Anbotek
eK.	Frequency Range	upo vok	Anabotek	868.1MF	Iz, 868.3MHz	, 868.5MHz	
_6	Power Supply	Pupor	K With	ek Anbotek	DC 3.3V	ek shotek	Anbore



# 3. EN 62479 REQUIREMENT

### 3.1. General Description of Applied Standards

Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz).

### 3.2. Human exposure to the Electromagnetic fields

This International Standard provides simple conformity assessment methods for low-power electronic and electrical equipment to an exposure limit relevant to electromagnetic fields (EMF). If such equipment cannot be shown to comply with the applicable EMF exposure requirements using the methods included in this standard for EMF assessment, then other standards, including IEC 62311 or other (EMF) product standards, may be used for conformity assessment.

### 3.3. RF Exposure Evaluation

#### 3.3.1. Limit:

According to EN 62479 clause 4.2 Low-power electronic and electrical equipment is deemed to comply with the provisions of this standard if it can be demonstrated using routes B, C or D that the available antenna power and/or the average total radiated power is less than or equal to the applicable low-power exclusion level Pmax.

P max = 20 mW (13.1dBm) according to ICNIRP guidelines, since the EUT is General public used.

B: The input power level to electrical or electronic components that are capable of radiating electromagnetic energy in the relevant frequency range is so low that the available antenna power and/or the average total radiated power cannot exceed the low-power exclusion level defined in EN 62479 clause 4.2

C: The available antenna power and/or the average total radiated power are limited by product standards for transmitters to levels below the low-power exclusion level defined in EN 62479 clause 4.2

D: Measurements or calculations show that the available antenna power and/or the average total radiated power are below the low-power exclusion level defined in EN 62479 clauses 4.2.

#### 3.3.2. Test result

The EIRP of the EUT which are below the max permitted sending level of 20 mW, and then the EUT is not need to conduct SAR measurement.

More details please refer to SZAWW180622001-04W.

				Anbo		
Anbotek						
Anbo		Anbotel				
Anbotel	End of I	<b>VEDOLU</b>	445			
	stek Anb		abotek P	Anbotek		
ek ap				ed notek	Anbore.	