

Appendix A: Grammar in EBNF

A.1 Non-Terminal Symbols

Compilation Units

#1 Compilation Unit

```
compilationUnit :
    prototype | definitionOfModule | IMPLEMENTATION? programModule ;
```

#2 Prototype

```
prototype :
    PROTOTYPE prototypeIdent "[" requiredConformance "]" ";"
    ( PLACEHOLDERS identList ";" )?
    requiredTypeDefinition
    ( ";" requiredBinding )*
    END prototypeIdent "." ;
```

#2.1 Prototype Identifier

```
prototypeIdent : Ident ;
```

#2.2 RequiredConformance

```
requiredConformance : prototypeIdent ;
```

#3 Program Module

```
programModule :
    MODULE moduleIdent ";"
    importList* block moduleIdent "." ;
```

#3.1 Module Identifier

```
moduleIdent : Ident ;
```

#4 Definition Of Module

```
definitionOfModule :
    DEFINITION MODULE moduleIdent ( "[" requiredConformance "]" )? ";"
    importList* definition*
    END moduleIdent "." ;
```

Prototype Definitions

#5 Required Type Definition

```
requiredTypeDefinition :
    TYPE "=" permittedTypeDefinition ( "|" permittedTypeDefinition )*
    ( "!=" protoliteral ( "|" protoliteral )* )?
```

#6 Permitted Type Definition

```
permittedTypeDef :
    RECORD | OPAQUE RECORD?
```

#7 Proto-Literal

```
protoliteral :
    simpleProtoliteral | structuredProtoliteral ;
```

#7.1 Simple Proto-Literal

```
simpleProtoliteral1 : Ident;
```

¹ Simple protoliterals are CHAR, INTEGER and REAL, representing any quoted literals, whole numbers and real numbers.

#8 Structured Proto-Literal

```
structuredProtoliteral :
    "{" ( VARIADIC OF simpleProtoliteral ( "," simpleProtoliteral )* |
    structuredProtoliteral ( "," structuredProtoliteral )* ) "}" ;
```

#9 Required Binding

```
requiredBinding :
    CONST "[" constBindableIdent "]" ":" pervasiveType |
    procedureHeader ;
```

#9.1 CONST Bindable Identifier

```
constBindableIdent2 : Ident ;
```

#9.2 Pervasive Type

```
pervasiveType : Ident ;
```

Import Lists, Blocks, Declarations and Definitions**#10 Import List**

```
importList :
    ( FROM moduleIdent IMPORT ( identList | "*" ) |
    IMPORT moduleIdent "+"? ( "," moduleIdent "+"? )* ) ";" ;
```

#11 Block

```
block :
    declaration*
    ( BEGIN statementSequence )? END ;
```

#12 Declaration

```
declaration :
    CONST ( constantDeclaration ";" )+ |
    TYPE ( Ident "=" type ";" )+ |
    VAR ( variableDeclaration ";" )+ |
    procedureDeclaration ";" ;
```

#13 Definition

```
definition :
    CONST ( ( "[" constBindableIdent "]" )? constantDeclaration ";" )+ |
    TYPE ( Ident "=" ( type | OPAQUE recordType? ) ";" )+ |
    VAR ( variableDeclaration ";" )+ |
    procedureHeader ";" ;
```

Constant Declarations**#14 Constant Declaration**

```
constantDeclaration :
    Ident "=" constExpression3 ;
```

#14.1 Constant Expression

```
constExpression : expression ;
```

² CONST bindable identifiers are TSIG and TEXP.

³ Constants may not be declared as aliases of type identifiers.

Type Declarations

#15 Type

```
type :
    ( ( ALIAS | range ) OF )? typeIdent | enumerationType |
    arrayType | recordType | setType | pointerType | procedureType ;
```

#15.1 Type Identifier

```
typeIdent : qualident ;
```

#16 Range

```
range :
    "[" constExpression ".." constExpression "]" ;
```

#17 Enumeration Type

```
enumerationType :
    "(" ( ( "+" enumTypeIdent ) | Ident )
    ( "," ( ( "+" enumTypeIdent ) | Ident ) ) * ")" ;
```

#17.1 Enumeration Type Identifier

```
enumTypeIdent : typeIdent ;
```

#18 Array Type

```
arrayType :
    ( ARRAY componentCount ( "," componentCount ) * |
    ASSOCIATIVE ARRAY ) OF typeIdent ;
```

#18.1 Component Count

```
componentCount : constExpression ;
```

#19 Record Type

```
recordType :
    RECORD ( fieldList ( ";" fieldList ) * indeterminateField |
    "(" baseType ")" fieldList ( ";" fieldList ) * ) END ;
```

#19.1 Field List

```
fieldList : variableDeclaration ;
```

#19.2 Base Type

```
baseType : typeIdent ;
```

#20 Indeterminate Field

```
indeterminateField :
    INDETERMINATE Ident ":" ARRAY discriminantField OF typeIdent ;
```

#20.1 Discriminant Field

```
discriminantField : Ident ;
```

#21 Set Type

```
setType :
    SET OF ( enumTypeIdent | "(" identList ")" ) ;
```

#22 Pointer Type

```
pointerType :
    POINTER TO CONST? typeIdent ;
```

#23 Procedure Type

```
procedureType :
    PROCEDURE
    ( "(" formalTypeList ")" )?
    ( ":" returnedType )? ;
```

#23.1 Returned Type

```
returnedType : typeIdent ;
```

#24 Formal Type List

```
formalTypeList :
    formalType ( "," formalType )* ;
```

#25 Formal Type

```
formalType :
    attributedFormalType | variadicFormalType ;
```

#26 Attributed Formal Type

```
attributedFormalType :
    ( CONST | VAR )? simpleFormalType ;
```

#27 Simple Formal Type

```
simpleFormalType :
    ( CAST? ARRAY OF )? namedType ;
```

#28 Variadic Formal Type

```
variadicFormalType :
    VARIADIC OF
    ( attributedFormalType |
    |      "{+" attributedFormalType ( "," attributedFormalType )* "+}" ) ;
```

Variable Declarations**#29 Variable Declaration**

```
variableDeclaration :
    identList ":" ( range OF )? typeIdent ;
```

Procedure Declarations**#30 Procedure Declaration**

```
procedureDeclaration :
    procedureHeader ";" block Ident ;
```

#31 Procedure Header

```
procedureHeader :
    PROCEDURE
    ( "[" bindableEntity "]" )?
    Ident ( "(" formalParamList ")" )? ( ":" returnedType )? ;
```

#32 Bindable Entity

```
bindableEntity :
    DIV | MOD | FOR | DESCENDING |
    ":" | ":=" | "?" | "!" | "~" | "+" | "-" | "*" | "/" | "=" | "<" | ">" |
    bindableIdent;
```

#32.1 Bindable Identifier

```
bindableIdent4 : Ident;
```

#33 Formal Parameter List

```
formalParamList :
    formalParams ( ";" formalParams )* ;
```

⁴ PROCEDURE bindable identifiers are ABS, NEG, ODD, COUNT, LENGTH, NEW, DISPOSE, RETAIN, RELEASE, TLIMIT, TMIN, TMAX, SXF and VAL.

#34 Formal Parameters

```
formalParams :
    simpleFormalParams | variadicFormalParams ;
```

#35 Simple Formal Parameters

```
simpleFormalParams :
    ( CONST | VAR )? identList ":" simpleFormalType ;
```

#36 Variadic Formal Parameters

```
variadicFormalParams :
    VARIADIC ( variadicCounter "[" variadicTerminator "]" )? OF
    ( simpleFormalType |
      "{{" simpleFormalParams ( ";" simpleFormalParams )* "}}" ) ;
variadicCounter := Ident ;
```

#36.1 Variadic Formal Parameters

```
variadicTerminator : constExpression ;
```

Statements**#37 Statement**

```
statement :
    ( assignmentOrProcedureCall | ifStatement | caseStatement |
      whileStatement | repeatStatement | loopStatement |
      forStatement | RETURN expression? | EXIT )? ;
```

#38 Statement Sequence

```
statementSequence :
    statement ( ";" statement )* ;
```

#39 Assignment Or Procedure Call

```
assignmentOrProcedureCall :
    designator ( "!=" expression | "++" | "--" | actualParameters )? ;
```

#40 IF Statement

```
ifStatement :
    IF expression THEN statementSequence
    ( ELSIF expression THEN statementSequence )*
    ( ELSE statementSequence )?
    END ;
```

#41 CASE Statement

```
caseStatement :
    CASE expression OF case ( "|" case )+ ( ELSE statementSequence )? END ;
```

#42 Case

```
case :
    caseLabels ( "," caseLabels )* ":" statementSequence ;
```

#43 Case Labels

```
caseLabels :
    constExpression ( ".." constExpression )? ;
```

#44 WHILE Statement

```
whileStatement :
    WHILE expression DO statementSequence END ;
```

#45 REPEAT Statement

```
repeatStatement :
    REPEAT statementSequence UNTIL expression ;
```

#46 LOOP Statement

```
loopStatement :
    LOOP statementSequence END ;
```

#47 FOR Statement

```
forStatement :
    FOR DESCENDING? controlVariable
    IN ( designator | range OF typeIdent )
    DO statementSequence END ;
```

#47.1 Control Variable

```
controlVariable : Ident ;
```

#48 Designator

```
designator :
    qualident designatorTail? ;
```

#49 Designator Tail

```
designatorTail :
    ( ( "[" expressionList "]" | "^" ) ( "." Ident )* )+ ;
```

Expressions**#50 Expression List**

```
expressionList :
    expression ( "," expression )* ;
```

#51 Expression

```
expression :
    simpleExpression ( relOp simpleExpression )? ;
```

#51.1 Relational Operator

```
relOp :
    "=" | "<" | "<=" | ">" | ">=" | IN ;
```

#52 Simple Expression

```
simpleExpression :
    ( "+" | "-" )? term ( addOp term )* ;
```

#52.1 Add Operator

```
addOp :
    "+" | "-" | OR ;
```

#53 Term

```
term :
    factor ( mulOp factor )* ;
```

#53.1 Multiply Operator

```
mulOp :
    "*" | "/" | DIV | MOD | AND ;
```

#54 Factor

```
factor :
    ( NumericLiteral | StringLiteral | structuredValue |
      designatorOrFunctionCall | "(" expression ")" )
    ( "::" namedType )? | NOT factor ;
```

#55 Designator Or Function Call

```
designatorOrFunctionCall :
    designator actualParameters? ;
```

#56 Actual Parameters

```
actualParameters :  
    "(" expressionList? ")" ;
```

Value Constructors**#57 Structured Value**

```
structuredValue :  
    "{" ( valueComponent ( "," valueComponent )* )? "}" ;
```

#58 Value Component

```
valueComponent :  
    expression ( ( BY | ".." ) constExpression )? ;
```

Identifiers**#59 Qualified Identifier**

```
qualident :  
    Ident ( "." Ident )* ;
```

#60 Identifier List

```
identList :  
    Ident ( "," Ident )* ;
```


#4.3 Quotable Character

QuotableCharacter :

Digit | Letter | Space | QuotableGraphicChar | EscapedCharacter ;

#4.4 Digit

Digit :

"0" | "1" | "2" | "3" | "4" | "5" | "6" | "7" | "8" | "9" ;

#4.5 Base-2 Digit

Base2Digit :

"0" | "1" ;

#4.6 Base-16 Digit

Base16Digit :

Digit | "A" | "B" | "C" | "D" | "E" | "F" ;

#4.7 Letter

Letter :

"A" .. "Z" | "a" .. "z" ;

#4.8 Space

Space : " " ;

#4.9 Quotable Graphic Character

QuotableGraphicChar :

"!"	"#"	"\$"	"%"	"&"	"("	")"	"*"	"+"	","	
"_"	"."	"/"	":"	";"	"<"	"="	">"	"?"	"@"	
"["	"]"	"^"	"_"	"`"	"{"	" "	"}"	"~"	;	

#4.10 Escaped Character

EscapedCharacter :

"\" ("0" | "n" | "t" | "\" | "'" | "'') ;

A.3 Ignore Symbols**#1 Whitespace**

Whitespace :

Space | ASCII_TAB ;

#2 Single-Line Comment

SingleLineComment :

"//" ~(EndOfLine) * EndOfLine ;

#3 Multi-Line Comment

MultiLineComment :

"(*" (~("(" | ")") * (MultiLineComment | EndOfLine) ?) * ")" ;

#4 End Of Line Marker

EndOfLine :

ASCII_LF ASCII_CR? | ASCII_CR ASCII_LF? ;

A.4 Control Codes**#1 Horizontal Tab**

ASCII_TAB : CHR(8) ;

#2 Line Feed

ASCII_LF : CHR(10) ;

#3 Carriage Return

ASCII_CR : CHR(13) ;

#4 UTF8 BOMUTF8_BOM⁵ : { 0xFE, 0xBB, 0xBF } ;

⁵ BOM support is optional. If supported, a BOM may only occur at the very beginning of a file.

A.5 Pragma Grammar

#1 Pragma

```
pragma :
    "<*" ( pragmaMSG | pragmaIF | pragmaENCODING | pragmaGENLIB | pragmaFFI |
    pragmaINLINE | pragmaALIGN | pragmaPADBITS | pragmaADDR | pragmaREG |
    pragmaPURITY | pragmaVOLATILE | pragmaFORWARD | implDefinedPragma ) ">" ;
```

#2 Body Of Compile Time Message Pragma

```
pragmaMSG :
    MSG "=" ( INFO | WARN | ERROR | FATAL ) ":"
    compileTimeMsgComponent ( "," compileTimeMsgComponent )* ;
```

#3 Compile Time Message Component

```
compileTimeMsgComponent :
    StringLiteral | ConstQualident |
    "?" ( ALIGN | ENCODING | implDefPragmaName ) ;
```

#3.1 Constant Qualified Identifier

```
constQualident : qualident ;
```

#3.2 Implementation Defined Pragma Name

```
implDefPragmaName : Ident ;
```

#4 Body Of Conditional Compilation Pragma

```
pragmaIF :
    ( IF | ELSIF ) inPragmaExpression | ELSE | ENDIF ;
```

#5 Body Of Character Encoding Pragma

```
pragmaENCODING :
    ENCODING "=" ( "ASCII" | "UTF8" ) ( ":" codePointSampleList )? ">" ;
```

#6 Code Point Sample List

```
codePointSampleList :
    quotedChar "=" characterCode ( "," quotedChar "=" characterCode )* ;
```

#6.1 Quoted Character Literal

```
quotedChar : StringLiteral ;
```

#6.2 Character Code Literal

```
characterCode : NumericLiteral ;
```

#7 Library Template Expansion Pragma

```
pragmaGENLIB :
    GENLIB moduleIdent FROM template ":" templateParamList ;
```

#7.1 Template Identifier

```
template : Ident ;
```

#8 Template Parameter List

```
templateParamList :
    placeholder "=" replacement ( "," placeholder "=" replacement )*
```

#8.1 Placeholder

```
placeholder : Ident ;
```

#8.2 Replacement

```
replacement : StringLiteral ;
```

#9 Body Of Foreign Function Interface Pragma

```
pragmaFFI :
    FFI "=" ( "C" | "Fortran" ) ;
```

#10 Body Of Function Inlining Pragma

```
pragmaINLINE :
    INLINE | NOINLINE ;
```

#11 Body Of Memory Alignment Pragma

```
pragmaALIGN :
    ALIGN "=" inPragmaExpression ;
```

#12 Body Of Bit Padding Pragma

```
pragmaPADBITS :
    PADBITS "=" inPragmaExpression ;
```

#13 Body Of Memory Mapping Pragma

```
pragmaADDR :
    ADDR "=" inPragmaExpression ;
```

#14 Body Of Register Mapping Pragma

```
pragmaREG :
    REG "=" inPragmaExpression ;
```

#15 Body Of Purity Attribute Pragma

```
pragmaPURITY :
    PURITY "=" inPragmaExpression ;
```

#16 Body Of Volatile Attribute Pragma

```
pragmaVOLATILE :
    VOLATILE ;
```

#16 Body Of Implementation Defined Pragma

```
implDefinedPragma :
    implDefPragmaName ( "=" inPragmaExpression )? ;
```

#18 In-Pragma Expression

```
inPragmaExpression :
    inPragmaSimpleExpr ( inPragmaRelOp inPragmaSimpleExpr )? ;
```

#18.1 In-Pragma Relational Operator

```
inPragmaRelOp :
    "=" | "#" | "<" | "<=" | ">" | ">=" ;
```

#19 In-Pragma Simple Expression

```
inPragmaSimpleExpr :
    ( "+" | "-" )? inPragmaTerm ( addOp inPragmaTerm )* ;
```

#20 In-Pragma Term

```
inPragmaTerm :
    inPragmaFactor ( inPragmaMulOp inPragmaFactor )* ;
```

#20.1 In-Pragma Multiply Operator

```
inPragmaMulOp :
    "*" | DIV | MOD | AND ;
```

#21 In-Pragma Factor

```
inPragmaFactor :
    wholeNumber | constQualident | "(" inPragmaExpression ")" |
    inPragmaPervasiveCall | NOT inPragmaFactor ;
```

#21.1 Whole Number

```
wholeNumber : NumericLiteral ;
```

#22 In-Pragma Pervasive Call

```
inPragmaPervasiveCall :
    Ident1 "(" inPragmaExpression ( "," inPragmaExpression )* ")" ;
```

¹ Permissible are ABS, NEG, ODD, ORD, LENGTH, TMIN, TMAX, TSIZE, TLIMIT and macros in module COMPILER.