

# 02 - Substitution

Lean: First Steps

Tariq Rashid

October 27, 2024

# Task

- Let's continue with another simple task. Imagine we have the following formula.

$$y = x + 4$$

- Given  $x = 3$ , our task is to prove

$$y = 7$$

- Here,  $x$ ,  $y$ , 3 and 4 are all real numbers.

- Easy task - an effort to think about the steps involved.

$$y = x + 4 \quad \text{given fact} \quad (1)$$

$$x = 3 \quad \text{given fact} \quad (2)$$

$$y = x + 4 \quad \text{using fact (1)}$$

$$= (3) + 4 \quad \text{substitution using fact (2)}$$

$$= 7 \quad \text{using arithmetic} \quad \square$$

- We start by listing the two given facts,  $y = x + 4$  and  $x = 3$ .
- We want to prove something about  $y$ . What is  $y$ ? The first fact tells us  $y = x + 4$ .
- At this point, we have  $y = x + 4$ , which is fine, but we do want to resolve that  $x$  into a number.
- The second fact tells us  $x = 3$ . We can use it to substitute 3 for the  $x$  in  $x + 4$ . This gives us  $y = (3) + 4$ .
- Finally, we can use arithmetic to evaluate  $(3) + 4$  as 7. That gives us what we want,  $y = 7$ .

- It is this kind of structured step-by-step thinking that we'll need to write proofs in Lean.
- It may seem disproportionate for simple tasks, but it is better to develop that thinking with simple tasks.

---

```
-- 02 - Simple Proof by Calculation
```

```
import Mathlib.Tactic
```

```
example {x y :  $\mathbb{R}$ } (h1 : y = x + 4) (h2 : x = 3) : y = 7 := by  
  calc
```

```
    y = x + 4 := by rw [h1]
```

```
    _ = 3 + 4 := by rw [h2]
```

```
    _ = 7 := by norm_num
```

---

- Lines beginning with `--` are comments.
- `import Mathlib.Tactic` loads into Lean information about fundamental results and common methods used in proofs, **tactics**.
- The next line is the beginning of the proof:
  - Theorem **name**, but `example` creates anonymous theorem.
  - **Variable types** `{x y : ℝ}` .
  - Named **hypotheses** `(h1 : y = x + 4) (h2 : x = 3)` .
  - After `:` is the **objective** or **goal** statement we want to prove, `y = 7` .
  - Finally, `:= by` signals the subsequent code will seek to prove the objective.

name	types	hypotheses	objective
<hr/>	<hr/>	<hr/>	<hr/>
<code>example {x y : ℝ} (h1 : y = x + 4) (h2 : x = 3) : y = 7 := by</code>			



- `calc` tells Lean we intend to do a proof by direct calculation.
- After that is the core of the proof.
  - `y = x + 4` is **justified** using `by rw [h1]`, a tactic for **rewriting** `y` using hypothesis `h1`.
  - Previous expression `x + 4`, denoted by the shorthand `_`, is equal to `3 + 4`. This is **justified** by hypothesis `h2`, which allows us to **rewrite** `x` as `3`.
  - Finally, `y = 7`. Simplification of `3 + 4` to `7` is justified with the `norm_num` tactic, which can do numerical arithmetic.

- Lean provides feedback through its **Infoview**, which will appear in a separate pane.
  - Usually to the right of your main code.
- **Updated as we edit our code**, provides **warnings** and **errors**.

- With the previous (correct) Lean code, Infoview tells us:

---

All Messages (0)

No messages.

---

- No messages means no warnings or errors. Lean thinks our proof is correct.

# InfoView - Deliberate Error

- Change the hypothesis `h2`, used to rewrite `x` as 3, to the incorrect hypothesis `h1`.
- Infoview updates with error message.

---

```
01_simple.lean:8:24
tactic 'rewrite' failed, did not find instance of the
  pattern in the target expression
y
```

---

- At line 8 of the code, Lean found the rewrite tactic had failed.
- Changing the hypothesis back to `h2` sees all error messages go away.

# Easy Exercise

- Write a Lean program to prove  $y = 0$  given  $y = x^2 - 9$  and  $x = -3$ , where  $x, y \in \mathbb{R}$ .