

IN4MATX 133: User Interface Software

Lecture:
Separation in Angular


Today's goals

By the end of today, you should be able to...

- Differentiate and explain the roles of Angular components, modules, and services
- Implement a service in Angular
- Navigate Angular's file structure


A “large” client interface

- Hundreds of pages and ways to navigate between pages
- Repeated UI elements (status updates)
 - Angular implements these as *components*
- Different content, links, etc. displayed for each person



A “large” client interface

- Loading lots of libraries can be slow and expensive
- So Angular supports sectioning parts of projects into distinct modules



Angular modules

- Segment code into a library, similar to a JavaScript library
- A component only imports the modules it needs

Angular modules

- Segment code into a library, similar to a JavaScript library
- A component only imports the modules it needs

Angular modules

- By default, each Angular app has one module, `app.module.ts`
- But an app can create multiple modules to section off code
- `ng generate module [name]`
- Modules can *import* other modules
- Modules also *declare* which components they use
 - When you create a new component (`ng generate component [name]`), it automatically gets added to the declarations for the root module

Angular modules

```
import { BrowserModule } from '@angular/platform-browser';
import { NgModule } from '@angular/core';
```

```
import { AppRoutingModule } from './app-routing.module';
import { AppComponent } from './app.component';
import { HelloComponent } from './hello/hello.component';
import { DayComponent } from './day/day.component';
```

```
@NgModule({
  declarations: [ ← Components used
    AppComponent,
    HelloComponent,
    DayComponent
  ],
  imports: [ ← Modules to import
    BrowserModule,
    AppRoutingModule
  ],
  providers: [],
  bootstrap: [AppComponent] ← The “root” component of the module
})
export class AppModule { }
```


Angular modules

- `BrowserModule` is included by default
 - Required to run any app in the browser
- When creating an Angular project, can specify whether a *Routing* module should be created
 - Routing: defines what URIs to send to what **endpoints**
 - For Angular, defines what URIs to send to what **components**

Angular routing

app-routing.module.ts

```
import { NgModule } from '@angular/core';
import { Routes, RouterModule } from '@angular/router';
import { ArtistPageComponent } from '../pages/artist-page/artist-page.component';
import { TrackPageComponent } from '../pages/track-page/track-page.component';
import { AlbumPageComponent } from '../pages/album-page/album-page.component';
import { HomeComponent } from '../pages/home-page/home-page.component';
```

```
const routes: Routes = [
  { path: 'artist/:id', component: ArtistPageComponent },
  { path: 'track/:id', component: TrackPageComponent },
  { path: 'album/:id', component: AlbumPageComponent },
  { path: '', component: HomeComponent }
];
```

```
@NgModule({
  imports: [RouterModule.forRoot(routes)],
  exports: [RouterModule]
})
export class AppRoutingModule { }
```

← Listens for any endpoint
artist/:id
id can be retrieved in
album-page.component.ts

Retrieving route in a component

```
import { Component, OnInit } from '@angular/core';
import { ActivatedRoute } from '@angular/router';

@Component ({
  selector: 'app-album-page',
  templateUrl: './album-page.component.html',
  styleUrls: ['./album-page.component.css']
})
export class AlbumPageComponent implements OnInit {

  constructor(private route: ActivatedRoute) { } ← “Injecting a service”

  ngOnInit () {
    var albumId = this.route.snapshot.paramMap.get('id'); ← Retrieve the id
                                                            from the URI
  }
}
```

Angular services

- Anything not associated with a specific view should be turned into a *service*
 - e.g., getting data from an API, parsing URIs for routing information
- Helps keep components lightweight
- Services can then be *injected* into a component (importing)
- To inject, import the service and retrieve it as a parameter in the constructor
- `ng generate service [name]`

Angular services

```
import { Component, OnInit } from '@angular/core';  
import { ActivatedRoute } from '@angular/router';
```

 ← Importing a service

```
@Component({  
  selector: 'app-album-page',  
  templateUrl: './album-page.component.html',  
  styleUrls: ['./album-page.component.css']  
})  
export class AlbumPageComponent implements OnInit {
```

```
  constructor(private route: ActivatedRoute) { } 
```

 ← Injecting it

```
  ngOnInit() {  
    var albumId = this.route.snapshot.paramMap.get('id');  
  }  
}
```

 ← Service can be referenced later

Angular services

```
import { Injectable } from '@angular/core'; ← Defined as injectable
import { HttpClient, HttpHeaders } from '@angular/common/http';

@Injectable({
  providedIn: 'root' ← What module(s) can use this service
})
export class SpotifyService {
  baseUrl: string = 'http://localhost:8888';

  constructor(private http: HttpClient) { } ← HttpClient injected

  private sendRequestToExpress(endpoint: string) {
  }
}
```

Import a custom service

```
import { Component, OnInit } from '@angular/core';  
import { ActivatedRoute } from '@angular/router';  
import { SpotifyService } from '../services/spotify.service';
```



Import service via file structure

```
@Component ({  
  selector: 'app-album-page',  
  templateUrl: './album-page.component.html',  
  styleUrls: ['./album-page.component.css']  
})  
export class AlbumPageComponent implements OnInit {  
  
  constructor(private route: ActivatedRoute,  
private spotifyService: SpotifyService) { }
```



Inject it like any other service

Angular classes

- Plain-old classes can also be made in Angular
 - Any processing or munging you need to do, for example

- `ng generate class [name]`

```
export class Dataparser {  
  public constructor() {  
    console.log('Hello, world!');  
  }  
}
```

Import a class

```
import { Component, OnInit, Input } from '@angular/core';  
import { Dataparser } from '../dataparser';
```

```
@Component({  
  selector: 'app-day',  
  templateUrl: './day.component.html',  
  styleUrls: ['./day.component.css']  
})
```

```
export class DayComponent implements OnInit {  
  @Input() today:string;
```

```
  days = ["Sunday", "Monday", "Tuesday", "Wednesday", "Thursday", "Friday", "Saturday"];
```

```
  constructor() {  
    var data = new Dataparser();  
  }
```

```
  ngOnInit() {  
  }  
}
```



Import class via file structure



Instantiate it like any other class

Import a library

- Since Angular is in TypeScript, it can use any JavaScript or TypeScript library
- Install as normal with npm: `npm install [packagename]`
 - If you want TypeScript typings, don't forget to install `@types/[packagename]`

Import a library

```
import * as chroma from 'chroma-js';
```

 ← Note: different syntax

```
export class Dataparser {
```

```
  constructor() {
```

```
    console.log(chroma('royalblue')); // '#4169e1'
```

```
  }
```

```
}
```



Can now be referenced

Angular's file structure

- Angular projects generate a *lot* of files
 - There are about 75 in the starter code for A3
- Most are boilerplate


```
▼ example
  ► e2e
  ► node_modules
  ▼ src
    ▼ app
      ► day
      ► hello
      /* app-routing.module.ts
      /* app.component.css
      <> app.component.html
      /* app.component.spec.ts
      /* app.component.ts
      /* app.module.ts
    ► assets
    ► environments
    browserslist
    favicon.ico
    <> index.html
    /* karma.conf.js
    /* main.ts
    /* polyfills.ts
    /* styles.css
    /* test.ts
    /* tsconfig.app.json
    /* tsconfig.spec.json
    /* tslint.json
    .editorconfig
    .gitignore
    /* angular.json
    /* package-lock.json
    /* package.json
    <> README.md
    /* tsconfig.json
    /* tslint.json
```

Socrative Quiz!

Enter your UCI Email when prompted for
name!!!
e.g.,

xxxxx@uci.edu

<https://api.socrative.com/rc/52QwBu>



Today's goals

By the end of today, you should be able to...

- Differentiate and explain the roles of Angular components, modules, and services
- Implement a service in Angular
- Navigate Angular's file structure

Deprecated...

Let's talk about ngModel

To refresh...

Two-way binding [()]

- “You often want to both display a data property and update that property when the user makes changes”
- Most common use: binding to user-generated input
- ngModel directive enables two-way binding to input fields

<!--enteredText variable contains inputted text-->

<!--textChanged() is called after every keystroke-->

<input [(ngModel)]="enteredText" (change)="textChanged()">

Deprecated...

Let's talk about ngModel

- ngModel has been deprecated for use in *reactive forms*
- ngModel has not been deprecated as it's used in assignment 3
- Assignment 3 uses *template-driven* forms
- ngModel was deprecated in reactive forms b/c it behaved differently than the ngModel in template forms...which was confusing.