
Geometrically Consistent Generalizable Splatting

Abstract

Gaussian splatting has emerged as the preferred 3D scene representation due to their incredible speed and accuracy in novel view generation. Various attempts thus have been made in adapting multi-view structure prediction networks to directly predict 3D-splats from images. However, most of the existing work in this domain have focused on enhancing existing to view structure predictors to estimate additional Gaussian Splats parameters – orientations, scale, opacity and appearance, by minimizing view-synthesis loss. We show that such view-synthesis loss is insufficient to learn geometrically meaningful splat representations. We systematically analyse and address the inherent ambiguities in 3D splats in representing structure and appearance of the scene in the learning process. We present a novel framework for to learn networks for self-supervised, pose-free generalisable splatting, that explicitly ensures geometric correctness . By, incorporating geometric consistency into learning, our proposed approach provides generalizable splats that provides (i) state of the art 3D reconstructions, (ii) two-view pose estimation and (iii) in domain novel-view synthesis on RealState10K dataset. We also showcase zero-shot capabilities of the proposed generalizable splat network indoor dataset ScanNet, where the proposed method outperforms the prior art substantially on geometric tasks.

1 Introduction

Gaussian splatting [?] has revolutionized 3D structure and appearance modelling from multiple 2D images in the recent past. Departing from traditional depth or point cloud representations for structure of the scene, 3D Gaussians allows to model both scene structure and appearance to provide high-fidelity 3D reconstruction from multiple views. 3D Gaussians implicitly model surface reflections and refractions properties and environment lighting to encode view dependent scene appearance, is memory efficient representation when compared to explicit volumetric alternatives. They facilitate rendering of the scene from arbitrary viewpoints in fraction of a second utilizing modern GPUs.

Owing to this success of 3DGS, a significant effort has been put to improve the 3DGS approach to work with few-views [], in presence of dynamically moving objects [] and in incorporating object semantics into 3D reconstructions []. Real-time simultaneous localization and mapping approaches have been adapting splats as the inherent scene representation []. Splats are also used for generation of geometrically consistent images and video sequences []. 3D Gaussian splats have become the prevalent choice for representing scenes in this era.

The deep-learning revolution of the last decade has drastically influenced geometric inference from one or multiple images as well. While earlier works in this direction focused on learning neural networks that map image(s) to their depth-maps provided by range sensors [?], recent works has explored reconstructing registered set of per-pixel point clouds for multiple images [?] to provide state-of-the-art relative pose and structure of the scene. It has also been shown that these feed-forward neural networks to predict geometry from image(s) can be trained without depth sensors, in a self-supervised manner, by minimizing view synthesis loss [? ? ? ? ?]. Structure prediction from single or few images have been used as the optimization-free building block in high-fidelity tracking and mapping systems []. Learning assisted recovery of scene geometry has truly become mainstream.

It is natural then, to marry the incredible capabilities of modern deep neural networks in learning useful geometric priors with the advantages of using 3D Gaussians as the scene representation. Various laudable attempts have been made recently, in training neural networks to predict 3D splats directly from images [1, 2, 3, 4, 5, 6]. These methods are usually dubbed as Generalizable Gaussian Splatting methods in the literature. Most Generalizable Gaussian Splatting methods, focus on designing or adapting structure prediction networks to estimate means of the Gaussian. Generally these networks consist of encoders for one or multiple images and decoders to predict geometry – usually in the form of depth or point cloud. Additional decoder layers are usually appended to decoders additionally predict the remaining Gaussian parameters (orientation, scale, opacities and view-dependent color). All or a partial set of neural network parameters are then learned by usually minimizing simple view-synthesis loss on a few target views by several generalizable splatting methods.

This prevalent setup used by Generalizable Gaussian Splatting methods overlooks several key issues that are inherited from underlne 3DGS optimization that is used for supervision by almost all aforementioned methods:

- Splats are grossly over-parametrized compared to traditional depth-maps or 3D point-clouds used for few view reconstruction. Successful estimation of 3D splats usually require a large number of densely sampled viewpoints. 3DGS with few-views is an active field of research, with several solutions relying on heavy regularization [7]. These developments are ignored in building a successful generalizable Gaussian splatting technique.
- Unlike per-pixel depths or 3D locations, that are uniquely defined for a scene (upto scale), numerous configurations of the 3D Gaussians can explain scene structure and appearance equally well. In absence of a unique definition for the optimal set of Gaussians, it is unclear how to learn 3D Gaussians even when scene structure is available for supervision in the form of depth-maps.
- Successful Gaussian splatting rely on multiple non-differentiable heuristics (such as pruning, splitting and duplication of Gaussian). Over the course of the optimization, many Gaussians die (reach close to zero opacity), or are introduced late in the optimization. In absence of differentiable approximations of these heuristics existing generalizable splatting approaches hope that the inductive biases in network design and large datasets will help keeping the Generalized Gaussians perpetually active during the training for stochastic gradient decent to work.

As result of these oversights, the current generalizable Gaussian splatting solutions often converge to geometrically degenerate scenarios. This is spacially true for Gaussian parameters other than their means. The means of the Gaussians are relatively stable thanks to the well studied problem of self supervised single of two-view depth estimation methods.

In Figure 1, we showcase how current generalizable splatting frameworks fail to learn meaningful opacities, orientations or scale of the Gaussians. These frameworks often end up over-fitting to single task of novel-view synthesis – which is used for learning Gaussian parameters. The plausibility of 3D Gaussians configurations learned by these methods is questionable and no geometric meaning can generally be inferred from the these predicted Gaussians directly. On the contrary, many interesting geometric properties are reflected directly in the visualization of the Gaussian opacity, scales and orientation the proposed method predicts. Briefly, one can see that proposed method reconstruct very low number of splats with small opacities (near dead Gaussians) compared to baselines, can provide correct surface normals directly from the predicted Gaussian orientations, and produce Gaussian shapes elongated perpendicular to the normal edges and very small scale along edges. We will extensively discuss the geometric inconsistency present in the current Generalizable 3DGS results and how proposed method alleviate these inconsistencies in section ??.

The two approaches we picked for visualization of the Gaussian quantities broadly represent separate underlne representation for encoding Gaussian means - namely (i) per-pixel depthmaps or (ii) per-pixel 3D locations aligned in a single frame of reference. However, to our knowledge, all the Generalizable 3DGS methods suffer from the same limitations.

[RG: intro again definitely starts from here](#)

In this work, we systematically aim to define what the ideal configuration for the geometrically consistent Gaussian should looks like and proposed appropriate priors to assist Generalized Gaussian

Splatting. To that end we opt to work on the recently published NoPo-Splat [?] as our baseline and enhance it. We select No-Po-splat as baseline because, aside from its state of performance on multiple geometric tasks, it is a self-supervised approach that does not require ground truth depth-maps unlike some of the other generalizable splatting adaptations[?]. Additionally, utilizing DUST3R framework, the approach is one of the few to provide generalizable splatting from a pair of images without requiring relative pose of these images. However, the addition ambiguities in using splats as representation poses similar problems in learning geometrically accurate Generalizable Gaussian Splatting and contribution of our work can help other alternative baselines as well.

We systematically address these ambiguities by carefully changing the scene representation and adding suitable regularizations to the traditionally used view synthesis loss. Our main observations are, (i) Defining the ideal Gaussian orientations to be dominant normals of the surfaces they are part of (as advocated in [?] help resolving structural ambiguities. We do that by intergrading 2D Gaussian splatting reparameterized used in [?] in place of the commonly used 3D Gaussian rasterizer [?] (ii) when relying on view synthesis loss, ensuring that Gaussians are pixel-aligned is extremely important. In particular, for the pose free methods that aim to use PnP style initialization for relative pose estimation, it is a crucial prior to introduce (iii) jointly learning pixel-aligned normals and 3D location is challenging when self supervision is used. It is best to rely on depth-derived pseudo-normals to supervise for Gaussian orientations for accurate normal predictions.

We train presented generalizable splatting networks on RealState10k dataset [?] and show that we outperform the NoPoSplat baseline on the tasks of Novel-View Synthesis, Geometric Correctness and relative pose estimation on RealState10k testset. We also showcase generalization capability of our trained models on Scan-net [?] and DTU datasets [?]. We outperform all existing methods in terms of relative-pose estimation from two-images by a large margin on all the dataset we test our approach on. This includes methods that are tailored specifically to estimate relative pose such as [? ?]. On all datasets, our approach provides state of the art view synthesis when compared to pose-free generalizable splatting and pose-free nerf alternatives. Our approach provides most accurate 3D reconstructions amongst all generalizable splatting approaches in the zero-shot testing setup on DTU and Scan-net datasets including methods that use ground truth relative pose. To the best of our knowledge, it is the first generalizable splatting approach to analyse and evaluate the veracity and meaningfulness of Gaussian Splatting parameters such as opacities and orientation. We believe that the presented analysis paves the way forward for future research in the domain.

2 Related Work

RG: This perhaps can be low priority but when you guys have some time start populating this. The big part will be copying the bib etc. Writup should be ok

2.1 Self-supervised two view / single view reconstruction

todo

2.2 3D and 2D GS

todo

2.3 Generalizable splats : an overview

RG: Copied from Intro maybe fits here better The first set of methods [1? ? , 2] (represented by MV-splat[2] results in figure 1). These methods use image depths as an internal representation for Gaussian centres. These centres are computed by directly back-projecting pixels of image with the help of known intrinsics and estimated depths. These Gaussians are thus explicitly aligned with pixels of the input (or context) image. Note that many of these methods rely on the reparameterization trick proposed in the pixel-splat [1] framework where opacities are considered proportional to the discrete depth probabilities.

The second set of methods [? ? ?] are represented by NoPoSplat [?]. These methods use DUST3R [6] setup to predict Gaussian centres directly from images. More precisely, they predict the 3D locations of pixel-aligned Gaussians for every input image in a single canonical frame of

reference – usually the first input frame. These methods usually estimate Gaussian opacities as an additional output of a decoder. Canonical Gaussian centres are expected to be projected onto image pixels providing a way to estimate intrinsics and extrinsic camera parameters using suitable objective function. These methods are also dubbed as "pose free" Generalizable 3DGS methods.

todo

2.3.1 Methods that use explicit depth parametrization but need relative pose

todo

2.3.2 Methods that use point cloud and extend duster requiring no pose

3 Method

In this section, we introduce our geometrically consistent Gaussian splatting framework. We build upon the NoPoSplat architecture but propose a novel loss function and architectural refinements to enhance its geometric consistency and generalization capabilities. We first define the problem formulation and notation, briefly review the NoPoSplat architecture and learning framework, and then detail the novel losses and architectural modifications introduced in this work.

We assume we are given a sparse set of multi-view images, each with known camera intrinsics. We denote these images by $\mathcal{I} = \{\mathbf{I}^i\}_{i=1}^K$, where $\mathbf{I}^i \in \mathbb{R}^{H \times W \times 3}$, and their corresponding camera intrinsics by $\mathbf{K}^i \in \mathbb{R}^{3 \times 3}$. The primary objective is to learn a feed-forward neural mapping f_θ , parameterized by θ , that predicts a set of 3D Gaussians representing both geometric structure and appearance attributes of the underlying scene:

$$f_\theta : \{(\mathbf{I}^i, \mathbf{K}^i)\}_{i=1}^K \mapsto \{(\boldsymbol{\mu}_j^i, \alpha_j^i, \mathbf{q}_j^i, \mathbf{s}_j^i, \mathbf{c}_j^i)\}_{j=1, \dots, H \times W}^{i=1, \dots, K}, \quad (1)$$

where each Gaussian is characterized by its center position $\boldsymbol{\mu} \in \mathbb{R}^3$, orientation represented by a unit quaternion $\mathbf{q}$, and scale parameters $\mathbf{s}$, which can be either $\mathbf{s} \in \mathbb{R}^2$ for 2D Gaussians or $\mathbf{s} \in \mathbb{R}^3$ for 3D Gaussians. The appearance parameters consist of an opacity value $\alpha \in \mathbb{R}$ and spherical harmonics (SH) coefficients $\mathbf{c} \in \mathbb{R}^k$, with k degrees of freedom.

3.1 Pipeline

Our approach builds upon the architecture proposed by [?] and involves three main modules: a transformer-based encoder, a corresponding decoder, and specialized heads to predict Gaussian parameters. Notably, both encoder and decoder employ Vision Transformer (ViT) backbones exclusively, without introducing geometric constraints such as epipolar geometry or multi-view cost volumes. Despite this simplicity, the purely transformer-based design achieves performance comparable or superior to approaches relying on geometric priors, especially in scenarios where input views exhibit minimal overlap.

Specifically, the encoder transforms RGB images into patch-based sequences, which are flattened and augmented by camera intrinsic tokens. These token sequences are individually processed by a ViT encoder with shared parameters across views. The resulting encoded features are subsequently fused via cross-attention layers in the ViT decoder, effectively aggregating information across multiple views. Gaussian parameters are estimated by two separate prediction heads: one head directly infers Gaussian centres positions from decoder features alone, while the other head predicts appearance-related and geometric parameters using both decoder outputs and the original RGB images.

3.2 Geometric Consistency

In this part, we introduce novel losses and architectural modifications aimed at ensuring geometric consistency in the predicted feed-forward Gaussians. Transitioning from a full 3D Gaussian representation to a 2D surfel-based representation, as demonstrated by [?], seems a natural step toward improved geometric consistency. However, an important open question is whether this change in representation alone suffices to achieve consistent scene geometry in a feed-forward setup, while simultaneously preserving or even enhancing novel-view synthesis quality.

As shown in Section 5, although switching to surfel-based representations improves geometric consistency compared to the original 3D Gaussian baseline, it degrades the quality of novel-view synthesis, consistent with findings reported in [?]. To further enhance geometric consistency without sacrificing image quality, we propose two novel regularization terms specifically designed for the context of feed-forward generalizable splatting: one to guide the orientation of Gaussian surfels, and another to enforce their alignment with the pixel grid.

Alongside the standard RGB reconstruction loss $\mathcal{L}_{color}$ —which integrates both an $\mathcal{L}_2$ and a perceptual LPIPS term—we introduce a normal consistency regularization $\mathcal{L}_{normal}$ to align Gaussian surfel orientations with rendered depth, and a grid alignment loss $\mathcal{L}_{grid}$ to ensure precise pixel-level alignment. These losses are combined into the final objective:

$$\mathcal{L} = \mathcal{L}_{color} + \lambda_n \mathcal{L}_{normal} + \lambda_g \mathcal{L}_{grid}, \quad (2)$$

where λ_n and λ_g are weighting factors balancing the influence of each regularization. Next, we provide detailed formulations and motivations for these novel losses.

3.2.1 2D-GS

Why 2DGS is better than 3DGS and how we change anything we had to. For example Scale prediction and rasterization change details goes here.

3.2.2 Learning Gaussian orientations

Normal loss goes here

RG: A couple of questions here:

- where are the grid and normal loss placed? I assume grid loss is on both context views? What about normal consistency loss? is it on context images, is it on virtual images? or both?

3.3 Making 3D Gaussian pixel aligned

Grid loss and details go here

3.4 Fixing dead Gaussians

Activation / alpha loss ? Even if they dont improve we can write about options but we end up saying that previous changes fixes alpha

4 Analysis of figure 1

RG: placeholder title and need to be forst experimental section

RG: maybe all of this goes in some analysis in a section we can cross reference? It is evident in Figure 1 that none of the existing Genralizable 3DGS approach provide meaningful orientations or scales for the estimated Gaussians. In particular, we visualize the normal of the dominant plane of 3D Gaussions that corresponds to the direction in which the Gaussians is minimally elongated. This minimal elongation is labelled as scale 3 in the figure and quantify the uncertainty in localising scene surface around this Gaussian. The estimated normals form the existing Generalizable 3DGS methods lack any geomtric meaning whereas the proposed method can provide meaningful normal-maps confirming to plausibile scene geometry. For example notice multiple planes confirming to Manhattan prior in the scene in Figure ?? and the corresponding normal predictions.

RG: paras below are too technical should we put them in some other section of analysis and write a broader paragraph? The existing Generalized 3DGS methods does not provide geometrically meaningful estimates of the shape (scales) to the Gaussians either. One can observe clear over-fitting to view synthesis loss – which is highly sensitive to location of image edges – in apparent image texture in the scales. Higher values in scale 3 suggest billboard like elongated Gaussians perpendicular to the scene surface that existing Generalizable 3DGS approaches produce. On the other hand our

approach uses 2DGS rasterizer by construction forces this scale to be 0 eliminating this billboard like Gaussians. Not only the proposed approach localizes scene surfaces but the dominant structural edges are clearly visible in the estimated scales. For example, look at an interesting case of the edge of the wall at the intersection of two corridors ???. You can see that the Gaussians estimated by the proposed methods are very skewed in one direction than the other (one scale is very large and another very small). This is expected out of geometrically consistent Gaussians to have a very narrow extent perpendicular to geometric edges whereas an arbitrarily large extent along the edge. You also can see clearly that more planar areas have more homogeneously elongated Gaussians. Whereas not as clear geometric edge or homogeneity in the size and shape of Gaussians can be found in the existing approaches.

We can also see the opacities of the reconstructed Gaussians. Large regions of the image have very low opacities pointing to many near dead Gaussians estimated by the existing Generalizable 3DGS methods. These low opacity Gaussians are often found in the regions of shadows, light sources and refraction suggesting that instead of modelling these variations with spherical harmonics as one would expect, the view dependent color is being modelled by changing opacities. In contrast it can be seen that proposed method consists of less number of near dead Gaussians and low opacity regions corresponding to image edges and shadows.

5 Experiments

RG: Some important notes and observations on the current experimental results are here:

- We need view synthesis numbers on the scanNet alongside other results.
- Not sure why PSNR goes down with normal loss on Re10K but I guess this is fine for now. The improvement in structure should be shown on some datasets though which is not evident.
- I would prefer if you have shared checkpoint evaluation in the novel view synthesis table for Re10K for completeness. This can be in the supplementary material but it is only 1 row so I don't mind it to be there.
- You have RANSAC-PnP for pose evaluation. Given we have grid loss in place now, there is a chance that some robust loss function (huber/L1) to estimate pose from all 2D - 3D pairs (all pixels) will be better. We can include this alongside the hacked photometric optimization for pose via 3DGS for the moment as alternative pose evaluation and create numbers as well. Some of this can go to supplementary material as extra analysis.
- For the depth estimation on scanNet. I understand that the context depths can be computed with pointclouds. We need to remove these columns in the main paper and aim to move to target view depth evaluation immediately. For simplicity just take all the images between the two context view (or just the center image if evaluation takes time) and compute these numbers on the target image(s) only.
- The number when computed on the target images should show differences between 2DGS+grids and 2DGS + Grid + Normal as well. It is important to sell the geometric accuracy going up with Normal Constraints. I still don't understand why the rendered context depths are not better while the estimated pose is much better especially when you talk about context depth 2.
- related to the same, there are two ways to evaluate the rendered depths for context views. (i) used GT relative pose and (ii) use the estimated pose to do the warping. I am not sure if we can sell the second evaluation? Perhaps not because we are deliberately fusing pose error in this case into the structure error. We need to see though why the structure is poor with normal loss and if switching to target views fixes the issue.
- Normal supervision: One last ditch effort perhaps. Can we use the orientations of Gaussian as pixel aligned normals and directly supervise them? What I mean by this is that we are sort of pushing the Gaussians to be pixel aligned with high opacity in general and this makes a difference. Why not then say that we have rendered depth for every context pixel, Gaussian orientation for the context view, use both together to enforce some sort of consistency. This way you are in fact predicting traditional normals (which is what you would have supervised for directly)

- I still want to run an experiment without Duster initialization. I have hopes for that.

Some notes on geometric evaluation: When we ideally have infinite views, we can extract the surface mesh and evaluate mesh reconstruction accuracy using metrics like Chamfer distance, typically on datasets like DTU. However, when we don't have dense multi-view coverage but instead have sufficient 2.5D RGB-D images (e.g., ScanNet), an alternative approach is to select two context views and evaluate the rendered depth. This serves as a proxy to assess interpolation/extrapolation quality on novel views—effectively measuring how well the model generalises depth consistency in a zero-shot setting.

RG: Not sure about para above. If we reconstructed the scene in full yes we can do Champer distance. As per the depth evaluation on context view, I don't like it because that raises a question if you should evaluate point maps or rendered depth. Simply switing the view to target is easiest. Write something like this:

Ideally on a dataset like DTU where 360 degree coverage of the scene is available, one can extract the ground truth surface mesh and evaluate reconstruction accuracy with a metric like Chamfer distance as done in []. As our method reconstruct scenes with two overlapping views only it is not a viable option. We have to limit the evaluation to the observed part of the scene – which is defined by union of view-frustum of input views. We thus try two alternatives: (i) mask the unobserved parts of the scene in the ground truth surface for evaluation of Chamfer distance or (ii) utilize depthmaps of the observed views within the union of context view-frustum and report average depth error (2.5D) on all the test views as a proxy for 3D geometric accuracy of estimated splats.

IMPORTANT TODO:

- evaluating the depths on the virtual view for all datasets in question, DTU, ScanNet for Noposplat and our methods.
- creating visualization for the figure 1 we discussed already yesterday.
- comparing geometry with other baselines. Pixel Splat, MV-splat at the very least but we need to see perhaps other variants that are recent as well. Does Splater3R become another baseline? It is understood that their so called point cloud is simply duster but if they have gaussian splatting trained we can still say that all other parameters are not trained well and rendered depths make no sense from their splat representation.
- comparing the pose estimation: here it is shown that we outperform the baseline of Noposplat but it only outperforms the state of art after the pose optimization via context view rendering. We should thus have the pose optimization included in our results to show we are overall state of the art here.
- View synthesis: Unfortunately with DTU as well as the Re10k, I dont think our performance is state of art when we compare against MV/pixel splat unless we test time optimize pose as noposplat. I dont believe they have state of art result is this peaking into pose optimization is not used. I propose following: First categorize baseline into two sections, pose required and pose inferred. Concede the fact that pose aware splatting methods should provide better results than pose-free methods first. Than (i) for all pose free methods (Duster Varients mainly and genralizable nerfs if any) we do test time optimization and report results to replicate what NoPosplat did. Be upfront that is is not ideal so option (ii) simply dont do anything with the pose and compare all pose free methods without test time optimization. Now I am not sure if option (ii) is easy at all so we have an issue.
- evaluated rendered normals with normal derived from GT.

5.1 Datasets

....

5.2 Evaluation Metrics

...

5.3 Baselines

...

5.4 Implementation Details

....

5.5 Results & Analysis

Quantitative, Qualitative, ...




Table 1: **Qualitative comparison of rendered novel-view depth on ScanNetV1 (top three rows) and RE10k (bottom row).**

5.6 Ablations Studies

...

6 Conclusion

Finally ...

Acknowledgments and Disclosure of Funding

Declare funding (financial activities supporting the submitted work).

References

- [1] David Charatan, Sizhe Lester Li, Andrea Tagliasacchi, and Vincent Sitzmann. pixelsplat: 3d gaussian splats from image pairs for scalable generalizable 3d reconstruction. In *CVPR*, 2024. [3](#)
- [2] Yuedong Chen, Haoifei Xu, Chuanxia Zheng, Bohan Zhuang, Marc Pollefeys, Andreas Geiger, Tat-Jen Cham, and Jianfei Cai. Mvsplat: Efficient 3d gaussian splatting from sparse multi-view images. *arXiv preprint arXiv:2403.14627*, 2024. [3](#)

Table 2: **Novel-view synthesis performance on the RealEstate10k dataset [7].** We compare pose-required and pose-free methods against our proposed variants. “NoPoSplat” refers to results from publicly available checkpoints, while “NoPoSplat*” indicates results from our retrained baseline using identical hyperparameters for fair comparison. The overall best results among all methods are highlighted in **bold**, and the best-performing pose-free method (without optimizing camera poses for target views) is indicated by underline. **RG: We should remove the pose aligned number form here altogether. ditto in other table**

		Small			Medium			Large			Average		
Method		PSNR↑	SSIM↑	LPIPS↓	PSNR↑	SSIM↑	LPIPS↓	PSNR↑	SSIM↑	LPIPS↓	PSNR↑	SSIM↑	LPIPS↓
Pose-Required	pixelNeRF	18.417	0.601	0.526	19.930	0.632	0.480	20.869	0.639	0.458	19.824	0.626	0.485
	AttnRend	19.151	0.663	0.368	22.532	0.763	0.269	25.897	0.845	0.186	22.664	0.762	0.269
	pixelSplat	20.263	0.717	0.266	23.711	0.809	0.181	27.151	0.879	0.122	23.848	0.806	0.185
	MVSplat	20.353	0.724	0.250	23.778	0.812	0.173	27.408	0.884	0.116	23.977	0.811	0.176
Pose-Free w/o Align.	NoPoSplat	21.086	0.721	0.237	23.134	0.776	0.185	25.086	0.818	0.141	23.189	0.775	0.185
	NoPoSplat*	21.097	0.723	0.237	23.191	0.779	0.187	25.107	0.817	0.144	23.244	0.778	0.187
	Ours (2DGS)	21.051	0.725	0.245	23.338	0.784	0.187	25.541	0.830	0.140	23.407	0.782	0.188
	Ours (2DGS+Grid)	21.341	0.736	0.236	23.453	0.788	0.185	25.529	0.829	0.141	23.528	0.787	0.185
	Ours (2DGS+Normal)	21.275	0.733	0.236	23.198	0.780	0.187	25.205	0.823	0.144	23.300	0.781	0.187
	Ours (2DGS+Grid+Normal)	<u>21.349</u>	<u>0.739</u>	<u>0.234</u>	<u>23.463</u>	<u>0.789</u>	<u>0.184</u>	<u>25.628</u>	<u>0.832</u>	<u>0.141</u>	<u>23.564</u>	<u>0.789</u>	<u>0.184</u>
Pose-Free w/ Align.	DUST3R	14.101	0.432	0.468	15.419	0.451	0.432	16.427	0.453	0.402	15.382	0.447	0.432
	MASt3R	13.534	0.407	0.494	14.945	0.436	0.451	16.028	0.444	0.418	14.907	0.431	0.452
	Splat3R	14.352	0.475	0.472	15.529	0.502	0.425	15.817	0.483	0.421	15.318	0.490	0.436
	CoPoNeRF	17.393	0.585	0.462	18.813	0.616	0.392	20.464	0.652	0.318	18.938	0.619	0.388
	NoPoSplat	22.514	0.784	0.210	24.899	0.839	0.160	27.411	0.883	0.119	25.033	0.838	0.160
	NoPoSplat*	22.533	0.785	0.211	24.905	0.839	0.161	27.419	0.884	0.120	25.036	0.839	0.161
	Ours (2DGS)	22.211	0.774	0.224	24.715	0.835	0.166	27.209	0.880	0.124	24.813	0.833	0.168
	Ours (2DGS+Grid)	22.376	0.780	0.217	24.733	0.836	0.166	27.228	0.880	0.125	24.869	0.835	0.167
	Ours (2DGS+Normal)	22.432	0.784	0.214	24.757	0.837	0.165	27.136	0.879	0.125	24.867	0.836	0.166
	Ours (2DGS+Grid+Normal)	22.423	0.784	0.215	24.787	0.838	0.165	27.282	0.882	0.124	24.941	0.838	0.165

Table 3: **Zero-shot out-of-distribution novel-view synthesis performance on ACID [5] and ScanNet-V1 [3], compared against state-of-the-art method.** All models are trained exclusively on the RE10k dataset. The best overall results are highlighted in **bold**, while the best-performing pose-free method (without optimizing camera poses for target views) is indicated by underline.

		ACID			ScanNet-V1		
Method		PSNR↑	SSIM↑	LPIPS↓	PSNR↑	SSIM↑	LPIPS↓
<i>w/o Eval. Align.</i>	NoPoSplat	23.379	0.683	0.238	21.068	0.646	0.268
	Ours (2DGS)	23.914	0.704	0.233	21.167	0.648	<u>0.267</u>
	Ours (2DGS+Grid)	23.745	0.697	0.235	20.919	0.644	0.271
	Ours (2DGS+Normal)	23.848	0.702	0.235	<u>21.178</u>	0.648	0.271
	Ours (2DGS+Grid+Normal)	<u>23.950</u>	<u>0.707</u>	<u>0.233</u>	21.163	<u>0.648</u>	0.268
<i>w/ Eval. Align.</i>	NoPoSplat	25.765	0.776	0.198	29.002	0.876	0.145
	Ours (2DGS)	25.627	0.773	0.202	28.728	0.868	0.145
	Ours (2DGS+Grid)	25.629	0.772	0.202	28.575	0.864	0.148
	Ours (2DGS+Normal)	25.618	0.772	0.203	28.769	0.869	0.149
	Ours (2DGS+Grid+Normal)	25.734	0.776	0.201	28.984	0.873	0.145

- [3] Angela Dai, Angel X Chang, Manolis Savva, Maciej Halber, Thomas Funkhouser, and Matthias Nießner. Scannet: Richly-annotated 3d reconstructions of indoor scenes. In *CVPR*, 2017. 9, 10, 11
- [4] Johan Edstedt, Qiyu Sun, Georg Bökman, Mårten Wadenbäck, and Michael Felsberg. Roma: Robust dense feature matching. In *CVPR*, 2024. 10
- [5] Andrew Liu, Richard Tucker, Varun Jampani, Ameesh Makadia, Noah Snavely, and Angjoo Kanazawa. Infinite nature: Perpetual view generation of natural scenes from a single image. In *ICCV*, 2021. 9, 10
- [6] Shuzhe Wang, Vincent Leroy, Yann Cabon, Boris Chidlovskii, and Jerome Revaud. Dust3r: Geometric 3d vision made easy. In *CVPR*, 2024. 3
- [7] Tinghui Zhou, Richard Tucker, John Flynn, Graham Fyffe, and Noah Snavely. Stereo magnification: learning view synthesis using multiplane images. *ACM TOG*, 2018. 9, 10

Table 4: **Pose estimation performance (AUC) across multiple error thresholds on RE10k [7] (in-domain), ScanNet-V1 [3], and ACID [5] (both cross-domain).** Our method achieves state-of-the-art results across all thresholds and datasets, despite not being trained on ScanNet or ACID. Remarkably, our approach significantly outperforms the baseline on the cross-domain ScanNet dataset using only PnP+RANSAC, without relying on additional photometric-based pose refinement, whereas the baseline depends on such optimization. The best overall results are highlighted in **bold**, and the best-performing PnP+RANSAC only method is indicated by underline. Note that RoMa [4], in contrast to our method, is directly trained on ScanNet.

Method	RE10k			ScanNet-V1			ACID		
	5° ↑	10° ↑	20° ↑	5° ↑	10° ↑	20° ↑	5° ↑	10° ↑	20° ↑
CoPoNeRF	0.161	0.362	0.575	-	-	-	0.078	0.216	0.398
DUS3R	0.301	0.495	0.657	-	-	-	0.166	0.304	0.437
MASt3R	0.372	0.561	0.709	-	-	-	0.234	0.396	0.541
RoMa	0.546	0.698	0.797	0.168	0.361	0.575	0.463	0.588	0.689
<i>PnP+RANSAC only</i>	NoPoSplat	0.572	0.728	0.833	0.078	0.198	0.394	0.337	0.497
	Ours (2DGS)	0.588	0.737	0.832	0.085	0.223	0.432	0.344	0.513
	Ours (2DGS+Grid)	0.621	0.760	0.849	0.123	0.279	0.471	0.382	0.540
	Ours (2DGS+Normal)	0.613	0.756	0.848	0.118	0.267	0.460	0.376	0.537
	Ours (2DGS+Grid+Normal)	<u>0.627</u>	<u>0.766</u>	<u>0.855</u>	<u>0.135</u>	<u>0.289</u>	<u>0.479</u>	<u>0.392</u>	<u>0.547</u>
<i>w/ Photometric Optimisation</i>	NoPoSplat	0.672	0.791	0.868	0.109	0.256	0.463	0.456	0.593
	Ours (2DGS)	0.672	0.788	0.859	0.129	0.298	0.515	0.460	0.599
	Ours (2DGS+Grid)	0.686	0.799	0.870	0.136	0.311	0.512	0.474	0.607
	Ours (2DGS+Normal)	0.679	0.798	0.871	0.141	0.323	0.520	0.475	0.610
	Ours (2DGS+Grid+Normal)	0.689	0.804	0.876	0.156	0.334	0.539	0.488	0.619

Table 5: **Pose estimation performance (AUC) across multiple error thresholds on ScanNet-1500 [3] (cross-domain).** Our method achieves state-of-the-art results across all thresholds despite not being trained on ScanNet. The best overall results are highlighted in **bold**, and the best-performing PnP+RANSAC only method is indicated by underline. Note that RoMa [4], in contrast to our method, is directly trained on ScanNet.

Method	ScanNet-1500		
	5° ↑	10° ↑	20° ↑
DUS3R	0.221	0.437	0.636
MASt3R	0.159	0.359	0.573
RoMa	0.271	0.476	0.653
<i>PnP+RANSAC only</i>	NoPoSplat	0.232	0.443
	Ours (2DGS)	0.237	0.451
	Ours (2DGS+Grid)	0.238	0.467
	Ours (2DGS+Normal)	0.242	0.471
	Ours (2DGS+Grid+Normal)	<u>0.250</u>	<u>0.476</u>
<i>w/ Photometric Optimisation</i>	NoPoSplat	0.262	0.474
	Ours (2DGS)	0.241	0.462
	Ours (2DGS+Grid)	0.261	0.473
	Ours (2DGS+Normal)	0.255	0.480
	Ours (2DGS+Grid+Normal)	0.263	0.479

A Appendix / supplemental material

Optionally include supplemental material (complete proofs, additional experiments and plots) in appendix. All such materials **SHOULD be included in the main submission**.

Table 6: **Depth estimation performance for novel views on ScanNet-V1 [3].** Two input camera views are used to reconstruct the scene using Gaussians. We propose using the accuracy of rendered depth for novel views as a holistic measure of the model’s interpolation capability for 3D reconstruction. Our method outperforms all other approaches across all evaluated metrics by clear margin. The best overall results are highlighted in **bold**, and the best-performing method without camera pose refinement is indicated by underline.

		Rendered Depth (Novel views)		
Method		Abs Rel↓	$\delta_1 < 1.10 \uparrow$	$\delta_1 < 1.25 \uparrow$
	pixelSplat	0.299	0.552	0.818
	MVSplat	0.189	0.412	0.745
<i>w/o</i> <i>Pose</i> Refine.	NoPoSplat	0.131	0.554	0.851
	NoPoSplat*	0.135	0.552	0.847
	Ours (2DGS)	0.110	0.676	0.889
	Ours (2DGS+Grid)	0.109	0.679	0.890
	Ours (2DGS+Normal)	0.115	0.674	0.884
	Ours (2DGS+Grid+Normal)	<u>0.108</u>	<u>0.680</u>	<u>0.892</u>
<i>w</i> <i>Pose</i> Refine.	NoPoSplat	0.126	0.567	0.861
	NoPoSplat*	0.130	0.564	0.856
	Ours (2DGS)	0.103	0.704	0.900
	Ours (2DGS+Grid)	0.102	0.706	0.901
	Ours (2DGS+Normal)	0.106	0.704	0.898
	Ours (2DGS+Grid+Normal)	0.100	0.707	0.904

Table 7: **Depth estimation performance for input views on ScanNet-V1 [3].** The scene is reconstructed from two input camera views using Gaussians, and the reported “rendered depth” is computed directly from these views. The first input view serves as the global reference frame. The best overall results are highlighted in **bold**, and the best-performing method without camera pose refinement is indicated by underline.

		Input 1 Rendered Depth			Input 2 Rendered Depth		
Method		Abs Rel↓	$\delta_1 < 1.10 \uparrow$	$\delta_1 < 1.25 \uparrow$	Abs Rel↓	$\delta_1 < 1.10 \uparrow$	$\delta_1 < 1.25 \uparrow$
<i>w/o</i> <i>Pose</i> Refine.	NoPoSplat	0.127	0.575	0.864	0.138	0.530	0.833
	NoPoSplat*	0.129	0.573	0.864	0.139	0.529	0.834
	Ours (2DGS)	0.104	0.706	0.900	0.120	0.628	0.867
	Ours (2DGS+Grid)	0.103	0.710	0.904	0.119	0.633	0.868
	Ours (2DGS+Normal)	0.105	0.709	0.898	0.123	0.632	0.863
	Ours (2DGS+Grid+Normal)	<u>0.101</u>	<u>0.713</u>	<u>0.906</u>	<u>0.118</u>	<u>0.637</u>	<u>0.870</u>
<i>w</i> <i>Pose</i> Refine.	NoPoSplat	0.127	0.575	0.864	0.122	0.572	0.865
	NoPoSplat*	0.129	0.573	0.864	0.123	0.569	0.865
	Ours (2DGS)	0.104	0.706	0.900	0.099	0.709	0.898
	Ours (2DGS+Grid)	0.103	0.710	0.904	0.097	0.717	0.903
	Ours (2DGS+Normal)	0.105	0.709	0.898	0.099	0.716	0.902
	Ours (2DGS+Grid+Normal)	0.101	0.713	0.906	0.095	0.719	0.908

NeurIPS Paper Checklist

The checklist is designed to encourage best practices for responsible machine learning research, addressing issues of reproducibility, transparency, research ethics, and societal impact. Do not remove the checklist: **The papers not including the checklist will be desk rejected.** The checklist should follow the references and follow the (optional) supplemental material. The checklist does NOT count towards the page limit.

Please read the checklist guidelines carefully for information on how to answer these questions. For each question in the checklist:

- You should answer [Yes], [No], or [NA].
- [NA] means either that the question is Not Applicable for that particular paper or the relevant information is Not Available.
- Please provide a short (1–2 sentence) justification right after your answer (even for NA).

The checklist answers are an integral part of your paper submission. They are visible to the reviewers, area chairs, senior area chairs, and ethics reviewers. You will be asked to also include it (after eventual revisions) with the final version of your paper, and its final version will be published with the paper.

The reviewers of your paper will be asked to use the checklist as one of the factors in their evaluation. While "[Yes]" is generally preferable to "[No]", it is perfectly acceptable to answer "[No]" provided a proper justification is given (e.g., "error bars are not reported because it would be too computationally expensive" or "we were unable to find the license for the dataset we used"). In general, answering "[No]" or "[NA]" is not grounds for rejection. While the questions are phrased in a binary way, we acknowledge that the true answer is often more nuanced, so please just use your best judgment and write a justification to elaborate. All supporting evidence can appear either in the main paper or the supplemental material, provided in appendix. If you answer [Yes] to a question, in the justification please point to the section(s) where related material for the question can be found.

IMPORTANT, please:

- **Delete this instruction block, but keep the section heading "NeurIPS paper checklist",**
- **Keep the checklist subsection headings, questions/answers and guidelines below.**
- **Do not modify the questions and only use the provided macros for your answers.**

1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

Answer: [TODO]

Justification: [TODO]

Guidelines:

- The answer NA means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A No or NA answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [TODO]

Justification: [TODO]

Guidelines:

- The answer NA means that the paper has no limitation while the answer No means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate "Limitations" section in their paper.

- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. Theory Assumptions and Proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer NA means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. Experimental Result Reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer NA means that the paper does not include experiments.
- If the paper includes experiments, a No answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.

- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general, releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
 - (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
 - (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
 - (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
 - (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer NA means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (<https://nips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so “No” is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (<https://nips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. Experimental Setting/Details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer, etc.) necessary to understand the results?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer NA means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. Experiment Statistical Significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer NA means that the paper does not include experiments.
- The authors should answer "Yes" if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g. negative error rates).
- If error bars are reported in tables or plots, The authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. Experiments Compute Resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer NA means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. Code Of Ethics

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics <https://neurips.cc/public/EthicsGuidelines>?

Answer: [TODO]

Justification: [TODO]

Guidelines:

- The answer NA means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer No, they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. Broader Impacts

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [TODO]

Justification: [TODO]

Guidelines:

- The answer NA means that there is no societal impact of the work performed.
- If the authors answer NA or No, they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. Safeguards

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pretrained language models, image generators, or scraped datasets)?

Answer: [TODO]

Justification: [TODO]

Guidelines:

- The answer NA means that the paper poses no such risks.
- Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.

- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. Licenses for existing assets

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer NA means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, paperswithcode.com/datasets has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. New Assets

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer NA means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
- The paper should discuss whether and how consent was obtained from people whose asset is used.
- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. Crowdsourcing and Research with Human Subjects

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.

- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. Institutional Review Board (IRB) Approvals or Equivalent for Research with Human Subjects

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.




Figure 1: Qualitative comparison of Gaussians. First row visualizes our 2D Gaussians with the second and third containing results from NoPoSplat and MVsplat respectively. All visualized Gaussians correspond to the context image (a). Row 1: (b-c) shows extent of 2D Gaussians along the estimated scene surface it belongs to. The surface is defined by its normal which is shown in (d). Row 2/3 for NoPoSplat and MVsplat respectively: (f/k) show minimal Gaussian elongation. This direction is assumed to be perpendicular to the dominant surface and the elongation quantizes the uncertainty in the surface localization. (g/l, h/m) show Gaussian elongation along the estimated dominant surface, i.e. comparable to corresponding columns in top row, (i/n) in the two rows shows estimated normals of the dominant surface for baseline methods. Additionally, (e,j,o) show the estimated opacity of the Gaussians.