## **DUBLIN CITY UNIVERSITY**

## ELECTRONIC AND COMPUTER ENGINEERING

# **EE515 - Real Time Digital Signal Processing**

# **Assignment 2**



Author

Michael Lenehan michael.lenehan4@mail.dcu.ie

Student Number: 15410402

13/12/2019

## **Declaration**

I declare that this material, which I now submit for assessment, is entirely my own work and has not been taken from the work of others, save and to the extent that such work has been cited and acknowledged within the text of my work. I understand that plagiarism, collusion, and copying are grave and serious offences in the university and accept the penalties that would be imposed should I engage in plagiarism, collusion or copying. I have read and understood the Assignment Regulations set out in the module documentation. I have identified and included the source of all facts, ideas, opinions, and viewpoints of others in the assignment references. Direct quotations from books, journal articles, internet sources, module text, or any other source whatsoever are acknowledged and the source cited are identified in the assignment references. This assignment, or any part of it, has not been previously submitted by me or any other person for assessment on this or any other course of study.

I have read and understood the DCU Academic Integrity and Plagiarism at https://www4.dcu.ie/sites/default/files/policy/1%20-%20integrity\_and\_plagiarism\_ovpaa\_v3.pdf and IEEE referencing guidelines found at https://loop.dcu.ie/mod/url/view.php?id=448779.

Signed:	Date: <u>13/12/2019</u>
Michael Lenehan	

# **Contents**

1	Que	tion 1	2
	1.1	Part 1	2
	1.2	Part b	3
	1.3	Part c	3
2	Que	tion 2	3
	2.1	Part a	3
	2.2	Part B	5
	2.3	Part C	5
	2.4	Part D	5
3	Que	tion 3	6
	3.1	Part a	6
	3.2	Part b	6
	3.3	Part c	6
	3.4	Part d	7
4	App	ndix	8
	4.1	Question 1	8
	12	Quarties 2	0

# 1 Question 1

All code for this section can be found within the appendices.

### 1.1 Part 1

$$y[n] = 2x[n] - 3x[n-1] + 2x[n-2]$$

y[n] in the range  $0 \le n \le 10$  for:

$$x[n] = \begin{cases} 0 & n < 0 \\ n+1 & n = 0, 1, 2 \\ 5-n & n = 3, 4 \\ 1 & n \ge 5 \end{cases}$$




Figure 1: Output for Question 1 Parts 1, 2, and 3

From Figure 1 it can be seen that the values for y[n] are  $\{2,1,2,-1,2,3,1,1,1,1,1,1\}$ .

### **1.2** Part b

### 1.3 Part c

# 2 Question 2

All code for this section can be found within the appendices.

### 2.1 Part a

The frequency response of the filter is given by the following:

$$y[n] = \frac{1}{11} \sum_{k=0}^{10} x[n-k]$$

Converting to the Frequency Domain

$$H(j\hat{\omega}) = \frac{1}{11} \sum_{k=0}^{10} e^{-j\hat{\omega}k}$$

Sum of a Geometric Series

$$\sum_{k=0}^{L-1} a^k = \frac{1-\alpha^L}{1-\alpha}$$

$$H(j\hat{\boldsymbol{\omega}}) = \frac{1}{L} (\frac{1 - e^{-j\hat{\boldsymbol{\omega}}L}}{1 - e^{-\hat{\boldsymbol{\omega}}}})$$

Taking out a factor of  $e^{\frac{-j\omega L}{2}}$  from the numerator

and  $e^{\frac{-j\hat{\omega}}{2}}$  from the denominator:

$$H(j\hat{\pmb{\omega}}) = \frac{1}{L} (\frac{e^{\frac{-j\hat{\pmb{\omega}}L}{2}}(e^{\frac{j\hat{\pmb{\omega}}}{2}} - e^{\frac{-j\hat{\pmb{\omega}}L}{2}})}{e^{\frac{-j\hat{\pmb{\omega}}}{2}}(e^{\frac{jo\hat{\pmb{\omega}}ega}{2}} - e^{-\frac{j\hat{\pmb{\omega}}}{2}})})$$

$$H(j\hat{\boldsymbol{\omega}}) = \left(\frac{\sin\left(\frac{\hat{\boldsymbol{\omega}}\hat{\boldsymbol{L}}}{2}\right)}{L\sin\left(\frac{\hat{\boldsymbol{\omega}}}{2}\right)}\right)e^{\frac{-j\hat{\boldsymbol{\omega}}(L-1)}{2}}$$

As in the code shown, the Dirichlet function is used for the computation of the magnitude. The output plot can be seen in the first plot in Figure 2, found below.




Figure 2: The output from Q2 Part 1, Part 2, and Part 3

### 2.2 Part B

The frequency response of the system with  $f_s = 1000$  is given in the second plot of Figure 2.

### 2.3 Part C

As no correct implementation could be completed for this section, there is no correct plot found in Figure 2. The code implementation can be found above this section.

### **2.4** Part D

This system can be described as a Rectangular Window FIR Filter.

# 3 Question 3

### 3.1 Part a

There are 3 loops within this DFG. These loops are indicated below:




Figure 3: DFG with Loops labelled

Each of these loops can be seen to begin and end at the addition node after the input x[n].

#### 3.2 Part b

The smallest loop, labelled Loop 3 has an iteration period of 5/2. The next smallest loop, labelled Loop 2 has an iteration period of 7/2. Finally, the largest loop, labelled Loop 1 has an iteration period of 4/2. Therefore, the iteration period bound has a value of 7/2.

#### 3.3 Part c

The computation times for each path, with no delay, are as follows:

• Loop 1: 1 Multiplication, 2 Additions

$$-2+(2*1)=4$$

• Loop 2: 2 Multiplications, 3 Additions

$$-(2*2)+(3*1)=7$$

• Loop 3: 1 Multiplication, 3 Additions

$$-2+(3*1)=5$$

Therefore, the critical path is found in the path labelled "Path 2" in Figure 3. This path has a length of 7 time units.

### 3.4 Part d

By shifting the register before the addition node "5" to between addition node "5" and multiplication node "6", the following iteration periods are achieved:

- Loop 1:
  - **-** 4/2
- Loop 2:
  - 7/3
- Loop 3:
  - 5/2

Therefore, the iteration period bound has been reduced. The changes to be made can be seen in Figure 4, found below.




Figure 4: Retimed DFG

# 4 Appendix

## 4.1 Question 1

```
clc
clear all

%% Part a

x = zeros(1,11)
n=0:10;

i=0;
while i<11
    if(i==0 || i==1 || i==2)
        x(i+1)=i+1;
    end
    if(i==3 || i==4)
        x(i+1)=5-i;
end
if(i>=5)
    x(i+1)=1;
```

```
end
    i=i+1;
end
Hz = [2 -3 2];
y = conv(x, Hz);
%% Part b
fig=figure;
subplot(3,1,1);
stem(n,x);
title('Input x[n]');
subplot(3,1,2);
stem(n,y(1:11));
title('Output y[n]');
%% Part c
x = zeros(1,11);
x(1)=1;
h=conv(Hz,x);
subplot (3,1,3)
stem(n,h(1:11));
title('Unit Impulse Response of y[n]');
saveas(fig , 'Q1.png')
4.2 Question 2
clc
clear all
```

```
%% Part a
% L=11;
% omega=linspace(0,2*pi,300);
% aliasSinc = ((sin((omega*L)/2))/(L*sin(omega/2)))
% h=exp((-j*omega*(L-1))/2).*aliasSinc
%
% plot (omega/pi,h)
L=11
x = linspace(0, 4*pi, 300);
h = diric(x,L).*exp((-j*x*(L-1)/2));
fig=figure
subplot (3,1,1)
plot(x/pi,h)
title ('L = 11')
%% Part b
f s = 1000
L=11
x = linspace(0,2*pi*fs,300);
h = diric(x,L).*exp((-j*x*(L-1)/2));
subplot (3,1,2)
plot(x/pi,h)
title ('fs = 1000')
```

```
%% Part c

t = 0:1

xfunc = cos(2*pi*25*t) + sin(2*pi*250*t)

out = conv(xfunc, h)

% subplot(3,1,3)

% plot(t,out)

% title('x(t) input')

saveas(fig, 'Q2.png')

%% Part d
```

% Rectangular Window FIR Filter