



# HOMEWORK 4 (RUNTIME STACK, SCOPING, PARAMETER PASSING)

*CS 381, Spring 2019*

JUNE 16, 2019

PREPARED BY

ADAM STEWART (*stewaada*)

ANISH ASRANI (*asrania*)

LUCAS FREY (*freyl*)

MAZEN ALOTAIBI (*alotaima*)

SERGEI POLIAKOV (*poliakos*)

## CONTENTS

<b>1</b>	<b>Exercise 1. Runtime Stack</b>	<b>2</b>
<b>2</b>	<b>Exercise 2. Static and Dynamic Scope</b>	<b>2</b>
2.1	Which value will be assigned to z in line 12 under static scoping? . . . . .	3
2.2	Which value will be assigned to z in line 12 under dynamic scoping? . . . . .	3
<b>3</b>	<b>Exercise 3. Parameter Passing</b>	<b>4</b>
3.1	Call-by-Name . . . . .	4
3.2	Call-by Need . . . . .	4



```

10      { int y;
11          y := 13;
12          z := g(2);
13      };
14  };
15 };
16 }

```

## 2.1 Which value will be assigned to z in line 12 under static scoping?

```

1 { int x;                                {x:?}
2   int y;                                {y:?,x:?}
3   int z;                                {z:?,y:?,x:?}
4   x := 3;                                {z:?,y:?,x:3}
5   y := 7;                                {z:?,y:7,x:3}
6   { int f(int y) { return x*y };         {f:{},z:?,y:7,x:3}
7       int y;                             {y:?,f:{},z:?,y:7,x:3}
8       y := 11;                           {y:11,f:{},z:?,y:7,x:3}
9       { int g(int x) { return f(y) };     {g:{},y:11,f:{},z:?,y:7,x:3}
10           { int y;                       {y:?,g:{},y:11,f:{},z:?,y:7,x:3}
11               y := 13;                   {y:13,g:{},y:11,f:{},z:?,y:7,x:3}
12               z := g(2);                 {y:13,g:{},y:11,f:{},z:?,y:7,x:3}
                                           {x:2,y:13,g:{},y:11,f:{},z:?,y:7,x:3}
                                           {y:11,x:2,y:13,g:{},y:11,f:{},z:?,y:7,x:3}
                                           {y:13,g:{},y:11,f:{},z:33,y:7,x:3}
13           };
14       };
15 };
16 }

```

## 2.2 Which value will be assigned to z in line 12 under dynamic scoping?

```

1 { int x;                                {x:?}
2   int y;                                {y:?,x:?}
3   int z;                                {z:?,y:?,x:?}
4   x := 3;                                {z:?,y:?,x:3}
5   y := 7;                                {z:?,y:7,x:3}
6   { int f(int y) { return x*y };         {f:{},z:?,y:7,x:3}
7       int y;                             {y:?,f:{},z:?,y:7,x:3}
8       y := 11;                           {y:11,f:{},z:?,y:7,x:3}
9       { int g(int x) { return f(y) };     {g:{},y:11,f:{},z:?,y:7,x:3}
10           { int y;                       {y:?,g:{},y:11,f:{},z:?,y:7,x:3}
11               y := 13;                   {y:13,g:{},y:11,f:{},z:?,y:7,x:3}
12               z := g(2);                 {y:13,g:{},y:11,f:{},z:?,y:7,x:3}
                                           {x:2,y:13,g:{},y:11,f:{},z:?,y:7,x:3}
                                           {y:13,x:2,y:13,g:{},y:11,f:{},z:?,y:7,x:3}
                                           {y:13,g:{},y:11,f:{},z:26,y:7,x:3}
13           };
14       };
15 };
16 }

```

### 3 EXERCISE 3. PARAMETER PASSING

Consider the following block. Assume dynamic scoping.

```

1 { int y;
2   int z;
3   y := 7;
4   { int f(int a) {
5       y := a+1;
6       return (y+a)
7     };
8     int g(int x) {
9       y := f(x+1)+1;
10      z := f(x-y+3);
11      return (z+1)
12    }
13    z := g(y*2);
14  };
15 }
```

#### 3.1 Call-by-Name

```

1 { int y;           [<y:?>]
2   int z;           [<z:? ,y:?>]
3   y := 7;          [<z:? ,y:7>]
4   { int f(int a) {  [<f:{},<z:? ,y:7>]
5       y := a+1;
6       return (y+a)
7     };
8     int g(int x) {  [<g:{},f:{},<z:? ,y:7>]
9       y := f(x+1)+1;
10      z := f(x-y+3);
11      return (z+1)
12    }
13    z := g(y*2);    [<x:y*2>,<g:{},f:{},<z:? ,y:7>]
                    [<a:x+1>,<x:y*2>,<g:{},f:{},<z:? ,y:7>]
                    [<a:x+1>,<x:y*2>,<g:{},f:{},<z:? ,y:16>]
                    [<x:y*2>,<g:{},f:{},<z:? ,y:49>]
                    [<a:x-y+3>,<x:y*2>,<g:{},f:{},<z:? ,y:49>]
                    [<a:x-y+3>,<x:y*2>,<g:{},f:{},<z:? ,y:53>]
                    [<x:y*2>,<g:{},f:{},<z:109,y:53>]
                    [<g:{},f:{},<z:110,y:53>]
14  };
15 }
```

#### 3.2 Call-by Need

```

1 { int y;           [<y:?>]
2   int z;           [<z:? ,y:?>]
3   y := 7;          [<z:? ,y:7>]
4   { int f(int a) {  [<f:{},<z:? ,y:7>]
5       y := a+1;
```

```

6      return (y+a)
7  };
8  int g(int x) {  [<g:{},f:{}>,<z:?,y:7>]
9      y := f(x+1)+1;
10     z := f(x-y+3);
11     return (z+1)
12 }
13 z := g(y*2);  [<x:y*2>,<g:{},f:{}>,<z:?,y:7>]
                [<a:x+1>,<x:14>,<g:{},f:{}>,<z:?,y:7>]
                [<a:15>,<x:14>,<g:{},f:{}>,<z:?,y:16>]
                [<x:14>,<g:{},f:{}>,<z:?,y:32>]
                [<a:x-y+3>,<x:14>,<g:{},f:{}>,<z:?,y:32>]
                [<a:-15>,<x:14>,<g:{},f:{}>,<z:?,y:-14>]
                [<x:14>,<g:{},f:{}>,<z:-29,y:-14>]
                [<g:{},f:{}>,<z:-28,y:-14>]
14 };
15 }

```