Rainbow Cookie at VLSP 2026: Small Models, Long Laws

Trần Đức Lâm, Lê Vân Anh, Phạm Thị Khánh Linh, Nguyễn Thị Hiền Trang
University of Engineering and Technology,
Vietnam National University, Hanoi, Vietnam
tranduclam06@gmail.com, vananh9684@gmail.com
24022385@vnu.edu.vn, 24022470@vnu.edu.vn

Abstract

We describe our system for the VLSP 2026 shared task on document-level English–Vietnamese legal machine translation with models below 3 billion parameters. The system combines LoRA adaptation of Hy-MT2-1.8B on a processed legal corpus with a structure-aware Markdown pipeline. Adjacent legal prose is translated in blocks to retain local context, while deterministic checks identify structural failures and trigger one recovery round. Length-based batching and a GPU repetition guard control inference cost. On the public test set, the submitted configuration obtains 70.87 BLEU for English-to-Vietnamese and 47.44 BLEU for Vietnamese-to-English, taking 2.0 and 1.4 hours with approximately 5 GB peak allocated GPU memory per direction on a T4. Development comparisons examine model adaptation and node grouping, providing practical evidence for combining domain-specific training with structured inference under the task's resource constraints.

1 Introduction

Legal machine translation (MT) must preserve specialised terminology, rights, obligations, conditions and exceptions. Document structure also matters: article numbers, nested clauses, tables and signature blocks carry information that should survive translation. Long legal documents make these requirements difficult to satisfy within a small model's context window.

The VLSP 2026 shared task addresses English–Vietnamese legal MT with models below 3 billion parameters, fully local inference and no external APIs (VLSP 2026 Organizers, 2026). Evaluation considers translation quality, terminology correctness and consistency, legal accuracy, inference time and peak memory. We describe a system built around Hy-MT2-1.8B, adapted with LoRA (Hu et al., 2022) and deployed through a Markdown-aware translation pipeline.

Our system has two main components: (1) a cleaned and extended legal corpus with document-based splitting, alignment review and text normalisation; and (2) a pipeline that groups adjacent prose, checks structural constraints, retries failed units and detects repetitive generation on the GPU. Experiments compare two base models, their pipeline variants and their fine-tuned variants. The largest observed gain comes from fine-tuning with the pipeline fixed; a development experiment also favours grouped translation over one-node requests. These are system-development comparisons, with limitations discussed in Section 5.

2 Related Work

Translation models and resources. ALMA adapts LLMs through monolingual and parallel-data fine-tuning (Xu et al., 2024), while Tower combines continued pre-training and instruction tuning (Alves et al., 2024). Hy-MT2 provides a 1.8B translation model supporting 33 languages (Zheng et al., 2026). For English–Vietnamese, PhoMT offers 3.02 million sentence pairs (Doan et al., 2021), and MTet provides 4.2 million training pairs and EnViT5 models (Ngo et al., 2022). Our training units instead follow the structure of the task's legal documents.

Document-level and legal MT. Context-aware MT targets discourse phenomena such as deixis, ellipsis and lexical cohesion (Voita et al., 2019); document-level approaches are surveyed by Maruf et al. (2022), and Wang et al. (2023) study LLMs as document translators. Legal adaptation includes QLoRA tuning of IndicTrans2 (Singh et al., 2025) and domain-specific tuning on EU legislation (Lorini et al., 2026). Our contribution is a practical system integrating legal-data adaptation with Markdown preservation and bounded recovery. Its repetition guard addresses a known generation failure (Holtzman et al., 2020), with a rep-

etition penalty (Keskar et al., 2019) used on the recovery path.

3 Method

The system combines legal-data preparation, LoRA fine-tuning and structured inference.

3.1 Training Data Processing

Parallel Markdown documents are sliced at preamble, article, clause, adjacent-article and whole-document boundaries. A row pairs a slice with its translation. Processing (Fig. 1) expands the initial 54,134 rows from 575 training documents to 82,203 rows from 612 documents; the latter comprise 571 retained training documents and all 41 development documents, with four initial training documents absent after filtering. The final composition is given in Table 1. Training data come from organiser-provided data or are written by the authors, and we use no external parallel or monolingual corpora; 72 of the added terminology rows are taken from the public-test references (see Section 5).

Alignment review. We flag 237 slices with inconsistent document codes or large numbers, exclude 158 after manual review, and propagate removals to slices containing the same erroneous segment. Flags require review because numbers may be written differently across languages.

Text normalisation. We normalise Unicode to NFC, repair look-alike and legacy characters, remove invisible characters and unify Vietnamese tone placement on *oa*, *oe* and *uy*. The same normaliser processes inference sources.

Glossary and data split. A glossary of 442 bilingual pairs supplies training hints in 19,495 of 82,203 rows (23.7%). Co-occurrence in aligned training texts is checked automatically; this does not constitute a complete expert semantic review. Splitting is by document, keeping all slices together. The development split is later merged into training, while 23 documents held out from the task's training data (not among the 575) are used only for validation loss and a fixed fit check, never for training.

Extension and filtering. We add paragraph pairs, hand-written legal formula phrases and terminology pairs (Table 1). Further filtering uses LaBSE similarity on flagged pairs (Feng et al., 2022), length ratios, national-title consistency, amounts and list labels. Manual edits correct residual OCR/typing errors and standardise thousands separators and fine-amount expressions.

Component	Rows
Original rows after cleaning	50,129
Paragraph-level rows	30,658
Hand-written formula rows	654
Terminology rows (training data)	690
Terminology rows (public-test refs.)	72
Total	**82,203**

Table 1: Composition of the final training data.

3.2 Base Models and Fine-Tuning

We fine-tune Hy-MT2-1.8B (Zheng et al., 2026) and Index-Translate-2B (Li et al., 2026) on the processed corpus, freezing base weights and learning LoRA matrices in attention and MLP projections. Hy-MT2 uses two consecutive training passes; configurations are summarised in Appendix B.

Loss function. Let z be the tokenised training conversation and $\mathcal{I}$ its unmasked label positions. Supervised fine-tuning minimises

$$\mathcal{L}(\theta) = -\frac{1}{|\mathcal{I}|} \sum_{t \in \mathcal{I}} \log p_\theta(z_t \mid z_{<t}). \qquad (1)$$

Source/instruction and padding labels are masked: for Hy-MT2, the loss covers the response from the assistant separator through EOS; for Index, all tokens after the generation prompt. Neither uses label smoothing or an auxiliary loss.

Prompt. For Hy-MT2, a training row is eligible for glossary hints with probability 0.5. We retain pairs whose source and target terms both occur in the aligned texts and include up to eight, preferring longer phrases. Rows without selected matches use the default instruction, as does all inference. Index uses its native Chinese translation-only instruction. Appendix A gives the prompt format.

3.3 Document-Level Translation Pipeline

Figure 2 outlines parsing, grouping, batched generation, validation, recovery and assembly. All checks compare source and output; inference never reads references.

Parsing and grouping. A rule-based parser extracts headings, articles, clauses, prose, table cells and signatures while preserving a lossless partition of the raw Markdown. We call each parsed element a *node*; a *unit* is one generation request, which may hold several nodes, and a *prose block* is a unit of coalesced adjacent prose. Adjacent prose




Figure 1: Preparation of the supervised fine-tuning corpus.




Figure 2: Structured translation with one selective recovery round.

of the same scope is coalesced with newline separators and no explicit markers. New articles and higher-level sections create boundaries. Packing targets 768 source tokens or eight nodes, closing at a full-stop boundary; these are soft thresholds to avoid cutting sentences. Tables and signatures use separate handling.

Validation. Hard failures include empty/unmappable outputs, missing EOS, lost protected headings/labels, multiline table-cell outputs and severe repetition. Number mismatches, suspicious length ratios, possible untranslated text and modal/negation discrepancies are warnings, not proofs of semantic errors. Multi-node newline units require one non-empty output line per node; coalesced prose blocks permit internal reflow and retain protected member labels. These checks detect structural failures but cannot guarantee semantic completeness.

Recovery and selection. One recovery round splits failed units into smaller sentence-preserving pieces, targeting 256 source tokens. Failed multi-node newline units are retried independently. When a protected label is lost, the retry prepends an instruction to preserve the listed source labels. Recovery can increase the directional output allowance and applies a 1.15 repetition penalty after loops. Selection favours fewer hard failures, retaining the first pass on ties; complete alternative node outputs can fill gaps. Remaining partial outputs are flagged, and empty translations fall back to source text with a warning.

Illustrative example. An article heading and its clauses “1.” and “2.” can share a prose block. If the translation drops the protected label “2.”, validation triggers recovery on smaller, sentence-preserving pieces. Changed line breaks alone do not fail a coalesced prose block, since the check

targets structure rather than meaning.

Decoding, batching and repetition guard. Generation is greedy in fp16, with penalty 1.0 on the first pass. Length buckets reduce padding, and a calibration run on the T4 sets the batch size to eight. Every 32 steps after at least 64 generated tokens, a GPU detector examines the last 512 generated tokens. It stops exact consecutive suffix cycles of period 4–64 tokens with at least six repeats covering at least 64 tokens, except patterns repeated at least as often in the input prompt. Tables, signatures and EOS-finished sequences are exempt. Stopped outputs enter validation and bounded recovery; repeated text is not deleted. With s source tokens, the target allowance is

$$b(s) = \max(256, \lceil as \rceil + 128), \tag{2}$$

where $a = 1.25$ for first-pass VI→EN prose and $a = 2.5$ for EN→VI, protected tables/signatures and full-budget recovery. The actual allowance is bounded by prompt length, a 128-token margin and the sequence limit: normally 8,192 tokens, with a 16,384-token ceiling when preserving a whole sentence requires it.

4 Experiments

4.1 Experimental Setup

Data. Following the task's recommendation to select systems on the public test set (VLSP 2026 Organizers, 2026), we report local results on its 50 document pairs in both directions; official private-test scores are not included.

Fine-tuning. For a frozen projection $W_0 \in \mathbb{R}^{d\times k}$, LoRA learns $B \in \mathbb{R}^{d\times r}$ and $A \in \mathbb{R}^{r\times k}$:

$$W = W_0 + \frac{\alpha}{r} BA. \tag{3}$$

Hy-MT2 uses $r = 64$, $\alpha = 128$ and dropout 0.05 on q, k, v, o, gate, up and down projections: 77.6 million trainable parameters (Appendix C). The sample-length check uses the complete model-specific chat template:

$$n(x, y) = \left| \mathrm{Tok}(\mathrm{Chat}(P(x), y)) \right|. \tag{4}$$

Here $P(x)$ includes the instruction and optional terminology hints; the chat renderer includes all special tokens. Hy-MT2 rejects samples above 3,072 tokens rather than truncating them; none were dropped in the final run.

Inference. Each direction runs on one Kaggle T4 with Transformers, greedy fp16 decoding, batch size eight and one recovery round. LoRA weights are merged into the base model before inference, so the deployed model has 1.79B parameters, below the 3B limit; inference runs locally without external APIs. Appendix B lists the remaining settings.

Metrics. We use case-sensitive SacreBLEU with tokenizer 13a (Post, 2018) and chrF with character order six, word order zero and $\beta = 2$ (Popović, 2015). Each complete Markdown document is one metric segment: 50 hypothesis–reference pairs per direction, without line splitting. Scores aggregate corpus statistics, rather than averaging document scores. Lexical and Unicode content is retained; Windows CRLF is restored to LF. BLEU on the reported 0–100 scale is (Papineni et al., 2002)

$$\begin{aligned} \mathrm{BLEU} &= 100\,\mathrm{BP}\exp\Big(\tfrac{1}{4}\sum_{n=1}^{4}\log p_n\Big), \\ \mathrm{BP} &= \min(1, e^{1-r_{\mathrm{ref}}/c}), \end{aligned} \tag{5}$$

where p_n are corpus modified precisions in $[0, 1]$, and c, r_{ref} are hypothesis/reference token counts. SacreBLEU handles zero-match and empty-output cases. Likewise,

$$\mathrm{chrF}_\beta = 100\,\frac{(1+\beta^2)\mathrm{chrP}\,\mathrm{chrR}}{\beta^2\mathrm{chrP} + \mathrm{chrR}}, \tag{6}$$

where precision and recall are averaged over effective character n-gram orders and expressed as fractions. Whitespace is excluded under the default chrF configuration; a zero denominator yields zero.

Paired bootstrap resampling (Koehn, 2004) draws 50 documents with replacement and recomputes corpus scores on the same sampled documents for both systems:

$$\Delta_b = \mathrm{BLEU}_b(S_2) - \mathrm{BLEU}_b(S_1). \tag{7}$$

The 2.5th and 97.5th percentiles define a 95% interval. We use seed 42 and 1,000 paired resamples for grouping comparisons, plus 2,000 resamples for final-system BLEU intervals. The latter quantify document-sampling uncertainty, not an improvement over a baseline or variability across training seeds.

4.2 Results

Table 2 compares (1) paragraph-wise base-model translation, (2) the base model with the pipeline and (3) the fine-tuned model with the pipeline. For Hy-MT2, (1) uses sampling and (2)–(3) use greedy decoding, so (1)–(2) changes both decoding and

Model	System	EN→VI		VI→EN	
		BLEU	chrF	BLEU	chrF
Hy-MT2-1.8B	(1) Base, no pipeline	36.53 ± 0.02	64.78	28.87 ± 0.04	68.26
	(2) Base + pipeline	39.96	65.43	30.27	68.89
	(3) Fine-tuned + pipeline	**70.87**	**84.48**	**47.44**	**79.50**
Index-Translate-2B	(1) Base, no pipeline	43.96	68.74	31.22	70.55
	(2) Base + pipeline	45.49	69.26	32.38	71.15
	(3) Fine-tuned + pipeline	62.59	78.89	41.76	76.48

Table 2: Results on the public test set, 50 documents per direction. In row (1), Hy-MT2 translates paragraph by paragraph with sampling following its model card, and the value is the mean ± standard deviation over three seeds. Index uses greedy decoding, so the two (1) rows are not directly comparable.

Design	EN→VI		VI→EN	
	BLEU	chrF	BLEU	chrF
A: markers	68.70	83.24	46.37	79.01
B: no markers	**68.90**	**83.39**	**46.62**	**79.17**
C: separate	67.69	82.64	45.23	78.23

Table 3: Two grouping designs and per-node translation on a model fine-tuned on about 53.5 thousand training rows, in the first version of the pipeline. Settings: repetition penalty 1.05, batch size 4, one run per design.

System	Time (s)		GPU alloc. (GB)	
	EN→VI	VI→EN	EN→VI	VI→EN
(1)	∼4.0k	∼4.1k	5.41	4.90
(2)	8,111	5,326	5.34	5.15
(3)	7,229	4,871	4.96	5.25

Table 4: Hy-MT2 running time and peak allocated GPU memory per direction on one T4 (decimal GB). Systems follow Table 2; (1) is per seed.

pipeline. The (2)–(3) comparison measures fine-tuning with the pipeline fixed, without separating the effects of cleaning and augmentation.

Pipeline and fine-tuning. For Index, where decoding is fixed, the pipeline adds 1.53/1.16 BLEU; for Hy-MT2 the gain also reflects the change from sampling to greedy decoding. For Hy-MT2, the 95% paired bootstrap interval of the BLEU difference between (1) and (2) excludes 0 in both directions, though it covers the combined effect of decoding and pipeline. Fine-tuning yields the largest observed gain: Hy-MT2 improves from 39.96 to 70.87 BLEU for EN→VI and from 30.27 to 47.44 for VI→EN, and the interval of this difference also excludes 0. Index shows the same trend, so the conclusion does not rest on one model. The final-system BLEU intervals are [65.68, 74.24] for EN→VI and [42.30, 50.99] for VI→EN. VI→EN scores lower in BLEU than EN→VI for every system; we believe the gap is partly due to non-equivalent score scales, since the chrF difference between the directions is only about 5 points for the final system. Scores in opposite directions are not directly comparable, so we report them separately.

Model choice. Index has higher base scores, including row (2), where both models use greedy decoding with the pipeline. After fine-tuning, however, Hy-MT2 scores higher in both directions and is selected for submission. The remaining analyses use Hy-MT2.

Pipeline design. An earlier checkpoint trained on approximately 53.5k rows compares grouped translation with markers (A), grouping without markers (B) and separate node requests (C), as shown in Table 3. Both grouped variants score higher than C. B exceeds A by 0.20/0.25 BLEU for EN→VI/VI→EN and avoids marker handling; it motivates the final prose-block design. Paired 95% intervals for B−A are [0.05, 0.37] (EN→VI) and [−0.06, 0.68] (VI→EN); B−C intervals are [0.75, 1.52] and [0.61, 2.20]. Thus grouping improves on separate requests in both directions, whereas the marker-free advantage over A is uncertain for VI→EN. This earlier-pipeline experiment does not isolate every final-system component.

4.3 Cost

Table 4 reports full-public-set inference cost. The fine-tuned pipeline takes 7,229 s (2.0 h) for EN→VI and 4,871 s (1.4 h) for VI→EN, with 4.96/5.25 GB peak allocated GPU memory (decimal GB), measured by PyTorch; this excludes the CUDA context and allocator cache, so process-

level usage is higher. Timing excludes model loading and calibration. Recovery re-translates 138 of 2,899 EN→VI units (4.76%) and 326 of 3,086 VI→EN units (10.56%), splitting them into 836 and 1,443 smaller requests. Earlier grouping runs took 4.6/2.9 h; their different checkpoint and pipeline preclude isolating one optimisation.

Fine-tuning adds no cost: system (3) is faster than system (2) in both directions. Against (2), for EN→VI it needs fewer recovery requests (836 vs. 962) and leaves fewer unresolved units (26 vs. 110). For VI→EN it needs more recovery requests (1,443 vs. 1,147) but still leaves fewer unresolved units (208 vs. 241). System (1) is fast because it makes one call per paragraph and neither validates nor re-translates its output.

Unresolved units total 26/2,899 (0.90%) across 11 documents for EN→VI: 25 have protected-label failures and one a protected-heading failure. For VI→EN, 208/3,086 (6.74%) across 29 documents include 198 with protected-block-label failures, 11 with line-count mismatches, three with inline-label failures and one with a heading failure; categories overlap. Final diagnostics record no unresolved empty nodes, source fallbacks, missing-EOS or repetition hard failures in either direction. Thus these rates measure remaining structural-check failures, not measured omission rates; partial content and semantic omissions still require direct translation review.

5 Limitations and Discussion

Systems are selected on the public set following the task guidance, so the reported scores describe development performance rather than an independent evaluation. In addition, 72 training rows are terminology pairs taken from the public-test references, so the reported scores may be somewhat optimistic for unseen documents. Some misaligned pairs probably remain undetected in the training data. Validation-loss monitoring uses the internal held-out split. We report no official private-test rankings, no legal-accuracy or terminology scores and no neural or LLM-based metrics, although the official evaluation includes them.

Structural validation cannot establish semantic fidelity or document-wide terminology consistency, and unresolved blocks can retain partial or untranslated text. The VI→EN direction remains clearly below EN→VI in BLEU for every system in Table 2. Further evaluation should examine omissions, obligations, negation and terminology with domain experts. Additional ablations could separate cleaning/augmentation, decoding, grouping and recovery; inference-time glossary hints remain untested systematically. Tone-mark normalisation follows the older placement used in most training text; public-test references using the newer placement are not normalised, which can lower EN→VI scores on those documents.

6 Conclusion

Our VLSP 2026 submission combines legal-domain LoRA adaptation of Hy-MT2-1.8B with structured Markdown translation and selective recovery. It reaches 70.87/47.44 public-test BLEU for EN→VI/VI→EN with approximately 5 GB peak allocated GPU memory and 2.0/1.4 h per direction on a T4. These development results motivate a practical small-model pipeline, while independent legal-accuracy and generalisation evaluation remains necessary.

References

Duarte M. Alves, José Pombal, Nuno M. Guerreiro, Pedro H. Martins, João Alves, Amin Farajian, Ben Peters, Ricardo Rei, Patrick Fernandes, Sweta Agrawal, Pierre Colombo, José G. C. de Souza, and André F. T. Martins. 2024. Tower: An Open Multilingual Large Language Model for Translation-Related Tasks. arXiv:2402.17733.

Long Doan, Linh The Nguyen, Nguyen Luong Tran, Thai Hoang, and Dat Quoc Nguyen. 2021. PhoMT: A high-quality and large-scale benchmark dataset for Vietnamese-English machine translation. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 4495–4503. Association for Computational Linguistics.

Fangxiaoyu Feng, Yinfei Yang, Daniel Cer, Naveen Arivazhagan, and Wei Wang. 2022. Language-agnostic BERT sentence embedding. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 878–891. Association for Computational Linguistics.

Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. 2020. The Curious Case of Neural Text Degeneration. In *International Conference on Learning Representations*.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-Rank Adaptation of Large Language Models. In *International Conference on Learning Representations*.

Nitish Shirish Keskar, Bryan McCann, Lav R. Varshney, Caiming Xiong, and Richard Socher. 2019. CTRL: A Conditional Transformer Language Model for Controllable Generation. arXiv:1909.05858.

Philipp Koehn. 2004. Statistical significance tests for machine translation evaluation. In *Proceedings of the 2004 Conference on Empirical Methods in Natural Language Processing*, pages 388–395. Association for Computational Linguistics.

Tianjiao Li, Mengran Yu, Chenyu Shi, Lusheng Zhang, Qisi Chen, Yanshan Zhou, Ji Qi, Jingying Liu, Yuang Feng, Ziang Cui, and Tianxing Yan. 2026. IndexTranslate: A Multilingual Translation Model Family — Text, Speech, Controlled Dubbing, and Long-Document Translation. arXiv:2609.40181.

Valerio Lorini, Paula Vlaic, Ulascan Akbulut, and Daniele Marcoaldi. 2026. One size does not fit all: Why EU legislative translation demands domain-specific fine-tuning of LLMs. In *Proceedings of the 26th Annual Conference of the European Association for Machine Translation (Volume 1)*, pages 304–320. European Association for Machine Translation.

Sameen Maruf, Fahimeh Saleh, and Gholamreza Haffari. 2022. A survey on document-level neural machine translation: Methods and evaluation. *ACM Computing Surveys*, 54(2):1–36.

Chinh Ngo, Trieu H. Trinh, Long Phan, Hieu Tran, Tai Dang, Hieu Nguyen, Minh Nguyen, and Minh-Thang Luong. 2022. MTet: Multi-domain Translation for English and Vietnamese. arXiv:2210.05610.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pages 311–318. Association for Computational Linguistics.

Maja Popović. 2015. chrF: character n-gram F-score for automatic MT evaluation. In *Proceedings of the Tenth Workshop on Statistical Machine Translation*, pages 392–395. Association for Computational Linguistics.

Matt Post. 2018. A call for clarity in reporting BLEU scores. In *Proceedings of the Third Conference on Machine Translation: Research Papers*, pages 186–191. Association for Computational Linguistics.

Akoijam Jenil Singh, Loitongbam Sanayai Meetei, and Yumnam Surajkanta. 2025. Adapting IndicTrans2 for legal domain MT via QLoRA fine-tuning at JUST-NLP 2025. In *Proceedings of the 1st Workshop on NLP for Empowering Justice (JUST-NLP 2025)*, pages 142–147. Association for Computational Linguistics.

VLSP 2026 Organizers. 2026. Document-level legal machine translation with limited-parameter models. Association for Vietnamese Language and Speech Processing.

Elena Voita, Rico Sennrich, and Ivan Titov. 2019. When a good translation is wrong in context: Context-aware machine translation improves on deixis, ellipsis, and lexical cohesion. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 1198–1212. Association for Computational Linguistics.

Longyue Wang, Chenyang Lyu, Tianbo Ji, Zhirui Zhang, Dian Yu, Shuming Shi, and Zhaopeng Tu. 2023. Document-level machine translation with large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 16646–16661. Association for Computational Linguistics.

Haoran Xu, Young Jin Kim, Amr Sharaf, and Hany Hassan Awadalla. 2024. A Paradigm Shift in Machine Translation: Boosting Translation Performance of Large Language Models. In *International Conference on Learning Representations*.

Mao Zheng, Zheng Li, Tao Chen, Bo Lv, Mingrui Sun, Mingyang Song, Jinlong Song, Hong Huang, Decheng Wu, Hai Wang, Yifan Song, Yanfeng Chen, and Guanwei Zhang. 2026. Hy-MT2: A Family of Fast, Efficient and Powerful Multilingual Translation Models in the Wild. arXiv:2605.22064.

A Prompts

For Hy-MT2, the user-turn inference prompt is:

```
Translate the following text
into {tgt}. Note that you should
only output the translated
result without any additional
explanation:

{src}
```

Here `tgt` is English or Vietnamese. Terminology training prompts prepend `Reference the following translations:`, newline-separated `source translates to target` pairs and a blank line; the instruction uses `must ONLY` instead of `should only`. Inference supplies neither glossary hints nor target history. Index uses its Chinese translation-only instruction with thinking disabled.

B Hyperparameters

Table 5 records the Hy-MT2 training and submitted inference configuration. Hy-MT2 trains first on approximately 53.5k rows and then on 82,203 rows. Base revisions are `9a341cd1b679` (Hy-MT2) and `a516854233b1` (Index); the final Hy-MT2 adapter SHA-256 starts with `30b5fc68a31c`.

Setting	Hy-MT2 value
LoRA	$r = 64$, $\alpha = 128$, dropout 0.05; q/k/v/o and gate/up/down
Schedule	1 epoch/pass; LR 2×10^{-4} then 5×10^{-5}; second pass: 2,569 steps, 25 warm-up steps, cosine decay to 10%
Training	fp16 DDP, two T4s; batch $1\times16\times2 = 32$; max length 3,072; weight decay 0; clipping 1; seed 42
Decoding	greedy fp16; batch 8; penalty 1.0, or 1.15 after a loop; one recovery round
Packing	prose 768 tokens/8 nodes (soft); tables 384/16; signatures 128; recovery 256 tokens
Budget	Eq. (2); context 8,192, sentence ceiling 16,384; margin 128
Repetition	GPU check every 32 generated steps, minimum 64 tokens
Runtime	torch 2.11.0+cu128; Transformers 5.8.1; tokenizers 0.22.2
Scoring	SacreBLEU 2.6.0; BLEU: 13a, mixed case, exponential smoothing; chrF: order 6, $\beta = 2$, word order 0, no whitespace

Table 5: Hy-MT2 training and inference settings. Runtime versions refer to the submission run.

C Computing the Number of LoRA Parameters

Each adapted projection contributes $r(d_{\text{in}} + d_{\text{out}})$ weights. For L identical layers and projection set $\mathcal{M}$,

$$N_{\text{LoRA}} = L \sum_{m\in\mathcal{M}} r(d_{\text{in}}^{(m)} + d_{\text{out}}^{(m)}), \tag{8}$$

$$\rho = \frac{N_{\text{LoRA}}}{N_{\text{base}} + N_{\text{LoRA}}}. \tag{9}$$

For Hy-MT2, $L = 32$, $r = 64$; q/o shapes are 2048×2048, k/v 512×2048, gate/up 6144×2048, and down 2048×6144. Thus $N_{\text{LoRA}} = 77{,}594{,}624$ and $\rho = 77{,}594{,}624/(1{,}791{,}080{,}448 + 77{,}594{,}624) \approx 4.15\%$. Relative to frozen base weights alone, the ratio is 4.33%.