

## MySQL JSON

JSON abbreviated as **JavaScript Object Notation**. It is a **lightweight data-interchange format** similar to other data types and can be easily read and write by humans. It can also be parsed and generate by machines easily.

Generally, the [JSON](#) data type supports two structures:

- A collection of name/value pairs chain, which acts as a data array.
- An ordered list of values.

Since it manages the individual values in a **name-value pair chain** that acts as a data array, we can retrieve the whole field using a single command. This useful feature allows us to retrieve the data in a large system quickly.

### Why we use JSON?

JavaScript Object Notation (JSON) is a standard text-based format for representing structured data based on JavaScript object syntax. It is commonly used for transmitting data in web applications

e.g., Sending some data from the server to the client, so it can be displayed on a web page, or vice versa.

### Advantages Of JSON :

The following are the advantages that the JSON data type gives over storing JSON-format strings:

- The JSON columns allow us to store the automatic validation of JSON documents. Otherwise, we will get an error.
- Optimized/Fast storage format means when the server reads a JSON value stored in binary format, it does not need to parse from a text representation. The binary format allows searching values within JSON documents directly with a key or array indexes without reading whole values.

The storage space required for the JSON document is roughly the same as the storage requirements for **LOB** and **TEXT**.

We can define the JSON data type column in the MySQL table using the following syntax :

```
CREATE TABLE table_name(  
    ...  
    json_column_name JSON,  
    ...  
);
```

### Example to create the table :

```
CREATE TABLE events  
(  
    id int auto_increment primary key,  
    event_name varchar(255),  
    visitor varchar(255),  
    properties json,  
    browser json  
)
```

### Example to insert the data:

```
INSERT INTO events(event_name, visitor,properties, browser)
VALUES (
  'pageview',
  '1',
  '{ "page": "/" }',
  '{ "name": "Safari", "os": "Mac", "resolution": { "x": 1920, "y": 1080 } }'
),
('pageview',
'2',
'{ "page": "/contact" }',
'{ "name": "Firefox", "os": "Windows", "resolution": { "x": 2560, "y": 1600 } }'
),
(
  'pageview',
  '1',
  '{ "page": "/products" }',
  '{ "name": "Safari", "os": "Mac", "resolution": { "x": 1920, "y": 1080 } }'
),
(
  'purchase',
  '3',
  '{ "amount": 200 }',
  '{ "name": "Firefox", "os": "Windows", "resolution": { "x": 1600, "y": 900 } }'
),
(
  'purchase',
  '4',
  '{ "amount": 150 }',
  '{ "name": "Firefox", "os": "Windows", "resolution": { "x": 1280, "y": 800 } }'
),
(
  'purchase',
  '4',
  '{ "amount": 500 }',
  '{ "name": "Chrome", "os": "Windows", "resolution": { "x": 1680, "y": 1050 } }'
);
```

### Reading Data

1. We can run a simple [SELECT statement](#) to see the data in the table.  
Select \* from tablename;
2. To pull values out of the JSON columns, you use the column path operator ( ->).

#### Example :

```
SELECT id, browser->'$.name' browser
FROM events;
```

3. To remove the quote marks, you use the inline path operator (->>) as follows:

**Example :**

```
SELECT id, browser->>'$.name' browser
FROM events;
```

or

**for multiple columns :**

```
SELECT id, browser ->> '$.name' field1, browser ->> '$.os' field2 FROM events;
```

or

**for multiple columns with where condition from JSON field:**

```
SELECT id, browser ->> '$.name' field1, browser ->> '$.os' field2 FROM events
where browser ->> '$.name' = 'Chrome';
```

or

**Select with where condition**

```
SELECT id, browser FROM events where browser ->> '$.name' = 'Chrome';
```

4. When used in combination with the JSON\_EXTRACT(), you can retrieve the values for the specified column.

**Example:**

```
SELECT event_name, JSON_EXTRACT(browser, '$.name') FROM events;
```

## Update JSON Data in MySQL

We can update data in JSON fields with the JSON\_INSERT(), JSON\_REPLACE(), and JSON\_SET() functions. These functions also require a path expression to specify which parts of the JSON object to modify. The output of these functions is a valid JSON object with the changes applied.

| Requirement   | Function     |
|---|--------------|
| Add a new key and value                                   | JSON_INSERT  |
| Update a value for an existing key                        | JSON_REPLACE |
| Add a new key and value or update an existing key's value | JSON_SET     |

### JSON\_INSERT

A member not present in an existing object. The member is added to the object and associated with the new value.

```
-- update events set browser = JSON_INSERT(browser,'$.version','4.0') where id =1;
-- update events set browser = JSON_INSERT(browser,'$.version','4.0' , '$.year','2000' )
  where id=1;
-- update events set browser = JSON_INSERT(browser,'$.resolution.z','4000') where id =1;
```

## JSON\_REPLACE

Replaces existing values in a JSON document and returns the result.

```
-- update events set browser = JSON_Replace(browser, '$.os', 'Macc') where id = 1;
```

## JSON\_SET

Inserts or updates data in a JSON document and returns the result.

```
-- update events set browser = json_set(browser, '$.os', 'Mac', '$.rating', '5') where id =1;
```

## Deleting the records

- We can delete data in JSON fields with the JSON\_REMOVE() function and DELETE.
- JSON\_REMOVE() : function returns the updated JSON after removing the specified key based on the path expression.
- Using JSON\_REMOVE function, it is possible to remove the screen key/value pairs from product:
- There are two DELETE operations you can do when working with JSON fields:
  - delete an attribute from a JSON field
  - delete a row from your table

### 1. delete a row from your table

```
--- delete from events where json_extract(browser, '$.os') = 'Mac';
```

### 2. delete an attribute from a JSON field

```
-- update events set browser = json_remove(browser, '$.rating') where id =3;
```

## JSON FUNCTIONS

### o JSON\_APPEND -

- Append data to JSON document
- Appends values to the end of the indicated arrays within a JSON document and returns the result. This function was renamed to [JSON\\_ARRAY\\_APPEND\(\)](#)

#### Example :

```
select json_array_append(browser, '$.name', 'Firefox') from events where id =3;
```

### o JSON\_INSERT

#### Example:

```
update events set browser = JSON_INSERT(browser, '$.resolution.z', '4000') where id =1;
```

### o JSON\_LENGTH

#### Example:

```
select json_length(browser) from events where id =3;
```

### o JSON\_MERGE()

#### Example:

select json\_merge(browser,properties) from events where id =3;

o **JSON\_PRETTY()**

**Example:**

select json\_pretty(browser) from events where id =3;

o **JSON\_REMOVE()**

**Example:**

update events set browser = json\_remove(browser,'\$.rating') where id =3;

o **JSON\_REPLACE()**

**Example:**

update events set browser = JSON\_Replace(browser , '\$.os','Macc') where id = 1;