TAKEOFF DISTANCE SHORT FIELD

CONDITIONS : Flaps up — Full throttle prior to brake release — Paved, level, dry runway — Zero wind

Maximum Weight	IAS		Pressure Altitude		0°C		10°C		20°C		30°C		40°C	
kg	Lift Off	At 15 m	ft	m	Ground Roll m	Total to Clear 15 m Obs m	Ground Roll m	Total to Clear 15 m Obs m	Ground Roll m	Total to Clear 15 m Obs m	Ground Roll m	Total to Clear 15 m Obs m	Ground Roll m	Total to Clear 15 m Obs m
1043	96 km/h	109 km/h	Sea level		219	396	236	424	255	454	273	485	293	518
	52 kt	59 kt	1000	305	241	433	259	465	279	497	299	532	320	568
	60 MPH	68 MPH	2000	610	264	474	283	509	305	546	328	584	352	626
			3000	914	290	521	312	559	335	600	361	645	387	690
			4000	1219	319	573	343	617	369	663	396	712	427	765
			5000	1524	351	632	378	683	407	735	437	791	469	852
			6000	1829	386	708	416	757	450	817	483	882	520	953
			7000	2134	427	782	460	844	497	914	535	989	576	1071
			8000	2438	472	875	511	948	550	1029	593	1119	639	1216

NOTES :

1. Short field technique as specified in Section 4.
2. Prior to takeoff from fields above 1000 ft - 914 m elevation, the mixture should be leaned to give maximum RPM in a full throttle, static runup.
3. Decrease distances 10 % for each 9 knots headwind. For operation with tailwinds up to 10 knots, increase distances by 10 % for each 2 knots.
4. For operation on a dry, grass runway, increase distances by 15 % of the "ground roll" figure.

5. SLOPE ± 10 % TOOK 1st SLOOP
6. WET GRASS + 45°