

Statement Blocks

- A Compound statement (or block) is a set of statements enclosed in braces

```
{  
    int x = 5;  
    double y = readDouble("y: ");  
    println("y = " + y);  
}
```

- Variable's *scope* is block in which it is declared
- **Scope**: lifetime of variable
 - When the variable is available to be used

if statement

- General form: **if** (*condition*) {
 statements }
 }
- Any boolean condition/variable

```
if ((num % 2) == 0)           // can omit braces
    println("num is even"); // if one statement
```

```
if ((num % 2) == 0) {
    println("num is even");
    println("Oh, and Beat Cal!");
}
```

- Use braces with **if** with more than one statement
- Good idea to use braces (block) even if there is only one statement in the **if**

if-else statement

- **General form:** **if** (*condition*) {
 statements
 }**else** {
 statements
 }

```
if ((num % 2) == 0) {
    println("num is even");
} else {
    println("num is odd");
    println("and so are you");
}
```

Cascading **if**

```
if (score >= 90) {  
    println("A");  
} else if (score >= 80) {  
    println("B");  
} else if (score >= 70) {  
    println("C");  
} else {  
    println("Bad Times");  
}
```

switch statement

```
int day = readInt("Day of week as int: ");
switch (day) {
    case 0:
        println("Sunday");
        break;
    case 6:
        println("Saturday");
        break;
    default:
        println("Weekday");
        break;
}
```

for loop

- General form:

```
for (init ; condition ; step) {  
    statements  
}
```

- *init* done once at start of loop
- *condition* checked before every iteration through loop
 - we execute *statements* if condition is true
- *step* every time through loop after *statements*

for loop

- **Example:**

```
for (int i = 0; i < 5; i++) {  
    println(i);  
}
```



0
1
2
3
4

- As computer scientists, we count starting at 0

for loop

- **Another Example:**

```
for (int i = 6; i > 0; i -= 2) {  
    println(i);  
}
```



6
4
2

- Note that 0 is not displayed!

while loop

- General form:

```
while ( condition ) {  
    statements  
}
```

- *condition* checked before every iteration through loop
 - we execute *statements* if condition is true

while loop

- **Example:**

```
int x = 15;  
while (x > 1) {  
    x /= 2;  
    println(x) ;  
}
```

```
7  
3  
1
```

Loop and a half ?!

```
public class Add extends ConsoleProgram {  
  
    // Constant value for SENTINEL  
    private static final int SENTINEL = 0;  
  
    public void run() {  
        int total = 0;  
  
        int val = readInt("Enter val:");  
        while (val != SENTINEL) {  
            total += val;  
            val = readInt("Enter val:");  
        }  
        println("Total = " + total);  
    }  
}
```

Loop and a half ?!

```
public class Add extends ConsoleProgram {  
  
    // Constant value for SENTINEL  
    private static final int SENTINEL = 0;  
  
    public void run() {  
        int total = 0;  
  
        do {  
            int val = readInt("Enter val:");  
            if (val != SENTINEL) {  
                total += val;  
            }  
        } while (val != SENTINEL);  
        println("Total = " + total);  
    }  
}
```

for versus while

```
for (init ; test ; step) {  
    statements  
}
```

- **for** loop used for *definite* iteration
- Generally, we know how many times we want to iterate

```
init  
while ( test ) {  
    statements  
    step  
}
```

- **while** loop used for *indefinite* iteration
- Generally, don't know how many times to iterate beforehand