BEGA

Postfach 3160 · 58689 Menden
Hennenbusch 1 · 58708 Menden
info@bega.com · www.bega.com
Phone +49 2373 966-0

Contact Person:
Mohamed Irfan
mohamed.irfan@bega.com
Phone

BEGA Gantenbrink-Leuchten KG · Postfach 3160 · 58689 Menden

Light Technologies Comp.
Limited (Head Office)
Mr. Yaseen Shariff
P.O. Box 75727
Riyadh 11588
SAUDI-ARABIEN

Quotation

Quotation Number:	11652666
Customer Number:	1002283
Date:	2026.02.25
Your enquiry dated:	2026.02.25
Object:	688526
Page:	1 / 9

Object: 688526 Wadi Safar Montage Hotel - Exterior Wadi Safar
Your enquiry Wadi Safar Montage Hotel - Exterior dated 2026.02.25

Dear Mr. Shariff,

We thank you for your enquiry and are pleased to provide you with the following quotation on the basis of our current technical data and the Terms of Delivery and Sale printed in our catalogues:

Quotation 11652666

Unless otherwise stated, the luminaires offered below correspond to the luminaires in standard version.
Data sheets can be found on the BEGA website.
Please check whether the technical specifications like the maximum ambient temperature of the luminaires are suitable for your application. If modifications are required, we will be glad to check the technical feasibility.

Item 1.0 LE01

Special version 24082S **45 Piece(s)**

BEGA Recessed wall luminaire 24082, modified:

- LED 2700 K
- CRI 90
- Luminaire luminous flux approx. 95 lumen
- DALI 2 power suply unit in external device box
  with approx. dimensions 273 × 84 × 46 mm
- with connecting cable between luminaire and device box,
length approx. 1000 mm

Please note that the device box has protection class IP 65 and is supplied with two cable glands for connecting cables Ø 4-10 mm.

IMPORTANT INFORMATION:
==========
Due to the dimensions of the external device box for the DALI LED driver the device box does not fit into the recessed opening of the luminaire!

Shielded light. LED, 2.7 W Luminaire connected wattage, L With replaceable BEGA LED module with overheating protection and an expected service life of at least 50,000 operating hours. 20 years warranty of availability of LED module and wear parts. Without power supply unit. Protection class IP 65. Luminaire cover made of cast bronze. Luminaire housing made of stainless steel. Safety glass, frosted. Dimensions dia. 85 x 22 x 90 mm. Luminaire for installation in a recessed opening whose dimensions are dia. 71 x 90 mm, or in installation housing 10415.

Net price per unit Piece(s):

Delivery time: 9 Week(s) **562.60** Euro

excl. VAT

Item 2.0

Installation housing 10415 **45 Piece(s)**

BEGA Installation housing 10415 for mounting recessed wall luminaires in walls made of concrete or plastered masonry. Installation housing made of aluminium. One cable entry for power connecting cable up to 10.5 mm in diameter, max. 3 x 1.5 qmm. Dimensions: Ø 80 x 105 mm. Recessed opening Ø 71 mm.

Net price per unit Piece(s):

Delivery time: stocked, subject to being unsold **52.70** Euro

excl. VAT

Item 3.0 LE01 ALT

Alternative **45 Piece(s)**
Special version 22369S
BEGA Recessed wall luminaire 22369, modified:

- LED 2700 K
- CRI 90
- Luminaire luminous flux approx. 100 lumen
- DALI 2 power suply unit in external device box with approx. dimensions 273 × 84 × 46 mm
- with connecting cable between luminaire and device box, length approx. 1000 mm
- Special lacquering colour RAL fine structure

Please note that the device box has protection class IP 65 and is supplied with two cable glands for connecting cables Ø 4-10 mm.

IMPORTANT INFORMATION:
==========
Due to the dimensions of the external device box for the DALI LED driver the device box does not fit into the recessed opening of the luminaire!

Shielded light. LED, 2.7 W luminaire connected wattage, With replaceable BEGA LED module with overheating protection and an expected service life of at least 50,000 operating hours. 20 years warranty of availability of LED module and wear parts. Protection class IP 65, Luminaire made of cast aluminium, aluminium and stainless steel Safety glass with optical texture. Dimensions dia. 80 x 80 x 20 mm. Luminaire for installation in a recessed opening whose dimensions are dia. 71 x 90 mm, or in installation housing 10415.

Net price per unit Piece(s):
Delivery time: 9 Week(s) **373.60** Euro
excl. VAT

Item 4.0

Alternative **45 Piece(s)**
Installation housing 10415
BEGA Installation housing 10415 for mounting recessed wall luminaires in walls made of concrete or plastered masonry. Installation housing made of aluminium. One cable entry for power connecting cable up to 10.5 mm in diameter, max. 3 x 1.5 qmm. Dimensions: Ø 80 x 105 mm. Recessed opening Ø 71 mm.

Net price per unit Piece(s):
Delivery time: stocked, subject to being unsold **52.70** Euro
excl. VAT

Item 5.0 LB01

++++++++++
DALI 2 = standard
++++++++++

Special version 84691S **551 Piece(s)**
BEGA Bollard head 84691, modified:

- LED 2700 K
- CRI 90
- Luminaire luminous flux approx. 770 lumen

Shielded with reflector, light emission 360°. Dark Sky: Luminous flux in the upper half-space < 1%. For usage in the modular system bollard range. Suitable for bollard tube 220 qmm. LED, 27.5 W Luminaire connected wattage, With replaceable BEGA LED module with an average rated service life of > 200.000 operating hours (L80B50 at ta = 25 °C). 20 years warranty of availability for the LED module and wear parts. With BEGA Ultimate Driver® LED power supply unit, DALI 2 controllable, 220-240 V, 0/50-60 Hz. Protection class IP 65. Luminaire head of cast aluminium, aluminium and stainless steel, colour graphite. Borosilicate glass. With connecting cable X05BQ-F 5 G 1 mm², length 1,4 m. Dimensions: 220 x 220 x 190 mm.

Net price per unit Piece(s):
Delivery time: 9 Week(s) **787.30** Euro
excl. VAT

Item 6.0

++++++++++++
Tyrol Pine is standard!
++++++++++++

Bollard tube 84467 **551 Piece(s)**
BEGA Bollard tube 84467 for BEGA system bollards. Accoya® wood and aluminium, colour graphite. For usage in the modular LED bollard concept. Without door, with integral connection box 71084. For through-wiring for 2 cables up to 7 x 6 qmm qmm with with micro fuse 6,3 A. With mounting plate for bolting onto a foundation or onto anchorage unit 70896. Dimensions: 220 x 220 mm. Height above ground: 875 mm.

Net price per unit Piece(s):
Delivery time: 14 Week(s) **1,158.40** Euro
excl. VAT

Item 7.0

Anchorage unit 70896 **551 Piece(s)**

BEGA Anchorage unit 70896, made of hot-dip galvanised steel, according to EN ISO 1461. Length 500 mm. A wielded construction comprises a bottom plate, tube and flange plate with threaded bushes with fixing screws M8 x 25 made of stainless steel, Steel grade number: 1.4301, lateral cable entry 70 x 30 mm. For fixing luminaires and luminaire poles with baseplate in the ground.

Net price per unit Piece(s):

Delivery time: 9 Week(s) **85.80** Euro

excl. VAT

Item 8.0 LB03

++++++++++
DALI 2 = standard
++++++++++

Sonderausführung 85312S **248 Piece(s)**

BEGA On-ground luminaire 85312, modified´:

- LED 2700 K
- CRI 90
- Luminaire luminous flux approx. 225 lumen
- With custom made pattern

Shielded light. LED, 4.8 W Luminaire connected wattage, Luminaire luminous flux 227 lm, colour temperature 2700 K. Colour rendering index (CRI) > 80. With replaceable BEGA LED module with an average rated service life of > 50.000 operating hours (L80B50 at ta = 25 °C). 20 years warranty of availability for the LED module and wear parts. With BEGA Ultimate Driver® LED power supply unit, DALI 2 controllable , 220-240 V, 0/50-60 Hz. Protection class IP 65. Luminaire made of cast aluminium, aluminium and stainless steel, colour Bronze. Safety glass, clear. Inner metal sheeting, colour gold. Without door. Two cable entries for through-wiring power connecting cable up to ø 8-15 mm in diameter. With mounting plate for bolting onto a foundation or onto the connection housing 71246. Dimensions: 145 x 145 x 375 mm.

Net price per unit Piece(s):

Delivery time: 9 Week(s) **743.50** Euro

excl. VAT

Item 8.1

Connection housing 71246 **248 Piece(s)**

BEGA Connection housing 71246 for the installation of on-ground luminaires on unpaved surfaces. Connection housing made of steel, hot-dip galvanised in compliance with EN ISO 1461. Adapter plate made of stainless steel, Material no.: 1.4301. 3 threaded inserts with mounting bolts M8 x 25 made of stainless steel, Pitch circle diameter 132 mm. 3 threaded inserts with mounting bolts M6 x 25 made of stainless steel, Pitch circle diameter 70 mm.

Net price per unit Piece(s):

Delivery time: stocked, subject to being unsold **99.80** Euro

excl. VAT

Item 9.0 LB05

++++++++++
DALI 2 = standard
Tyrol Pine = standard
++++++++++

Special version 85293S **86 Piece(s)**

BEGA Bollard 85293, modified:

- LED 2700 k
- CRI 90
- R9 = 56
- Luminaire luminous flux approx. 735 lumen
- Special lacquering Antique Bronze

IMPORTANT INFORMATION:
==========
For this luminaire type the R9 value is maximum 56.
There is no other suitable LED chip available with
an R9 value larger than 60.

Shielded light. Dark Sky: Luminous flux in the upper half-space < 1%. BEGA Constant Optics® : An efficient optical system that is virtually impervious to wear and tear. LED, 9.2 W Luminaire connected wattage, With replaceable BEGA LED module with an average rated service life of > 200.000 operating hours (L80B50 at ta = 25 °C). 20 years warranty of availability for the LED module and wear parts. With BEGA Ultimate Driver® LED power supply unit, DALI 2 controllable , 220-240 V, 0/50-60 Hz. Protection class IP 65. Vertical tube made of Accoya® wood and aluminium, metal components are powder coated and painted. Luminaire housing made of cast aluminium, aluminium and stainless steel. Safety glass. Reflector made of pure anodised aluminium. Connection box with 2 cable entries for through-wiring of the mains supply cable from ø 8-17 mm, max. 5 x 4 qmm. With mounting plate for bolting onto a foundation or onto anchorage unit 70895. Dimensions: 160 x 160 mm. Height of luminaire above ground 1040 mm.

Net price per unit Piece(s):

Delivery time: 9 Week(s) **1,822.60** Euro

excl. VAT

Item 10.0

Anchorage unit 70895 **86 Piece(s)**

BEGA Anchorage unit 70895, made of hot-dip galvanised steel, according to EN ISO 1461. Length 400 mm. A wielded construction comprises a bottom plate, tube and flange plate with threaded bushes with fixing screws M8 x 25 made of stainless steel, Steel grade number: 1.4301, lateral cable entry 70 x 30 mm. For fixing luminaires and luminaire poles with baseplate in the ground.

Net price per unit Piece(s):

Delivery time: stocked, subject to being unsold **71.90** Euro

excl. VAT

Item 11.0 LB06

++++++++++++
DALI 2 = standard
++++++++++++

Special version 84751S **480 Piece(s)**

BEGA Garden and pathway luminaire 84751, modified:

- LED 2700 K
- CRI 90
- Luminaire luminous flux 779 lummen
- Special lacquering colour RAL fine structure

Shielded light. Dark Sky: Luminous flux in the upper half-space < 1%. Rotationally symmetrical light distribution. BEGA Constant Optics® : An efficient optical system that is virtually impervious to wear and tear. LED, 8.9 W Luminaire connected wattage, With replaceable BEGA LED module with an average rated service life of > 200.000 operating hours (L80B50 at ta = 25 °C). 20 years warranty of availability for the LED module and wear parts. With LED power supply unit, DALI 2 controllable, 220-240 V, 0/50-60 Hz. Protection class IP 65. Luminaire made of cast aluminium, aluminium and stainless steel BEGA Unidure® coating technology , colour graphite. Safety glass, clear. Without door. Connection box with 2 cable entries for through-wiring of the mains supply cable from ø 8-17 mm, max. 5 x 4 qmm. With mounting plate for bolting onto a foundation or onto anchorage unit 70894. Standing tube diameter 110 mm, Luminaire head diameter 250 mm. Height above ground 550 mm.

Net price per unit Piece(s):

Delivery time: 9 Week(s) **782.80** Euro

excl. VAT

Item 11.1

Anchorage unit 70894 **480 Piece(s)**

BEGA Anchorage unit 70894, made of hot-dip galvanised steel, according to EN ISO 1461. Length 400 mm. A wielded construction comprises a bottom plate, tube and flange plate with threaded bushes with fixing screws made of stainless steel M6 x 16, Steel grade number: 1.4301, lateral cable entry 50 x 30 mm. For fixing luminaires and luminaire poles with baseplate in the ground.

Net price per unit Piece(s):

Delivery time: stocked, subject to being unsold **65.60** Euro

excl. VAT

Please note that the a/m prices have been calculated on the quantity enquired. In case the quantity is reduced or in case of partial orders, the price might increase.

Prices:
EXW, net in EURO per piece
Luminaires complete with LED

Delivery:
ex works Menden
Outer packing will be charged separately!

Payment:
100 % advance

Please consider that additional costs that may arise for example for certification or legalization, etc. will be invoiced at actual price.

Delivery:	as agreed
Price validity:	Prices refer to the quantity stated and are based on our pricelist of 2025.04.01. They are valid until 2026.03.31.

Please note that the above mentioned delivery periods are non-binding.
The delivery date will be checked based on current conditions and material availability when the order is placed.
Our prices do not cover installation.

Our delivery terms available at www.bega.de/terms-of-delivery apply.

We hope that our quotation meets your approval and remain

Yours faithfully,

BEGA Gantenbrink-Leuchten KG

i. A. Mohamed Irfan