Swagger Supported by SMARTBEAR

Select a definition: ACU API Gateway v1

ACU API Gateway

v1 OAS 3.0

/swagger/v1/swagger.json

ACU Container REST API – C# edition

Acu

- GET `/api/health` Health check — used by bots and the UI to detect if the ACU is reachable.
- GET `/api/acu/devices` Fetch all registered devices, each annotated with its current workflow assignment.
- POST `/api/acu/accept/{deviceId}` Approve a pending device.
- POST `/api/acu/reject/{deviceId}` Reject a pending device.
- GET `/api/acu/device-status/{deviceId}` Read the latest telemetry snapshot of a device.
- POST `/api/acu/instructions/{deviceId}` Send an instruction to an approved, online robot.

Acu.ApiGateway

- GET `/ws/bot/{deviceId}`

bot

- POST `/api/bot/register` Robot registers itself with the ACU.
- GET `/api/bot/registration-status/{deviceId}` Robot polls its own registration state.

DELETE /api/bot/unregister/{deviceId}

POST /api/bot/device-status/{deviceId} Robot sends live telemetry (battery, location, etc.).

GET /api/bot/instructions/{deviceId} Robot polls for its registration status and latest instruction.

GET /api/bot/workflow/{deviceId}
Returns the full workflow assigned to this device. The bot should call this after receiving `approved` status and whenever it needs to reload its workflow definition.

Camera

GET /camera-prototype

Parameters Cancel

No parameters

Execute Clear

Responses

Curl

```
curl -X 'GET' \
  'http://10.27.239.122:3000/camera-prototype' \
  -H 'accept: */*'
```

Request URL

```
http://10.27.239.122:3000/camera-prototype
```

Server response

Code	Details
200	Response body

Code

```
    let busy = false;
    let connecting = false;
    let timer = null;
    let continuousFramesSaved = 0;

    function createArchive(batch) {
      const encoder = new TextEncoder();
      const parts = [];
      const modified = Math.floor(Date.now() / 1000);
      for (const frame of batch) {
        const header = new Uint8Array(512);
        const text = (offset, value) => header.set(encoder.encode(value), offse
t);
        const octal = (offset, length, value) => text(offset, value.toString(8).p
adStart(length - 1, '0') + '\0');
        text(0, frame.filename);
        octal(100, 8, 420);
        octal(108, 8, 0);
        octal(116, 8, 0);
        octal(124, 12, frame.blob.size);
        octal(136, 12, modified);
```

Download

Response headers

```
content-length: 13362
content-type: text/html
date: Fri,23 Oct 2026 11:33:34 GMT
last-modified: Fri,23 Oct 2026 09:03:02 GMT
server: Kestrel
```

Responses

Code	Description	Links
200	OK	*No links*

POST /api/camera/frames

GET /api/camera/frames

GET /api/camera/latest

GET /api/camera/frames/{id}

Map APIs

POST /api/bot/destinations/{deviceId} Store the destination list for a device.

GET /api/bot/destinations/{deviceId} Returns the stored destination list for a device.

Robot camera feeds

GET	`/api/acu/robots/{robotId}/cameras/front/stream`	Watch front camera as multipart MJPEG. Open the URL in a browser or an MJPEG client, not Swagger Try it out.
GET	`/api/acu/robots/{robotId}/cameras/tray-1/stream`	Watch tray camera 1 (native layer 0) as multipart MJPEG.
GET	`/api/acu/robots/{robotId}/cameras/tray-2/stream`	Watch tray camera 2 (native layer 1) as multipart MJPEG.
GET	`/api/acu/robots/{robotId}/cameras/front/latest`	Get the latest fresh front-camera JPEG; 503 if no frame has arrived in ten seconds.
GET	`/api/acu/robots/{robotId}/cameras/tray-1/latest`	Get the latest fresh tray-1 JPEG (native layer 0).
GET	`/api/acu/robots/{robotId}/cameras/tray-2/latest`	Get the latest fresh tray-2 JPEG (native layer 1).
GET	`/api/acu/robots/{robotId}/cameras/front/frames`	List retained front-camera images, newest first.
GET	`/api/acu/robots/{robotId}/cameras/tray-1/frames`	List retained tray-1 images, newest first.
GET	`/api/acu/robots/{robotId}/cameras/tray-2/frames`	List retained tray-2 images, newest first.
GET	`/api/acu/robots/{robotId}/cameras/front/frames/{id}`	Download a retained front-camera JPEG by ID.
GET	`/api/acu/robots/{robotId}/cameras/tray-1/frames/{id}`	Download a retained tray-1 JPEG by ID.
GET	`/api/acu/robots/{robotId}/cameras/tray-2/frames/{id}`	Download a retained tray-2 JPEG by ID.

Robot microphone clips

POST	`/api/bot/{deviceId}/microphone-clips`	Share a ten-second WAV from an approved robot after explicit operator consent.
GET	`/api/acu/robots/{deviceId}/microphone-clips`	List shared recordings for a robot, newest first. Does not start recording.

GET `/api/acu/robots/{deviceId}/microphone-clips/latest`
Download the latest saved WAV. While Stream is on, a new clip arrives after each recording/upload cycle.

GET `/api/acu/robots/{deviceId}/microphone-clips/{id}`
Download a recorded ten-second mono PCM16 WAV (16 kHz).

DELETE `/api/acu/robots/{deviceId}/microphone-clips/{id}`
Delete a shared clip permanently. Unauthenticated: coordinate deletions with organizers.

Settings

GET `/api/acu/settings` Returns the ACU settings.

PUT `/api/acu/settings` Replaces the ACU settings.

Workflows

POST `/api/acu/robot-workflows/media`
Upload media for PWA workflows only and return its ACU REST path.

GET `/api/bot/robot-workflows/media/{name}`
Stream uploaded PWA workflow media with seeking support.

GET `/api/acu/robot-workflows` List robot-schema workflows separately from legacy workflows.

GET `/api/acu/robot-workflows/{id}` Read a robot-schema workflow.

PUT `/api/acu/robot-workflows/{id}`
Update a robot-schema workflow without changing legacy workflows.

DELETE `/api/acu/robot-workflows/{id}` Delete a robot-schema workflow.

GET `/api/acu/robot-workflows/assignments`
List unfinished in-memory assignments in the workflow schema document shape.

POST `/api/acu/robot-workflows/{id}/assignments/{deviceId}`
Assign a robot workflow snapshot over REST only.

DELETE `/api/acu/robot-workflows/assignments/{deviceId}`
Remove only the separate robot workflow assignment.

GET `/api/bot/robot-workflows/{deviceId}/workflow`
Return the robot's assignment in the workflow.schema.json document shape.

POST `/api/bot/robot-workflows/{deviceId}/workflow/start` Start the current schema workflow.

POST `/api/bot/robot-workflows/{deviceId}/workflows/{workflowId}/complete`
Complete a workflow identified by WorkflowID and RobotId, without a run JSON payload.

POST `/api/workflows/robot`
Create a workflow in the workflow.schema.json format and persist it to the robot workflows file.

GET `/api/workflows` List all saved workflows.

POST `/api/workflows` Create a new workflow. Fails if a workflow with the same id already exists.

PUT `/api/workflows/{id}` Update an existing workflow (matched by id).

DELETE `/api/workflows/{id}` Delete a workflow (and clear any assignments referencing it).

GET `/api/workflows/assignments` Get the device→workflow assignment map.

PUT `/api/workflows/assignments/{deviceId}` Assign a workflow to a device.

DELETE `/api/workflows/assignments/{deviceId}` Remove a device's workflow assignment.

Schemas

- AcuSettings
- AssignmentRequest
- ButtonAction
- CameraFrame

CreateMicrophoneClipRequest ›

Destination ›

InstructionRequest ›

MapDestination ›

MicrophoneClipResponse ›

ProblemDetails ›

RegisterRequest ›

RobotWorkflow ›

RobotWorkflowButtons ›

RobotWorkflowData ›

RobotWorkflowMedia ›

RobotWorkflowStep ›

UnregisterRequest ›

Workflow ›

WorkflowDataEntry ›

WorkflowStep ›