

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title>Valentine </title>
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<style>
body {
margin: 0;
height: 100vh;
background: linear-gradient(135deg, #ff9a9e, #fad0c4);
display: flex;
justify-content: center;
align-items: center;
font-family: Arial, sans-serif;
overflow: hidden;
}
.card {
background: white;
padding: 30px;
border-radius: 20px;
text-align: center;
box-shadow: 0 10px 30px rgba(0,0,0,0.2);
width: 90%;
max-width: 350px;
position: relative;
}
h1 {
color: #ff4d6d;
margin-bottom: 25px;
}
button {
padding: 12px 25px;
font-size: 16px;
border: none;
border-radius: 25px;
cursor: pointer;
}
.yes {
background: #ff4d6d;
color: white;
}
.no {
background: #ddd;
position: absolute;
left: 20px;
top: 120px;
}
</style>
</head>
<body>
<div class="card">
<h1> yourname, will you be my Valentine? </h1>
<button class="yes" onclick="yesClick()">Yes </button>
<button class="no" id="noBtn">No </button>
</div>
<script>
```

```

const noBtn = document.getElementById("noBtn");
const card = document.querySelector(".card");
function randomMove() {
  const maxX = card.clientWidth - noBtn.offsetWidth;
  const maxY = card.clientHeight - noBtn.offsetHeight;
  const x = Math.random() * maxX;
  const y = Math.random() * maxY;
  noBtn.style.left = x + "px";
  noBtn.style.top = y + "px";
}

// No button keeps moving
setInterval(randomMove, 700);
function yesClick() {
  document.body.innerHTML = `
<div style="
display:flex;
flex-direction:column;
justify-content:center;
align-items:center;
height:100vh;
background:#ff9a9e;
color:white;
text-align:center;
padding:20px;
">

<h1> Yayyy yourname! I knew it </h1>



</div>`;
}
</script>
</body>
</html>

```