
Matt Bachmeier

Table of Contents

3.1 Image analysis using 2D DFT	1
3.2 Image filtering	3
3.3 Image filter using the DFT	4
4.1 Image restoration	5
4.1a generate blurred image	6
4.1b deblurring using inverse filtering	7
4.1c deblurring in frequency domain	8
4.1d deblurring in frequency domain (improved)	9
4.1e deblurring noisy blurred image	10
4.2a extract the LSB bit plane of an image	12
4.3a 2D DCT	13
4.3b Block DCT transform	14
4.3c applying quantization	15
4.4d decompression	16



Lab 8 Image processing and compression 4/30/2017

3.1 Image analysis using 2D DFT

```
clear all
close all

load cameraman.mat
figure(1)
imagesc(x)
colormap(gray)
axis('square')
figure(2)
spec_x = fft2(x);
imagesc(fftshift(log10(abs(spec_x))));
colormap(gray)
axis('square')

% <= enter matlab code here
```



3.2 Image filtering

```
% you should turn in 4 figures. the first one will use the title
'after
% horizontal filtering' the second with title 'after vertical
  filtering'.
% The third one with title 'after lowpass filtering' The fourth one
  with
% title 'abs(x-LPF(x))'

h_h = [1/4 1/4; -1/4 -1/4];
h_v = [1/4 -1/4; 1/4 -1/4];
h_lp = [1/4 1/4; 1/4 1/4];


y_h = conv2(x, h_h, 'same');
figure,
subplot(2,2,1), imagesc(y_h); colormap('gray'); axis square
title('After horizontal filtering');

y_v = conv2(x, h_v, 'same');
subplot(2,2,2), image(y_v); colormap('gray'); axis square
title('After vertical filtering');

y_lp = conv2(x, h_lp, 'same');
subplot(2,2,3), image(y_lp); colormap('gray'); axis square
title('After lowpass filtering');

diff1 = abs(x-y_lp);
subplot(2,2,4), image(diff1); colormap('gray'); axis square
title('abs(x-LFP(x))');

% <= enter matlab code here
```




3.3 Image filter using the DFT

you should submit 1 figure with title 'abs(x-LPT(x)) via DFT'

```
fftx = fft2(x);
fft_hlp = fft2(h_lp, 256,256);
filtered_image = fftx.*fft_hlp;
LPT_DFT = ifft2(filtered_image);

diff2 = abs(x - LPT_DFT);
figure,
imagesc(diff2); colormap(gray); axis square
title('abs(x-LPT(x)) via DFT');

% <= enter matlab code here
```




4.1 Image restoration

```
% load blur.mat and display it with title 'original image'

clear all

load blur.mat
load nimes_france.mat
figure,
imagesc(x); colormap('gray'); axis square
title('original image');

% <= enter matlab code here
```




4.1a generate blurred image

```
% display the blurred image with title 'blurred image'

blurred_image = conv2(h,x);

figure,
imagesc(blurred_image); colormap('gray'); axis square
title('blurred image');

% <= enter matlab code here
```



4.1b deblurring using inverse filtering

```
% remember to use 'same' in conv2 to ensure the image after
convolution
% has the same size.
% submit 1 figure with title 'after deblurring with invh'


load blurinv.mat

tic
deblurred_image = conv2(blurred_image, invh, 'same');
toc

figure,
imagesc(deblurred_image); colormap('gray'); axis square
title('after deblurring with invh');

% <= enter matlab code here

Elapsed time is 0.042919 seconds.
```



4.1c deblurring in frequency domain

```
% the division is performed element by element using ./ operator.
% denote the recovered image Xrecovery
% submit 1 figure with title 'after deblurring in frequency domain'
% print elapse time and compare it against that in 4.1b (longer?
  shorter?)
```

```
fft_blurred = fft2(blurred_image);
fft_blurring = fft2(h, 553, 553);


tic
deblurred_DFT = fft_blurred./fft_blurring;
Xrecovery = ifft2(deblurred_DFT);
toc
```

```
%Using the frequency domain method is faster than the convolution
  method
```

```
figure,
imagesc(Xrecovery); colormap('gray'); axis square
title('after deblurring in frequency domain');
```

```
% <= enter matlab code here
```

```
Elapsed time is 0.032033 seconds.
```


4.1d deblurring in frequency domain (improved)

```
% submit 1 figure with title 'after deblurring in frequency domain and
% shifting'
% Image name to be used: Xrecovery1
N = length(Xrecovery);

shift = exp(-j*2*pi*21/N*(0:N-1))'*exp(-j*2*pi*21/N*(0:N-1));
Xrecovery1 = real(ifft2(fft2(Xrecovery).*shift));

figure,
imagesc(Xrecovery1); colormap('gray'); axis square
title('after deblurring in frequency domain and shifting');

% <= enter matlab code here
```



4.1e deblurring noisy blurred image

```
% generate the blurred image plus noise as instructed in the handout.
% part I. apply deblurring method in 4.1d. submit the result with
title
% 'deblurring in frequency domain with noise'
% Also comment on the result.
```

```
y = conv2(x,h, 'same') + randn(size(x));
```

```
N = length(y);
```

```
fft_blurred = fft2(y);
fft_blurring = fft2(h, 512, 512);
deblurred_DFT = fft_blurred./fft_blurring;
Xrecovery2 = ifft2(deblurred_DFT);
```

```
shift = exp(-j*2*pi*21/N*(0:N-1))*exp(-j*2*pi*21/N*(0:N-1));
Xrecovery3 = real(ifft2(fft2(Xrecovery2).*shift));
```

```
figure,
imagesc(abs(Xrecovery3)); colormap('gray'); axis square
title('deblurring in frequency domain with noise');
```


```
%This image looks much more blurry and has more static than the
    previously
%deblurred image using the DFT.


% <= enter matlab code here

% Part II. repeat part I but with suggested improvement in handout.
    submit
% the result with title 'deblurring in frequency domain with noise
% (modified)'

Xrecovery4 = fft_blurred.*conj(fft_blurring)./(abs(fft_blurring).^2 +
    0.01);
figure,
imagesc(abs(ifft2(Xrecovery4))); colormap('gray'); axis square
title('deblurring in frequency domain with noise (modified)');

% <= enter matlab code here
```






4.2a extract the LSB bit plane of an image

```
% load cam_wm.mat in which an image called y.  
% to extract least significant bit, note that each pixel is an integer  
% with  
% value between 0 to 255 ( $2^8 - 1$ ). The LSB determines if the value is  
% an  
% odd number (LSB = 1) or an even number (LSB=0).  
% if y is an even number, then  $y - 2*\text{floor}(y/2) = 0$  where  $\text{floor}(x)$  is  
% the  
% largest integer smaller than x. If y is an odd number,  
%  $y - 2*\text{floor}(y/2) = 1$   
% to check, if  $y = 4$ ,  $4 - 2*\text{floor}(4/2) = 0$ . If  $y = 5$ ,  $5 - 2*\text{floor}(5/2) =$   
%  $5 - 2*2 =$   
% 1. Use this method you can find the LSB for each pixel of the image.  
% the  
% matrix of the LSB value form a binary image (contains 0 or 1).  
% submit 1 figure of the LSB image with title 'the water mark at the  
% LSB'  
  
load cam_wm.mat  
water_mark = y - 2*floor(y/2);  
figure,  
imagesc(water_mark); colormap('gray'); axis square  
title('the water mark at the LSB');
```

% <= enter matlab code here




4.3a 2D DCT

display DCT basis. follow the instruction in the handout. Watch out for the quotation marks for text strings.
submit 1 figure title '2D DCT Basis function'

```
figure,
N=8;
for m=1:N
    for n=1:N
        e=zeros(N,N);
        e(m,n)=1;
        b = idct2(e);
        subplot(8,8,m+(n-1)*N)
        imagesc(b)
        colormap(gray)
        set(gca,'Xtick',[])
        set(gca,'Ytick',[])
        axis('square')
    end
end
```

% <= enter matlab code here



4.3b Block DCT transform

submit two subplots, subplot(1,2,1) title 'original image' subplot(1,2,2), title 'magnitude of DCT coefficients'


```
load cameraman.mat

[M,N] = size(x);
Mblocks = M/8;
Nblocks = N/8;
% compute DCT of 8x8 subimages
for m = 1:Mblocks
    for n=1:Nblocks
        Mrange = (m-1)*8+1:(m-1)*8+8;
        Nrange = (n-1)*8+1:(n-1)*8+8;
        block = x(Mrange,Nrange);
        DCTblock = dct2(block);
        y(Mrange,Nrange) = DCTblock;
    end
end

figure,
subplot(1,2,1)
imagesc(x); colormap('gray'); axis square
title('original image');
```

```
subplot(1,2,2)
imagesc(y); colormap('gray'); axis square
title('Magnitude of DCT coefficients');

% <= enter matlab code here
```



4.3c applying quantization

remember the quantization may be applied to each element in the DCT coefficient matrix. print out compression ratio

```
% quantization matrix
Q = [16 11 10 16 24 40 51 61;
     12 12 14 19 26 58 60 55;
     14 13 16 24 40 57 69 56;
     14 17 22 29 51 87 80 62;
     18 22 37 56 68 109 103 77;
     24 35 55 64 81 104 113 92;
     49 64 78 87 103 121 120 101;
     72 92 95 98 112 100 103 99];

yquantized=zeros(M,N); % initialize quanized DCT coefficients
% quantize each DCT coefficient
for m = 1:Mblocks
    for n=1:Nblocks
        Mrange = (m-1)*8+1:(m-1)*8+8;
```

```

        Nrange = (n-1)*8+1:(n-1)*8+8;
        quantized_DCTblock = round(y(Mrange,Nrange)./Q);
        yquantized(Mrange,Nrange)=quantized_DCTblock;
    end
end

% Now compute non-zero quantized DCT coefficients
nNZ=sum(sum(double(abs(yquantized >0))))); % number of non-zero
entries.
CR = 100*nNZ/(M*N);
fprintf('Compression ratio = %g \n', CR)

% <= enter matlab code here

Compression ratio = 8.26263

```

4.4d decompression

IDCT needs to be applied block by block submit 1 figure title ('decompressed image')

```

xdecompressed=zeros(M,N);
% Finally reconstruct x from yquantized
for m = 1:Mblocks
    for n=1:Nblocks
        Mrange = (m-1)*8+1:(m-1)*8+8;
        Nrange = (n-1)*8+1:(n-1)*8+8;
        block = yquantized(Mrange,Nrange);
        IDCTblock = idct2(block);
        xdecompressed(Mrange,Nrange) = IDCTblock;
    end
end

figure,
imagesc(xdecompressed),colormap('gray'),axis square
title('decompressed image')

% <= enter matlab code here

```




Published with MATLAB® R2016a