

Fondamenti di Basi di Dati per Intelligenza Artificiale Generativa

Programma Dettagliato - 8 Settimane (60 ore totali)

FILOSOFIA DEL CORSO

Messaggio centrale: "L'AI generativa non è magia - è matematica applicata a DATI. Questo corso vi insegna a gestire il carburante che alimenta l'AI."

Approccio: Ogni concetto database → Applicazione AI immediata

SETTIMANA 1: Database e AI - Il Fondamento Necessario

Lezione 1: Perché l'AI Ha Bisogno di Database (3 ore)

Parte 1: Il Ruolo dei Dati nell'AI (1.5h)

- **Opening provocatorio:**
 - Demo live: ChatGPT che "allucina" vs ChatGPT con RAG
 - Domanda: "Cosa fa la differenza?" → DATI BEN ORGANIZZATI
- **Training data pipeline:**
 - Come GPT-4 è stato addestrato: miliardi di righe in database
 - Stable Diffusion: database di immagini + metadata
 - Come Netflix raccomanda film: database + AI
- **Types of data in AI:**
 - Training data (storico, immutabile)
 - Production data (real-time, transazionale)
 - User data (conversazioni, preferenze)
 - Model metadata (versioni, performance)
- **Case study:**
 - Midjourney: 100M+ immagini organizzate in database
 - Come cercano "un gatto steampunk" tra miliardi di dati?

Parte 2: Panoramica Ecosistema Database (1.5h)

- **Traditional SQL Databases:**

- Quando: dati strutturati, transazioni, consistency
- AI use case: user management, analytics, logs
- **NoSQL Databases:**
 - Quando: dati non strutturati, scalabilità, flessibilità
 - AI use case: training data storage, JSON responses
- **Vector Databases (preview):**
 - Quando: similarity search, embeddings
 - AI use case: RAG systems, semantic search
 - Demo rapida: Pinecone o Chroma
- **Cloud Database Services:**
 - AWS RDS, DynamoDB, Azure Cosmos DB
 - Perché le aziende AI usano cloud database

Lab (45 min):

- Setup ambiente: DB Browser for SQLite
- Esplorare sample database "AI Training Logs"
- Identificare strutture dati tipiche AI apps

Homework: Research un'AI application famosa e identificare che tipo di database potrebbe usare (es: Spotify, Netflix, ChatGPT)

Lezione 2: Organizzazione Dati - Tabelle e Relazioni (3 ore)

Parte 1: Database Relazionali Basics (1.5h)

- **Concetti fondamentali:**
 - Tabelle = spreadsheets strutturati
 - Righe (records) vs Colonne (fields)
 - Schema: la "blueprint" del database
- **AI Context:**
 - Tabella "Users" per AI chatbot
 - Tabella "Conversations" con user_id
 - Tabella "Prompts" con metadata

- Tabella "Model_Outputs" per logging
- **Tipi di dato rilevanti AI:**
 - TEXT: prompt, responses, descriptions
 - INTEGER: IDs, counters, ratings
 - FLOAT: scores, embeddings (accenno)
 - DATETIME: timestamps cruciali per AI
 - BLOB: immagini, file (cenni)

Parte 2: Relazioni tra Tabelle (1.5h)

- **One-to-Many:**
 - Un utente → molte conversazioni
 - Un model → molti outputs
 - Una categoria → molte immagini generate
- **Many-to-Many:**
 - Utenti ↔ Progetti AI
 - Prompts ↔ Tags
 - Training examples ↔ Labels
- **Primary Keys e Foreign Keys:**
 - Perché cruciali per integrità dati
 - Come linkare tabelle
 - Esempi AI pratici

Lab (45 min):

- Design su carta: Database per "AI Image Generator"
 - Tabelle: Users, Images, Prompts, Styles, Generations
- Identificare relazioni
- Peer review dei design

Homework: Design database per un chatbot AI (Users, Conversations, Messages, Feedback)

Lezione 3: DBMS e Componenti (2 ore)

Parte 1: Cos'è un DBMS (1h)

- **Definizione e funzioni:**
 - Database Management System
 - Query processor
 - Storage engine
 - Transaction manager
- **Perché non usare file Excel/CSV:**
 - Concurrent access (multi-user)
 - Data integrity
 - Query optimization
 - Backup e recovery
- **DBMS popolari:**
 - SQLite: embedded, perfetto per prototipare
 - PostgreSQL: open source, potente, estensibile
 - MySQL: diffuso, web applications
 - MongoDB: NoSQL, flessibile

Parte 2: DBMS nel Contesto AI (1h)

- **PostgreSQL + pgvector:**
 - Estensione per vector embeddings
 - Usato da molte startup AI
- **MongoDB:**
 - Storage JSON responses da LLM
 - Flexible schema per dati AI
- **Redis:**
 - Caching responses AI (velocità!)
 - Session management chatbot
- **Cloud-managed DBMS:**
 - AWS RDS (gestito, scalabile)
 - Supabase (PostgreSQL + API instant)
 - MongoDB Atlas

Demo Live:

- Creare database SQLite locale
 - Inserire dati sample "AI conversations"
 - Mostrare come query veloce vs file search
-

Lezione 4: Progettazione ER - Modellare i Dati (3 ore)

Parte 1: Entity-Relationship Diagrams (1.5h)

- **Entities:** "cose" nel nostro dominio
 - User, Prompt, Image, Model, Conversation
- **Attributes:** proprietà delle entities
 - User: id, email, created_at, tier
 - Prompt: id, text, user_id, timestamp, tokens
- **Relationships:** come entities si collegano
 - User "has many" Prompts
 - Prompt "generates" Image
 - User "rates" Image
- **Cardinalità:**
 - 1:1, 1:N, N:M
 - Esempi pratici AI

Parte 2: ER per AI Applications (1.5h)

- **Case Study 1: AI Chatbot**
 - Entities: User, Conversation, Message, Feedback
 - ER diagram completo
- **Case Study 2: Image Generation Platform**
 - Entities: User, Project, Image, Prompt, Style
 - Relazioni complesse
- **Case Study 3: RAG System**
 - Entities: Document, Chunk, Embedding, Query, Response
 - Come modellare il flusso RAG

Lab (45 min):

- Gruppi di 3: Design ER per una delle seguenti app AI:
 1. AI Video Generator con prompts e styles
 2. Code Assistant con project context
 3. AI Content Moderation system
- Presentazione rapida (5 min per gruppo)

Homework: Completare ER diagram del progetto gruppo + documentazione

Lezione 5: Normalizzazione e Best Practices (2 ore)

Parte 1: Concetti di Normalizzazione (1h)

- **Perché normalizzare:**
 - Ridurre ridondanza
 - Evitare anomalie (insert, update, delete)
 - Ottimizzare storage
- **1NF, 2NF, 3NF** (concetti, non formule):
 - 1NF: Atomic values, no repeating groups
 - 2NF: No partial dependencies
 - 3NF: No transitive dependencies
- **AI Context:**
 - Prompt template separato da prompt instances
 - User profile separato da user activity
 - Model metadata separato da model runs

Parte 2: Design Patterns per AI Data (1h)

- **Temporal data:**
 - Tracking changes nel tempo (versioning prompts)
 - Audit logs per AI decisions
- **Metadata management:**
 - Tags, categories per AI assets
 - Flexible schema con JSONB (PostgreSQL)

- **Performance considerations:**
 - Quando denormalizzare per speed
 - Trade-offs in AI applications (speed vs consistency)

Lab pratico:

- Analizzare database "mal progettato" per AI app
 - Identificare problemi
 - Proporre normalizzazione
-

WEEKEND PROJECT - Settimana 1

Deliverable: Database Design Document per un'AI Application

Scegliere uno scenario:

1. AI Writing Assistant con history e templates
2. AI Art Gallery con generations e collections
3. AI Code Review Tool con projects e feedback

Documento include:

- ER Diagram completo
- Schema tabelle (nomi, tipi dato, constraints)
- Descrizione relazioni
- Giustificazione design choices
- Casi d'uso principali

Presentazione: Lunedì Settimana 2 (10 min per studente/gruppo)

SETTIMANA 2: SQL Fundamentals - Data Definition Language

Lezione 1: Introduzione a SQL e CREATE (3 ore)

Parte 1: SQL Overview (1h)

- **Cos'è SQL:**
 - Structured Query Language

- Standard per database relazionali
- Linguaggio dichiarativo (cosa, non come)
- **SQL Categories:**
 - DDL: Data Definition (CREATE, ALTER, DROP)
 - DML: Data Manipulation (INSERT, UPDATE, DELETE)
 - DQL: Data Query (SELECT)
 - DCL: Data Control (GRANT, REVOKE)
- **SQL per AI Engineers:**
 - Setup schema per AI apps
 - CRUD operations su training data
 - Query analytics su model performance
 - Backup e migration

Parte 2: CREATE DATABASE e CREATE TABLE (2h)

- **CREATE DATABASE** (SQLite: attach database)

```
sql

-- Per PostgreSQL/MySQL
CREATE DATABASE ai_chatbot_prod;
```

- **CREATE TABLE syntax completa:**

```
sql
```



```
CREATE TABLE users (  
  user_id INTEGER PRIMARY KEY AUTOINCREMENT,  
  email TEXT NOT NULL UNIQUE,  
  username TEXT NOT NULL,  
  created_at DATETIME DEFAULT CURRENT_TIMESTAMP,  
  subscription_tier TEXT DEFAULT 'free'  
);  
  
CREATE TABLE conversations (  
  conversation_id INTEGER PRIMARY KEY AUTOINCREMENT,  
  user_id INTEGER NOT NULL,  
  title TEXT,  
  created_at DATETIME DEFAULT CURRENT_TIMESTAMP,  
  model_version TEXT DEFAULT 'gpt-4',  
  FOREIGN KEY (user_id) REFERENCES users(user_id)  
);  
  
CREATE TABLE messages (  
  message_id INTEGER PRIMARY KEY AUTOINCREMENT,  
  conversation_id INTEGER NOT NULL,  
  role TEXT NOT NULL CHECK(role IN ('user', 'assistant', 'system')),  
  content TEXT NOT NULL,  
  tokens_used INTEGER,  
  timestamp DATETIME DEFAULT CURRENT_TIMESTAMP,  
  FOREIGN KEY (conversation_id) REFERENCES conversations(conversation_id)  
);
```

Lab (1h):

Esercizio Guidato: Creare database per "AI Image Generator"

- Tabella users
- Tabella prompts (con user_id FK)
- Tabella generated_images (con prompt_id FK)
- Tabella image_ratings (user feedback)

Challenge: Aggiungere tabelle per:

- Style presets
- Generation history con parametri (steps, cfg_scale, seed)

Parte 1: Tipi di Dato SQL (1.5h)

Numerici:

- INTEGER: IDs, counters, ratings (1-5)
- REAL/FLOAT: scores (0.0-1.0), probabilities
- DECIMAL: prezzi (se monetization)

Testo:

- TEXT: prompts, responses, descriptions (unlimited in SQLite)
- VARCHAR(n): email, username (limited)
- CHAR(n): fixed (codes, tags)

Temporal:

- DATETIME: timestamps cruciali per AI
- DATE: solo data
- TIME: solo ora

Binari (cenni):

- BLOB: embeddings, immagini small
- Meglio: store path, file in object storage (S3)

JSON (PostgreSQL/MySQL):

- JSONB: metadata flessibili AI

```
sql
```

```
generation_params JSONB -- {steps: 50, cfg_scale: 7.5, seed: 42}
```

Parte 2: Constraints per Data Integrity (1.5h)

PRIMARY KEY:

```
sql
```

```
user_id INTEGER PRIMARY KEY AUTOINCREMENT
```

FOREIGN KEY:

```
sql
```

```
FOREIGN KEY (user_id) REFERENCES users(user_id)
ON DELETE CASCADE -- Delete conversations if user deleted
ON UPDATE CASCADE
```

NOT NULL:

```
sql
```

```
email TEXT NOT NULL -- Email obbligatoria
```

UNIQUE:

```
sql
```

```
email TEXT UNIQUE -- No duplicate emails
```

CHECK:

```
sql
```

```
rating INTEGER CHECK(rating BETWEEN 1 AND 5)
model_name TEXT CHECK(model_name IN ('gpt-4', 'claude-3', 'llama-2'))
```

DEFAULT:

```
sql
```

```
created_at DATETIME DEFAULT CURRENT_TIMESTAMP
status TEXT DEFAULT 'pending'
```

AI-Specific Constraints Examples:

```
sql
```

```
CREATE TABLE ai_generations (  
  generation_id INTEGER PRIMARY KEY,  
  user_id INTEGER NOT NULL,  
  prompt TEXT NOT NULL CHECK(length(prompt) >= 3),  
  negative_prompt TEXT,  
  steps INTEGER DEFAULT 50 CHECK(steps BETWEEN 1 AND 150),  
  cfg_scale REAL DEFAULT 7.5 CHECK(cfg_scale BETWEEN 1.0 AND 20.0),  
  seed INTEGER,  
  model_version TEXT DEFAULT 'stable-diffusion-xl',  
  status TEXT DEFAULT 'pending' CHECK(status IN ('pending', 'processing', 'completed', 'failed')),  
  created_at DATETIME DEFAULT CURRENT_TIMESTAMP,  
  completed_at DATETIME,  
  image_path TEXT,  
  generation_time_seconds REAL,  
  FOREIGN KEY (user_id) REFERENCES users(user_id) ON DELETE CASCADE  
);
```

Lab (1h):

Hands-on: Creare schema completo per AI Text-to-Speech service

- Users table
- Voice models table
- Text inputs table
- Audio outputs table (con constraints appropriati)

Lezione 3: INSERT, UPDATE, DELETE (3 ore)

Parte 1: INSERT - Popolare Dati (1h)

INSERT single row:

```
sql  
  
INSERT INTO users (email, username, subscription_tier)  
VALUES ('alice@example.com', 'alice_ai', 'pro');
```

INSERT multiple rows:

```
sql
```

```
INSERT INTO users (email, username, subscription_tier) VALUES
('bob@example.com', 'bob_dev', 'free'),
('charlie@example.com', 'charlie_creator', 'enterprise'),
('diana@example.com', 'diana_artist', 'pro');
```

INSERT with auto-generated ID:

```
sql

INSERT INTO conversations (user_id, title, model_version)
VALUES (1, 'Debug my Python code', 'gpt-4');
-- conversation_id auto-generated
```

INSERT ... SELECT (advanced):

```
sql

-- Copy successful generations to archive
INSERT INTO archived_generations
SELECT * FROM ai_generations
WHERE status = 'completed' AND created_at < '2024-01-01';
```

Parte 2: UPDATE - Modificare Dati (1h)

UPDATE syntax:

```
sql

UPDATE table_name
SET column1 = value1, column2 = value2
WHERE condition;
```

AI Examples:

```
sql
```

```
-- Update generation status
UPDATE ai_generations
SET status = 'completed',
    completed_at = CURRENT_TIMESTAMP,
    generation_time_seconds = 12.5,
    image_path = '/outputs/img_12345.png'
WHERE generation_id = 12345;

-- Upgrade user subscription
UPDATE users
SET subscription_tier = 'pro',
    updated_at = CURRENT_TIMESTAMP
WHERE user_id = 42;

-- Update model version per conversation
UPDATE conversations
SET model_version = 'gpt-4-turbo'
WHERE created_at > '2024-06-01' AND model_version = 'gpt-4';
```

 **WARNING: Always use WHERE!**

```
sql

-- BAD: Updates ALL rows!
UPDATE users SET subscription_tier = 'free';

-- GOOD: Updates specific user
UPDATE users SET subscription_tier = 'free' WHERE user_id = 99;
```

Parte 3: DELETE - Rimuovere Dati (1h)

DELETE syntax:

```
sql

DELETE FROM table_name
WHERE condition;
```

AI Examples:

```
sql
```

```
-- Delete failed generations older than 7 days
```

```
DELETE FROM ai_generations
WHERE status = 'failed'
AND created_at < datetime('now', '-7 days');
```

```
-- Delete spam feedback
```

```
DELETE FROM generation_ratings
WHERE rating = 1 AND comment LIKE '%spam%';
```

```
-- Delete test users
```

```
DELETE FROM users
WHERE email LIKE '%@test.com';
```

CASCADE DELETE (via FK constraint):

```
sql
```

```
-- Deleting user also deletes their conversations and messages
```

```
DELETE FROM users WHERE user_id = 999;
```

```
-- FK ON DELETE CASCADE handles the rest
```

TRUNCATE (delete all, fast):

```
sql
```

```
-- SQLite doesn't have TRUNCATE, use:
```

```
DELETE FROM temp_generations;
```

```
VACUUM; -- Reclaim space
```

⚠ Safety practices:

1. Always use WHERE unless truly deleting all
2. Use transactions for important deletes
3. Backup before bulk deletes
4. Test with SELECT first:

```
sql
```

```
-- First: see what you'll delete
```

```
SELECT * FROM ai_generations WHERE status = 'failed';
```

```
-- Then: actually delete
```

```
DELETE FROM ai_generations WHERE status = 'failed';
```

Lab (1h):

Scenario-based exercises:

1. Populate AI Chatbot Database:

- Insert 5 users
- Insert 10 conversations (spread across users)
- Insert 30 messages (mix of user/assistant/system)

2. Update Operations:

- Mark pending generations as completed
- Update user subscription tiers
- Fix model version names

3. Cleanup Operations:

- Delete failed generations older than 30 days
- Remove inactive users (no conversations)
- Clear test data

Challenge: Write a "data sanitization" script:

- Anonymize user emails (replace with "user_XXX@anonymized.com")
 - Clear sensitive prompts containing "password" or "credit card"
 - Archive old data before deletion
-

Lezione 4: ALTER TABLE e Schema Evolution (2 ore)

Parte 1: ALTER TABLE Operations (1h)

Add Column:

```
sql
```


-- Add feature flag

ALTER TABLE users

ADD COLUMN beta_features_enabled **INTEGER DEFAULT 0**;

-- Add embedding column (for vector search later)

ALTER TABLE prompts

ADD COLUMN embedding_vector **TEXT**;

-- Add usage tracking

ALTER TABLE conversations

ADD COLUMN total_tokens_used **INTEGER DEFAULT 0**;

Rename Column (SQLite 3.25+):

sql

ALTER TABLE ai_generations

RENAME COLUMN cfg_scale **TO** guidance_scale;

Drop Column (SQLite 3.35+, PostgreSQL):

sql

ALTER TABLE users

DROP COLUMN legacy_password_hash;

Rename Table:

sql

ALTER TABLE old_generations

RENAME TO archived_generations;

Parte 2: Schema Evolution in AI Applications (1h)

Common scenarios:

1. Adding Model Versioning:

sql

-- Initially: single model

```
CREATE TABLE conversations (id INTEGER, user_id INTEGER, ...);
```

-- Evolution: track model versions

```
ALTER TABLE conversations
```

```
ADD COLUMN model_version TEXT DEFAULT 'gpt-3.5-turbo';
```

```
ALTER TABLE conversations
```

```
ADD COLUMN model_provider TEXT DEFAULT 'openai';
```

2. Adding Analytics Columns:

sql

```
ALTER TABLE ai_generations
```

```
ADD COLUMN user_rating INTEGER CHECK(user_rating BETWEEN 1 AND 5);
```

```
ALTER TABLE ai_generations
```

```
ADD COLUMN reported_as_inappropriate INTEGER DEFAULT 0;
```

```
ALTER TABLE conversations
```

```
ADD COLUMN average_response_time REAL;
```

3. Migrating to Support New Features:

sql

-- Initially: simple prompts

```
CREATE TABLE prompts (id INTEGER, text TEXT, ...);
```

-- Add support for system prompts

```
ALTER TABLE prompts
```

```
ADD COLUMN system_prompt TEXT;
```

-- Add support for few-shot examples

```
ALTER TABLE prompts
```

```
ADD COLUMN example_conversations TEXT; -- JSON array
```

Migration Strategy:

1. Add column with DEFAULT value (safe for existing data)
2. Backfill data if needed (UPDATE)
3. Make NOT NULL if required
4. Add indexes if needed for performance

Example migration:

```
sql

-- Step 1: Add nullable column
ALTER TABLE messages ADD COLUMN token_count INTEGER;

-- Step 2: Backfill (estimate tokens for old messages)
UPDATE messages
SET token_count = length(content) / 4 -- rough estimate
WHERE token_count IS NULL;

-- Step 3: Make NOT NULL for future inserts
-- (SQLite limitation: can't add NOT NULL after creation easily)
```

Lab (30 min):

Evolution Exercise: Given initial schema for AI assistant, evolve it:

- Add support for voice mode (audio input/output)
 - Add conversation sharing feature (share_token, is_public)
 - Add content moderation flags
 - Add cost tracking (cost_usd per generation)
-

WEEKEND PROJECT - Settimana 2

Deliverable: SQL Scripts + Populated Database

Task: Implement il database design della Settimana 1

Requirements:

1. CREATE TABLE statements con tutti i constraints
2. INSERT sample data (realistico per AI app):
 - Almeno 10 users
 - 30+ conversations/generations
 - 100+ messages/outputs
3. UPDATE statements (esempio: mark completed, update ratings)
4. DELETE statements (cleanup operations)
5. ALTER TABLE statements (evolve schema)

Bonus:

- Script di seed data automatico
- Comments in SQL spiegando scelte
- Sample data realistico (use ChatGPT per generare!)

Presentazione: Lunedì Settimana 3 - Live demo del database funzionante

SETTIMANA 3: SQL Queries - SELECT e Data Retrieval

Lezione 1: SELECT Basics e WHERE (3 ore)

Parte 1: SELECT Fundamentals (1h)

Basic SELECT:

```
sql

-- All columns
SELECT * FROM users;

-- Specific columns
SELECT user_id, email, username FROM users;

-- Column aliases
SELECT
  user_id AS id,
  email AS user_email,
  created_at AS registration_date
FROM users;

-- Calculated columns
SELECT
  prompt,
  length(prompt) AS prompt_length,
  length(prompt) * 0.75 AS estimated_tokens
FROM prompts;
```

AI Context Queries:

```
sql
```

-- Get all AI generations with metadata

SELECT

generation_id,
prompt,
model_version,
steps,
cfg_scale,
status,
generation_time_seconds AS gen_time_sec

FROM ai_generations;

-- Get conversation with message count estimate

SELECT

conversation_id,
title,
model_version,
created_at,

-- (actual count requires subquery, preview for later)

FROM conversations;

Parte 2: WHERE Clause - Filtering (1h)

Comparison operators:

sql

-- Equals

SELECT * FROM users WHERE subscription_tier = 'pro';

-- Not equals

SELECT * FROM ai_generations WHERE status != 'failed';

-- Numeric comparisons

SELECT * FROM ai_generations WHERE steps > 50;

SELECT * FROM users WHERE created_at >= '2024-01-01';

-- Text patterns (LIKE)

SELECT * FROM prompts WHERE prompt LIKE '%cat%';

SELECT * FROM users WHERE email LIKE '%@gmail.com';

SELECT * FROM prompts WHERE prompt LIKE 'a photo of%';

Logical operators:

sql

-- *AND*

```
SELECT * FROM users
WHERE subscription_tier = 'pro'
AND created_at > '2024-01-01';
```

-- *OR*

```
SELECT * FROM ai_generations
WHERE status = 'failed' OR status = 'pending';
```

-- *NOT*

```
SELECT * FROM prompts
WHERE NOT (prompt LIKE '%nsfw%');
```

-- *IN operator*

```
SELECT * FROM ai_generations
WHERE model_version IN ('sd-xl', 'sd-2.1', 'midjourney-v6');
```

-- *BETWEEN*

```
SELECT * FROM ai_generations
WHERE steps BETWEEN 20 AND 80;
```

NULL handling:

sql

-- *Find conversations without titles*

```
SELECT * FROM conversations WHERE title IS NULL;
```

-- *Find generations with completion time*

```
SELECT * FROM ai_generations WHERE completed_at IS NOT NULL;
```

Parte 3: AI-Specific Query Patterns (1h)

Find problematic generations:

sql

```
SELECT * FROM ai_generations
WHERE status = 'failed'
AND created_at > datetime('now', '-24 hours');
```

Find power users:

sql

```
-- Users with many generations (preview - needs aggregation)
```

```
SELECT user_id, email FROM users
WHERE user_id IN (
  SELECT user_id FROM ai_generations
  GROUP BY user_id
  HAVING COUNT(*) > 100
);
```

Find expensive prompts:

```
sql

SELECT prompt, steps, cfg_scale, generation_time_seconds
FROM ai_generations
WHERE generation_time_seconds > 30
ORDER BY generation_time_seconds DESC
LIMIT 10;
```

Content moderation queries:

```
sql

-- Flagged content
SELECT * FROM ai_generations
WHERE reported_as_inappropriate = 1;

-- Suspicious patterns
SELECT * FROM prompts
WHERE prompt LIKE '%violence%'
  OR prompt LIKE '%illegal%';
```

Lab (1h):

Query Writing Practice - AI Image Generator database:

1. Find all pro users registered in last 30 days
2. Find all failed generations from yesterday
3. Find all prompts containing "cyberpunk" or "sci-fi"
4. Find generations that took longer than 60 seconds
5. Find users with no generations yet
6. Find all NSFW-flagged content from last week

Challenge: Write queries for:

- Most common model versions used
 - Average generation time by model
 - Identify potential bot users (>100 generations per day)
-

Lezione 2: DISTINCT, LIMIT, ORDER BY (3 ore)

Parte 1: DISTINCT - Unique Values (45min)

Basic DISTINCT:

```
sql

-- All unique model versions used
SELECT DISTINCT model_version FROM ai_generations;

-- Unique subscription tiers
SELECT DISTINCT subscription_tier FROM users;

-- Unique combinations
SELECT DISTINCT model_version, steps
FROM ai_generations
ORDER BY model_version, steps;
```

AI Applications:

```
sql

-- What models have users tried?
SELECT DISTINCT model_version FROM conversations;

-- What are all the unique styles users requested?
SELECT DISTINCT style_preset FROM ai_generations
WHERE style_preset IS NOT NULL;

-- Unique error types
SELECT DISTINCT error_message FROM failed_generations;
```

COUNT DISTINCT:

```
sql
```


-- How many unique users have generated content?

```
SELECT COUNT(DISTINCT user_id) as active_users
FROM ai_generations;
```

-- How many different models are being used?

```
SELECT COUNT(DISTINCT model_version) as models_in_use
FROM conversations;
```

Parte 2: ORDER BY - Sorting (1h)

Basic sorting:

sql

-- Ascending (default)

```
SELECT * FROM users ORDER BY created_at;
SELECT * FROM users ORDER BY created_at ASC;
```

-- Descending

```
SELECT * FROM ai_generations
ORDER BY created_at DESC;
```

-- Multiple columns

```
SELECT * FROM users
ORDER BY subscription_tier DESC, created_at ASC;
```

AI Query Examples:

sql

-- Most recent generations

```
SELECT * FROM ai_generations
ORDER BY created_at DESC
LIMIT 10;
```

-- Slowest generations

```
SELECT prompt, generation_time_seconds
FROM ai_generations
WHERE status = 'completed'
ORDER BY generation_time_seconds DESC;
```

-- Best rated content

```
SELECT * FROM ai_generations
WHERE user_rating IS NOT NULL
ORDER BY user_rating DESC, created_at DESC;
```

-- Alphabetical prompt listing

```
SELECT DISTINCT prompt FROM ai_generations
ORDER BY prompt;
```

NULL ordering:

sql

-- SQLite: NULLs come first in ASC, last in DESC

```
SELECT * FROM conversations
ORDER BY title; -- NULL titles first
```

-- Force NULLs last (SQLite trick)

```
SELECT * FROM conversations
ORDER BY title IS NULL, title;
```

Parte 3: LIMIT e OFFSET - Pagination (1h15)

LIMIT basics:

sql

-- Top 10 most recent

```
SELECT * FROM ai_generations
ORDER BY created_at DESC
LIMIT 10;
```

-- Just one (latest)

```
SELECT * FROM conversations
ORDER BY created_at DESC
LIMIT 1;
```

OFFSET for pagination:

sql

-- Page 1 (first 20)

```
SELECT * FROM ai_generations
ORDER BY created_at DESC
LIMIT 20 OFFSET 0;
```

-- Page 2 (next 20)

```
SELECT * FROM ai_generations
ORDER BY created_at DESC
LIMIT 20 OFFSET 20;
```

-- Page 3

```
SELECT * FROM ai_generations
ORDER BY created_at DESC
LIMIT 20 OFFSET 40;
```

-- General formula: $LIMIT\ page_size\ OFFSET\ (page_number - 1) * page_size$

AI Application - Infinite Scroll:

sql

```
-- Initial load: 30 generations
```

```
SELECT generation_id, prompt, image_path, user_rating  
FROM ai_generations  
WHERE status = 'completed'  
ORDER BY created_at DESC  
LIMIT 30;
```

```
-- Load more (next 30)
```

```
SELECT generation_id, prompt, image_path, user_rating  
FROM ai_generations  
WHERE status = 'completed'  
ORDER BY created_at DESC  
LIMIT 30 OFFSET 30;
```

Performance consideration:

- Large OFFSETs are slow (database still scans all rows)
- Better: cursor-based pagination

```
sql
```

```
-- Instead of OFFSET, use last seen ID
```

```
SELECT * FROM ai_generations  
WHERE generation_id < 12345 -- last seen  
ORDER BY generation_id DESC  
LIMIT 30;
```

Lab (1h):

Analytics Queries:

1. Top 10 most active users (by generation count - hint: needs COUNT)
2. List all unique model versions, sorte