

Micromouse Documentation

McMaster Micromouse

Last Updated: July 30, 2026

Contents

1	Introduction	3
1.1	What is Micromouse?	3
1.2	Club Objectives	3
1.3	How to Use This Guide	4
2	System Overview	5
2.1	Robot Architecture	5
2.2	Hardware Overview	5
2.3	Software Overview	5
I	Hardware	6
3	Materials	7
3.1	Components	7
3.2	Alternatives	7
4	Hardware Theory	10
4.1	ESP32	10
4.2	Time-of-Flight Sensors	12
4.3	Motors	12
4.4	Motor Driver	12
4.5	Encoders	12
4.6	Power System	12
5	Electrical Design	13
5.1	Wiring Schematic	13
5.2	Pin Assignments	13
II	Software	14
6	Software Architecture	15
6.1	Project Structure	15
6.2	Control Loop	15

7	Firmware Setup	16
7.1	Development Environment	16
7.2	Libraries	16
7.3	Uploading Code	16
8	Sensors	17
8.1	Reading ToF Sensors	17
8.2	Reading Encoders	17
8.3	Sensor Calibration	17
9	Motion Control	18
9.1	Differential Drive	18
9.2	PID Control	18
10	Mapping and Localization	19
10.1	Maze Representation	19
10.2	Localization	19
10.3	Wall Detection	19
11	Path Planning	20
11.1	Flood Fill	20
11.2	Shortest Path Optimization	20
11.3	Alternative Algorithms	20
III	Reference Implementation	21
12	Mechanical Assembly	22
13	Electronics Assembly	23
14	Firmware Configuration	24
15	Testing	25
A	Pinout Tables	26
B	Datasheets	27
C	Equations	28
D	Troubleshooting	29
E	Glossary	30

Chapter 1

Introduction

1.1 What is Micromouse?

A Micromouse is a small autonomous robot that navigates and solves a maze as quickly as possible. The robot begins with no knowledge of the maze layout and must explore it using external sensors. As it explores, it constructs an internal map of the maze, determines the most efficient route, and then completes subsequent runs at increasingly high speeds.

Micromouse has existed as an international engineering competition hosted by IEEE for decades, and remains a great project for learning embedded systems. A successful Micromouse requires the integration of mechanical design, electronics, and software development.

1.2 Club Objectives

The goal of our club is to make the process of designing, building, and programming a Micromouse accessible to students of all experience levels. Robotics projects often require knowledge from multiple disciplines, which can make them difficult to approach independently. Through structured workshops, hands-on resources, and comprehensive documentation, the club aims to lower this barrier and provide a clear path from beginner to autonomous robot.

Participants will be guided through the complete development process, from assembling hardware and programming embedded systems to implementing sensing, localization, and path-planning algorithms. Rather than simply providing a finished design, the club emphasizes understanding the engineering principles behind each subsystem so members can modify, improve, and extend their own robots.

While the club provides a complete reference robot, members are encouraged to explore their own ideas and improvements. Topics such as custom PCB design, alternative hardware, and advanced control strategies are beyond the scope of the workshops but are left open for exploration. The provided platform should be viewed as a foundation upon which participants can experiment, iterate, and develop their own designs.

1.3 How to Use This Guide

This document serves as both a workshop and technical reference for the Micromouse Club. It is intended to complement our workshops by providing detailed explanation of concepts, design decisions, and implementation details that we may not have time to cover during workshops. It also allows members to revisit or look ahead.

The guide is organized into four main sections:

1. **Hardware:** Introduces the electrical components used in the robot. Explains how they operate and covers wiring.
2. **Software:** Describes sensor integration, motion control, localization, and path- finding algorithms.
3. **Reference Implementation:** Documents the club's reference Micromouse design. This section serves as a starting point for members building their own robots.

Chapter 2

System Overview

2.1 Robot Architecture

2.2 Hardware Overview

2.3 Software Overview

Part I

Hardware

Chapter 3

Materials

3.1 Components

There are a variety of components that can be used for a Micromouse. The main categories are summarized in System Overview. Table 3.1 lists all the components provided in our kits.

Components	Quantity	Purpose
ESP32-DEVKIT	1	Selected microcontroller. Main "brain" of the bot.
VL53L1X	3	Time of Flight sensor. Used to align the bot.
TB6612FNG	1	Motor driver; to control the motors.
G12-N20 Motors	2	Motors for the wheels.
N20 Motor Encoders	2	Attached to motors to track of motor position.
N20 Gear Wheels	2	Wheels for the bot to move.

Table 3.1: Component List

These provide a good starting point for a basic Micromouse bot, and will be the parts we focus on throughout our workshops. The Hardware Theory section will also go in-depth on how each component works. However, you are free to choose your own parts. Some alternative options are described in the next section.

3.2 Alternatives

This section briefly introduces several alternative components that can be used for your own Micromouse, along with the rationale behind our selected components. Keep in mind that the options presented are not exhaustive; you are encouraged to research additional alternatives. A summary list (Table 3.2) is included at the end of this section.

Microcontroller

Micromouse robots require enough of computing power, memory, and peripheral support to handle sensor readings, motor control, and path-finding algorithms. While basic Arduino boards such as the Arduino Uno or Nano(ATmega328P) can be used for simple robots, they become restrictive for

more advanced algorithms.

The STM32 family (e.g. the STM32F103, 'blue pill', 'black pill', and STM32F4 Series) is a popular choice for more advanced Micromouse bots due to its performance, low-level hardware control, and extensive timer and interrupt capabilities. However, due to the learning curve of using the STM32CubeIDE, can be more challenging for beginners. For this reason, an ESP32 board was chosen to provide a more accessible development while still providing sufficient performance for a Micromouse.

Alternative ESP32 boards, such as the ESP32-C3 and ESP32-S3, can also be considered. These boards are smaller and have different peripheral options, but have fewer available GPIO pins compared to some ESP32 development boards. With careful planning, they can still support the required sensors, motor drivers, and encoders.

Distance Sensors

Distance sensors are one of the most important parts of a Micromouse bot. When selecting a sensor, it is important to consider range, update rate, field of view, and physical size.

We will be using the VL53L1X time-of-flight (ToF) sensor due to its relatively long sensing range, accuracy, and size. Alternatives of the ToF sensor include the VL53L0X (shorter range) or VL53L4CX (longer range).

Infrared (IR) distance sensors are another common choice, especially in advanced Micromouses. Compared to ToF sensors, IR sensors have faster update rates and lower latency. However, they require analog signal processing and require more calibration.

Ultrasonic sensors may also be used for slower bots, but are not recommended in general. They are physically larger and are slower since they use a sound waves rather than light.

IMU Sensors

For advanced and faster Micromouses, it is worth considering adding an IMU (inertial measuring unit). Common choices include the MPU6050 and MPU6500. These provide more accurate turns and smoother motion control, but are not strictly necessary for beginner robots. As a result, we have not provided any in the kits as beginner robots work with just wheel encoders.

Motors

Micromouse motors do not need huge amounts of power. The focus is on speed, control, smoothness, size, and accurate encoder readings. Encoders often come together with the motor.

N20 DC Gear Motor would work are common choices for beginner Micromous bots. They come in various gear ratios, are compact, cheap and widely available. The ones we provide have a gear ratio of 30:1, however other ratios can also be used. Coreless DC gear motors are also worth looking into for advanced Micromouses.

Stepper motors are not recommended for Micromouse bots. Although they provide precise position control, they are larger, heavier, consume more power, and have lower speeds and acceleration compared to DC motors.

Motor Driver

The motor driver acts as the bridge between the microcontroller and the motors. Since we are just using N20 gear motors, the chosen motor driver was the TB6612FNG. It is a popular choice for small bots as it is small, cheap and can control two separate motors.

Alternatives include the DRV8833 (similar to TB6612FNG) or the DRV8871 (for larger motors). The L298N is not really recommended due to its bulky size and large voltage drops.

Summary

Components	Selected	Alternative
Microcontroller	ESP32-WROOM	ESP32-C3, ESP32-S3, STM32F103/F4
Distance Sensor	VL53L1X	VL53L0X, VL53L4CX, IR sensors
IMU	None	MPU6050, MPU6500
Motors	N20 DC Gear Motor(30:1)	Other N20 gear ratios, Coreless DC motors
Motor Driver	TB6612FNG	DRV8833, DRV8871

Table 3.2: Summary of Component Alternatives

Chapter 4

Hardware Theory

Rather than a complete explanation of how each component works in detail, this section just highlights necessary information for the Micromouse build. Some additional references or further readings may be included throughout.

4.1 ESP32

We will be using the 30-pin ESP32 DevKit. Although it is commonly known for its Wifi and Bluetooth capabilities, it also has strong processing power, large memory capacity and is beginner-friendly.

Some key specs are:

- 32-bit dual-core processor (Up to 240MHz)
- 520KB SRAM
- 4MB Flash
- Up to 25 usable GPIO pins

Since all the wiring is done to the ESP32, this section will elaborate on the pinout of the ESP32. It is mainly based on the article [ESP32 Pinout Reference](#). Only the relevant sections are highlighted here.

For our bot, we will be using the GPIO pins for general-purposes, in addition to PWM and I2C pins. Figure 4.1 provides a visual summary of which peripherals are available for each pin.

There are 25 GPIO pins available for general use. GPIO 35-36 are input only pins that do not include internal pull-ups or pull-downs; an external resistor can be added if needed. Pay attention to pins GPIO 0, 2, 5, 12, and 15 as they are connected to boot configuration(strapping) and may prevent the ESP32 from starting; try not to use them unless necessary.

PWM (Pulse Width Modulation) pins are used to control motor speed. Instead of producing a constant analog voltage, PWM constantly switches between HIGH and LOW by adjusting the "duty cycle" (percent of time the pin is ON vs OFF). This allows the average voltage supplied to the

motor to be controlled. Any output GPIO pin can be used for PWM.

I2C pins are the SDA (data line) and SCL (clock line) pin. By default, GPIO21(SDA) and GPIO22 (SCL) are used as the I2C pins, but any GPIO pin can be configured as SDA and SCL. Multiple devices can share the same I2C bus as long as each device has a unique device. Since we are using three ToF sensors, the XSHUT pins are used to configure their unique addresses. (See Time-of-Flight Sensors)




Figure 4.1: ESP32-Pinout

The ESP32 also includes interrupts, which allow the board to quickly respond to external events without constantly checking the state of a pin (polling). For Micromouse, interrupts are used for reading motor encoder data; this allows accurate measurement even while the processor is performing other tasks. (See Encoders)

Finally, the ESP32 runs at 3.3V. It has two power pins: VIN and 3V3. The VIN pin can accept external power (typically 5V to 12V) which is internally regulated to 3.3V. The 3V3 pin provides 3.3V to compatible components. DO NOT apply voltages higher than 3.3V to the 3V3 pin or GPIO pins. Avoid powering the ESP32 simultaneously through both the USB and external power source. All connected components must share a common ground (GND).

4.2 Time-of-Flight Sensors

4.3 Motors

4.4 Motor Driver

4.5 Encoders

4.6 Power System

Chapter 5

Electrical Design

5.1 Wiring Schematic

5.2 Pin Assignments

Part II

Software

Chapter 6

Software Architecture

6.1 Project Structure

6.2 Control Loop

Chapter 7

Firmware Setup

7.1 Development Environment

7.2 Libraries

7.3 Uploading Code

Chapter 8

Sensors

8.1 Reading ToF Sensors

8.2 Reading Encoders

8.3 Sensor Calibration

Chapter 9

Motion Control

9.1 Differential Drive

9.2 PID Control

Chapter 10

Mapping and Localization

10.1 Maze Representation

10.2 Localization

10.3 Wall Detection

Chapter 11

Path Planning

11.1 Flood Fill

11.2 Shortest Path Optimization

11.3 Alternative Algorithms

Part III

Reference Implementation

Chapter 12

Mechanical Assembly

Chapter 13

Electronics Assembly

Chapter 14

Firmware Configuration

Chapter 15

Testing

Appendix A

Pinout Tables

Appendix B

Datasheets

Appendix C

Equations

Appendix D

Troubleshooting

Appendix E

Glossary