aardio 范例: HTTP 状态码、错误代码检测 - aardio

```
//错误码检测
import win.ui;
/*DSG{{*/
var winform = win.form(text="HTTP 状态码、错误代码检测 - aardio";right=485;bottom=347;)
btnCheck={cls="button";text="检测";left=393;top=30;right=455;bottom=56;z=2};
behicker {cls="statio"; text="simple for the first text of the fi
//开启自动完成
////n H = MJTUM.
::Shlwapi:= ..raw.loadDll("Shlwapi.dll")
::Shlwapi.SHAutoComplete( winform.editUrl.hwnd,0/*_SHACF_DEFAULT*/);
import inet.errorMessage;
winform.btnCheck.oncommand = function(id,event){
           var url = winform.editUrl.text;
           if(! ..inet.url.is(url) ) {
   if( tonumber(url) ) {
                                import inet.httpStatusCode;
                                 winform.editResult.text = inet.httpStatusCode[tonumber(url)] || inet.errorMessage[tonumber(url)] || "未知错误代码"
                               return;
                      winform.msgboxErr("请输入正确的网址");
winform.editUrl.setFocus(0,-1);
                      return;
           //禁用按钮,避免重复点击
          winform.btnCheck.disabled = true;
winform.editResult.text = "请稍候,正在连接......"
           winform.editResult.text = thread.invokeAndWait(
                      function (url) {
                               import inet.http;
import inet.httpStatusCode;
import inet.errorMessage;
                                 //创建http对象
                               //busenctpnsk
var http = inet.http();
if( !http.beginRequest( url,"HEAD",,,0x200000/*_INTERNET_FLAG_NO_AUTO_REDIRECT*/ ) ) {
  http.close();
  return "无效的请求";
                                 //发送请求
                                 // X A H A Var ret,errMsg,errCode = http.send();
if(http.statusCode){
    var msg = string.concat( "返回状态码: ", http.statusCode + '\r\n'
        , inet.httpStatusCode[http.statusCode] ,'\r\n',http.readHeader() ,);
                                           http.close();
                                            return msq;
                                 else {
                                           http.close();
                                           if( type(errCode) == type.number ){
    var msg = "请求失败,借误代码; " + errCode + '\r\n'
    + ( inet.errorMessage[errCode] : "")
                                                       if( errCode == 12003 ) msq = ..string.concat(errCode,'\r\n',inet.lastResponse() );
                                                      return msq;
                                            return"请求失败";
           winform.btnCheck.disabled = false;
win.setOwner(winform.hwnd,ide.getMainHwnd());
```

Markdown 格式

win.loopMessage();