aardio 范例: 系统已注册 COM 类名列表 (点列标题排序,双击列显示编辑框,右键菜单查看对象文档)

```
//COM 类名列表
import win.ui;
import win.ui.menu;
import fonts.fontAwesome;
/*DSG{{*/
          winform.add (listview=[cls="listview";left=17;top=40;right=1094;bottom=640;acceptfiles=1;asel=false;bgcolor=16777215;db=1;dl=1;dr=1;dt=1;edge=1;font=LOGFONT (name='SimSun');fullRow=1;gridLines=plusLoading={cls="plus";left=372;top=188;right=743;bottom=450;color=15780518;db=1;dl=1;dr=1;dt=1;font=LOGFONT (h=-96;name='FontAwesome');iconStyle={font=LOGFONT (h=-96;na
winform.listview.insertColumn("CLSID",250) winform.listview.insertColumn("控件",70)
winform.listview.insertColumn("描述
winform.listview.insertColumn("路径",-1
          function(winform) {
                    import win.reg;
import win.guid;
                   winform.plusLoading.hide = false;
winform.plusSearch.hide = true;
winform.listview.hide = true;
winform.plusLoading.disabledText = {'\uF254';'\uF251';'\uF252';'\uF253';'\uF250'}
                   var items = {};
var progIds = {}
var onOpenRegClsId = function(regClsId,clsId) {
  var regClsIdProgId = regClsId.open("ProgID",true)
  if(regClsIdProgId) {
                                        var progId = regClsIdProgId.queryValue("")
if(progId && !progIds[progId]) {
   progIds[progId] = true;
                                                   var description;
var regProgId = win.regReader("HKEY_CLASSES_ROOT\"+progId)
if(regProgId){
                                                              description = regProgId.queryValue("");
                                                             regProgId.close();
                                                   val paul
var regServer32 = regClsId.open("InprocServer32",true) || regClsId.open("LocalServer32",true)
if(regServer32){
   path = regServer32.queryValue("");
   regServer32.close();
                                                   var clsIdKevs = regClsId.kevs();
                                                   });
                                         regClsIdProgId.close()
                              regClsId.close()
                    var regClsId = reg.open(clsId,true);
if(regClsId) onOpenRegClsId(regClsId,clsId);
clsIds[clsId] = true;
                                          = win.regReaderWow64("HKEY_CLASSES_ROOT\CLSID\")
                    for(clsId, writetime in reg.eachKey() ) {
   if(!string.match(clsId, "%{}")) {
      continue;
                              if(clsIds[clsId]){
                                        var regClsId = reg.open(clsId, true);
if(regClsId) onOpenRegClsId(regClsId, clsId);
                     ..table.sort(items,lambda(a) owner[1]<a[1])
                    .table.sort(items,lambda(a) owner[I]<al winform.listview.items = items; winform.listview.itemData = items; winform.listview.itemBortColumn = 1; winform.plusLoading.disabledText = null; winform.plusLoading.hide = true;
                     winform.listview.hide = false;
winform.plusSearch.hide = false;
                     winform.plusSearch.setFocus();
import win.imageList;
import win.imageList(16, 15);
war iml = win.imageList(16, 15);
iml.add('GIF\56\57a \0\15\0\x80\x80\x80\x80\xff\0\xff\33\xf9\4\0\0\0\0\0\0\0\0\0\0\0\0\15\0\0\2\31\x8c
\x8f\xa9\xcb\xed\15\xa3\x9c\xb4N\xf0\x80\xde\56k\xbfA\\xd7\x84 \x97Y\xea\xca\xb6\xee\11\xc7F\1\0;', 0xff00ff);
winform.listview.setColumnImageList(iml);
var reloadItemData = function() {
  var sortColumn = winform.listview.itemSortColumn;
  var word = string.trim(winform.plusSearch.text);
  var itemData = winform.listview.itemData;
         var ttemmeda - ......
if(#word) {
   word = "00" + word;
   itemData = table.filter(itemData
        ,lambda(v) string.find(v[1],word) || string.find(v[2],word) || string.find(v[4],word) || string.find(v[5],word) )
        .
```

Markdown 格式