aardio 范例: sqlite 库 - replace 语句

```
//sqlite 库 - replace 语句
import sqlite;
import console;
//打开内存数据库
var db = sqlite(":memory:");
if( not db.existsTable("tableName2") ) {
    //创建单主键表
   db.exec( "CREATE TABLE tableName(title PRIMARY KEY, length, tm);" )
   db.exec( "CREATE TABLE tableName2(title,length,tm, constraint pk tableName2 PRIMARY KEY (title,length));")
//replace语句根据主键查询,不存在相同数据则插入新的,否则更新已存在的数据
db.exec( "REPLACE INTO tableName VALUES ('Silence of the Lambs, The', 11.8, datetime('now','localtime') );")
db.exec( "REPLACE INTO tableName2 VALUES @values;", {
   values = {
       { 'Contact', 32, time.now() }, 
{ 'Contact', 16, time.now() }
})
REPLACE INTO 必须要设置所有无默认值字段的值,
如果要在插入冲突时修改部分字段,请用下面的方法
db.exec("
   INSERT OR IGNORE INTO tableName (title, length, tm) VALUES (@title, @length, @tm);
   UPDATE tableName SET tm=@tm WHERE title=@title", {
       title = 'Silence of the Lambs, The';
       length = 123;
       tm = "456"
for title, length, tm in db.each("SELECT * FROM tableName") {
   console.log( title,length,tm );
for title,length,tm in db.each("SELECT * FROM tableName2") {
    console.log( title,length,tm );
db.close();
console.pause();
```

Markdown 格式