a) First let's look at the ratings.csv file. The first few columns of ratings.csv is as shown in the picture below:

	userId	movieId	rating	timestamp
0	1	31	2.5	1260759144
1	1	1029	3.0	1260759179
2	1	1061	3.0	1260759182
3	1	1129	2.0	1260759185
4	1	1172	4.0	1260759205

### 

b) MAE, Mean Absolute Error measures the average magnitude of the errors in a set of predictions RMSE, Root Mean Squared Error is a quadratic scoring that measures the average magnitude of the error.

RMSE will always be larger or equal to the MAE. The greater the difference between them, the greater the variance in the individual errors in the sample. Both measures can range from 0 to infinity. Lower the values of MAE and RMSE, the better.

```
RMSE and MAE for five-fold PMF: {'test_mae': array([0.76888102, 0.77694119, 0.78394215, 0.78330379, 0.78947437]), 'test_mae': array([0.99355912, 1.00720332, 1.01273677, 1.01490639, 1.02196274]), 'fit_time': (3.1727535724639893, 3.1059951782226562, 3.1052229404449463, 3.1319563388824463, 3.12854 2900085449), 'test_time': (0.144212007522583, 0.1401071548461914, 0.12485003471374512, 0.1422138214111328, 0.12299180030822754)}
```

```
RMSE and MAE for five-fold PMF:
{'test_mae': array([0.76888102, 0.77694119, 0.78394215, 0.78330379, 0.78947437]),
'test_rmse': array([0.99355912, 1.00720332, 1.01273677, 1.01490639, 1.02196274]),
'fit_time': (3.1727535724639893, 3.1059951782226562, 3.1052229404449463, 3.1319563388824463, 3.128542900085449),
'test_time': (0.144212007522583, 0.1401071548461914, 0.12485003471374512, 0.1422138214111328, 0.12299180030822754)}
```

```
RMSE and MAE for five-fold User Based Collaborative Filtering: {'test_mae': array([0.7141557 , 0.7064661 , 0.70278552, 0.70853913, 0.70401333]), 'test_rmse': array([0.93101601, 0.91979979, 0.92004312, 0.92286234, 0.92019265]), 'fit_time': (0.2722916603088379, 0.276334285736084, 0.28095579147338867, 0.2749972343444824, 0.2758452892303467), 'test_time': (1.305346965789795, 1.2526752948760986, 1.2655532360076904, 1.2794365882873535, 1.250403881072998)}
```

```
RMSE and MAE for five-fold User Based Collaborative Filtering: {'test_mae': array([0.7141557 , 0.7064661 , 0.70278552, 0.70853913, 0.70401333]), 'test_rmse': array([0.93101601, 0.91979979, 0.92004312, 0.92286234, 0.92019265]), 'fit_time': (0.2722916603088379, 0.276334285736084, 0.28095579147338867, 0.2749972343444824, 0.2758452892303467), 'test_time': (1.305346965789795, 1.2526752948760986, 1.2655532360076904, 1.2794365882873535, 1.250403881072998)}
```

```
RMSE and MAE for five-fold Item Based Collaborative Filtering:
{'test_mae': array([0.69668777, 0.6834048 , 0.69497176, 0.68137891, 0.68707677]), 'test_
rmse': array([0.91582721, 0.89923181, 0.91691483, 0.89652777, 0.90592884]), 'fit_time':
(7.029903888702393, 6.840514659881592, 6.929088354110718, 6.81726861000061, 6.9107584953
308105), 'test_time': (4.7717673778533936, 4.765731334686279, 4.694500923156738, 4.67408
3471298218, 4.624952793121338)}
```

```
{'test_mae': array([0.69668777, 0.6834048 , 0.69497176, 0.68137891, 0.68707677]),
'test_rmse': array([0.91582721, 0.89923181, 0.91691483, 0.89652777, 0.90592884]),
'fit_time': (7.029903888702393, 6.840514659881592, 6.929088354110718, 6.81726861000061, 6.9107584953308105), 'test_time': (4.7717673778533936, 4.765731334686279, 4.694500923156738, 4.674083471298218, 4.624952793121338)}
```

Average MAE of Probabilistic Matrix Factorization (PMF): 0.7805085024399361 Average RMSE of Probabilistic Matrix Factorization (PMF): 1.0100736692057644

Average MAE of User based Collaborative Filtering: 0.7071919558018237 Average RMSE of User based Collaborative Filtering: 0.9227827816757037

Average MAE of Item based Collaborative Filtering: 0.6887040013969324 Average RMSE of Item based Collaborative Filtering: 0.9068860902612874

## 

Lower MAE and RMSE indicates better fit. Hence, based on the average MAE and RMSE values, Item based Collaborative Filtering has a better fit.


- e) The following are the graphs for MSE and RMSE over five-fold cross validation for Item and User based collaborative filtering with MSD, Pearson and Cosine distance. The dashed line represents the mean value for the corresponding value.

RMSE: [0.91995992 0.91516118 0.91864677 0.92968895 0.91343338]

RMSE mean: 0.919378040396331

MAE: [0.70246464 0.69703964 0.70412455 0.71342336 0.69828168]






Done computing similarity matrix.

RMSE: [0.91859457 0.92663286 0.92087915 0.92785224 0.93102311]

RMSE mean: 0.9249963866311152

MAE: [0.70049484 0.70725768 0.70079237 0.71013973 0.70793123]


MAE mean: 0.7053231697587835



# 

RMSE: [0.91382918 0.93446099 0.92477793 0.92152215 0.92343715]
RMSE mean: 0.9236054800674249
MAE: [0.70051696 0.7188593 0.70698608 0.70598475 0.70561073]






RMSE: [0.9017048 0.90802927 0.91362797 0.91276238 0.91781909]

RMSE mean: 0.9107887016237737

AE: [0.69143847 0.69217989 0.70029861 0.70047108 0.70323328]





RMSE: [0.92610148 0.91765773 0.92963856 0.93115523 0.924585 ]

RMSE mean: 0.9258276007593409

MAE: [0.70717239 0.70138695 0.70681952 0.70491089 0.70699121]

MAE mean: 0.7054561927885127






RMSE: [0.92180239 0.92385006 0.92325792 0.92139516 0.93197032]

RMSE mean: 0.9244551671905237

MAE: [0.70816245 0.70830466 0.70446769 0.7053181 0.71426998]

**HOMEWORK 6** 



### 


Fold Values


Among User based Collaborative filtering with MSD, Pearson and Cosine similarity, it was noticed that Mean Squared Distance (MSD) had the lowest mean RMSE and MAE.

Fold Values

Among Item based Collaborative filtering with MSD, Pearson and Cosine similarity, once again, it was noticed that Mean Squared Distance (MSD) had the lowest mean RMSE and MAE.

- f) Since MSD gave us the smallest RMSE and MAE for both user-based and item-based collaborative filtering, I decided to use this similarity metric for tasks f and g. K vs Error graphs were draw for K 1 to 100.
  - 1) User based Collaborative Filtering using MSD:





g) The best K was the K value that gives us the lowest RMSE and MAE value. For User based CF, the lowest RMSE value was 0.91782 and it was obtained when K = 73

The minimum RMSE value in User based Collaborative Filtering using MSD is: 0.9174160874647195

The K value that gives the minimum RMSE in User based Collaborative Filtering using MSD is: 60

The minimum RMSE value in User based Collaborative Filtering using MSD is: 0.9174160874647195 The K value that gives the minimum RMSE in User based Collaborative Filtering using MSD is: 60

Similarly, for Item based CF, the lowest RMSE value was 0.908932 and it was obtained when K = 93

The minimum RMSE value in Item based Collaborative Filtering using MSD is: 0.9089329378274155

The K value that gives the minimum RMSE in Item based Collaborative Filtering using MSD is: 93

The minimum RMSE value in Item based Collaborative Filtering using MSD is: 0.9089329378274155 The K value that gives the minimum RMSE in Item based Collaborative Filtering using MSD is: 93

GitHub Link: Assignment 06

https://github.com/monicabernard/CAP-5610 Machine-Learning.git