


SHORT CANONICAL DECOMPOSITION FOR NON-ORIENTABLE SURFACES

Niloufar FULADI Alfredo HUBARD
Arnaud de MESMAY


CNRS, Université Gustave Eiffel, Paris



AMS-EMS-SMF 2022- Grenoble


GRAPHS EMBEDDED ON SURFACES /A DISCRETE METRIC

- A **surface** is a topological space that locally looks like the plane.




GRAPHS EMBEDDED ON SURFACES /A DISCRETE METRIC

- A **surface** is a topological space that locally looks like the plane.
- An **embedding** of G on a surface S is an injective map $G \rightarrow S$.



GRAPHS EMBEDDED ON SURFACES / A DISCRETE METRIC



- A **surface** is a topological space that locally looks like the plane.
- An **embedding** of G on a surface S is an injective map $G \rightarrow S$.



- This graph introduces a discrete metric to the surface.



DECOMPOSITIONS

- A **decomposition** for the embedded graph, is a second graph intersecting the first graph **transversely** and cuts it into a **disk**.



DECOMPOSITIONS



- A **decomposition** for the embedded graph, is a second graph intersecting the first graph **transversely** and cuts it into a **disk**.



- How much can we control the **length** of a decomposition?

DECOMPOSITIONS



- A **decomposition** for the embedded graph, is a second graph intersecting the first graph **transversely** and cuts it into a **disk**.



- How much can we control the **length** of a decomposition?
- **Orientable canonical system of loops:** a one-vertex graph with the fixed rotation system $a_1 b_1 \bar{a}_1 \bar{b}_1 a_2 b_2 \bar{a}_2 \bar{b}_2 \dots$

DECOMPOSITIONS

- A **decomposition** for the embedded graph, is a second graph intersecting the first graph **transversely** and cuts it into a **disk**.




- How much can we control the **length** of a decomposition?
- **Orientable canonical system of loops:** a one-vertex graph with the fixed rotation system $a_1 b_1 \bar{a}_1 \bar{b}_1 a_2 b_2 \bar{a}_2 \bar{b}_2 \dots$

THEOREM (LAZARUS, POCCHIOLA, VEGTER, VERRAUST '01)

Given a graph cellularly embedded on an **orientable** surface of genus g , there exists an orientable canonical system of loops, so that **each** loop crosses **each** edge of the graph at most 4 times (total length $O(gn)$).


CANONICAL DECOMPOSITIONS FOR NON-ORIENTABLE SURFACES

- What about non-orientable surfaces? Can I cut along **the non-orientable canonical system of loops?**



CANONICAL DECOMPOSITIONS FOR NON-ORIENTABLE SURFACES

- What about non-orientable surfaces? Can I cut along **the non-orientable canonical system of loops?**



THEOREM (F., HUBARD, DE MESMAY)

*Given a graph cellularly embedded on a non-orientable surface, there exists a **non-orientable canonical system of loops** such that each loop in the system crosses each edge of the graph at most in 30 points (total length $O(gn)$).*

- Previous best bound for the total length is $O(g^2n)$ (Lazarus '14).

OTHER CUTTING SHAPES?

A more general question on finding short decompositions is the following open problem.

NEGAMI'S CONJECTURE '01

Let G_1 and G_2 be two graphs cellularly embedded on a surface S of genus g . Is there a homeomorphism $h : S \rightarrow S$ such that each edge of $h(G_1)$ crosses each edge of G_2 at most a constant number of times?

Best known bound:

THEOREM (NEGAMI '01)

Let G_1 and G_2 be two graphs cellularly embedded on a surface S of genus g . There exists a homeomorphism $h : S \rightarrow S$ such that each edge of $h(G_1)$ crosses each edge of G_2 **at most $O(g)$ times**.

OTHER CUTTING SHAPES?

A more general question on finding short decompositions is the following open problem.

NEGAMI'S CONJECTURE '01

Let G_1 and G_2 be two graphs cellularly embedded on a surface S of genus g . Is there a homeomorphism $h : S \rightarrow S$ such that each edge of $h(G_1)$ crosses each edge of G_2 at most a constant number of times?

Best known bound:

THEOREM (NEGAMI '01)

Let G_1 and G_2 be two graphs cellularly embedded on a surface S of genus g . There exists a homeomorphism $h : S \rightarrow S$ such that each edge of $h(G_1)$ crosses each edge of G_2 **at most $O(g)$ times**.

TWO REASONS TO DECOMPOSE A SURFACE

1. Combinatorial group theory: How to change bases?

Given an orientable surface S , and a family of simple curves inducing a presentation of the fundamental group:

$$\pi_1(S) = \langle a, b, c, d \mid abcd\overline{abcd} = 1 \rangle$$

How do I go from this presentation to my “favorite” presentation?

$$\pi_1(S) = \langle a_1, a_2, b_1, b_2 \mid a_1 b_1 \overline{a_1 b_1} a_2 b_2 \overline{a_2 b_2} = 1 \rangle$$

TWO REASONS TO DECOMPOSE A SURFACE

1. Combinatorial group theory: How to change bases?

Given an orientable surface S , and a family of simple curves inducing a presentation of the fundamental group:

$$\pi_1(S) = \langle a, b, c, d \mid abcd\overline{abcd} = 1 \rangle$$


How do I go from this presentation to my “favorite” presentation?

$$\pi_1(S) = \langle a_1, a_2, b_1, b_2 \mid a_1 b_1 \overline{a_1 b_1} a_2 b_2 \overline{a_2 b_2} = 1 \rangle$$

- Here, one can take $a_1 = \overline{dca}$, $b_1 = bcd$, $a_2 = \overline{c}$ and $b_2 = \overline{d}$. How much can we bound the length of these words?



TWO REASONS TO DECOMPOSE A SURFACE

2. Visualisation: How to represent an embedded graph?





TWO REASONS TO DECOMPOSE A SURFACE

2. Visualisation: How to represent an embedded graph?






TWO REASONS TO DECOMPOSE A SURFACE

2. Visualisation: How to represent an embedded graph?






TWO REASONS TO DECOMPOSE A SURFACE

2. Visualisation: How to represent an embedded graph?



TWO REASONS TO DECOMPOSE A SURFACE


2. Visualisation: How to represent an embedded graph?




- Why non-orientable surfaces?
they are more flexible; a graph with n edges might need $O(n)$ handles to be embedded while **one** cross-cap is enough.

REDUCTION TO THE ONE-VERTEX CASE

- By contracting a **spanning tree**, our problem reduces to the case of one-vertex graphs.




- An embedding for a one-vertex graph, is entirely described by the cyclic ordering of the edges around the vertex, and, in the non-orientable case, the sidedness of the curves, **an embedding scheme**.



CROSS-CAP DRAWING


- **Cross-cap drawings**, a planar drawing in which the cross-caps are localized.



A DIFFERENT APPROACH

THEOREM (SCHAEFER-ŠTEFANKOVIČ '15)


A graph G embeddable on a non-orientable surface admits a cross-cap drawing in which each edge enters each cross-cap at most twice.



A DIFFERENT APPROACH

THEOREM (SCHAEFER-ŠTEFANKOVIČ '15)


A graph G embeddable on a non-orientable surface admits a cross-cap drawing in which each edge enters each cross-cap at most twice.



A DIFFERENT APPROACH

THEOREM (SCHAEFER-ŠTEFANKOVIČ '15)


A graph G embeddable on a non-orientable surface admits a cross-cap drawing in which each edge enters each cross-cap at most twice.



- If we can control the diameter of this cross-cap drawing, we can control the length of the canonical system of loops.


SKETCH OF THE PROOF

- The proof is by induction on the number of edges.




SKETCH OF THE PROOF

- The proof is by induction on the number of edges.
- We build a system of short paths upon this algorithm.




SKETCH OF THE PROOF

- The proof is by induction on the number of edges.
- We build a system of short paths upon this algorithm.
- When dealing with separating curves:



SKETCH OF THE PROOF


- The proof is by induction on the number of edges.
- We build a system of short paths upon this algorithm.
- When dealing with separating curves:



- To avoid cascading, we make sure to deal with all the separating loops at once.


A NICE RELATION

- The **signed reversal distance** between two signed permutations is the minimum number of reversals to go from one to the other.
- Very important in **computational biology**, computable in **polynomial time** [Hannenhalli-Pevzner '99].
- Strong similarities with crosscap drawings, which we leverage in our proof.




A NICE RELATION

- The **signed reversal distance** between two signed permutations is the minimum number of reversals to go from one to the other.
- Very important in **computational biology**, computable in **polynomial time** [Hannenhalli-Pevzner '99].
- Strong similarities with crosscap drawings, which we leverage in our proof.



A NICE RELATION

- The **signed reversal distance** between two signed permutations is the minimum number of reversals to go from one to the other.
- Very important in **computational biology**, computable in **polynomial time** [Hannenhalli-Pevzner '99].
- Strong similarities with crosscap drawings, which we leverage in our proof.



OPEN QUESTIONS

- Negami's conjecture remains open

NEGAMI'S CONJECTURE '01

Let G_1 and G_2 be two graphs cellularly embedded on a surface S of genus g . Is there a homeomorphism $h : S \rightarrow S$ such that each edge of $h(G_1)$ crosses each edge of G_2 at most a constant number of times?

- On cross-cap drawings of *loopless* graphs

MOHAR'S CONJECTURE '09

Every loopless graph G embeddable on a non-orientable surface of genus g admits a cross-cap drawing in which each edge enters each cross-cap **at most once**.

OPEN QUESTIONS

- Negami's conjecture remains open

NEGAMI'S CONJECTURE '01

Let G_1 and G_2 be two graphs cellularly embedded on a surface S of genus g . Is there a homeomorphism $h : S \rightarrow S$ such that each edge of $h(G_1)$ crosses each edge of G_2 at most a constant number of times?

- On cross-cap drawings of *loopless* graphs

MOHAR'S CONJECTURE '09

Every loopless graph G embeddable on a non-orientable surface of genus g admits a cross-cap drawing in which each edge enters each cross-cap **at most once**.

Thank You!