

---

# ToFu : Topologie eEffective et calcUl

---

Projet équipe-action  
Mathematics : from Fundamentals to Applications  
Porteurs du projet : **Greg McShane** (IF), **Francis Lazarus** (G-SCOP)

## 1 Presentation of the team

The team consists of eight members in total (7 tenured faculty and one PhD student : Joanny Perret) du projet belonging to two laboratories on the Grenoble campus : Institut Fourier (IF) and G-SCOP.

Laboratoire	Équipe	Nom	
IF	Géométrie et Topologie	<b>Martin Deraux</b>	
G-SCOP	Optimisation Combinatoire	<b>Louis Esperet</b>	
G-SCOP	Optimisation Combinatoire	<b>Francis Lazarus</b>	francis.lazarus@gipsa-lab.grenoble-inp.fr
IF	Géométrie et Topologie	<b>Greg McShane</b>	mcshane@univ-grenoble.fr
IF	Géométrie et Topologie	<b>Anne Parreau</b>	
G-SCOP	Optimisation Combinatoire	<b>Joanny Perret</b>	
IF	Géométrie et Topologie	<b>Andrea Seppi</b>	
G-SCOP	Optimisation Combinatoire	<b>Matěj Stehlik</b>	

## 2 Synopsis

The purpose of the present project is to develop a synergy between colleagues with a background in fundamental mathematics and others coming from more an applied/computer science background in order to study important problems related to the complexity of topological spaces (such as surfaces but more generally manifolds with particular geometric structures) and initiate investigations using computer software. The problems we intend to study are those which have both combinatorial and analytical aspects. Past experience shows that this kind of problem has often lead to rich exchanges between those who have a purely theoretical background on one side and a more applied/numerical one on the other.

We believe that by combining the knowledge of theoretical mathematicians and computer scientists present on the Grenoble campus we can make significant progress on a number of geometric problems which have an analytic, combinatorial and algorithmic nature. This is something we have come to realise collectively in the past few years through participating together in seminars at IF and G-SCOP, in evaluation committees for our PhD students and in workshops.

## 3 Research Context

In this project we aim to study ways to describe the geometry of space from two points of view :

- combinatorial/analytic
- analytical

This double headed approach has been central to the field of low dimensional topology since its inception. It has proven spectacularly successful particularly now that computers allow us to make very accurate calculations rapidly as we shall now see.

### 3.1 Thurston and SnapPea

The dual analytic/combinatorial approach was pioneered by the likes of Felix Klein, Henri Poincaré and Max Dehn in the late 19th century and early 20th century. They studied surfaces and 3 manifolds using differential equations, combinatorial constructions and transformation groups. Of particular note was the proof of the classification of triangulated surfaces in 1907 by Dehn which uses a clever algorithm. Nearly 100 years later Bill Thurston used complex analytic techniques to prove existence theorems for hyperbolic structures on 3 manifolds [16] – that is to show that the fundamental group of the 3 manifold is isomorphic to a discrete group of isometries of hyperbolic 3 space. Thurston’s results are based on fixed point theorems on *Teichmüller space* and are non constructive. Though very elegant they were certainly not *effective*. With the advent of computers there were many new possibilities for constructing and exploring Thurston’s manifolds. Jeffrey Weeks, as part of his 1985 doctoral thesis supervised by Thurston, created a remarkable piece of software called SnapPea which tries to find a hyperbolic structure on the complement of a knot. To do this it starts by finding a good decomposition of the space into tetrahedra analogous in some sense to Dehn’s triangulation of a surface. It then associates to each tetrahedron a complex number and constructs a set of nonlinear equations of complex variables from the adjacencies between the tetrahedra. A solution of this system gives a complete hyperbolic metric on the space. SnapPea uses an iterative method - essentially Newton’s method - to search for solutions. Once a solution is found many invariants of the manifold can be computed : volume, Chern-Simons invariant, etc. One can also understand relations to other 3-manifolds which are related to it by doing *Dehn surgery*.

SnapPea has proven to be a very useful piece of software. It has been used to verify conjectures in base cases, investigate statistics of topological invariants and visualize 3 manifolds. Its architecture has allowed it to be extended to include additional functionality [12] and ported to a variety of operating systems. One important development is a version called Snap written by Oliver Goodman [7] which uses the number theory package Pari incorporating high precision arithmetic and number theoretic functions. This allows one to *certify* results which is not possible using ordinary floating point arithmetic.

There is certainly a demand for quality free software packages like SnapPea which would allow researchers to study geometric objects in geometric topology and we will give several examples where our expertise could reply to this demand below.

### 3.2 Surface theory

It is perhaps surprising but due to work of Mostow [15] if there is a hyperbolic structure of finite volume on a 3 manifold like the ones that SnapPea finds then it is unique up to isometry. This is in contrast to the variety of such structures on a surface. In fact the key to proving Thurston’s existence theorem is a profound study of these structures, the space of all Riemann surfaces of a fixed genus the so-called *Teichmüller space*. The Teichmüller space is naturally an analytic object. But the theory of how surfaces vary is extremely rich requiring many tools coming from different branches of mathematics - algebra, topology and differential geometry but also combinatorial and algorithmic analysis.

An important topic is understanding the group of automorphisms of Teichmüller space which turns out to be isomorphic to the diffeomorphisms of a surface up to isotopy. This is a group which is difficult to study using algebra as it is not known to be a linear group in general. Instead one studies it via its actions on spaces constructed from the combinatorics of curves on the surface. Of course it acts on Teichmüller space but also on Thurston’s measured lamination space [6] and Harvey’s curve complex. The former is a finite dimensional piecewise linear manifold which one should think of as the completion of the space of simple closed curves on the surface. The latter

is an infinite graph associated to a surface : a vertex is a homotopy class of simple curves and vertices are joined by an edge if the corresponding curves can be chosen to be disjoint.

The curve graph is known to be a negatively curved space in the sense of Gromov [14]. There are many interesting questions concerning the metric geometry/combinatorics of this graph [4] and several algorithms related to them : the Bestvina–Handel algorithm, Bell–Webb algorithm [3], Leasure and Shackleton algorithms.

So studying the mapping class group of a surface requires an understanding of the lengths of closed simple geodesics which in turn requires both analytic tools coming from hyperbolic geometry and Teichmüller theory but has also a fundamentally algorithmic approach. This fits well with the goal of our project – combining the knowledge of theoretical mathematicians and computer scientists in order to study questions in geometry which have both a combinatorial and algorithmic nature.

On the analytic side we hope to extend the inequalities between entropy of diffeomorphisms and hyperbolic invariants [11] to other problems and relate this to combinatorial problems of curve graphs etc. On the effective side we will develop and use programs to explore the combinatorics of the various graphs that one can associate to a surface.

## 4 Objectives

We now describe the main research challenges that we intend to tackle.

### 4.1 Combinatorial length and rigidity

Calculate the length spectrum of a combinatorial surface, that is a graph which is cellularly embedded in a surface. For such a graph one associates a length to each homotopy class of loops which is just the minimal number of edges traversed by a circuit in the graph representing it. The combinatorial length spectrum is the collection of all these lengths. One can study the inverse spectral problem : to what extent does this spectrum determine the surface ? Exploring the connection of the length spectrum with graph Laplacian spectrum could be a promising angle of attack. Another intriguing question relates to the action of the mapping class group on this combinatorial length spectrum. Indeed, an automorphism of the surface permutes the homotopy class of curves, hence the length spectrum. Does the discrete nature of the graph metric induce specific properties of this action ? In other words, can we learn the graph structure from this action ?

### 4.2 Algorithmic study of lengths

Lazarus and Damiand have added a package to the C++ library CGAL which tests if two curves are in the same free homotopy class. The algorithm test has linear complexity : in about 30 seconds one can test two paths of combinatorial length of 30 million on a surface of genus 100. The next step is to implement a test to see if a path is homotopic to a simple loop. There is already an algorithm, of “quasi”-linear complexity [8], which just needs to be implemented. With this one can count the number of simple curves of length less than a given threshold and hopefully check the numerical values of certain important constants which appear in the work of Mirzakhani.

### 4.3 Curve complex

Curver is a program for performing calculations in the curve complex which implements the Bell–Webb algorithm to determine the Nielsen–Thurston type of a mapping class [1, 2]. The algorithm runs in polynomial time but the constants involved currently make this implementation impractical. There is a sister program called Flipper<sup>1</sup> which does calculations for surfaces with boundary. There seems to be room to improve this situation and implement this situation. Namely,

---

1. <https://markcbell.github.io/build/html/software.html>

finding a way of making the algorithm practical by solving the problem of large constants and extending the work to cover closed surfaces without boundary [13].

## 4.4 Harmonic maps

A very important tool in the study of Teichmüller space, namely the space of deformation of Riemann surface structures, is represented by harmonic maps [17]. Harmony is software developed in C++ by Loustau and Gaster [10], which computes harmonic maps between two hyperbolic surfaces, described in terms of their Fenchel-Nielsen coordinates, by means of a discrete heat flow method. In other words, a hyperbolic surface is approximated by a finite graph which encodes its geometry, then one searches a discrete harmonic map by a recursive procedure stopping when a prescribed tolerance is reached. Very interesting developments would be constituted by developing programs to compute harmonic maps with target a metric tree, or a quasi-Fuchsian three-manifold, or to compute minimal Lagrangian maps between closed hyperbolic surfaces [5].

## 5 Méthodologie envisagée

Grenoble has a very strong tradition both as a center for in low dimensional topology as well as for discrete mathematics and computer science (including graph theory and some aspects of algorithms). We believe that the group of researchers from the Institut Fourier and G-SCOP involved in this project possess a blend of complementary skills perfectly adapted to working together on the objectives above. On the one hand the G-SCOP team *Optimisation Combinatoire* is certainly one of the leading groups in graph theory with an emphasis on topological aspects of graphs on surfaces [9]. On the other the topology team at the Institut Fourier is a leading group in low dimensional topology especially the theory of surfaces with its many facets - dynamical, variational and spectral, interactions with classical and quantum algebra.

More precisely :

- Martin Deraux is an expert in complex hyperbolic spaces. He has created programs in JAVA to determine *fundamental domains* for groups acting on these spaces. This is a very delicate task and he must certify all his calculations so that they can be used in rigorously proving theorems.
- Greg McShane has worked extensively on moduli of surfaces and the action of the mapping class group. He has discovered surprising relations between the moduli which can be used to explore the size and shape of the moduli space that is the space of all complex structures on a surface of fixed type.
- Anne Parreau works on representations of the fundamental group of a surface into Lie groups. In her work there are functions which appear which generalise the lengths of curves on a surface.
- Francis Lazarus is interested in the combinatorics of surfaces.

One of the things that makes our proposal particularly relevant at this time is that the theme of the Master of Mathematics (M2R) for 2020-21 will be geometric group theory, including its combinatorial aspects with applications to topology. In particular, Martin Deraud, Anne Parreau and Francis Lazarus will both be giving courses as part of this Master. So accepting our proposal would be an excellent opportunity to reinforce what is at the moment a tentative synergy between team members in quite distinct laboratories and academic programs. The possibility to recruit students from these Masters courses by offering fundings would be undoubtedly be good for the attractivity of Grenoble as a place to study both in the short and long term.

Each of the challenges in the above scientific description of the project could certainly yield at least one subject for a PhD in the context of this project. Students would not only have the chance to work with members of our team but would have interactions with the many seminar speakers in the geometry and topology seminars at the Institut Fourier and the possibility of short visits

to other teams with whom the team members have scientific collaborations (ICJ Lyon, IMJ Paris, University of Luxembourg).

## 6 Résultats attendus

The first challenge concerning the length spectrum of a combinatorial surface sits at the interface of graph theory and surface topology. Progress on this should provide a new point of view that fits perfectly in the structural approach of Robertson and Seymour. We are quite confident when we say that there are few research groups with the same level of competence in this domain.

The other challenges are related to implementations and experimental mathematics, which are again strengths of the mathematical/computer science community Grenoble. It is our intention to develop and distribute open source softwares and packages.

## 7 Principales étapes envisagées

## 8 Request budget and scientific justification

We plan to hire one PhD students and one post-doctoral student. Both the PhD student and the postdoctoral student will be supervised jointly by members of the IF and the G-SCOP. Ideally the PhD student would come from the M2R at the IF in the academic year 2020-21. Depending on the background of the student, the PhD thesis will focus on the questions raised in sections ???. The post-doctoral student is expected to have skills in both theoretical mathematics and algorithms to be involved in the research direction raised in section (??).

In addition to this, we plan to organize a workshop gathering all members of the team and which could be entitled "???" and several meetings or one-day workshops with related ANR projects (???). We also intend to organize a bimonthly all day meeting at which all members would participate to reinforce the cohesion of the TOFU team and facilitate the exchange of ideas.

A joint meeting of the SMF and AMS will take place in June 2021 and we would like to organise a special session. This would be the perfect occasion to establish new contacts and identify promising questions where geometry and computer science may fruitfully interact. In the same time it would dramatically increase the visibility of our initiative and be an efficient way to attract very good post-doctoral students.

— Financement de thèse :	100.000 €
Le sujet portera sur ...	
— Post-doc (1 an)	50.000 €
...	
— Gratifications de stage :	6.000 €
correspondant à 3 stages M2 de 5 mois.	
— Invitations de chercheurs extérieurs :	6.000 €
...	
— Missions :	20.000 €
(1200€/par personne et par an)	
— Matériel :	4.000 €
— Fonctionnement :	4.000 €
— Congrès-colloques :	10.000 €
— TOTAL demandé :	200.000 €

## Références

- [1] Mark C. Bell. `curver` (computer software). [pypi.python.org/pypi/curver](https://pypi.python.org/pypi/curver), 2017-2019. Version 0.3.5.
- [2] Mark C Bell. Experimental statistics for mirzakhani’s theorem. arXiv preprint 1910.08155, 2019.
- [3] Mark C Bell and Richard CH Webb. Polynomial-time algorithms for the curve graph. arXiv preprint 1609.09392, 2016.
- [4] Joan Birman, Dan Margalit, and William Menasco. Efficient geodesics and an effective algorithm for distance in the complex of curves. *Mathematische Annalen*, 366(3-4) :1253–1279, 2016.
- [5] J. Bonsante, F. Schlenker. Maximal surfaces and the universal teichmüller spac. *Invent. math.*, 182 :279–333, 2010.
- [6] Collectif. *Travaux de Thurston sur les surfaces - Séminaire Orsay*. Number 66-67 in Astérisque. Société mathématique de France, 1979.
- [7] D. Coulson, Oliver Goodman, and C. Hodgson. Computing arithmetic invariants of 3-manifolds. *Experimental Mathematics*, 9, 09 1998.
- [8] Vincent Despré and Francis Lazarus. Computing the geometric intersection number of curves. *Journal of the ACM (JACM)*, 66(6) :1–49, 2019.
- [9] Louis Esperet and Matěj Stehlík. The width of quadrangulations of the projective plane. *Journal of Graph Theory*, 89(1) :76–88, 2018.
- [10] Jonah Gaster, Brice Loustau, and Léonard Monsaingeon. Computing discrete equivariant harmonic maps. arXiv preprint 1810.11932, 2018.
- [11] Sadayoshi Kojima and Greg McShane. Normalized entropy versus volume for pseudo-anosovs. *Geometry & Topology*, 22(4) :2403–2426, 2018.
- [12] Nathan Dunfield Marc Culler and Matthias Goerner. Snappy (computer software). <https://snappy.math.uic.edu/>, July 2019. Version 2.7.
- [13] Hidetoshi Masai and Greg McShane. On systoles and ortho spectrum rigidity. arXiv preprint 1909.09829, 2019.
- [14] Y. Masur, H. Minsky. Geometry of the complex of curves i : Hyperbolicity. *Invent. math.*, 138 :103–149, 1999.
- [15] G. D. MOSTOW. *Strong Rigidity of Locally Symmetric Spaces. (AM-78)*. Princeton University Press, 1973.
- [16] William P. Thurston. Hyperbolic structures on 3-manifolds i : Deformation of acylindrical manifolds. *Annals of Mathematics*, 124(2) :203–246, 1986.
- [17] Michael Wolf. The teichmüller theory of harmonic maps. *J. Differential Geom.*, 29(2) :449–479, 1989.