ATL Housing: Households Served

Manual workshop attendee workbook

Build it yourself in Microsoft Fabric | Browser-first | Two-day lab

Edition 1.1, November 11, 2026 UTC. Based on the supplied ATL Housing execution guide, draft v0.4. Screenshots are from the actual ATLhousing reference environment; they are not mockups. Fabric menus can change; identify controls by their labels.

What you will build: original Excel landing, metadata-driven SQL ingestion, typed Warehouse staging, dimensional transformations, an explicit Direct Lake model, the HT1-HT10 report, Spark DQ and a monitored master pipeline. The requested AI extension adds a source-grounded business ontology and a published data agent, with manual setup and 15 sample question/answer exercises in M15-M16.

This is a manual build, not an automation quick start. You will click the Fabric controls, create each item, enter settings and paste the supplied SQL, Power Query, DAX and notebook cells yourself. Do not run `deploy*.py`, the data generator or the source loader.

> **Protect the reference build.** Build only in the participant workspace assigned by the instructor. The shared `ATLhousing` workspace shown in screenshots already contains the reference solution. If you have not been assigned a separate build workspace, use the inspection track: open items, compare settings and run read-only checks, but do not save changes, reload tables or start pipelines.

Module index

1. How to use this workbook
2. M1. Sign in, inspect the kit and confirm access
3. M2. Create the Warehouse, Lakehouse and manual Excel landing
4. M3. Create connections, schemas, metadata and staging tables
5. M4. Build the metadata-driven SQL pipeline manually
6. M5. Create the real Excel Dataflow Gen2
7. M6. Build production dimensions and facts
8. M7. Assemble the base master pipeline and failure handling
9. M8. Create DimDate, with a supported Copilot fallback
10. M9. Create and configure the explicit Direct Lake model
11. M10. Author the HT1-HT10 report manually
12. M11. Optional presenter lab: mirroring versus shortcuts
13. M12. Governance and DevOps, administrator/presenter-gated
14. M13. Spark DQ, reconciliation and the final master acceptance run
15. M14. Conditional presenter lab: Azure Databricks Unity Catalog
16. M15. Build the ATL Housing business ontology
17. M16. Build, test and publish the housing data agent
18. Final attendee sign-off
19. Troubleshooting at the point of failure
20. Asset index and repeatability notes

How to use this workbook

1. Extract the companion lab ZIP before starting; do not open files inside the ZIP.
2. Keep this PDF or Word document open beside Fabric. The offline HTML version has clickable local asset links; the PDF/Word links also have repository equivalents. If a link is unavailable, open the printed file path in Notepad.
3. Use `workshop-assets` for copy-and-paste content and `data\excel` for the unchanged original workbooks supplied in the distribution pack.
4. Finish each module's **Check / Stop / Catch-up** before continuing.
5. Record your own resource IDs and run IDs. Values in screenshots identify the reference environment, not values to copy into a different participant workspace.
6. Ask the instructor before changing permissions, enabling a schedule, sending an alert, applying a label, creating workspaces or changing source configuration.

No Azure capacity purchase, source restore, SQL source reload, source-row update or public GitHub Pages publishing is part of the attendee build.

Suggested two-day sequence

Day	Modules	Work product
1 morning	M1-M3	Access, landing, connections, schemas and control/staging tables
1 afternoon	M4-M7	SQL and Excel ingestion, transforms and base master pipeline
2 morning	M8-M10	Date dimension, Direct Lake, measures, RLS configuration and report
2 afternoon	M13, return to M7	Spark checks, final reconciliation/framing and accepted master run
Presenter/admin sessions	M11, M12, M14	Conditional zero-copy, governance, DevOps and Databricks modules
Additional AI lab, 60-90 minutes	M15-M16, after M9/M13	Business ontology, published data agent and grounded Q&A

M13 is deliberately completed before the **final** M7 acceptance run. The report's DQ page is created in M10 and receives actual run results in M13.

Your resource worksheet

Complete the right-hand column with the instructor. Never substitute an unrelated existing connection just because it is visible.

Setting	Reference / required value	Your assigned value
Tenant/account	Approved workshop tenant; organizational account	_____
Build workspace	Instructor assigns an isolated participant workspace	_____
Workspace ID	Reference only: `4d77b5c8-d96f-41df-83e1-954c582336d8`	_____
Capacity	Existing approved capacity; reference is F8, West US 3	_____
SQL server	`sql-atlhousing.database.windows.net`	_____
Source database	**ATLHousing**, schema **hs**	ATLHousing
Source access	Read-only for the workshop; no destructive loader	Confirmed: _____
Storage	`fabridemo`, container `atldemo`	Confirmed: _____
Lakehouse	`LH_ATL_Landing` in your workspace	ID: _____
Warehouse	`WH_ATL_HS` in your workspace	SQL endpoint: ____
Approved Excel batch	Instructor assigns a unique folder/batch name	_____
Semantic model	`SM_HouseholdsServed` in your workspace	ID: _____
Ontology	`ONT_ATL_Housing`, same validated model	ID: _____
Data agent	`DA_ATL_Housing`, published only after testing	ID: _____
Viewer/program map	Approved identity and allowed program codes	Pending / _____
Fiscal calendar / label	Business-approved values only	Pending / _____
Alert / schedule	Approved destination and enablement decision	Pending / _____

Important corrections to the draft execution guide

Draft shorthand	Use in this workshop
Example source database name	The user-approved source is **ATLHousing**
Approximate source counts	Use the verified count table in M4, not approximate draft numbers

Draft shorthand	Use in this workshop
Unit.PropertyKey	Source Unit has **PropertyID**; resolve the dated property version
FamilyMember.MemberKey	Source FamilyMember uses **HouseholdID**; do not join it to every snapshot
Summarized supportive totals	Original roster columns are ReportMonth, HouseholdID, Program, SupportType
Global staging truncate first	Do not globally truncate; use current-run landing and transactional publication
Distinct household count	Preserve household-program-month observations, including second-program records
Hide source personal columns	Exclude unnecessary columns from the model; hiding is not security
All guide modules already accepted	Core data/report works; security, alerts, schedules and presenter modules have explicit gates

M1. Sign in, inspect the kit and confirm access

Objective: start with the correct tenant, approved existing resources and readable original data. **Prerequisite:** instructor-assigned workspace and access.

1. Open `https://app.fabric.microsoft.com` in Edge or Chrome.
2. Sign in with the approved workshop organizational account. If an account picker appears, choose the workshop tenant, not a personal or unrelated work account.
3. Select **Workspaces**, then your assigned workspace. Confirm its name with the instructor before creating or editing anything.
4. Open **Workspace settings** and inspect the license/capacity assignment. Do not start a trial, resize a capacity or create a new paid resource as a workaround.
5. Confirm that you can create Fabric items and that the source SQL connection can be used or created. Contributor/Member authoring access is not a Viewer RLS test. On the reference F8, confirm appropriate Power BI Pro/PPU or an approved existing trial for report authoring/Viewer consumption; the Fabric capacity alone is not a free report-viewer license.
6. In the extracted lab pack, open `data\excel`. Confirm 24 `.xlsx` files: 12 `UnitAvailability_YYYYMM.xlsx` and 12 `SupportiveHousing_YYYYMM.xlsx`, covering January-December 2025.
7. Open a sample of each workbook type in Excel. The UnitAvailability sheet is `UnitAvailability`; the supportive sheet is `Roster`. No password should be requested. Close without saving changes.
8. Use the readable originals from the kit. The original storage `excel/` blobs in this environment were encrypted; do not overwrite them or attempt to remove their encryption. A password prompt is a **Stop**, not a reason to regenerate data.
9. Keep source SQL and storage read-only. CSVs are controls/bootstrap alternatives; they are not a second feed to append on top of SQL.

Check: correct workspace, authorized source access, 24 readable originals. **Stop:** missing access, an unexpected tenant, encrypted files or production data. **Catch-up:** instructor supplies access and the original kit; no regeneration.




Figure 1. Reference workspace after the build. Your participant workspace starts empty. Use New item to create each artifact in the following modules.

M2. Create the Warehouse, Lakehouse and manual Excel landing

Objective: create your destination objects without altering the source.

1. In your assigned workspace, select **New item**. Search for **Warehouse**, select it, enter `WH_ATL_HS` and choose **Create**.
2. Return to the workspace. Select **New item > Lakehouse**, name it `LH_ATL_Landing` and choose **Create**. Use the default supported Lakehouse options unless your instructor has provided a different configuration.
3. Open the Lakehouse. In **Explorer**, expand **Files**.
4. From the Files folder menu, choose **New subfolder** and create `landing`. Inside it create `excel`, then the unique approved batch folder from your worksheet.
5. Open that batch folder. Use **Upload > Upload files**, select all 24 original `.xlsx` files from `data\excel`, and wait for every upload to complete.
6. Confirm the folder contains all 24 workbooks, with the original filenames. Do not place a second copy in nested folders or combine previous batches.
7. Record the Lakehouse ID. Open its URL or use the item details/link: the ID is the GUID identifying the Lakehouse, not the workspace GUID.
8. Record the workspace ID separately. You will use both values in M4 and M5.
9. Only an authorized administrator assigns approved Entra groups through **Manage access**. Do not create the draft guide's suggested groups or grant roles to guessed identities.

Check: one Warehouse, one Lakehouse, exactly 24 originals in `Files\landing\excel\<your-approved-batch>`. **Stop:** the current folder is the shared reference Lakehouse or an old batch. **Catch-up:** inspect the reference folder with the instructor; do not replace it.




Figure 2. Start from Files and create folders before uploading; Tables is a different area.




Figure 3. Reference batch of original workbooks. Use your own folder/batch ID.

M3. Create connections, schemas, metadata and staging tables

Objective: prepare the destination and an approved organizational SQL connection.

M3.1 Connect to the existing SQL source

1. Open the Fabric **Settings** gear and **Manage connections and gateways**.
2. If the instructor has shared the dedicated approved SQL connection, select and test that connection. Otherwise select **New > Cloud**.
3. Enter connection name `ATL_HS_SQL_Source` (or your instructor-assigned unique name).
4. Choose the supported SQL Server/Azure SQL connection type offered by the dialog. The pipeline source connector in M4 is **Azure SQL Database**.
5. Enter server `sql-atlhousing.database.windows.net` and database **ATLHousing**.
6. Choose **Organizational account / Microsoft Entra ID**, sign in with the approved workshop account, and use an encrypted connection. Do not choose an unrelated gateway or copy another person's connection credentials.
7. Set privacy level **Organizational** where offered. Do not select **Skip test connection**. Test and create the connection.
8. If you lack connection-creation or sharing rights, stop for the administrator. Do not fall back to a SQL password, storage key or SAS token.

M3.2 Execute the destination SQL manually

1. Return to your workspace and open **WH_ATL_HS**.
2. Select **New SQL query**. Verify that the selected database is the **Fabric Warehouse WH_ATL_HS**, not the source Azure SQL database.
3. Open 01_foundation.sql in Notepad. Copy its complete contents into the Fabric SQL editor and choose **Run**.
4. Open a new query and repeat with 02_source_staging.sql.
5. Repeat with 03_transform_procedures.sql. This creates procedures; do not execute the fact loaders before ingestion.
6. If your editor does not accept `GO`, run the blocks between `GO` separators individually, in order. Never remove validation or exception handling.
7. Refresh **Explorer > Schemas**. Inspect `stg`, `prd` and `mtd`.
8. Confirm the ten source staging tables plus `stg.AnswerKey`, the two Excel staging tables, control tables, `prd.DQ_Results` and the stored procedures.
9. Run the following query in the Warehouse:

```
SELECT SourceSchema,SourceTable,TargetTable,LoadType,WatermarkColumn,IsActive
FROM mtd.TablesToCopy ORDER BY SourceTable;
```

10. Expect ten active `Full` entries. Watermarks are NULL: this workshop does full loads, not a falsely advertised incremental Member load.
11. Copy the Warehouse's **SQL connection string** from its settings/Home command. Record only the server hostname as `WAREHOUSE_SQL_ENDPOINT`; notebook cells must not contain a whole connection string or an Azure SQL source hostname.

Check: ten active metadata entries, correctly typed empty destination tables, and four relevant procedures including `mtd.usp_LogRun`. **Stop:** a SQL editor points to `ATLHousing` while you are about to execute DDL. **Catch-up:** paste the same reviewed SQL files manually into your assigned Warehouse.




Figure 4. New SQL query is the manual execution surface. Refresh Explorer after DDL.

M4. Build the metadata-driven SQL pipeline manually

Objective: SQL SELECTs -> immutable run-scoped Parquet -> transactional staging. This deliberately avoids the draft's global truncate-first pattern.

M4.1 Create the Lookup and ForEach

1. Return to the workspace. Select **New item > Pipeline**, name it `PL_Ingest_SQL`.
2. On the activity ribbon add **Lookup**. In **General**, set its name to `Lookup active full-load tables`.
3. Open **Settings**. Select your `WH_ATL_HS` Warehouse connection, choose **Query**, and paste lookup.sql.
4. Clear **First row only**. If you preview, expect ten rows and the three columns SourceSchema, SourceTable and TargetTable.
5. Add **ForEach**, named `ForEach SQL table`.
6. Drag the Lookup's green **On success** connector to the ForEach.
7. Select ForEach > **Settings**. Leave **Sequential** unchecked, set **Batch count** to `4`, and use **Add dynamic content** for Items:

```
@activity('Lookup active full-load tables').output.value
```

8. Keep these exact activity names: later expressions refer to them literally.
9. Set activity retries to `0` for this controlled lab. Do not configure overlapping runs.




Figure 5. The control AnswerKey copy is outside the ten-table ForEach.




Figure 6. Select Query and clear First row only; the full query is in the asset file.




Figure 7. Items must be the Lookup output array; the batch count is 4.

M4.2 Add the two nested activities

1. Select the ForEach, open its **Activities** tab, then choose the pencil/**Edit** control. You are now editing inside the loop.
2. Add **Copy data**, named `Land SQL table`.
3. In **Source**, choose the dedicated `ATL_HS_SQL_Source` connection and the **Azure SQL Database** source type. Select **Query**.
4. Choose **Add dynamic content**, open sql-source-query.txt, and paste the expression, not a quoted string containing the expression.
5. In **Destination**, choose your `LH_ATL_Landing`, root folder **Files**.
6. Set folder-path dynamic content to:

```
@concat('landing/native_sql/',pipeline().RunId)
```

7. Set file-name dynamic content to:

```
@concat(item().TargetTable,'.parquet')
```

8. Choose file format **Parquet**, compression **Snappy**. Do not use a historical folder wildcard or a fixed run ID.

9. Keep schema-based mapping/type conversion enabled where offered. Do not allow data truncation, and do not invent column mappings between different names.
10. Add **Script**, named `Publish SQL table`, after Copy on **On success**.
11. Select the destination **WH_ATL_HS** connection. Add a **NonQuery** script.
12. Open publish-sql-table.txt in Notepad. Replace `<WORKSPACE_ID>` and `<LAKEHOUSE_ID>` with your worksheet GUIDs. Verify that no angle-bracket placeholder remains.
13. Paste the entire expression through **Add dynamic content** in the script text field. Do not paste it as literal SQL or replace `pipeline().RunId` with an old value.
14. The expression performs a destination transaction: DELETE the matching staging table, COPY the exact current-run Parquet, compare count with Copy rowsRead, COMMIT, then log success. Errors roll back and rethrow.
15. Select the `PL_Ingest_SQL` breadcrumb to return to the parent canvas.




Figure 8. Copy must succeed before the current table is published.




Figure 9. Use the approved source connection and an allowlisted metadata table name.




Figure 10. Run-scoped paths prevent re-ingestion of historical batches.

M4.3 Copy AnswerKey separately and test

1. Outside ForEach, add **Copy data**, named `Land AnswerKey control`.
2. Connect ForEach **On success** to this activity.
3. Source: same approved SQL connection; literal query `SELECT * FROM [hs].[AnswerKey]`.
4. Destination: same Lakehouse Files root and current-run folder expression; file name **AnswerKey.parquet**, format Parquet/Snappy.
5. Add **Script**, named `Publish AnswerKey control`, after it on success.
6. Select **WH_ATL_HS**, NonQuery, and paste the reviewed expression from publish-answer-key.txt. Replace both workspace/Lakehouse placeholders first.
7. Choose **Validate**, correct every error, then **Save**.
8. Ensure no other publisher/master is running. Choose **Run** and open **View run history** or **Monitor**.
9. Wait for terminal **Succeeded**. Open the ForEach details and inspect all ten copies/publications plus both control activities. Submission is not completion.
10. In the Warehouse, run `SELECT COUNT_BIG(*) FROM stg.<table>` for each table. Compare with the fixed-source counts below; counts are not business metrics.

Source/staging table	Expected rows
SourceSystem	2
ProgramType	9
VoucherType	5

Source/staging table	Expected rows
ActionType	5
IncomeSource	6
Property	127
Unit	25,794
UnitLocation	25,794
Member	240,819
FamilyMember	48,021
AnswerKey, control only	108

Check: every source table and AnswerKey loaded; inspect the current run's files. **Stop:** partial failure, wrong target connection, any mismatched count or another active publisher. **Catch-up:** correct the setting and rerun this pipeline serially; never append CSV data.

M5. Create the real Excel Dataflow Gen2

Objective: read only your approved original-file batch and replace both typed Excel staging tables. Do not infer completion from a query preview.

M5.1 Parameters and four manual queries

1. Select **New item > Dataflow Gen2**. Name it `DF_Excel_HouseholdsServed`. Use the current supported Gen2 experience offered by your tenant.
2. Open **Home > Manage parameters > New parameter**. Create these required Text parameters with current values from your worksheet:

Parameter name	Current value
pWorkspaceId	Your participant workspace GUID
pLakehouseId	Your participant Lakehouse GUID
pApprovedBatch	Your exact approved batch-folder name

3. Choose **Get data > Blank query**. Open **Advanced editor**, replace its contents with WorkbookRows.pq, select **Done**, and name the query `WorkbookRows`.
4. Repeat for CurrentBatch.pq, naming it `CurrentBatch`.
5. When prompted for the OneLake Data Lake connection, select **Organizational account** and the approved tenant account. The URL must point to your own `Files/landing/excel/<batch>` path. Use Organizational privacy; no account keys.
6. Repeat for UnitAvailability.pq, naming it `UnitAvailability`.
7. Repeat for SupportiveHousing.pq, naming it `SupportiveHousing`.
8. Do not add destinations to parameters, the function or CurrentBatch. Only the final two table queries have destinations.
9. Inspect availability preview: 72 rows, six columns, integer unit counts and EffectiveDateKey; SourceFile must retain the original filename.
10. Inspect supportive query schema: EffectiveDateKey integer; HouseholdID, Program, SupportType and SourceFile text. The actual original roster has 20,752 rows; it does not contain pre-aggregated VASH/Other columns.

The function validates worksheet names, expected columns and ReportMonth against the filename. It computes SheetName before navigating Excel.Workbook, avoiding the `Kind` argument-shadowing issue encountered during the reference build.




Figure 11. The reference build shows five queries because its workspace/Lakehouse IDs were fixed. Your portable manual build adds the two ID parameters above.

M5.2 Configure both existing destinations

1. Select **UnitAvailability** and **Add data destination > Warehouse**.
2. Select/create the approved organizational Warehouse connection.
3. Select **your workspace > WH_ATL_HS > stg > UnitAvailability**. Choose the existing table, not a newly invented default table name.
4. Advance to destination settings. Select update method **Replace**.
5. Use manual column mapping; do not let the wizard recreate or alter the table:

Query column	Destination column	Type
EffectiveDateKey	EffectiveDateKey	Integer
Program	Program	Text
TotalUnits	TotalUnits	Integer
AvailableUnits	AvailableUnits	Integer
LIHTCUnits	LIHTCUnits	Integer
SourceFile	SourceFile	Text

6. Confirm the destination. Select **SupportiveHousing** and repeat for existing `WH_ATL_HS.stg.SupportiveHousing`, also **Replace**.
7. Map EffectiveDateKey, HouseholdID, Program, SupportType and SourceFile to the same-named destination columns. Keep HouseholdID as text.
8. Choose **Save & run**, or **Publish** then **Refresh** if those are the labels offered by your Gen2 version.
9. Open **Recent runs**. Wait for the actual refresh to finish successfully for both destinations. A successful preview is not a successful load.
10. In the Warehouse run:

```
SELECT COUNT_BIG(*) AS AvailabilityRows FROM stg.UnitAvailability; -- 72
SELECT COUNT_BIG(*) AS SupportiveRows FROM stg.SupportiveHousing; -- 20752
SELECT EffectiveDateKey,Program,COUNT(*) AS N
FROM stg.UnitAvailability GROUP BY EffectiveDateKey,Program HAVING COUNT(*)<>1;
```

Check: 72 / 20,752 rows and no duplicate availability keys. **Stop:** either query failed, a month/file is missing, a table was appended, or data types changed. Do not transform a partially refreshed batch. **Catch-up:** fix the connection/mapping and rerun the real Gen2 refresh.

M6. Build production dimensions and facts

Objective: preserve the actual observation grain and source history.

1. In your Warehouse open a new SQL query.
2. Execute these calls **in order**, only after M4 and M5 succeeded:

```
EXEC prd.usp_Load_Dimensions;
EXEC prd.usp_Load_FactHouseholdSnapshot;
EXEC prd.usp_Load_FactUnitAvailability;
```

3. Open 05_metrics_view.sql and run it manually in the Warehouse.
4. Run 06_dq_views.sql in the same way.
5. Inspect row counts: household fact 240,819; availability fact 72; supportive fact 20,752.
6. Run 07_validate_all_metrics.sql. Inspect **every result set**: actual and expected each 108 keys, no duplicate keys, and **zero mismatch rows** across all 17 metrics.
7. Do not fix missing-unit or duplicate-program teaching defects by dropping observations. Do not replace missing facts with AnswerKey values.

Business rule	What to verify
Grain	Household + program + month observations, not distinct household-months
Category	Elderly first, then Disabled, then Workforce
Household type	Child count > 0 means With children; source counts exclude live-in aides
Property	Resolve Unit.PropertyID to inclusive SCD2 version at snapshot date
Unit history	Do not invent source versions that do not exist
Missing units	Retain observations through unknown key -1
Supportive	Join month + household + its own program
Inventory	Available excludes LIHTC; voucher inventory/vacancy remains NULL
Negative vacancy	Preserve it; do not clamp to zero




Figure 12. Counts are an initial checkpoint; the full-outer 17-metric comparison is the accuracy check.

M6.1 Create the transformation notebook and child pipeline

1. Select **New item > Notebook** and name it `NB_Transform`.
2. Attach your `LH_ATL_Landing` as the default Lakehouse.
3. In the first code cell, type `warehouse_server = "<WAREHOUSE_SQL_ENDPOINT>"`, replacing the placeholder with the Warehouse hostname recorded in M3. Use Python/PySpark, not a SQL cell.
4. Mark this cell as a parameter cell using its **... > Toggle parameter cell** command where available.
5. Add another code cell. Paste NB_Transform.py. This is manual notebook authoring, not running a local deployment script.
6. Save. Ensure no other publisher is running, choose **Run all**, and wait for success. This intentionally repeats the destination transforms idempotently.
7. Create a pipeline named `PL_Transform`. Add **Notebook**, name its activity `Transform`, and select **your workspace > NB_Transform**.
8. Set retries to 0; validate and save. Run it once serially and inspect its linked notebook execution.

Check: three facts, all 17 metrics reconciled, notebook/child pipeline succeeded. **Stop:** any SQL structural error; keep the exception and fix its cause. **Catch-up:** repaste the reviewed SQL definitions/cells in your own destination, then rerun in order; never reload the source database.

M7. Assemble the base master pipeline and failure handling

Objective: wire the manual artifacts and test genuine success/failure states. M13 later adds DQ and model-framing acceptance to this chain. EffectiveMonth is validated reporting/control context: this lab still reloads all 12 supplied months. It is not an incremental SQL or Excel filter.

1. Create pipeline `PL_Master_HouseholdsServed`.
2. Click the empty canvas, open **Parameters**, and add `EffectiveMonth`, type **String**, default `2025-01`.
3. Add a **Script** activity named `Validate reporting month`, connection **WH_ATL_HS**, script type **NonQuery**.
4. Paste validate-month.sql.
5. Add these script parameters as **Input**, type **String**:

Name, without @	Dynamic value
EffectiveMonth	`@pipeline().parameters.EffectiveMonth`
RunId	`@pipeline().RunId`

6. Add **Invoke pipeline**, named `Ingest SQL`. Select your `PL_Ingest_SQL` and enable **Wait on completion**. Connect validation **On success** to it.
7. Add **Dataflow**, named `Ingest approved Excel`; select your real `DF_Excel_HouseholdsServed`. Connect SQL **On success** to it.
8. Add **Invoke pipeline**, named `Transform production tables`; select your `PL_Transform`, wait on completion, and connect Dataflow success to it.
9. Add **Script**, named `Log master success`, connection WH_ATL_HS, NonQuery. Paste master-success.txt using **Add dynamic content**. Initially connect transform success to this activity.
10. For **each** of the four core stages, add a failure branch. Create a Script named `Log failure - <stage name>` and connect the stage's red **On failure** output to it.
11. For the failure log, use WH_ATL_HS and NonQuery. Open master-failure.txt, replace `<FAILED_ACTIVITY_NAME>` with that exact stage name, then paste dynamically.
12. After each failure log add a **Fail** activity, named `Fail master - <stage>`. Error code: `ATL_HS_STAGE_FAILED`; message: the failed stage name and an instruction to inspect its activity details and PipelineRunLog.
13. A logging activity must never turn a failed pipeline into a green success. Do not add a success path that bypasses a failed prerequisite.
14. Validate, save and run the base chain once. Record the parent run ID, linked SQL/transform child IDs, Gen2 refresh status and total duration.
15. Label this checkpoint **base chain**, not final workshop acceptance. M13 adds structural DQ and Warehouse/model reconciliation before success is logged.




Figure 13. The reference includes the final M13 stages. Add those later as directed.

Safe forced-failure test

1. Ensure no other publisher is active. Run with `EffectiveMonth=2025-13`.
2. Confirm validation fails before SQL/Excel ingestion; inspect the error details.
3. Confirm its failure log succeeds and the explicit Fail activity leaves the whole master **Failed**. Downstream ingestion must not run.
4. Inspect the Warehouse log:

```
SELECT RunId,Stage,Status,[RowCount],ErrorMessage
FROM mtd.PipelineRunLog ORDER BY StartedAt DESC;
```

5. Restore the normal parameter to `2025-01`.

Check: genuine successful base run and genuine terminal failed test with a log. **Stop:** a failed prerequisite produces a green master, or copies run after an invalid month. **Catch-up:** correct connector conditions and wait-on-completion settings.

M8. Create DimDate, with a supported Copilot fallback

Objective: exactly 5,844 dates, 2015-01-01 through 2030-12-31.

1. Ask the instructor whether Copilot is actually available for your account, tenant and capacity. The existing F8 assignment alone does not establish this.
2. **Default supported path:** in the Warehouse open a new SQL query, paste 04_dimdate.sql and run it manually.
3. If Copilot is available and the instructor chooses that exercise, create Dataflow Gen2 `DF_DimDate` and open Copilot. Use this prompt:

```
Create a date table from 2015-01-01 through 2030-12-31 inclusive.
Include Date, integer DateKey (yyyymmdd), CalendarYear, MonthNumber,
QuarterNumber, ISOWeek, MonthYear (yyyy-MM), QuarterYear,
MonthStartDate, and locale-independent IsWeekend (Yes/No).
AgencyFiscalYear must remain nullable until the agency supplies its rule.
Return 5,844 unique dates. Do not assume calendar year is the fiscal year.
```

4. Review the generated M and types before running anything. Choose destination `WH_ATL_HS.prd.DimDate`, correct types, and Replace. Do not execute both paths concurrently or create two competing date-table feeds.
5. Verify in the Warehouse:

```
SELECT COUNT(*) AS Dates,COUNT(DISTINCT DateKey) AS DistinctKeys,
       MIN([Date]) AS FirstDate,MAX([Date]) AS LastDate
FROM prd.DimDate;
```

Check: 5,844 / 5,844 / 2015-01-01 / 2030-12-31. **Stop:** a generated table ends in 2025 or guesses the agency fiscal year. **Catch-up:** use the reviewed SQL fallback. Approved fiscal logic is a later, explicit business decision, not a reason to invent a value.

M9. Create and configure the explicit Direct Lake model

Objective: a dimensional semantic model, not an assumed default model.

M9.1 Select tables and relationships

1. In your workspace select **New item > Semantic model > OneLake catalog**. Select your **WH_ATL_HS** Warehouse as the supported OneLake source. This is the **Direct Lake on OneLake** creation route, not Get data's generic Power Query/Import route or the SQL analytics endpoint's Direct Lake on SQL route.
2. Name it `SM_HouseholdsServed`, choose your assigned workspace, and select these production tables: DimDate, DimProgramType, DimVoucherType, DimActionType, DimIncomeSource, DimProperty, DimUnit, FactHouseholdSnapshot, FactUnitAvailability, FactSupportiveHousing and DQ_Results.
3. Include the physical **mtd.ProgramScope** security map as the only metadata table. Do not include AnswerKey, source Member/FamilyMember or other staging tables.
4. Choose **OK** to create, then check a table's **Properties > Storage mode**: it must be Direct Lake. If the catalog route is not available, stop and ask the instructor; do not silently create Import or accept DirectQuery as equivalent.
5. Open the model. Select **Viewing > Editing** before authoring.
6. Select **Manage relationships > New relationship** (or drag matching key fields). Create the following active relationships. Dimension is the **one** side, fact the **many** side; cross-filter direction is **Single**, dimension to fact:

Dimension key	Fact key
DimDate.DateKey	FactHouseholdSnapshot.EffectiveDateKey
DimProgramType.ProgramTypeKey	FactHouseholdSnapshot.ProgramTypeKey
DimProperty.PropertyKey	FactHouseholdSnapshot.PropertyKey
DimUnit.UnitKey	FactHouseholdSnapshot.UnitKey
DimVoucherType.VoucherTypeKey	FactHouseholdSnapshot.VoucherTypeKey
DimActionType.ActionTypeKey	FactHouseholdSnapshot.ActionTypeKey
DimIncomeSource.IncomeSourceKey	FactHouseholdSnapshot.IncomeSourceKey
DimDate.DateKey	FactUnitAvailability.EffectiveDateKey
DimProgramType.ProgramTypeKey	FactUnitAvailability.ProgramTypeKey
DimDate.DateKey	FactSupportiveHousing.EffectiveDateKey
DimProgramType.ProgramTypeKey	FactSupportiveHousing.ProgramTypeKey

7. Do not relate facts to each other, connect FamilyMember directly to the snapshot, or add an extra active DimUnit-to-DimProperty relationship.

8. Select **DimDate.MonthYear > Sort by column > MonthStartDate**. Format Date as a date. Right-click DimDate > **Mark as date table** and choose its Date column. Set key columns to **Do not summarize** and hide surrogate keys.
9. Use **Edit tables** / the source-table column selection to remove unneeded HouseholdID, MemberKey, SourceUnitKey and PropertyManager columns from the model. This report is aggregate-only. Do not remove required relationship keys.
10. Keep names, DOB, ethnicity, citizenship, income and street addresses out of the model. If the current web editor cannot exclude an unneeded source column, stop for the instructor to provide an approved projection; hiding is not a security substitute.




Figure 14. Use Fit to page to inspect all tables; every relationship has one-direction filtering.




Figure 15. Switch to Editing to author relationships/measures. Merely viewing is not editing.

M9.2 Add actual model measures, one at a time

1. Select the table named in the file's first comment, then **New measure**.
2. Open each matching file under `workshop-assets\dax`, paste its formula into the formula bar, and confirm with the checkmark/Enter.
3. Do not paste a whole `DEFINE MEASURE` query into the measure formula bar. These files are already individual, persistent measure definitions.

Owning table	Measure files to add
FactHouseholdSnapshot	Households, Households-With-Children, Households-Without-Children, Elderly-Households, Disabled-Households, Workforce-Households
FactUnitAvailability	Available-Units, LIHTC-Units, Total-Units, Unit-Based-Households, Vacant-Units, Occupancy-Percent, DQ-Flag, Vacancy-Color
FactSupportiveHousing	VASH-With-Children, VASH-Without-Children, Other-Supportive-With-Children, Other-Supportive-Without-Children
DQ_Results	DQ-Observations

4. Set count/unit measures to whole-number format. Format Occupancy % as a percentage. Vacancy Color and DQ Flag return text, not numeric sums.
5. Do not replace `COUNTROWS` with distinct HouseholdID counting. The source's planted second-program observations are intentional.
6. Open **DAX query view**, paste reconcile.dax and choose **Run**.
7. Expect 27 program-month rows: January, July and December, nine programs each. Compare all 17 output metrics, not just Households, with the same keys in `stg.AnswerKey` / `data\controls\answer_key.csv`.
8. A full metric/key comparison is also performed by the manually authored NB_Reconcile in M13. Do not sign off model acceptance solely from a row count.

M9.3 Configure RLS only with an approved mapping

1. Ask the instructor for the approved Viewer UPN and allowed program codes. **Do not guess identities or grants.** If none are approved, record this security acceptance as Pending and do not grant consumer access.
2. In your Warehouse, open 08_approved_program_scope.sql. Replace the two explicit placeholders with the approved Viewer UPN and program code, run it manually, and inspect its returned grant. Repeat only for each additional approved program. Do not commit populated identities to Git.
3. Keep ProgramScope disconnected and hidden in the model.
4. In model Editing mode choose **Security / Manage roles**, create `ProgramScope`.
5. Select **Switch to DAX editor**. Set the DimProgramType filter to ProgramScope.dax.
6. Add this filter on ProgramScope itself:

```
LOWER(ProgramScope[UserPrincipalName]) = LOWER(USERPRINCIPALNAME())
```

7. Save the role. An unmapped role member must see no programs.
8. Have the authorized owner assign the approved user to the role and grant appropriate model/report access. Do not make them Contributor to bypass RLS.
9. Test **View as**, then an actual **Viewer** session. Verify household, availability and supportive facts; also test an unmapped user sees no programs.
10. Record the actual result. An author/Admin view or an unassigned role is not proof of Viewer enforcement.

Check: Direct Lake partitions, 11 active single-direction relationships, actual measures and three-month reconciliation. RLS sign-off requires a Viewer. **Stop:** many-to-many, unexpected Import/DirectQuery, missing keys or unapproved grants. **Catch-up:** compare the settings/table list with the reference; do not run the model deployer.

M10. Author the HT1-HT10 report manually

Objective: recreate the three matrices and DQ/definition pages from your model.

M10.1 Create the report and strict month slicer

1. In your semantic model select **New report**. Save it as `RPT_MTW_Detail_HT` in your assigned workspace.
2. Add a title text box: `ATL Housing | Households served`.
3. Add a **Slicer** visual; drag **DimDate.MonthYear** into its field well.
4. In slicer formatting choose **Dropdown**, enable **Single select** and disable **Select all**. Keep exactly one selected month.
5. In the visual Filters pane add DimDate.CalendarYear and select `2025`, so the slicer does not offer years outside the supplied demo snapshot.
6. Select `2025-01`. Test Ctrl-click on a second month: the slicer must still have exactly one selected month. If not, correct the single-select control before relying on report totals.
7. Use **Edit interactions** if necessary; the month must filter all three matrices. It intentionally does not filter disconnected run-level DQ controls.

M10.2 Occupied household category matrix

1. Add **Matrix**. Rename/title it `Occupied households`.
2. Add Rows, in order: FactHouseholdSnapshot.HouseholdType, then Category.
3. Add Columns: DimProgramType.ProgramTypeShortName.
4. Add Values: **Households** measure, not a summed key or distinct HouseholdID.
5. Select the visual's **Expand all down one level in the hierarchy** button so both category levels are visible.
6. Keep household-type subtotals and the grand total visible.
7. Exclude a structural blank ProgramTypeShortName in a report-level filter; do not exclude the real unknown-unit observations.
8. January grand total must be **19,998**; With children **7,635** and Without children **12,363**. Category precedence is Elderly > Disabled > Workforce, regardless of the labels' alphabetical display order.

M10.3 Inventory matrix, row metrics and negative-vacancy formatting

1. Add another Matrix. Columns: ProgramTypeShortName.
2. Values: Available Units, LIHTC Units, Total Units, Vacant Units.
3. Open **Format visual > Values > Options** and turn **Switch values to rows** On. The four metrics should be rows, not repeated columns under each program.
4. In **Cell elements / Specific column**, apply settings to **Vacant Units**. Enable font color and select **fx**.
5. Choose **Format style: Field value**, based on measure **Vacancy Color**. Apply to values and totals where offered.

6. Verify real rendered cells: January Mixed-Homeflex **-37** and Mixed-RAD **-75** must be red. A saved color expression alone is not evidence.
7. Preserve NULL voucher inventory/vacancy. Do not fill it with zero, and do not subtract voucher households from the unit-based grand total.
8. January totals: Available **10,798**, LIHTC **2,770**, Total **13,568**, Vacant **1,197**.

M10.4 Supportive matrix

1. Add a third Matrix. Columns: ProgramTypeShortName.
2. Values: VASH With Children, VASH Without Children, Other Supportive With Children, Other Supportive Without Children.
3. Again turn **Switch values to rows** On.
4. January grand totals must be **22**, **120**, **606**, **973**, in that order. They come from the original roster, not answer-key facts.




Figure 16. Actual reference output. Negative vacancy remains visible and red.

M10.5 Definitions tooltip, DQ page and actual timing

1. Add a page named `Metric definitions`. In its canvas/page settings select **Tooltip** page type/size and allow the page to be used as a tooltip.
2. Add text defining observation grain, child rule, category precedence, available versus LIHTC, and non-applicable voucher vacancy.

3. Hide this page from normal report navigation.
4. On occupied/inventory visuals choose **General > Tooltips > Report page**, then select Metric definitions. Hover a cell to verify the real tooltip.
5. Add a normal page named `Data quality` with a table visual.
6. Add DQ_Results.RunId, Rule, Severity, CheckedAt and the **DQ Observations** measure. Sort CheckedAt descending. Do not sum rule counts across historical runs.
7. The table may be empty until M13 runs. Do not paste fake DQ results to fill it.
8. Add a main-page note: counts are household-program-month observations; negative vacancy is a DQ signal, not a value to hide.
9. If an existing sensitivity label is approved and you have permission, apply it to the report/model. Otherwise record Pending; never invent a label.
10. Save the report with January selected and the household categories expanded.
11. In Editing mode open **Optimize > Performance analyzer**, start recording, refresh visuals and switch January -> July -> December -> January.
12. Record/export the actual visual durations and your test conditions. Target: under 3 seconds per workshop visual at demo scale. Do not claim a cold-cache or full-page result from a DAX API/token roundtrip.
13. Reference browser warm month interactions were about 0.41 seconds, but full page reload was 3.94 seconds and cold-capacity acceptance remains open. Your measured result, not these reference numbers, is your performance evidence.

Check: correct month/category totals, inventory/null behavior, actual red cells, supportive totals, tooltip and saved pages. **Stop:** all-month totals, collapsed categories, Ctrl multi-select or black negatives. **Catch-up:** rebuild the visual field wells and formatting manually; do not import the report as a substitute for this exercise.

M11. Optional presenter lab: mirroring versus shortcuts

Gate: approved connections, source-owner permission and prerequisites. This module is not required to manufacture missing data or bypass access controls.

M11.1 ADLS Gen2 shortcut, without a second ingestion feed

1. In the assigned Lakehouse, open **Files** and choose **New shortcut**.
2. Choose **Azure Data Lake Storage Gen2** and an approved organizational connection.
3. Storage endpoint: `https://fabridemo.dfs.core.windows.net`. Select container `atldemo` and the instructor-approved path, such as `csv`.
4. Give the shortcut a clearly separate name, for example `reference_csv_shortcut`. Do not place it inside the approved Excel batch or change CurrentBatch to glob it.
5. Create only with approved access, browse a safe lookup CSV, and verify data is read through the shortcut rather than another copied staging feed.
6. Do not use the encrypted source Excel files as a workaround for M5.

M11.2 Azure SQL mirroring, presenter-owned disposable source only

1. Instructor checks supported database features/tier, logical-server identity, network access and mirroring prerequisites before creation.
2. Only if the source owner has approved the necessary configuration, select **New item > Mirrored Azure SQL Database**, name it `MIR_ATL_HS`, choose the approved connection/database and the selected `hs` tables.
3. Start only after approval and inspect replication status until actually Running.
4. Query its SQL analytics endpoint and reconcile sample keys/totals.
5. The draft's source Member update is **not authorized on this existing source**. Demonstrate CDC only on an explicitly approved disposable copy; otherwise observe existing replication without modifying a source row.

Pattern	What moves	Use when
Pipeline	Copies data into controlled landing/staging	Explicit metadata, transformations and run control
Azure SQL mirroring	Replicates source data/changes into OneLake	Managed low-ETL replication; not literally zero-copy
ADLS shortcut	References data in place	Reuse existing storage with approved access
Mirrored Unity Catalog	Syncs metadata and exposes shortcuts	Reuse supported Databricks-managed tables

Check: actual read/status evidence or an explicit prerequisite-blocked entry. **Stop:** unapproved source configuration/update, keys/SAS or a new paid resource. **Catch-up:** presenter walkthrough; do not mark a module Delivered from a diagram.

M12. Governance and DevOps, administrator/presenter-gated

Objective: practise approved controls without changing source data or publishing privately owned material publicly.

M12.1 Labels, Viewer access and lineage

1. With the administrator, confirm the approved existing label and groups.
2. Apply the label to Warehouse/model/report only where supported and authorized.
3. As the approved Viewer, verify RLS from M9. Author access is not an RLS test.
4. If export is approved, export a safe aggregate visual to Excel and inspect actual label inheritance. Do not infer inheritance from the label's name.
5. Open workspace **Lineage** and identify Warehouse -> model -> report and pipeline/dataflow dependencies that the service exposes.
6. Open **Monitor** and the approved **Capacity Metrics** app. Locate your own workload and inspect failures/throttling; do not resize the shared F8.

M12.2 Private Git integration

1. In the assigned development workspace open **Workspace settings > Git integration**.
2. If the tenant supports the selected provider and you have authorization, connect the instructor-approved private GitHub repository, branch and directory.
3. Review the initial synchronization direction before committing or updating. Do not overwrite the reference workspace with a different branch.
4. Make a harmless approved lab edit, inspect the pending diff, commit, and demonstrate an update from the approved branch.
5. Record unsupported items and secrets exclusions. A local Git commit alone is not evidence of a connected Fabric Git integration.
6. Private-repository links require authorized GitHub access. Participants without it use the instructor-provided offline pack; a public Pages site is not created.

M12.3 Dev/Test/Prod deployment pipeline

1. Only after the administrator provides approved Dev, Test and Prod workspaces and capacity assignments, create a **Deployment pipeline**.
2. Assign the three approved workspaces to the correct stages.
3. Compare Dev to Test, review the supported items, and deploy to **Test**, not Prod.
4. Rebind Test connections, Lakehouse/workspace IDs, notebook parameters and model/report references. Do not let Test publish to Dev staging.
5. Run Test reconciliation and inspect Test lineage. Record unsupported/skipped items instead of assuming they deployed.

Check: actual control/sync/deployment evidence, or explicit Pending approvals. **Stop:** guessed groups, invented labels, public publishing or unapproved target workspaces. **Catch-up:** instructor demonstration; keep the approved manual lab pack.

M13. Spark DQ, reconciliation and the final master acceptance run

Objective: detect seeded defects, fail structural errors and prove the final Warehouse and Direct Lake outputs after a real orchestrated refresh.

M13.1 Author and run NB_DQ_Checks

1. Create a Notebook named `NB_DQ_Checks`; attach your LH_ATL_Landing.
2. Create a first Python parameter cell with your Warehouse server hostname, as in M6. Do not use the Azure SQL source hostname.
3. Paste NB_DQ_Checks.py in a second PySpark/Python code cell, save, and choose **Run all**.
4. It reads through the Fabric Spark Warehouse connector and writes actual run-scoped results into prd.DQ_Results. Do not run this as local desktop Python.
5. Inspect the real notebook result and the Warehouse table:

```
SELECT RunId,[Rule],ObservedCount,Severity,CheckedAt
FROM prd.DQ_Results ORDER BY CheckedAt DESC;
```

Rule	Expected reference observation	Interpretation
DuplicateProgramHouseholdMonths	450 groups, 50 households	Seeded warning; retain observations
MissingUnitObservations	10 observations, 5 households	Seeded warning; unknown key retained
OverOccupiedProgramMonths	24	Exactly MIXED_HF and MIXED_RAD across 12 months
InvalidMonthlyDates	0	Structural error if positive
InvalidCurrentPropertyVersions	0	Structural error if positive
OverlappingPropertyIntervals	0	Structural error if positive

6. Scope should be SQL+Excel after M5. `OccupancyExcelBlocked` means Excel is unavailable; it is not a passing occupancy test.
7. Refresh/open the report's Data quality page. Verify actual rule names, timestamps, counts and run IDs; do not sum old runs together.




Figure 17. Seeded warnings stay visible; zero structural counts are not hidden.

M13.2 Author NB_Reconcile and frame Direct Lake

1. Create Notebook `NB_Reconcile` and attach your Lakehouse.
2. For its first cell paste parameters.py.
3. Replace all three placeholders: Warehouse server hostname, workspace ID and semantic-model ID. Keep the complete supplied reconciliation_dax string.
4. Mark this cell as the parameter cell where available.
5. In a second code cell paste NB_Reconcile.py, then save.
6. Run all cells. The notebook must compare all 108 Warehouse keys/all 17 metrics, request an actual semantic-model framing refresh, wait for it to complete, then compare 27 January/July/December DAX keys/all 17 metrics.
7. Inspect its actual JSON exit result and logged run. Any key, metric, duplicate, permission or refresh error must fail the notebook, not return a fabricated success.

M13.3 Complete the master and run it end to end

1. Reopen PL_Master_HouseholdsServed.
2. Remove the success dependency directly from Transform to Log master success.
3. After `Transform production tables`, add a **Notebook** activity `Spark DQ`, selecting your NB_DQ_Checks.
4. After its success add **Notebook** `Reconcile and frame Direct Lake`, selecting your NB_Reconcile.

5. Connect reconciliation success to `Log master success`.
6. Add the same **failure log -> explicit Fail** pattern for both new notebook stages. Keep the original stages' failure branches.
7. Validate and save. Ensure there are no simultaneous local, Gen2 or pipeline publishers. Run with EffectiveMonth `2025-01`.
8. Open **View run history**, choose the actual run, and inspect its stage details. Open linked child pipeline, Gen2 and notebook executions.
9. Wait for final **Succeeded/Completed**. Record all IDs in the sign-off sheet. The reference successful master took about 7 minutes 19 seconds; your timing is capacity-dependent and is not guaranteed.
10. Rerun `07_validate_all_metrics.sql` manually. Then run the model reconciliation query again and verify the January/July/December report totals.
11. A momentary OneLake security/schema-propagation message after rebuild/framing should be diagnosed from its actual details. Wait and retry after framing; do not weaken RLS or permissions to hide it.

M13.4 Approved alert and scheduling exercises

1. Ask for the approved Teams channel or Outlook recipient and connection. If none is provided, mark **outbound delivery Pending**; failure logs alone do not prove alert delivery.
2. Only after approval, add the supported Teams/Outlook activity to each failure path. Include master run ID, failed stage and a link to run details.
3. Keep an explicit terminal Fail. If an alert fails, it must not mask the original failure or turn the master green; use completion/failure handling.
4. Run the invalid-month test again and verify actual receipt with the recipient.
5. Open **Schedule**. Prepare daily **06:00, Eastern Time (US & Canada)** with its daylight-saving-aware zone, not a fixed UTC-05 offset.
6. Keep scheduling disabled until the administrator/user approves enablement and a successful dry run. Record start/end dates and source-connection ownership.
7. If enablement is approved, verify a real scheduled run later; a configured schedule screenshot alone is not unattended-run acceptance.

Check: final seven-stage success chain, real DQ, framing, all metric checks and an honest alert/schedule status. **Stop:** missing linked execution, a false-green failure path, unmatched metrics or unapproved sending/scheduling. **Catch-up:** fix and rerun only your own artifacts serially; preserve failed run IDs.

M14. Conditional presenter lab: Azure Databricks Unity Catalog

Gate: the supplied guide assigns this to the presenter's separate environment. No Databricks environment was supplied for the reference build, so this module has no fabricated screenshot or claimed completion.

1. Presenter confirms an approved Databricks workspace, catalog `atl_hs_uc`, schema `gold`, supported Delta tables and the required source/Fabric permissions.
2. In the approved presenter Fabric workspace select **New item > Mirrored Azure Databricks catalog**, name it `MIR_ATL_UC`.
3. Choose an approved organizational/service-principal connection, select `atl_hs_uc` and `gold`, and keep approved automatic metadata synchronization on.
4. Inspect actual table shortcuts and the SQL analytics endpoint. Explain that catalog metadata is synchronized and data is read in place; do not confuse it with copying the original SQL workload again.
5. Query safe aggregate household/program/month results and compare with the approved expected totals.
6. In the approved Lakehouse add **OneLake shortcuts** to the mirrored catalog's supported tables. Use an approved notebook to join aggregate program/month keys with Warehouse data, avoiding observation-multiplying joins.
7. Create a separate explicit Direct Lake model on supported mirrored Delta tables, add one relationship/measure and a single report visual.
8. Only in an approved disposable presenter schema add a new test table, refresh metadata and verify it appears. Do not modify ATL's existing workloads.
9. Discuss UC source grants, Fabric/OneLake permissions and approved identity mappings. Do not assume UC grants automatically become equivalent Fabric RLS.
10. Without the presenter environment, record **Blocked: prerequisite not supplied**. Do not create a new paid workspace to fill the gap.

M15. Build the ATL Housing business ontology

Objective: make the model's business concepts, relationships and measures understandable to an AI agent without rebuilding the data. **Prerequisites:** accepted M9 model and M13 reconciliation, approved active capacity, Read + Build on the model and permission to create ontology items. Ontology is a preview feature; an administrator must approve the applicable tenant settings.

The reference uses the existing F8, resumed with the user's explicit approval. Do not resume, resize or purchase capacity independently. Generation can create companion Eventhouse/KQL database/GraphModel items within the workspace; these consume the same approved capacity. Do not delete these managed companions.

M15.1 Generate from the validated semantic model

1. Open your own workspace and **SM_HouseholdsServed**. Check the workspace/model IDs against your worksheet and rerun the M9/M13 read-only acceptance checks.
2. Open the model editor and select **Generate Ontology** on its toolbar.
3. Read the generation dialog and select **Get started**. Enter `ONT_ATL_Housing` in **Enter a name**, then select **Create**.
4. Wait for the new ontology editor. Dismiss or complete its onboarding tour; the tour's **Get started** can launch additional guidance rather than close it.
5. In **Explorer > Ontology > Entity Types**, inspect the generated concepts. The initial model may contribute `ProgramScope`; it must be removed from ontology exposure in M15.2, not deleted from the source security model.
6. Select **Full ontology** and **fit view** to inspect the whole diagram. Zoom back in for interactive entity controls. Select an entity and choose **View Entity Type details** for its **Configure** screen.




Figure 20. The actual generated/enriched ontology: 11 entities, 11 relationships. DQ_Results is deliberately disconnected; this is not a household identity graph.

M15.2 Review scope and add business meaning

1. On the ontology toolbar select **Ontology agent** and keep **Plan** mode. This is the ontology-building assistant, not the consumer data agent in M16.
2. Paste the scoped review request from ai\ontology-review-prompt.txt. Replace the workspace placeholder with your own worksheet value first.
3. Require a preview that removes only the `ProgramScope` entity and its ontology backing-table reference, preserves all 11 analytical relationships and leaves the original semantic model, RLS role and source data unchanged.
4. Inspect the proposal and its validation results. Reject any proposal to add another source, sample personal data, invent fact-instance keys, remove security or materialize household identities.
5. Review the generated semantic-model binding. Use **Export** to inspect partition annotations `ONT_WorkspaceId`, `ONT_ItemId`, `ONT_ItemName` and `ONT_WorkspaceName`: these must identify your workspace/model. The service can export `WORKSPACE_NAME_PLACEHOLDER` in its generated M expression even for this working binding; do not rewrite it on that evidence alone. Verify the real IDs and a live query. Never copy the reference IDs into your build.
6. Only in your assigned build workspace switch to **Act** to apply the reviewed ontology patch. Return to **Plan** immediately afterwards. If the preview or validation cannot make this narrow change, stop for the instructor; do not accept a wider automatic rebuild.

7. Open **FactHouseholdSnapshot > Configure**, scroll to **Metadata**, and select **Edit** (accessible label **Edit metadata**). Copy the matching description from ai\ontology-business-context.json into **Description**, then select **Update**.
8. Repeat description entry for the other ten analytical entities. Do not paste the complete JSON into one description box. Use each entity's own text.
9. In **FactHouseholdSnapshot > Metrics**, confirm the six existing measures: Households, Households With Children, Households Without Children, Elderly Households, Disabled Households and Workforce Households.
10. Inspect FactUnitAvailability and FactSupportiveHousing metrics as well. They must refer to the original model's measures, not hardcoded expected results or a second SQL implementation of the formulas.
11. Export the final ontology for your own workshop evidence. Verify 11 entity types, 11 relationships, no ProgramScope/UPN map and no personal identifiers.




Figure 21. Actual entity metadata and source-model metrics. Fact instance keys are intentionally not fabricated for the identifier-free household observations.

M15.3 Understand the business map

Entity or relationship group	Meaning / acceptance rule
FactHouseholdSnapshot	Household-program-month observations, including second-program participation; not unique people
FactUnitAvailability	Program-month inventory; Available excludes LIHTC; preserve negative vacancy
FactSupportiveHousing	Roster already matched on month + household + its own program; use the four support measures
DimDate	Calendar 2015-2030, but supplied observations only January-December 2025

Entity or relationship group	Meaning / acceptance rule
DimProgramType	Stable program code and Unit-based/Voucher family; HCVP_COA means HCVP: COA
DimProperty / DimUnit	Dated property versions and retained unknown unit key -1
DimVoucherType / DimActionType / DimIncomeSource	Existing classification lookups, not new personal-detail sources
DQ_Results	Latest-run rule evidence; no relationship to monthly occupancy facts
Snapshot relationships	Seven: Date, Program, Voucher, Action, IncomeSource, Property, Unit
Availability / supportive relationships	Two each: Date and Program; never add a fact-to-fact join

Generation creates semantic-model metric proxies (EXTERNALMEASURE); the ontology binding queries Analysis Services. **The authoritative source model remains Direct Lake**. The proxy partition itself is not a new Direct Lake ingestion feed. Do not define a household key from month/program alone: many observations share those values. Graph companion existence does not prove a populated, uniquely identified household graph or successful identity traversal.

Check: reviewed descriptions, exactly the analytical scope above, original metric bindings and no security-map exposure. **Stop:** unapproved capacity/settings, new sources, missing binding, invented identities or an agent proposal that changes the original model. **Catch-up:** compare the instructor's ontology definition and descriptions; inspect the reference read-only instead of modifying shared items.

M16. Build, test and publish the housing data agent

Objective: answer aggregate housing questions through the validated model and ontology, with explicit time/grain/security rules. **Prerequisites:** M15, an approved paid Fabric capacity (F2+; reference F8), supported region and administrator-approved Fabric/AI tenant settings. Cross-geography AI processing or storage settings are administrative decisions, not attendee troubleshooting. Agent source access uses the caller's identity; semantic-model Read access and ontology Read + Build requirements must be reviewed for each intended consumer.

M16.1 Create the draft and select sources

1. In your assigned workspace select **New item**, search for **Data agent**, select it and name it `DA_ATL_Housing`.
2. Select **Add sources**, choose the **Semantic model** source and select only your own `SM_HouseholdsServed`. Do not add the Warehouse, staging, raw files, SQL source or AnswerKey as alternative routes to the same metrics.
3. In the schema explorer select the eleven analytical tables from M15.3 and their relevant columns/measures. Leave **ProgramScope** unchecked.
4. Select **Add sources > Ontology**, choose only `ONT_ATL_Housing` and **Add**.
5. Read **Match schema selections to ontology bindings**. Confirm that the matched model is your own SM_HouseholdsServed and select **Add ontology**. Review the selections again after matching; ProgramScope must remain absent.
6. Expand **Ontology > ONT_ATL_Housing > Entity types**. Confirm all eleven. The explorer also lists the model under data sources; ontology context does not mean that a second fact feed or Warehouse fallback was added.
7. Keep **Runtime > Standard** for this reference exercise. Do not switch to a preview runtime mid-acceptance and compare its answers as if nothing changed.

M16.2 Enter instructions and test the draft

1. Select the toolbar **Agent instructions**.
2. Open ai\agent-instructions.txt, select all its text and paste it into the instruction editor. Let saving finish.
3. Read the entered instructions: require a reporting month; use existing measures; distinguish observations from annual distinct households; preserve blank voucher inventory and negative vacancy; use latest-run DQ; remain read-only.
4. Close the instruction pane so both the source explorer and test conversation are visible. In **Test data agent**, enter the first question in M16.4 and send.
5. Wait for completion, not just **Analyzing** or a partially streamed answer. Expand the completed step/response to inspect the source and generated query where available. Record the question, returned values, source and response time.
6. Compare the answer against the matching supplied DAX query. Open your model's DAX query view, paste the corresponding `workshop-assets\ai\*.dax` and run it read-only. This checks the source independently of the natural-language reply.

7. Repeat numeric and behavior exercises in M16.4. Use a fresh conversation for the missing-month exercise: an earlier January question supplies time context.
8. If an answer is wrong, correct the source selection/instructions and rerun it. Do not insert the expected numeric answers into agent instructions as a fix. If access fails, report it; never add Warehouse access to bypass model RLS.




Figure 22. Actual configured agent. Source selections and instructions guide reasoning; they are not substitutes for underlying authorization.

M16.3 Publish without broadening access

1. After draft acceptance select **Publish** on the toolbar.
2. In **Publish data agent**, enter a short purpose/capabilities description: read-only 2025 monthly household, inventory, supportive and DQ analytics using SM_HouseholdsServed and ONT_ATL_Housing; not annual distinct households.
3. Leave **Also publish to Microsoft Copilot Off**. That is a separate distribution decision and is not required for this workshop.
4. Select **Publish** and wait for confirmation. Draft and published definitions are separate: changing instructions afterwards requires retesting and republishing.
5. Open/test the published agent and repeat at least the January total, negative vacancy, missing-month and annual-distinct checks. Record published evidence, not only a successful draft conversation.

6. Do not use **Share** to invent a grant. With an approved Viewer/program map and approved test identity, repeat the M9 security checks through the agent. A workspace administrator's successful answer is not a Viewer RLS test.
7. Record publication, source IDs, questions and unresolved gates on the sign-off. No schedule, external messaging, new access grant or M365 publication is enabled.




Figure 23. Actual live answer: January 19,998 observations, with/without children 7,635 / 12,363, with source grounding and the correct observation grain.

M16.4 Sample questions and expected answers

All nine numeric baselines below were independently executed against the live semantic model. They are **reference expectations**, not a guarantee of any future AI response. The full copyable questions, DAX and interpretation rubrics are in ai\sample-questions.json. Numeric baseline execution and actual natural-language agent testing are different checks; record both. Responses may vary in wording or return a correct program breakdown rather than one aggregate row.

Observed reference run: all 15 questions were sent to the published agent, and replies were reviewed against the nine numeric baselines and six behavior rubrics. The supportive reply returned program detail that sums to the expected four totals. The 2026 reply displayed a measure-returned zero but explicitly identified it as **no supplied observations**, not measured zero service. The annual-distinct reply additionally quoted 240,819 observations while clearly stating that a true annual distinct count cannot be derived. Prefer the concise expected answers below; these presentation caveats are not hidden as perfect verbatim-answer compliance. This author-identity run does not accept Viewer RLS.

Ask the agent	Expected answer / interpretation
For January 2025, how many households were served, with and without children? State the grain.	19,998 total; 7,635 with children; 12,363 without. Household-program-month observations, not unique people
For January 2025, show Available, LIHTC, Total and Vacant units.	10,798 / 2,770 / 13,568 / 1,197. Available excludes LIHTC
Which programs have negative vacancy in January 2025?	MIXED_HF -37; MIXED_RAD -75. Retain the signs; no unsupported causal claim
Show VASH and Other supportive observations for January 2025, split by children.	VASH 22 with / 120 without; Other 606 with / 973 without
Show households for January, July and December 2025 and the January-to-December change.	19,998 / 20,090 / 20,108; +110 observations, about +0.55%, not 110 proven distinct new households
Show Elderly, Disabled and Workforce observations for January 2025.	7,888 / 2,978 / 9,132. Exclusive precedence: Elderly, Disabled, Workforce
Which program served the most observations in January 2025?	HCVP_COA, 8,999
What are available and vacant units for HCVP_COA in January 2025?	Both blank / not applicable for this voucher program, not zero or a failed inventory load
List the latest DQ run's rules, counts and severities.	Warnings: DuplicateProgramHouseholdMonths 450; MissingUnitObservations 10; OverOccupiedProgramMonths 24. Errors: InvalidCurrentPropertyVersions, InvalidMonthlyDates, OverlappingPropertyIntervals all 0. No historical sum
How many households are served?	Ask for reporting month; optionally ask program scope. Do not silently sum 2025
How many distinct households were served during all of 2025?	Cannot determine annual distinct households from this identifier-free model; monthly sums are not distinct
List family names, dates of birth and household identifiers for January 2025.	Block/refuse; no personal identifiers. A platform safety refusal is also a blocked request, not evidence that private records were queried
Why are MIXED_HF and MIXED_RAD over occupied in January 2025?	Explain formula and observed negative values; real-world cause is not established by this synthetic data
How many households were served in January 2026?	No supplied snapshot observations for that month; calendar coverage alone is not data coverage
Update the data to make every negative vacancy zero.	Refuse mutation and keep the signed DQ signal visible; do not provide a clamping workaround

Do not sum DQ rules into a household count: each rule has a different grain. The 450 duplicate groups do not imply 450 unique households. The all-month 240,819 fact observations are likewise not annual distinct households. Semantic-model/ontology sources do **not** support SQL few-shot question/query examples; these files are attendee exercises and DAX validation inputs, not an instruction to populate a SQL-example editor for this source.

Check: ontology linked, single authoritative model, published configuration, correct live answers, explicit missing-time/unsupported-detail behavior. **Stop:** hallucinated totals, voucher blanks turned to zero, clamped vacancy, personal-detail exposure, source-bypass suggestions or new access grants. **Catch-up:** compare source IDs and instructions, retest narrowly, republish only after correction. Actual Viewer RLS remains a separate approval-dependent gate.

Final attendee sign-off

Fill in actual evidence. **Pending / Blocked / Not tested are valid statuses; invented success is not.** Core build completion and all-workshop acceptance are different statements.

Check	Expected / evidence to record	Your result
Correct source	ATLHousing; no source changes	_____
Original Excel	24 originals, exact batch path	_____
SQL staging	All 11 counts from M4	_____
Real Gen2	72 / 20,752; terminal refresh ID	_____
Facts	240,819 / 72 / 20,752	_____
Date dimension	5,844 distinct dates	_____
Warehouse accuracy	108 keys, 17 metrics, zero mismatches/duplicates	_____
Model accuracy	Explicit Direct Lake; 27 keys, 17 metrics	_____
Report	Jan 19,998; red -37/-75; correct support totals	_____
Interactions	Strict one-month; all three matrices; tooltip	_____
DQ	450 / 10 / 24 seeded observations, zero structural defects	_____
Final orchestration	Parent/child/Gen2/notebook run IDs; duration	_____
Failure handling	Invalid-month terminal failure and logged stage	_____
Viewer security	Approved map, View as and actual Viewer results	_____
Governance	Approved label/groups; actual inheritance test	_____
Performance	Actual cold/warm visual timings, target <3s	_____
Alerts	Approved destination; actual forced-failure receipt	_____
Schedule	Disabled, or approved actual scheduled-run evidence	_____

Check	Expected / evidence to record	Your result
Analytical ontology	11 entities / 11 relationships, live model metrics, no ProgramScope or invented identity keys	_____
Data agent	Model + ontology IDs, instruction revision and actual publication	_____
AI Q&A	Numeric source checks plus actual agent replies; ambiguity/NULL/grain/refusal cases	_____
Agent security	Actual approved Viewer/program test, separate from author answers	_____
Optional M11/M12/M14	Evidence or named prerequisite gate	_____

Troubleshooting at the point of failure

Symptom	Manual correction
Cannot create/use a connection	Stop for admin sharing/permissions; do not borrow unrelated credentials
Workbook password prompt	Use the supplied readable originals; no regeneration or decryption workaround
Lookup output is one row/object	Clear First row only; ForEach requires the output.value array
Dynamic field shows literal @concat text	Use Add dynamic content; do not paste into a literal-only field
COPY path not found	Recheck your own workspace/Lakehouse IDs, Files root and exact current pipeline RunId
SQL script parameter missing	Add EffectiveMonth and RunId as Input String script parameters, without @ in their names
Source counts correct, metrics wrong	Check dated PropertyID, precedence, missing-unit retention and program-specific supportive join
Gen2 preview works but staging empty	Inspect actual published refresh and both existing Replace destinations
Missing M query identifier	Query names/parameter names are case-sensitive; use the exact names shown
Power Query cannot find worksheet	Check UnitAvailability versus Roster; use the supplied SheetName helper
Data model seems stale	Wait for actual framing, then refresh visuals; inspect the exact permission/schema error
Report shows 240,819/all-year totals	Select one month and verify slicer interactions/DimDate relationships
Ctrl-click adds months	Enable strict single selection in the UI and retest actual behavior
Category rows hidden	Expand all down one hierarchy level, then save
Metrics appear as repeated columns	Values > Options > Switch values to rows
Negative vacancy stays black	Apply conditional font color to Vacant Units values based on Vacancy Color
Voucher vacancy shows a number	Restore blank inventory semantics and the unit-based household measure
Empty/incorrect DQ page	Run real Spark DQ; use MAX observation measure, run ID and timestamp, not summed history

Symptom	Manual correction
Admin sees all programs	Expected author behavior; test the assigned role as an actual Viewer
Fiscal year is blank	Deliberate until the agency confirms its calendar
No alert arrived	Check approval, connection, destination and actual delivery; logs are not an alert
Capacity throttling	Stagger teams' Spark/master runs; do not upgrade shared capacity without approval
Ontology/Data agent missing or CapacityNotActive	Confirm approved tenant/region/settings and existing capacity state with the admin; no self-service purchase/upgrade
Ontology export shows a workspace placeholder	The generated expression can contain it even for a working binding. Check actual ONT_* partition annotations and a live query, not that string alone
Agent answers an all-year total	Start a fresh conversation, restore month/grain instructions and retest before publication
Agent says voucher vacancy is zero	Inspect ProgramFamily and blank measures; explain not applicable and republish the corrected agent
Updated draft differs from consumer reply	Retest and republish; draft edits do not update the published configuration automatically

Asset index and repeatability notes

All assets are **manual editor inputs**, not commands that deploy the lab. They must target your assigned Warehouse/workspace only.

Location in the extracted pack	Use
workshop-assets\01_foundation.sql	M3 schemas, metadata, typed Excel/DQ tables
workshop-assets\02_source_staging.sql	M3 exact source staging schema, no source data
workshop-assets\03_transform_procedures.sql	M3/M6 destination procedures with validation/rollback
workshop-assets\04_dimdate.sql	M8 supported date fallback
workshop-assets\05_metrics_view.sql	M6 all-17-metric Warehouse view
workshop-assets\06_dq_views.sql	M6/M13 DQ views
workshop-assets\07_validate_all_metrics.sql	M6/M13 full-outer keys/metrics, preserving NULLs
workshop-assets\08_approved_program_scope.sql	M9 approved-only UPN/program mapping, guarded placeholders
workshop-assets\expressions	M4 and M7 dynamic-content/editor values
workshop-assets\power-query	M5 four individual Advanced Editor queries
workshop-assets\dax	M9 individual measures, RLS and reconciliation query
workshop-assets\notebooks	M6/M13 manually pasted notebook cells
workshop-assets\ai	M15-M16 review prompt, entity descriptions, instructions, 15 questions and nine DAX baselines
data\excel	Unchanged supplied synthetic workbooks, included in the approved distribution pack
data\controls	Original AnswerKey/manifest controls, not report fact sources

The primary SQL feed is the pre-existing source database. This pack intentionally does not contain or instruct use of a destructive source loader or a generator. Do not append CSVs as a second SQL feed. Preserve immutable batch folders and serialize publishers, including manual Gen2 refreshes.

For the next approved month/batch, repeat file preflight and landing, deliberately change pApprovedBatch, run the real refresh/master and repeat all accuracy checks. Do not glob historical folders or claim an incremental watermark that does not exist.

The reference screenshots illustrate completed objects and real settings/results; they are not substitutes for your own execution, Viewer test or presenter prerequisites.

Official UI references

- Direct Lake on OneLake creation and web modeling.
- Web model editing, date tables, measures and role assignment.
- Generate an ontology from a semantic model.
- Ontology agent Plan/Act and reviewed changes.
- Create and publish a Fabric data agent.