

# Lecture 2.1 – Computing with Data

M30299 Programming

School of Computing  
University of Portsmouth

# Introduction to Lecture

- The information processed by a program is known as **data**.
- In this lecture we:
  - investigate different kinds of data;
  - define what we mean by a **data type**; and
  - look at the basics of Python's **numeric** data types.
- We'll cover more on the numeric types next lecture, and look at some other data types in detail in the following few lectures.

# Data

- There are many kinds of data, and different programs process data of various kinds.
- Many programs process **numerical** data.
- Commonly in programming we distinguish between:
  - **integers** (e.g. 3245, -76 and 2), and
  - **fractional numbers** (e.g. -8.3, 0.5274 and 2.0).
- There are also **strings** (e.g. "Enter a weight in kilos").
- Most programs also need to use truth values (or **Boolean** values). There are only two of these: True and False.

# Data types (1)

- The terms “integer”, “float” (which we use for fractional numbers), “string” and “Boolean” are names of **data types**.
- We often say **type**, or in some contexts **class**, instead of data type.
- Any particular data value belongs to a **single** type.
- For example, what are the types of the following values?
  - "Hello, World!"
  - -57.3
  - 12
  - False
  - 9.0
  - "12"

# Data types (2)

- Python's basic types have the names: `int`, `float`, `str` & `bool`.
- Most programming languages provide types such as these.
- However, there are many other kinds of data we'd like to process; for example:
  - in a graphics program: windows, textboxes, rectangles, lines, ...
  - in an adventure game: players, rooms, objects, food, ...
  - in a word processor: words, paragraphs, styles, fonts, ...
  - in a music program: tracks, albums, artists, ...
- These types are not part of any programming language; they are defined **using the language**; we'll see how later in the module.

# Data types and operations

- A data type can be considered as a **set** of all its data values.
- But a data type also has some **operations** associated with it.
- For example, the numerical data types `int` and `float` both include the arithmetic operations:
  - `+` (addition) and `-` (subtraction)
  - `*` (multiplication) and `/` (division)
- What other operations might be associated with `int` and `float`?
- What operations do you think the following data types have?
  - `str`
  - `bool`

# int data values

- The integer type, `int`, comprises whole numbers (i.e. numbers without a decimal point).
- Examples of `int` values are:

312

-54

0

1424567768534345328

# float data values

- The float data type comprises numbers with a decimal point.

- Examples of float values are:

3.14159

-27.0

6.24e273    ( $6.24 \times 10^{273}$ )

- They are represented in **floating point** form, typically using 64 binary digits (for details, see Architecture and Operating Systems).
- The range of float is huge, but the accuracy is limited to about 15 significant figures.



# Numeric operators - example expressions

```
>>> x = 8
```

```
>>> 2 * x + 7.5
```

```
23.5
```

```
>>> x ** 2
```

```
64
```

```
>>> x / 5
```

```
1.6
```

```
>>> x / 2
```

```
4.0
```

- Notice that the result is an `int` only when both **operands** are `ints`, but that division **always** gives a result of type `float`.

# Operator precedence (1)

- Each operator has a **precedence** which determines the evaluation order of expressions.
- Operators with higher precedence are applied before those with lower precedence.
- For example:

```
>>> 1 + 2 * 3  
7
```

# Operator precedence (2)

- Operators with equal precedence are applied from left to right:

```
>>> x = 10
>>> 100 / x * 2
20.0
```

- **Brackets** impose a desired order of evaluation:

```
>>> (1 + 2) * 3
9
>>> x = 10
>>> 100 / (x * 2)
5.0
```

# Type conversions (1)

- It's useful to convert values between types `str`, `int` and `float`.
- To convert a value to a particular type, we use the name of that type as a function:

```
>>> float(5)
```

```
5.0
```

```
>>> int(6.8)
```

```
6
```

```
>>> str(6.8)
```

```
'6.8'
```

```
>>> int("12")
```

```
12
```

```
>>> float("3.8")
```

```
3.8
```

# Type conversions (2)

- See that when we convert a float into an int, rounding is not performed—the part after the decimal point is simply chopped.
- We can only convert sensible values; the following will cause errors:

```
>>> float("cheese and ham")
```

```
error!
```

```
>>> int("3.8")
```

```
error! (Python doesn't convert this to 3)
```

# Reading input from the user (1)

- Recall the use of `float` from the last lecture:

```
kilos = float(input("Enter a weight in kilos: "))  
pounds = 2.2 * kilos  
print("The weight in pounds is", pounds)
```

- The value given by the `input` function, e.g.:

```
input("Enter a weight in kilos: ")
```

will be a **string** containing the digits inputted by the user.

- `float` then converts this string value to a float value.

# Reading input from the user (2)

- We have to use `float` in this program, since:
  - we need `kilos` to be of a numeric type;
  - the inputted value might not be a whole number.
- How would we write statements which have the following prompts?
  - What is your name?
  - How many sisters do you have?