

ICPC 2026

PROBLEM	READ	SOLVED	WRITTEN	OPENED	COMMENT
A					
B					
C					
D					
E					
F					
G					
H					
I					
J					
K					
L					
M					
N					

Time	Andrey	Taisia	Timofey
0:30			
1:00			
1:30			
2:00			
2:30			
3:00			
3:30			
4:00			
4:30			
5:00			

Contents

1	Algebra	2
1.1	Gauss	2
2	Combinatorics	2
2.1	Gray Code	2
3	Convex Hull Trick	2
3.1	Convex Hull Trick	2
4	Convolutions	3
4.1	FFT MOD	3
4.2	FFT	4
4.3	FHT	5
4.4	SOS DP	6
5	Data Structures	6
5.1	Centroid Decomposition	6
5.2	DSU	7
5.3	Disjoint Sparse Table	8
5.4	Fenwick 2D	8
5.5	Fenwick Tree	9
5.6	HLD	9
5.7	Implicit Segment Tree	10
5.8	Persistent DSU	12
5.9	Prefix Automate	12
5.10	Segment Tree Beats	13
5.11	Segment Tree Mass	15
5.12	Segment Tree	17
5.13	Sparse Table	18
5.14	Treap	18
6	Flows	20
6.1	Dinic	20
7	Graphs	21
7.1	2 SAT	21
7.2	Euler Path	22
7.3	Hopcroft Karp	22
7.4	Hungarian	23
7.5	Initial Pairing	24
7.6	Kuhn	24
8	Matroids	25

8.1	MatroidExamples	25
8.2	MatroidIntersectionUnweighted	29
8.3	MatroidIntersectionWeighted	30
9	Number Theory	31
9.1	Eratosthenes	31
9.2	FloorSum	31
9.3	Miller Rabin	31
10	Strings	32
10.1	LCP	32
10.2	Prefix Function	32
10.3	Suffix Massive	32
10.4	Z Function	33

1 Algebra

1.1 Gauss

```
// a: n x (m + 1), last column is free terms
// returns one solution (free vars = 0), empty vector if no solutions
vector<ld> gauss(vector<vector<ld>> a) {
    const ld EPS = 1e-12;
    ll n = a.size();
    if (n == 0) {
        return {};
    }
    ll m = a[0].size() - 1;

    vector<ll> where(m, -1);
    for (ll col = 0, row = 0; col < m && row < n; ++col) {
        ll sel = row;
        for (ll i = row; i < n; ++i) {
            if (fabs1(a[i][col]) > fabs1(a[sel][col]))
                sel = i;
        }
        if (fabs1(a[sel][col]) < EPS)
            continue;

        swap(a[sel], a[row]);
        where[col] = row;
```

```
        for (ll i = 0; i < n; ++i) {
            if (i == row)
                continue;
            ld c = a[i][col] / a[row][col];
            if (fabs1(c) < EPS)
                continue;
            for (ll j = col; j <= m; ++j)
                a[i][j] -= a[row][j] * c;
        }
        ++row;
    }

    vector<ld> ans(m, 0);
    for (ll i = 0; i < m; ++i) {
        if (where[i] != -1)
            ans[i] = a[where[i]][m] / a[where[i]][i];
    }

    for (ll i = 0; i < n; ++i) {
        ld sum = 0;
        for (ll j = 0; j < m; ++j)
            sum += ans[j] * a[i][j];
        if (fabs1(sum - a[i][m]) > EPS)
            return {};
    }
    return ans;
}
```

2 Combinatorics

2.1 Gray Code

```
inline ll g(ll n) {
    return n ^ (n >> 1);
}
```

3 Convex Hull Trick

3.1 Convex Hull Trick

```
// monotone lines
```

```

struct ConvexHullTrick {
    // a, b of length k, p of lengths max(0, k - 1)
    // all lines is a[i] * x + b[i]
    // and line i > 0 maximum from x = p[i - 1] to x = p[i] - 1
    vector<ll> a, b, p;

    // a1 < a2
    static ll intersect(ll a1, ll b1, ll a2, ll b2) {
        ll den = a2 - a1;
        ll num = b1 - b2;
        if (num >= 0) {
            return (num + den - 1) / den;
        } else {
            return num / den;
        }
    }

    // na >= a[i] forall i
    void add_line(ll na, ll nb) {
        if (a.empty()) {
            a.push_back(na);
            b.push_back(nb);
            return;
        }
        if (a.back() > na) {
            return;
        }
        while (!p.empty() && a.back() * p.back() + b.back() <= na * p.
back() + nb) {
            p.pop_back();
            a.pop_back();
            b.pop_back();
        }
        // else na == a.back() and in one concrete point
        // new line leq of old > in all points new line >
        if (a.back() < na) {
            p.push_back(intersect(a.back(), b.back(), na, nb));
            a.push_back(na);
            b.push_back(nb);
        }
    }

    ll query(ll x) {
        if (a.empty()) {

```

```

            return -inf;
        }
        ll l = 0, r = (ll)a.size();
        while (r - l > 1) {
            ll m = (r + l) / 2;
            if (p[m - 1] <= x) {
                l = m;
            } else {
                r = m;
            }
        }
        return a[l] * x + b[l];
    }
};

```

4 Convolutions

4.1 FFT MOD

```

const ll MOD = 998244353;
const ll ROOT = 31;
const int ROOT_PW = (1ll << 23);

vector<vector<ll>> w;

void precalc_ws(ll lg_n) {
    w.resize(lg_n + 1);
    w[0].resize(1, 1);
    for (int l = 1; l <= lg_n; ++l) {
        ll n = (1ll << l);
        w[l].resize(n / 2);

        ll fw = ROOT;
        for (int i = 0; i < 23 - l; ++i) {
            fw = (fw * fw) % MOD;
        }
        for (int j = 0; j < (n >> 1); ++j) {
            if (j % 2 == 0) {
                w[l][j] = w[l - 1][j / 2];
            } else {
                w[l][j] = (w[l - 1][j / 2] * fw) % MOD;
            }
        }
    }
}

```

```

    }
}

void fft_inpl(vector<ll>& a, bool invert) {
    int n = a.size();

    // apply permutation by bit_rev
    for (int i = 1, j = 0; i < n; ++i) {
        int bit = n >> 1;
        for (; j & bit; bit >>= 1)
            j ^= bit;
        j ^= bit;
        if (i < j)
            swap(a[i], a[j]);
    }

    for (int len = 2, lg = 1; len <= n; len <= 1, ++lg) {
        for (int i = 0; i < n; i += len) {
            for (int j = 0; j < (len >> 1); ++j) {
                ll root = w[lg][j];
                if (invert && j) {
                    root = MOD - w[lg][(len >> 1) - j];
                }
                ll u = a[i + j], v = (a[i + j + len / 2] * root) % MOD;
                a[i + j] = u + v < MOD ? u + v : u + v - MOD;
                a[i + j + len / 2] = u - v >= 0 ? u - v : u - v + MOD;
            }
        }
    }

    if (invert) {
        int nrev = rev(n);
        for (int i = 0; i < n; ++i) {
            a[i] *= nrev;
            a[i] %= MOD;
        }
    }
}

vector<ll> vect_mult(const vector<ll>& a, const vector<ll>& b) {
    ll sz = a.size() + b.size() - 1;
    ll n = 1;
    int lg_n = 0;
    while (n < sz) {
        n <= 1;

```

```

        ++lg_n;
    }
    if (w.size() <= lg_n) {
        precalc_ws(lg_n);
    }

    vector<ll> fa(n, 0), fb(n, 0);
    for (int i = 0; i < n; ++i) {
        if (i < a.size()) {
            fa[i] = a[i];
        }
        if (i < b.size()) {
            fb[i] = b[i];
        }
    }

    fft_inpl(fa, false);
    fft_inpl(fb, false);
    for (int i = 0; i < n; ++i) {
        fa[i] *= fb[i];
        fa[i] %= MOD;
    }
    fft_inpl(fa, true);

    vector<ll> mult(sz);
    for (int i = 0; i < sz; ++i) {
        mult[i] = fa[i];
    }
    return mult;
}

```

4.2 FFT

```

vector<vector<comp>> w;

void precalc_ws(ll lg_n) {
    w.resize(lg_n + 1);
    w[0].resize(1, 1);
    for (int l = 1; l <= lg_n; ++l) {
        ll n = (1ll << l);
        w[l].resize(n / 2);

        // need cosl, sinl for complex<ld>
        comp fw(cos(2 * PI / n), sin(2 * PI / n));

```

```

    for (int j = 0; j < (n >> 1); ++j) {
        if (j % 2 == 0) {
            w[l][j] = w[l - 1][j / 2];
        } else {
            w[l][j] = w[l - 1][j / 2] * fw;
        }
    }
}

void fft_inpl(vector<comp>& a, bool invert) {
    int n = a.size();

    for (int i = 1, j = 0; i < n; ++i) {
        int bit = n >> 1;
        for (; j & bit; bit >>= 1)
            j ^= bit;
        j ^= bit;
        if (i < j)
            swap(a[i], a[j]);
    }

    for (int len = 2, lg = 1; len <= n; len <= 1, ++lg) {
        for (int i = 0; i < n; i += len) {
            for (int j = 0; j < (len >> 1); ++j) {
                comp root = w[lg][j];
                if (invert && j)
                    root = -w[lg][(len >> 1) - j];
                comp u = a[i + j], v = a[i + j + (len >> 1)] * root;
                a[i + j] = u + v;
                a[i + j + (len >> 1)] = u - v;
            }
        }
    }

    if (invert) {
        double rev_n = 1.0 / n;
        for (int i = 0; i < n; ++i) {
            a[i] *= rev_n;
        }
    }
}

vector<ll> vect_mult(const vector<ll>& a, const vector<ll>& b) {
    ll sz = a.size() + b.size() - 1;

```

```

    ll n = 1;
    int lg_n = 0;
    while (n < sz) {
        n <= 1;
        ++lg_n;
    }
    if (w.size() <= lg_n) {
        precalc_ws(lg_n);
    }

    vector<comp> p(n, 0);
    for (int i = 0; i < n; ++i) {
        p[i] = comp(i < a.size() ? a[i] : 0, i < b.size() ? b[i] : 0);
    }

    fft_inpl(p, false);
    for (int i = 0; i < n; ++i) {
        p[i] *= p[i];
    }
    fft_inpl(p, true);

    vector<ll> mult(sz);
    for (int i = 0; i < sz; ++i) {
        // need roundl for complex<ld>
        mult[i] = round(p[i].imag() * 0.5);
    }
    return mult;
}

```

4.3 FHT

```

inline ll soft_mod(ll a) {
    return a >= MOD ? a - MOD : a;
}

void FHT(vector<ll>& a) {
    ll sz = a.size();
    for (int mid = 1; mid < sz; mid <= 1) {
        for (int i = 0; i < sz; i += mid << 1) {
            for (int j = 0; j < mid; ++j) {
                ll x = a[i + j];
                ll y = a[i + j + mid];
                a[i + j] = soft_mod(x + y);
                a[i + j + mid] = soft_mod(x - y + MOD);
            }
        }
    }
}

```

```

    }
}

vector<ll> xor_mult(vector<ll> a, vector<ll> b) {
    FHT(a);
    FHT(b);
    ll n = a.size();
    vector<ll> c(n);

    for (int i = 0; i < n; ++i) {
        c[i] = (a[i] * b[i]) % MOD;
    }

    FHT(c);
    ll revn = bin_pow(n, MOD - 2);
    for (int i = 0; i < n; ++i) {
        c[i] *= revn;
        c[i] %= MOD;
    }
    return c;
}

```

4.4 SOS DP

```

void sos(vector<ll>& dp) {
    ll n = dp.size();
    ll k = 0;
    while ((1ll << k) < n) {
        ++k;
    }

    for (int j = 0; j < k; ++j) {
        for (int i = 0; i < n; ++i) {
            if (i & (1ll << j)) {
                dp[i] += dp[i ^ (1ll << j)];
            }
        }
    }
}

void revsos(vector<ll>& dp) {
    ll n = dp.size();

```

```

    ll k = 0;
    while ((1ll << k) < n) {
        ++k;
    }

    for (int j = k - 1; j >= 0; --j) {
        for (int i = 0; i < n; ++i) {
            if (i & (1ll << j)) {
                dp[i] -= dp[i ^ (1ll << j)];
            }
        }
    }
}

```

5 Data Structures

5.1 Centroid Decomposition

```

struct CentroidDecomp {
    ll n;
    vector<ll> parent;

    void calc_sizes(ll v, ll mark, vector<ll>& used, vector<vector<ll>>& g, vector<ll>& s) {
        s[v] = 1;
        used[v] = mark;

        for (ll u : g[v]) {
            if (used[u] < mark) {
                calc_sizes(u, mark, used, g, s);
                s[v] += s[u];
            }
        }
    }

    ll find_centroid(ll v, ll mark, vector<ll>& used, vector<vector<ll>>& g, vector<ll>& s, ll sz) {
        used[v] = mark;

        for (ll u : g[v]) {
            if (used[u] < mark) {
                if (s[u] > sz / 2) {

```

```

        return find_centroid(u, mark, used, g, s, sz);
    }
}

return v;
}

void set_parent(ll v, ll mark, vector<ll>& used, vector<vector<ll>>&
g, ll cent) {
    if (v != cent)
        parent[v] = cent;
    used[v] = mark;

    for (ll u : g[v]) {
        if (used[u] < mark) {
            set_parent(u, mark, used, g, cent);
        }
    }
}

```

```

CentroidDecomp(ll N, vector<vector<ll>>& g) {
    n = N;
    parent.assign(n, -1);

    vector<ll> used(n, 0);
    vector<ll> s(n, 0);
    ll cnt_used = 0;
    ll mark = 0;

    while (cnt_used < n) {
        ++mark;
        ll pass_mark = mark;
        for (int i = 0; i < n; ++i) {
            if (used[i] >= pass_mark)
                continue;
            calc_sizes(i, pass_mark, used, g, s);
            ++mark;
            ll cent = find_centroid(i, mark, used, g, s, s[i]);

            ++mark;
            set_parent(i, mark, used, g, cent);
            used[cent] = inf;
            ++cnt_used;
        }
    }
}

```

```

    }
}
};

```

5.2 DSU

```

struct DSU {
    ll n;
    vector<ll> prev, size;

    DSU(ll N) : n(N) {
        prev.assign(n, -1);
        size.assign(n, 1);
    }

    ll root(ll a) {
        ll aa = a;
        while (prev[a] != -1)
            a = prev[a];

        while (prev[aa] != -1) {
            ll last = prev[aa];
            prev[aa] = a;
            aa = last;
        }
        return a;
    }

    bool connected(ll a, ll b) {
        return root(a) == root(b);
    }

    bool unite(ll a, ll b) {
        a = root(a);
        b = root(b);
        if (a == b)
            return false;
        if (size[a] < size[b])
            swap(a, b);
        prev[b] = a;
        size[a] += size[b];
        return true;
    }
}

```

};

5.3 Disjoint Sparse Table

```

struct DisjointSparseTable {
    vector<vector<ll>> dp;

    ll neutral() {
        return 0;
    }
    ll merge(ll a, ll b) {
        return a + b;
    }

    DisjointSparseTable() {}

    DisjointSparseTable(const vector<ll>& a) {
        ll n = a.size();
        ll k = 0;
        ll nn = 1;
        while (nn <= n) {
            ++k;
            nn <<= 1;
        }

        dp.assign(k, vector<ll>(n + 1, neutral()));

        ll t = 0;
        for (ll len = 1; len <= n; len <<= 1, ++t) {
            for (ll cent = len; cent <= n; cent += len * 2) {
                dp[t][cent - 1] = a[cent - 1];
                for (ll i = cent - 2; i >= cent - len; --i) {
                    dp[t][i] = merge(a[i], dp[t][i + 1]);
                }

                dp[t][cent] = neutral();
                for (ll i = cent + 1; i < min(cent + len, n + 1); ++i) {
                    dp[t][i] = merge(dp[t][i - 1], a[i - 1]);
                }
            }
        }
    }
};

```

```

// query on [l, r)
ll query(ll l, ll r) {
    if (r <= 1)
        return neutral();
    ll t = 63 - __builtin_clzll((ull)(1 ^ r));
    return merge(dp[t][l], dp[t][r]);
}
};

```

5.4 Fenwick 2D

```

template <class T>
struct Fenwick2D {
    ll n = 0, m = 0;
    vector<vector<T>> bit;

    Fenwick2D() = default;
    Fenwick2D(int n_, int m_) {
        init(n_, m_);
    }

    void init(int n_, int m_) {
        n = n_;
        m = m_;
        bit.assign((int)n + 1, vector<T>((int)m + 1, T{}));
    }

    // add delta at (x, y), 0-indexed
    void add(ll x, ll y, T delta) {
        for (ll i = x + 1; i <= n; i += i & -i)
            for (ll j = y + 1; j <= m; j += j & -j)
                bit[i][j] += delta;
    }

    // sum over [0..x] x [0..y], 0-indexed; returns 0 if x<0 or y<0
    T sum_prefix(ll x, ll y) const {
        if (x < 0 || y < 0)
            return T{};
        T res{};
        for (ll i = x + 1; i > 0; i -= i & -i)
            for (ll j = y + 1; j > 0; j -= j & -j)
                res += bit[i][j];
        return res;
    }
};

```



```

// sum over rectangle [x1..x2] x [y1..y2], inclusive, 0-indexed
T sum_rect(ll x1, ll y1, ll x2, ll y2) const {
    return sum_prefix(x2, y2) - sum_prefix(x1 - 1, y2) - sum_prefix(
x2, y1 - 1) + sum_prefix(x1 - 1, y1 - 1);
}
};

```

5.5 Fenwick Tree

```

struct FenwickTree {
    vector<ll> tree;
    ll n;

    FenwickTree(ll N) {
        n = N;
        tree.assign(n, 0);
    }

    ll F(ll x) {
        return x & (x + 1);
    }

    ll H(ll x) {
        return x | (x + 1);
    }

    // [0, r)
    ll query(ll r) {
        if (r > n) {
            r = n;
        }
        --r;
        ll ans = 0;
        while (r >= 0) {
            ans ^= tree[r];
            r = F(r) - 1;
        }
        return ans;
    }

    // [l, r)
    ll query(ll l, ll r) {
        return query(r) ^ query(l);
    }
};

```

```

}

void add(ll id, ll val) {
    while (id < n) {
        tree[id] ^= val;
        id = H(id);
    }
}
};

```

5.6 HLD

```

struct HLD {
    ll n;
    vector<ll> top, pos, h, par;

    ll gpos = 0;

    SegmentTree st;

    void calc_sizes(ll v, vector<char>& used, const vector<vector<ll>>& g
, vector<ll>& s) {
        s[v] = 1;
        used[v] = 1;

        for (ll u : g[v]) {
            if (!used[u]) {
                calc_sizes(u, used, g, s);
                s[v] += s[u];
            }
        }
    }

    void build_dec(ll v, ll p, ll pr, vector<char>& used, const vector<
vector<ll>>& g, vector<ll>& s) {
        used[v] = 1;
        pos[v] = gpos++;
        top[pos[v]] = pos[p];
        par[pos[v]] = pos[pr];
        if (pr != v)
            h[pos[v]] = h[pos[pr]] + 1;

        vector<ll> child;
    }
};

```

```

    for (ll u : g[v]) {
        if (!used[u]) {
            child.push_back(u);
        }
    }

    for (int i = 1; i < child.size(); ++i) {
        if (s[child[i]] > s[child[0]]) {
            swap(child[i], child[0]);
        }
    }

    if (!child.empty()) {
        build_dec(child[0], p, v, used, g, s);
        for (int i = 1; i < child.size(); ++i) {
            build_dec(child[i], child[i], v, used, g, s);
        }
    }
}

HLD(ll N, const vector<vector<ll>>& g, const vector<ll>& a) {
    n = N;

    top.resize(n, 0);
    pos.resize(n, 0);
    h.resize(n, 0);
    par.resize(n, 0);
    vector<char> used(n, 0);
    vector<ll> s(n, 0);

    calc_sizes(0, used, g, s);
    used.assign(n, 0);
    build_dec(0, 0, 0, used, g, s);

    vector<ll> pa(n, 0);
    for (int i = 0; i < n; ++i) {
        pa[pos[i]] = a[i];
    }

    st = SegmentTree(pa);
}

ll query(ll u, ll v) {
    ll ans = 0;

```

```

    u = pos[u];
    v = pos[v];

    ll pu = top[u];
    ll pv = top[v];

    while (pu != pv) {
        if (h[pu] >= h[pv]) {
            ans += st.query(pu, u + 1).sum;
            u = par[pu];
            pu = top[u];
        } else {
            ans += st.query(pv, v + 1).sum;
            v = par[pv];
            pv = top[v];
        }
    }
    ans += st.query(min(u, v), max(u, v) + 1).sum;

    return ans;
}

void change(ll u, ll val) {
    u = pos[u];
    st.change(u, val);
}
};

```

5.7 Implicit Segment Tree

```

struct ImplicitSegmentTree {
    struct Node {
        Node* left = nullptr;
        Node* right = nullptr;
        ll sum = 0;
        ll add = 0;
    };

    Node neutral = Node();
    ll n;
    Node* root = nullptr;

    Node merge(Node n1, Node n2) {

```

```

    Node res;
    res.sum = n1.sum + n2.sum;
    return res;
}

void fix(Node* node) {
    node->sum = 0;
    if (node->left) {
        node->sum += node->left->sum;
    }
    if (node->right) {
        node->sum += node->right->sum;
    }
}

void apply(Node* node, ll l, ll r, ll val) {
    node->sum += val * (r - l);
    node->add += val;
}

void push(Node* node, ll l, ll r) {
    if (node->add == 0) {
        return;
    }
    ll m = (l + r) / 2;
    if (!node->left) {
        node->left = new Node();
    }
    if (!node->right) {
        node->right = new Node();
    }
    apply(node->left, l, m, node->add);
    apply(node->right, m, r, node->add);
    node->add = 0;
}

ImplicitSegmentTree() {
}

ImplicitSegmentTree(ll N) {
    n = N;
}

ImplicitSegmentTree(const vector<ll>& start) {

```

```

    n = start.size();
    for (ll i = 0; i < n; i++) {
        change(i, start[i]);
    }
}

void change(Node*& node, ll l, ll r, ll id, ll val) {
    if (!node) {
        node = new Node();
    }
    if (l + 1 == r) {
        node->sum = val;
        node->add = 0;
        return;
    }
    push(node, l, r);
    ll m = (l + r) / 2;
    if (id < m) {
        change(node->left, l, m, id, val);
    } else {
        change(node->right, m, r, id, val);
    }
    fix(node);
}

void change(ll id, ll val) {
    change(root, 0, n, id, val);
}

void add(Node*& node, ll l, ll r, ll ql, ll qr, ll val) {
    if (qr <= l || r <= ql) {
        return;
    }
    if (!node) {
        node = new Node();
    }
    if (ql <= l && r <= qr) {
        apply(node, l, r, val);
        return;
    }
    push(node, l, r);
    ll m = (l + r) / 2;
    add(node->left, l, m, ql, qr, val);
    add(node->right, m, r, ql, qr, val);
}

```

```

    fix(node);
}

void add(ll ql, ll qr, ll val) {
    add(root, 0, n, ql, qr, val);
}

Node query(Node* node, ll l, ll r, ll ql, ll qr) {
    if (!node || qr <= l || r <= ql) {
        return neutral;
    }
    if (ql <= l && r <= qr) {
        return *node;
    }
    push(node, l, r);
    ll m = (l + r) / 2;
    return merge(query(node->left, l, m, ql, qr), query(node->right,
m, r, ql, qr));
}

Node query(ll ql, ll qr) {
    return query(root, 0, n, ql, qr);
}
};

```

5.8 Persistent DSU

```

struct PersistentDSU {
    ll n;
    vector<ll> prev, size;

    PersistentDSU(ll N) : n(N) {
        prev.assign(n, -1);
        size.assign(n, 1);
    }

    ll root(ll a) {
        while (prev[a] != -1)
            a = prev[a];
        return a;
    }

    bool connected(ll a, ll b) {
        return root(a) == root(b);
    }
};

```

```

}

vector<pair<ll, ll>> changes; //

bool unite(ll a, ll b) {
    a = root(a);
    b = root(b);
    if (a == b)
        return false;
    if (size[a] < size[b])
        swap(a, b);
    prev[b] = a;
    size[a] += size[b];
    changes.push_back({b, a});
    return true;
}

bool rollback() {
    if (changes.empty())
        return false;
    pair<ll, ll> ba = changes.back();
    changes.pop_back();
    prev[ba.first] = -1;
    size[ba.second] -= size[ba.first];
    return true;
}

};

```

5.9 Prefix Automate

```

struct PrefixAutomate {
    const static int A = 26;

    struct Node {
        int next[A] = {-1};
        int link = -1;

        int prev = -1;
        int pe = -1;

        int has = 0;
    };

    vector<Node> tree;
};

```

```

PrefixAutomate() {
    tree.push_back(Node());
}

void add(const string& s) {
    int v = 0;
    for (char c : s) {
        int e = c - 'a';
        if (tree[v].next[e] == -1) {
            tree[v].next[e] = tree.size();
            tree.push_back(Node());
            tree.back().prev = v;
            tree.back().pe = e;
        }
        v = tree[v].next[e];
    }
    tree[v].has = 1;
}

void addVect(const vector<string>& vs) {
    for (const auto& s : vs) {
        add(s);
    }
}

void del(const string& s) {
    int v = 0;
    for (char c : s) {
        int e = c - 'a';
        if (tree[v].next[e] == -1) {
            return;
        }
        v = tree[v].next[e];
    }
    tree[v].has = 0;
}

void ahoCorasick() {
    queue<int> que;

    tree[0].prev = 0;
    tree[0].pe = -1;

```

```

    tree[0].link = 0;
    for (int i = 0; i < A; ++i) {
        if (tree[0].next[i] == -1) {
            tree[0].next[i] = 0;
        } else {
            que.push(tree[0].next[i]);
        }
    }

    while (!que.empty()) {
        int v = que.front();
        que.pop();

        if (tree[v].link == -1) {
            if (v == 0 || tree[v].prev == 0)
                tree[v].link = 0;
            else
                tree[v].link = tree[tree[v].prev].next[tree[v].pe];
        }

        for (int i = 0; i < A; ++i) {
            if (tree[v].next[i] == -1) {
                tree[v].next[i] = tree[tree[v].link].next[i];
            } else {
                que.push(tree[v].next[i]);
            }
        }
    }
};

```

5.10 Segment Tree Beats

```

struct SegmentTreeBeats {
    struct Node {
        ll val = 0;
        ll firstMax = -inf;
        ll cntMax = 0;
        ll secondMax = -inf;

        ll min_eq = inf;

        Node(ll Val = 0, ll FirstMax = -inf, ll CntMax = 0, ll SecondMax
= -inf) {

```

```

        val = Val;
        firstMax = FirstMax;
        cntMax = CntMax;
        secondMax = SecondMax;
    }
};

Node fromOne(ll a) {
    return Node(a, a, 1, -inf);
}

Node neutral = Node();
ll n;
vector<Node> tree;

SegmentTreeBeats(const vector<ll>& start) {
    n = start.size();
    tree.resize(4 * n + 3);
    init(start);
}

SegmentTreeBeats(ll N) {
    n = N;
    tree.resize(4 * n + 3);
    vector<ll> start(n, 0);
    init(start);
}

Node merge(Node n1, Node n2) {
    Node res(n1.val + n2.val);

    if (n1.firstMax > n2.firstMax) {
        res.firstMax = n1.firstMax;
        res.cntMax = n1.cntMax;
        res.secondMax = max(n1.secondMax, n2.firstMax);
    } else if (n1.firstMax < n2.firstMax) {
        res.firstMax = n2.firstMax;
        res.cntMax = n2.cntMax;
        res.secondMax = max(n1.firstMax, n2.secondMax);
    } else {
        res.firstMax = n1.firstMax;
        res.cntMax = n1.cntMax + n2.cntMax;
        res.secondMax = max(n1.secondMax, n2.secondMax);
    }
}

```

```

        return res;
    }

    void fix(ll v, ll l, ll r) {
        tree[v] = merge(tree[v * 2 + 1], tree[v * 2 + 2]);
    }

    void init(ll v, ll l, ll r, const vector<ll>& start) {
        if (l + 1 == r) {
            tree[v] = fromOne(start[l]);
            return;
        }

        ll m = (r + 1) / 2;
        init(v * 2 + 1, l, m, start);
        init(v * 2 + 2, m, r, start);
        fix(v, l, r);
    }

    void init(const vector<ll>& start) {
        init(0, 0, n, start);
    }

    // [l: r)
    Node query(ll v, ll l, ll r, ll ql, ll qr) {
        if (ql <= l && r <= qr) {
            return tree[v];
        }
        if (r <= ql || qr <= l) {
            return neutral;
        }

        ll m = (r + 1) / 2;
        push(v, l, r);
        return merge(query(v * 2 + 1, l, m, ql, qr), query(v * 2 + 2, m,
r, ql, qr));
    }

    Node query(ll ql, ll qr) {
        return query(0, 0, n, ql, qr);
    }

    bool breakCondition(ll v, ll l, ll r, ll val) {
        return tree[v].firstMax <= val;
    }
}

```

```

}

bool tagCondition(ll v, ll l, ll r, ll val) {
    return tree[v].secondMax < val;
}

void apply(ll v, ll l, ll r, ll val) {
    // only if tagCondition() == true
    ll diff = min(tree[v].firstMax, val) - tree[v].firstMax;
    tree[v].val += tree[v].cntMax * diff;
    tree[v].firstMax += diff;

    tree[v].min_eq = min(val, tree[v].min_eq);
}

void push(ll v, ll l, ll r) {
    ll m = (r + 1) / 2;

    apply(v * 2 + 1, l, m, tree[v].min_eq);
    apply(v * 2 + 2, m, r, tree[v].min_eq);
    tree[v].min_eq = inf;
}

void update(ll v, ll l, ll r, ll ql, ll qr, ll val) {
    if (r <= ql || qr <= l || breakCondition(v, l, r, val)) {
        return;
    }
    if (ql <= l && r <= qr && tagCondition(v, l, r, val)) {
        apply(v, l, r, val);
        return;
    }

    ll m = (r + 1) / 2;
    push(v, l, r);
    update(v * 2 + 1, l, m, ql, qr, val);
    update(v * 2 + 2, m, r, ql, qr, val);
    fix(v, l, r);
}

void update(ll ql, ll qr, ll val) {
    update(0, 0, n, ql, qr, val);
}

pair<ll, ll> descent(ll v, ll l, ll r, ll ql, ll qr, ll x) {

```

```

    if (r <= ql || qr <= l)
        return {-1, x};
    if (ql <= l && r <= qr) {
        if (tree[v].val < x)
            return {-1, x - tree[v].val};
        if (l + 1 == r)
            return {l + 1, x};
    }
    if (l + 1 == r)
        return {-1, x};

    ll m = (r + 1) / 2;
    push(v, l, r);
    auto left = descent(v * 2 + 1, l, m, ql, qr, x);
    if (left.first != -1)
        return left;
    return descent(v * 2 + 2, m, r, ql, qr, left.second);
}

ll descent(ll ql, ll qr, ll x) {
    if (x <= 0)
        return ql;
    return descent(0, 0, n, ql, qr, x).first;
}

};

```

5.11 Segment Tree Mass

```

struct SegmentTreeMass {
    struct Node {
        ll val = inf;
        ll add = 0;

        Node(ll Val = inf, ll Add = 0) {
            val = Val;
            add = Add;
        }
    };

    Node neutral = Node(inf, 0);
    ll n;
    vector<Node> tree;

    SegmentTreeMass(const vector<ll>& start) {

```

```

    n = start.size();
    tree.resize(4 * n + 3);
    init(start);
}

SegmentTreeMass(ll N) {
    n = N;
    tree.resize(4 * n + 3);
    vector<ll> start(n, 0);
    init(start);
}

Node merge(Node n1, Node n2) {
    return Node(min(n1.val, n2.val));
}

void fix(ll v, ll l, ll r) {
    tree[v] = merge(tree[v * 2 + 1], tree[v * 2 + 2]);
}

void apply(ll v, ll l, ll r, ll val) {
    tree[v].add += val;
    tree[v].val += val;
}

void push(ll v, ll l, ll r) {
    ll m = (r + 1) / 2;

    apply(v * 2 + 1, l, m, tree[v].add);
    apply(v * 2 + 2, m, r, tree[v].add);
    tree[v].add = 0;
}

void init(ll v, ll l, ll r, const vector<ll>& start) {
    if (l + 1 == r) {
        tree[v] = Node(start[l], 0);
        return;
    }

    ll m = (r + 1) / 2;
    init(v * 2 + 1, l, m, start);
    init(v * 2 + 2, m, r, start);
    fix(v, l, r);
}

```

```

void init(const vector<ll>& start) {
    init(0, 0, n, start);
}

// [l: r)
Node query(ll v, ll l, ll r, ll ql, ll qr) {
    if (ql <= l && r <= qr) {
        return tree[v];
    }
    if (r <= ql || qr <= l) {
        return neutral;
    }

    ll m = (r + 1) / 2;
    push(v, l, r);
    return merge(query(v * 2 + 1, l, m, ql, qr), query(v * 2 + 2, m,
r, ql, qr));
}

Node query(ll ql, ll qr) {
    return query(0, 0, n, ql, qr);
}

void add(ll v, ll l, ll r, ll ql, ll qr, ll val) {
    if (ql <= l && r <= qr) {
        apply(v, l, r, val);
        return;
    }
    if (r <= ql || qr <= l) {
        return;
    }

    ll m = (r + 1) / 2;
    push(v, l, r);
    add(v * 2 + 1, l, m, ql, qr, val);
    add(v * 2 + 2, m, r, ql, qr, val);
    fix(v, l, r);
}

void add(ll ql, ll qr, ll val) {
    add(0, 0, n, ql, qr, val);
}

```



```

11 descent(11 v, 11 l, 11 r, 11 ql, 11 qr, 11 x) {
    if (r <= ql || qr <= l)
        return -1;
    if (tree[v].val >= x)
        return -1;
    if (l + 1 == r)
        return 1;

    11 m = (r + 1) / 2;
    push(v, l, r);
    11 left = descent(v * 2 + 1, l, m, ql, qr, x);
    if (left != -1)
        return left;
    return descent(v * 2 + 2, m, r, ql, qr, x);
}

11 descent(11 ql, 11 qr, 11 x) {
    return descent(0, 0, n, ql, qr, x);
}
};

```

5.12 Segment Tree

```

struct SegmentTree {
    struct Node {
        11 val;

        Node(11 Val = inf) : val(Val) {}
    };

    Node neutral = Node();

    11 n;
    vector<Node> tree;

    void init(11 v, 11 l, 11 r, const vector<11>& start) {
        if (l + 1 == r) {
            tree[v] = Node(start[l]);
            return;
        }

        11 m = (l + r) / 2;

```

```

        init(v * 2 + 1, l, m, start);
        init(v * 2 + 2, m, r, start);
        tree[v] = merge(tree[v * 2 + 1], tree[v * 2 + 2]);
    }

    SegmentTree() {}

    SegmentTree(const vector<11>& start) {
        n = start.size();
        tree.resize(n * 4 + 3);
        init(0, 0, n, start);
    }

    Node merge(Node n1, Node n2) {
        return Node(min(n1.val, n2.val));
    }

    Node query(11 v, 11 l, 11 r, 11 ql, 11 qr) {
        if (ql <= l && r <= qr)
            return tree[v];
        if (qr <= l || r <= ql)
            return neutral;

        11 m = (l + r) / 2;
        return merge(query(v * 2 + 1, l, m, ql, qr), query(v * 2 + 2, m,
r, ql, qr));
    }

    Node query(11 ql, 11 qr) {
        return query(0, 0, n, ql, qr);
    }

    void change(11 v, 11 l, 11 r, 11 id, 11 val) {
        if (l + 1 == r && l == id) {
            tree[v] = Node(val);
            return;
        }
        if (r <= id || id < l) {
            return;
        }

        11 m = (l + r) / 2;
        change(v * 2 + 1, l, m, id, val);

```

```

        change(v * 2 + 2, m, r, id, val);
        tree[v] = merge(tree[v * 2 + 1], tree[v * 2 + 2]);
    }

    void change(ll id, ll val) {
        change(0, 0, n, id, val);
    }

    ll descent(ll v, ll l, ll r, ll ql, ll qr, ll x) {
        if (r <= ql || qr <= l)
            return -1;
        if (tree[v].val >= x)
            return -1;
        if (l + 1 == r)
            return l;

        ll m = (l + r) / 2;
        ll left = descent(v * 2 + 1, l, m, ql, qr, x);
        if (left != -1)
            return left;
        return descent(v * 2 + 2, m, r, ql, qr, x);
    }

    ll descent(ll ql, ll qr, ll x) {
        return descent(0, 0, n, ql, qr, x);
    }
};

```

5.13 Sparse Table

```

template <class T>
struct SparseTable {
    ll n, k;
    vector<T> a;
    vector<vector<T>> sparse;
    vector<ll> length;

    SparseTable(vector<T>& start) {
        n = start.size();
        k = 0;
        for (ll d = 1; d <= n; d *= 2, ++k) {}
        a.assign(start.begin(), start.end());
        sparse.assign(n, vector<T>(k));
    }
};

```

```

        countSparse();
        precalc();
    }

    void precalc() {
        length.assign(n + 1, 0);
        ll t = 0;
        for (int l = 1; l <= n; ++l) {
            if ((1ll << (t + 1)) < l)
                ++t;
            length[l] = t;
        }
    }

    void countSparse() {
        for (int i = 0; i < n; ++i) {
            sparse[i][0] = a[i];
        }
        for (int j = 1; j < k; ++j) {
            for (int i = 0; i < n; ++i) {
                ll d = (1ll << (j - 1));
                sparse[i][j] = max(sparse[i][j - 1], sparse[min(n - 1, i
+ d)][j - 1]);
            }
        }
    }

    T query(ll l, ll r) {
        ll t = length[r - l];

        ll d = (1ll << t);

        return max(sparse[l][t], sparse[r - d][t]);
    }
};

```

5.14 Treap

```

random_device rd;
mt19937 mersenne(rd());

struct Treap {
    Treap* left;
    Treap* right;
};

```

```

    ll x;
    unsigned int y;
    unsigned int size;
    ll dp;

    Treap(ll val = 0) {
        left = nullptr;
        right = nullptr;
        size = 1;
        x = val;
        y = mersenne();
        update(this);
    }

    friend ll get_dp(Treap* node) {
        if (node == nullptr)
            return 0;
        return node->dp;
    }

    friend unsigned int get_size(Treap* node) {
        if (node == nullptr)
            return 0;
        return node->size;
    }

    friend void update(Treap* node) {
        if (node == nullptr)
            return;
        node->size = 1 + get_size(node->left) + get_size(node->right);
        node->dp = max({node->x, get_dp(node->left), get_dp(node->right)});
    };

    // split by size
    friend pair<Treap*, Treap*> split_k(Treap* node, unsigned int k) {
        if (node == nullptr)
            return {nullptr, nullptr};
        if (get_size(node->left) < k) {
            auto res = split_k(node->right, k - get_size(node->left) - 1);
            node->right = res.first;
            update(node);
            return {node, res.second};
        }
    };

```

```

    } else {
        auto res = split_k(node->left, k);
        node->left = res.second;
        update(node);
        return {res.first, node};
    }
}

// split by dp: dp in left < k
friend pair<Treap*, Treap*> split_dp(Treap* node, unsigned int k) {
    if (node == nullptr)
        return {nullptr, nullptr};
    if (get_dp(node) < k) {
        auto res = split_dp(node->right, k);
        node->right = res.first;
        update(node);
        return {node, res.second};
    } else {
        auto res = split_dp(node->left, k);
        node->left = res.second;
        update(node);
        return {res.first, node};
    }
}

friend Treap* merge(Treap* left, Treap* right) {
    if (left == nullptr)
        return right;
    if (right == nullptr)
        return left;
    if (left->y > right->y) {
        left->right = merge(left->right, right);
        update(left);
        return left;
    } else {
        right->left = merge(left, right->left);
        update(right);
        return right;
    }
}

friend Treap* insert(Treap* node, unsigned int pos, ll val) {
    auto res = split_k(node, pos);
    Treap* tr = new Treap(val);

```

```

    return merge(merge(res.first, tr), res.second);
}

friend Treap* erase(Treap* node, unsigned int pos) {
    auto res = split_k(node, pos + 1);
    auto left_res = split_k(res.first, pos);
    return merge(left_res.first, res.second);
}

// return {element, root}
friend pair<Treap*, Treap*> kth_element(Treap* node, unsigned int k)
{
    if (get_size(node) < k)
        return {nullptr, node};
    auto res = split_k(node, k + 1);
    auto left_res = split_k(res.first, k);
    return {left_res.second, merge(left_res.first, merge(left_res.
second, res.second))};
}

// return sub segment [l, r) and remaineng Treap [0, l) + [r + 1,
size)
friend pair<Treap*, Treap*> cut(Treap* node, unsigned int l, unsigned
int r) {
    auto res = split_k(node, r);
    auto left_res = split_k(res.first, l);
    return {left_res.second, merge(left_res.first, res.second)};
}
};

```

6 Flows

6.1 Dinic

```

struct FlowSolver {
    struct DinicEdge {
        ll a, b, cap, flow;
    };

    vector<DinicEdge> edges;
    vector<vector<ll>> g;
    ll n;

```

```

FlowSolver(ll N) {
    n = N;
    g.resize(n);
}

void add_edge(ll u, ll v, ll w) {
    g[u].push_back(edges.size());
    edges.push_back({u, v, w, 0});
    g[v].push_back(edges.size());
    edges.push_back({v, u, 0, 0});
}

bool bfs(ll s, ll t, vector<ll>& d) {
    queue<ll> q;
    d.assign(n, -1);
    d[s] = 0;
    q.push(s);

    while (!q.empty()) {
        ll v = q.front();
        q.pop();

        for (ll id : g[v]) {
            ll u = edges[id].b;
            if (d[u] == -1) {
                if (edges[id].cap > edges[id].flow) {
                    d[u] = d[v] + 1;
                    q.push(u);
                }
            }
        }
    }

    return d[t] != -1;
}

ll dfs(ll v, ll t, ll flow, vector<ll>& d, vector<ll>& ptr) {
    if (flow == 0) {
        return 0;
    }
    if (v == t) {
        return flow;
    }

```

```

    for (; ptr[v] < g[v].size(); ++ptr[v]) {
        ll id = g[v][ptr[v]];
        ll u = edges[id].b;

        if (d[u] == d[v] + 1) {
            ll add_flow = dfs(u, t, min(flow, edges[id].cap - edges[
id].flow), d, ptr);
            if (add_flow > 0) {
                edges[id].flow += add_flow;
                edges[id ^ 1].flow -= add_flow;
                return add_flow;
            }
        }
    }
    return 0;
}

ll dinic(ll s, ll t) {
    ll flow = 0;
    vector<ll> d;
    while (bfs(s, t, d)) {
        vector<ll> ptr(n, 0);
        while (ll add_flow = dfs(s, t, inf, d, ptr)) {
            flow += add_flow;
        }
    }
    return flow;
}
};

```

7 Graphs

7.1 2 SAT

```

struct SATSolver {
    ll n;
    vector<vector<ll>> g, gt;
    vector<char> used;
    vector<ll> order, comp;

    void init(ll N) {
        n = N;
        g.assign(2 * n, {});

```

```

        gt.assign(2 * n, {});
    }

    // literal: var in [0..n), val=false -> 2*var, val=true -> 2*var+1
    ll lit(ll var, ll val) {
        return 2 * var + (val ? 1 : 0);
    }

    ll neg(ll x) {
        return x ^ 1;
    }

    void add_imp(ll a, ll b) {
        g[a].push_back(b);
        gt[b].push_back(a);
    }

    // (a_var is a_val) OR (b_var is b_val)
    void add_or(ll a_var, ll a_val, ll b_var, ll b_val) {
        ll a = lit(a_var, a_val);
        ll b = lit(b_var, b_val);
        add_imp(neg(a), b);
        add_imp(neg(b), a);
    }

    void dfs1(ll v) {
        used[v] = 1;
        for (ll to : g[v])
            if (!used[to])
                dfs1(to);
        order.push_back(v);
    }

    void dfs2(ll v, ll cl) {
        comp[v] = cl;
        for (ll to : gt[v])
            if (comp[to] == -1)
                dfs2(to, cl);
    }

    // returns empty vector if unsat; otherwise assignment[i] in {0,1}
    vector<ll> solve() {
        used.assign(2 * n, 0);
        order.clear();
        for (ll i = 0; i < 2 * n; ++i)

```

```

        if (!used[i])
            dfs1(i);

    comp.assign(2 * n, -1);
    ll j = 0;
    for (ll i = 2 * n - 1; i >= 0; --i) {
        ll v = order[i];
        if (comp[v] == -1)
            dfs2(v, j++);
    }

    vector<ll> ans(n);
    for (ll i = 0; i < n; ++i) {
        if (comp[2 * i] == comp[2 * i + 1])
            return {};
        ans[i] = (comp[2 * i] < comp[2 * i + 1]);
    }
    return ans;
}
};

```

7.2 Euler Path

```

void cycle(ll prev, ll v, vector<vector<pair<ll, ll>>>& g, vector<ll>&
ans) {
    while (!g[v].empty()) {
        auto iu = g[v].back();
        ll u = iu.second;
        g[v].pop_back();
        cycle(iu.first, u, g, ans);
    }
    if (prev >= 0)
        ans.push_back(prev);
}

```

7.3 Hopcroft Karp

```

struct HopcroftKarp {
    ll n1, n2;
    vector<vector<ll>> g;
    vector<ll> dist;
    vector<ll> mt1, mt2;

```

```

    void init(ll N1, ll N2) {
        n1 = N1;
        n2 = N2;
        g.assign((int)n1, {});
        mt1.assign((int)n1, -1);
        mt2.assign((int)n2, -1);
        dist.assign((int)n1, 0);
    }

    void add_edge(ll u, ll v) {
        // u in [0..n1), v in [0..n2)
        g[(int)u].push_back(v);
    }

    bool bfs() {
        queue<ll> q;
        for (ll i = 0; i < n1; ++i) {
            if (mt1[(int)i] == -1) {
                dist[(int)i] = 0;
                q.push(i);
            } else {
                dist[(int)i] = -1;
            }
        }

        bool found = false;
        while (!q.empty()) {
            ll v = q.front();
            q.pop();

            for (ll to : g[(int)v]) {
                ll u = mt2[(int)to];
                if (u == -1) {
                    found = true;
                } else if (dist[(int)u] == -1) {
                    dist[(int)u] = dist[(int)v] + 1;
                    q.push(u);
                }
            }
        }
        return found;
    }

    bool dfs(ll v) {

```

```

    for (ll to : g[(int)v]) {
        ll u = mt2[(int)to];
        if (u == -1 || (dist[(int)u] == dist[(int)v] + 1 && dfs(u)))
    {
        mt1[(int)v] = to;
        mt2[(int)to] = v;
        return true;
    }
    }
    dist[(int)v] = -1;
    return false;
}

ll solve() {
    ll matching = 0;
    while (bfs()) {
        for (ll i = 0; i < n1; ++i) {
            if (mt1[(int)i] == -1) {
                if (dfs(i)) {
                    ++matching;
                }
            }
        }
    }
    return matching;
}
};

```

7.4 Hungarian

```

// a size is (n + 1) x (m + 1), 1-indexing
// n <= m; if n < m than a[i][j] must be >= 0
pair<ll, vector<int>> hungarian(const vector<vector<ll>>& a, int n, int m)
{
    vector<ll> u(n + 1, 0), v(m + 1, 0);
    vector<int> p(m + 1, 0), way(m + 1, 0);
    for (int i = 1; i <= n; ++i) {
        int j0 = 0;
        p[j0] = i;

        vector<char> used(m + 1, 0);
        vector<ll> minv(m + 1, inf);
        do {
            used[j0] = true;

```

```

            int i0 = p[j0];
            int j1 = -1, delta = inf;

            // run step of dfs from i0
            for (int j = 1; j <= m; ++j) {
                if (used[j]) {
                    continue;
                }

                int cur = a[i0][j] - u[i0] - v[j];
                if (cur < minv[j]) {
                    minv[j] = cur;
                    way[j] = j0;
                }
                if (minv[j] < delta) {
                    delta = minv[j];
                    j1 = j;
                }
            }

            // update potentials
            for (int j = 0; j <= m; ++j) {
                if (used[j]) {
                    u[p[j]] += delta;
                    v[j] -= delta;
                } else {
                    minv[j] -= delta;
                }
            }

            j0 = j1;
        } while (p[j0] != 0);

        while (j0) {
            int j1 = way[j0];
            p[j0] = p[j1];
            j0 = j1;
        }

        return {-v[0], p};
    }
}

```

7.5 Initial Pairing

```

int init_pairing(int n1, int n2, const vector<vector<int>>& g, vector<int>
    >& mt, vector<int>& rmt) {
    auto PACK = [](int x, int y) { return ((1l)x << 30) + y; };
    auto SUNPACK = [](int x) {
        const static 1l mask = (1ll << 30) - 1;
        return x & mask;
    };

    vector<int> deg(n1, 0);
    vector<vector<int>> ng(n1);
    vector<vector<pair<int, int>>> rg(n2);
    vector<int> next(n1, 0);
    set<1l> que;
    for (int i = 0; i < n1; ++i) {
        for (auto j : g[i]) {
            ++deg[i];
            rg[j].push_back({i, ng[i].size()});
            ng[i].push_back(j);
        }
        que.insert(PACK(deg[i], i));
    }

    int pairing = 0;

    while (!que.empty()) {
        auto res = *que.begin();
        que.erase(res);

        int i = SUNPACK(res);
        if (deg[i] == 0) {
            continue;
        }

        while (ng[i][next[i]] == -1) {
            ++next[i];
        }
        int j = ng[i][next[i]++];

        deg[i] = 0;
        for (auto ks : rg[j]) {
            int k = ks.first;

```

```

            int sz = ks.second;
            if (deg[k] != 0) {
                ng[k][sz] = -1;
                que.erase(PACK(deg[k], k));
                --deg[k];
                que.insert(PACK(deg[k], k));
            }
        }
        mt[j] = i;
        rmt[i] = j;
        ++pairing;
    }
    return pairing;
}

vector<int> fast_kuhn(int n1, int n2, vector<vector<int>>& g) {
    vector<char> used(n1, 0);
    vector<int> mt(n2, -1), rmt(n1, -1);

    init_pairing(n1, n2, g, mt, rmt);

    int mark = 0;

    for (int run = 1; run;) {
        ++mark;
        run = 0;
        for (int i = 0; i < n1; ++i) {
            if (rmt[i] == -1 && kuhn_dfs(i, used, mark, g, mt)) {
                run = 1;
            }
        }

        for (int j = 0; j < n2; ++j) {
            if (mt[j] != -1) {
                rmt[mt[j]] = j;
            }
        }
    }

    return mt;
}

```

7.6 Kuhn


```

bool kuhn_dfs(int v, vector<int>& used, int mark, vector<vector<int>>& g,
    vector<int>& mt) {
    if (used[v] == mark) {
        return false;
    }
    used[v] = mark;

    for (int u : g[v]) {
        if (mt[u] == -1 || kuhn_dfs(mt[u], used, mark, g, mt)) {
            mt[u] = v;
            return true;
        }
    }
    return false;
}

vector<int> kuhn(int n1, int n2, vector<vector<int>>& g) {
    vector<int> used(n1, 0);
    vector<int> mt(n2, -1);

    int mark = 1;

    for (int i = 0; i < n1; ++i) {
        if (kuhn_dfs(i, used, mark, g, mt)) {
            ++mark;
        }
    }

    return mt;
}

```

8 Matroids

8.1 MatroidExamples

```

struct Matroid {
    virtual int size() const = 0;
    virtual void build(const vector<int> &on) = 0;
    virtual vector<int> circuit(int u) const = 0;
    virtual ~Matroid() = default;
};

```

// independent $\Leftrightarrow$ forest

```

struct ForestMatroid : Matroid {
    int n;
    vector<pair<int, int>> edges;
    ForestMatroid() {}
    ForestMatroid(int n_) : n(n_) {}
    void ae(int u, int v) {
        edges.emplace_back(u, v);
    }
    inline int size() const override {
        return edges.size();
    }
    void build(const vector<int> &on) override {
        const int m = edges.size();
        g.assign(n, {});
        for (int i = 0; i < m; ++i) {
            if (on[i]) {
                g[edges[i].first].push_back(i);
                g[edges[i].second].push_back(i);
            }
        }
        rs.assign(n, -1);
        pari.assign(n, -1);
        dep.assign(n, -1);
        for (int r = 0; r < n; ++r)
            if (!~rs[r])
                dfs(r, r, -1, 0);
    }
    // i0, then tree edges from edges[i0].first to edges[i0].second
    vector<int> circuit(int i0) const override {
        int u = edges[i0].first, v = edges[i0].second;
        if (rs[u] != rs[v])
            return {};
        vector<int> isU, isV;
        auto upU = [&]() -> void {
            const int i = pari[u];
            isU.push_back(i);
            u ^= edges[i].first ^ edges[i].second;
        };
        auto upV = [&]() -> void {
            const int i = pari[v];
            isV.push_back(i);
            v ^= edges[i].first ^ edges[i].second;
        };
    }
};

```

```

};
for (; dep[u] > dep[v]; upU()) {
}
for (; dep[u] < dep[v]; upV()) {
}
for (; u != v; upU(), upV()) {
}
reverse(isV.begin(), isV.end());
vector<int> is{i0};
is.insert(is.end(), isU.begin(), isU.end());
is.insert(is.end(), isV.begin(), isV.end());
return is;
}
vector<vector<int>> g;
vector<int> rs, pari, dep;
void dfs(int r, int u, int pi, int d) {
    rs[u] = r;
    pari[u] = pi;
    dep[u] = d;
    for (const int i : g[u])
        if (pi != i)
            dfs(r, edges[i].first ^ edges[i].second ^ u, i, d + 1);
}
};

```

// independent <=> each connected component contains (<= 1) cycle

```

struct PseudoforestMatroid : Matroid {
    int n;
    vector<pair<int, int>> edges;
    PseudoforestMatroid() {
    }
    PseudoforestMatroid(int n_) : n(n_) {
    }
    void ae(int u, int v) {
        edges.emplace_back(u, v);
    }
    inline int size() const override {
        return edges.size();
    }
    void build(const vector<int> &on) override {
        const int m = edges.size();
        g.assign(n, {});
        for (int i = 0; i < m; ++i) {
            if (on[i]) {

```

```

                g[edges[i].first].push_back(i);
                g[edges[i].second].push_back(i);
            }
        }
        rs.assign(n, -1);
        pari.assign(n, -1);
        dep.assign(n, -1);
        cycs.assign(n, -1);
        for (int r = 0; r < n; ++r)
            if (!~rs[r])
                dfs(r, r, -1, 0);
    }
    vector<int> circuit(int i0) const override {
        vector<int> is;
        // Add edges in the smallest subtree containing us.
        auto addSubtree = [&](vector<int> us) -> void {
            while (true) {
                sort(us.begin(), us.end());
                us.erase(unique(us.begin(), us.end()), us.end());
                if (us.size() == 1)
                    break;
                int mx = -1;
                for (const int u : us)
                    if (mx < dep[u])
                        mx = dep[u];
                for (int &u : us)
                    if (mx == dep[u]) {
                        const int i = pari[u];
                        is.push_back(i);
                        u ^= edges[i].first ^ edges[i].second;
                    }
            }
        };
        const int u = edges[i0].first, v = edges[i0].second;
        if (rs[u] != rs[v]) {
            if (~cycs[rs[u]] && ~cycs[rs[v]]) {
                is.push_back(i0);
                is.push_back(cycs[rs[u]]);
                addSubtree({u, edges[cycs[rs[u]]].first, edges[cycs[rs[u]]].second});
                is.push_back(cycs[rs[v]]);
                addSubtree({v, edges[cycs[rs[v]]].first, edges[cycs[rs[v]]].second});
            }
        }
    }
}

```

```

    } else {
        if (~cycs[rs[u]]) {
            is.push_back(i0);
            is.push_back(cycs[rs[u]]);
            addSubtree({u, v, edges[cycs[rs[u]]].first, edges[cycs[rs
[u]]].second});
        }
    }
    return is;
}
vector<vector<int>> g;
vector<int> rs, pari, dep, cycs;
void dfs(int r, int u, int pi, int d) {
    rs[u] = r;
    pari[u] = pi;
    dep[u] = d;
    for (const int i : g[u]) {
        if (pi != i) {
            const int v = edges[i].first ^ edges[i].second ^ u;
            if (~rs[v]) {
                cycs[r] = i;
            } else {
                dfs(r, v, i, d + 1);
            }
        }
    }
}
};

// independent <=> #{ i | colors[i] = c } <= lims[c]
struct PartitionMatroid : Matroid {
    int n;
    vector<int> colors;
    vector<int> lims;
    PartitionMatroid() {
    }
    PartitionMatroid(const vector<int> &colors_, const vector<int> &lims_
)
        : n(colors_.size()), colors(colors_), lims(lims_) {
    }
    inline int size() const override {
        return n;
    }
    void build(const vector<int> &on) override {

```

```

        iss.assign(lims.size(), {});
        for (int i = 0; i < n; ++i)
            if (on[i])
                iss[colors[i]].push_back(i);
    }
    vector<int> circuit(int i0) const override {
        const int c = colors[i0];
        if (static_cast<int>(iss[c].size()) == lims[c]) {
            vector<int> is = iss[c];
            is.push_back(i0);
            return is;
        } else {
            return {};
        }
    }
    vector<vector<int>> iss;
};

// independent <=> vectors are linearly independent over GF(2)
struct LinearMatroid : Matroid {
    int n;
    int maxLog;
    vector<ull> vals;

    int blocks;
    vector<ull> basis;
    vector<vector<ull>> basisMask;

    LinearMatroid() {
    }
    LinearMatroid(const vector<ull> &vals_, int maxLog_ = 64) {
        vals = vals_;
        n = vals.size();
        maxLog = maxLog_;
        blocks = (n + 63) / 64;
    }

    inline int size() const override {
        return n;
    }

    void set_bit(vector<ull> &mask, int i) {
        mask[i >> 6] |= (1ULL << (i & 63));
    }
}

```

```

void xor_mask(vector<ull> &a, const vector<ull> &b) {
    for (int i = 0; i < blocks; ++i)
        a[i] ^= b[i];
}

void add_vector(ull x, int id) {
    vector<ull> cur(blocks, 0);
    set_bit(cur, id);

    for (int b = maxLog - 1; b >= 0; --b) {
        if (((x >> b) & 1ULL) == 0)
            continue;
        if (!basis[b]) {
            basis[b] = x;
            basisMask[b] = cur;
            return;
        }
        x ^= basis[b];
        xor_mask(cur, basisMask[b]);
    }
}

void build(const vector<int> &on) override {
    basis.assign(maxLog, 0);
    basisMask.assign(maxLog, vector<ull>(blocks, 0));
    for (int i = 0; i < n; ++i) {
        if (on[i])
            add_vector(vals[i], i);
    }
}

vector<int> circuit(int u) const override {
    ull x = vals[u];
    vector<ull> cur(blocks, 0);
    cur[u >> 6] |= (1ULL << (u & 63));

    for (int b = maxLog - 1; b >= 0; --b) {
        if (((x >> b) & 1ULL) == 0)
            continue;
        if (!basis[b]) {
            return {};
        }
        x ^= basis[b];
    }
}

```

```

        for (int i = 0; i < blocks; ++i)
            cur[i] ^= basisMask[b][i];
    }

    vector<int> res;
    for (int i = 0; i < n; ++i) {
        if ((cur[i >> 6] >> (i & 63)) & 1ULL)
            res.push_back(i);
    }
    return res;
};

// independent <=> selected left vertices can be fully matched to right
// part
struct TransversalMatroid : Matroid {
    int n, m;
    vector<vector<int>> g;
    vector<int> cur_on;

    vector<int> matchL, matchR;
    vector<int> used;
    int used_timer;

    TransversalMatroid() {
    }
    TransversalMatroid(int n_, int m_) : n(n_), m(m_) {
        g.assign(n, {});
    }

    void ae(int u, int v) {
        g[u].push_back(v);
    }

    inline int size() const override {
        return n;
    }

    bool dfs_kuhn(int u) {
        if (used[u] == used_timer)
            return false;
        used[u] = used_timer;
        for (int v : g[u]) {
            int w = matchR[v];

```

```

        if (w == -1 || dfs_kuhn(w)) {
            matchL[u] = v;
            matchR[v] = u;
            return true;
        }
    }
    return false;
}

void build(const vector<int> &on) override {
    cur_on = on;
    matchL.assign(n, -1);
    matchR.assign(m, -1);
    used.assign(n, 0);
    used_timer = 0;
    for (int u = 0; u < n; ++u) {
        if (cur_on[u]) {
            ++used_timer;
            dfs_kuhn(u);
        }
    }
}

vector<int> circuit(int u0) const override {
    vector<int> visL(n, 0), visR(m, 0);
    queue<int> q;
    visL[u0] = 1;
    q.push(u0);

    while (!q.empty()) {
        int u = q.front();
        q.pop();
        for (int v : g[u]) {
            if (visR[v])
                continue;
            visR[v] = 1;
            if (matchR[v] == -1) {
                return {};
            }
            int w = matchR[v];
            if (!visL[w] && cur_on[w]) {
                visL[w] = 1;
                q.push(w);
            }
        }
    }
}

```

```

    }
}

vector<int> res;
for (int u = 0; u < n; ++u) {
    if (u == u0 || (cur_on[u] && visL[u]))
        res.push_back(u);
}
return res;
}
};

```

8.2 MatroidIntersectionUnweighted

```

// Find max size independent set.
// score: max size
// on: optimal independent set (0/1)
// M0, M1: matroid
// size(): |ground set|
// build(on): Current independent set is given.
// circuit(u): Returns the circuit by adding u (must contain u), or {}
// if still independent.
pair<int, vector<int>> matroidIntersection(Matroid& m0, Matroid& m1) {
    const int n = m0.size();
    vector<int> on(n, 0);
    while (true) {
        m0.build(on);
        m1.build(on);
        vector<vector<int>> graph(n + 2);
        for (int u = 0; u < n; ++u) {
            if (!on[u]) {
                const vector<int> c0 = m0.circuit(u);
                if (c0.empty())
                    graph[n].push_back(u);
                for (const int v : c0)
                    if (u != v)
                        graph[v].push_back(u);
                const vector<int> c1 = m1.circuit(u);
                if (c1.empty())
                    graph[u].push_back(n + 1);
                for (const int v : c1)
                    if (u != v)
                        graph[u].push_back(v);
            }
        }
    }
}

```

```

    }
    queue<int> que;
    vector<int> prv(n + 2, -1);
    prv[n] = -2;
    que.push(n);
    while (!que.empty() && !~prv[n + 1]) {
        const int u = que.front();
        que.pop();
        for (const int v : graph[u]) {
            if (!~prv[v]) {
                prv[v] = u;
                que.push(v);
            }
        }
    }
    if (~prv[n + 1]) {
        for (int u = n + 1; (u = prv[u]) != n;)
            on[u] ^= 1;
    } else {
        break;
    }
}
int score = 0;
for (int u = 0; u < n; ++u)
    if (on[u])
        ++score;
return make_pair(score, on);
};

```

8.3 MatroidIntersectionWeighted

```

// Find max weight independent set.
// score: max weight
// on: optimal independent set (0/1)
// M0, M1: matroid
// size(): |ground set|
// build(on): Current independent set is given.
// circuit(u): Returns the circuit by adding u (must contain u), or {}
// if still independent.
pair<ll, vector<int>> matroidIntersection(Matroid& m0, Matroid& m1, const
    vector<ll>& weights) {
    const int n = weights.size();
    vector<int> on(n, 0);
    while (true) {

```

```

        m0.build(on);
        m1.build(on);
        vector<vector<int>> graph(n + 2);
        for (int u = 0; u < n; ++u) {
            if (!on[u]) {
                const vector<int> c0 = m0.circuit(u);
                if (c0.empty())
                    graph[n].push_back(u);
                for (const int v : c0)
                    if (u != v)
                        graph[v].push_back(u);
                const vector<int> c1 = m1.circuit(u);
                if (c1.empty())
                    graph[u].push_back(n + 1);
                for (const int v : c1)
                    if (u != v)
                        graph[u].push_back(v);
            }
        }
        queue<int> que;
        vector<int> inq(n + 2, 0);
        vector<int> prv(n + 2, -1);
        vector<ll> dist(n + 2, 0);
        prv[n] = -2;
        inq[n] = 1;
        que.push(n);
        while (!que.empty()) {
            const int u = que.front();
            que.pop();
            inq[u] = 0;
            for (const int v : graph[u]) {
                ll cc = dist[u];
                if (v < n)
                    on[v] ? (cc -= weights[v]) : (cc += weights[v]);
                if (!~prv[v] || dist[v] < cc) {
                    prv[v] = u;
                    dist[v] = cc;
                    if (!inq[v]) {
                        inq[v] = 1;
                        que.push(v);
                    }
                }
            }
        }
    }
}

```

```

    if (~prv[n + 1] && dist[n + 1] > 0) { // alarm: delete ES dist[
n + 1] > 0 if want max size
        for (int u = n + 1; (u = prv[u]) != n;)
            on[u] ^= 1;
    } else {
        break;
    }
}
ll score = 0;
for (int u = 0; u < n; ++u)
    if (on[u])
        score += weights[u];
return make_pair(score, on);
};

```

9 Number Theory

9.1 Eratosthenes

```

void erat(ll N, vector<ll>& primes, vector<ll>& mi) {
    mi.assign(N, 0);
    for (int i = 2; i < N; ++i) {
        if (mi[i] == 0) {
            primes.push_back(i);
            mi[i] = i;
        }

        for (int j = 0; j < primes.size() && primes[j] <= mi[i] && i *
primes[j] < N; ++j) {
            mi[primes[j] * i] = primes[j];
        }
    }
}

```

9.2 FloorSum

```

ll floor_div(ll a, ll b) { // b > 0
    if (a >= 0)
        return a / b;
    return (a - b + 1) / b;
}

```

```

// sum_{x=0}^{n-1} floor((a*x + b) / m), m > 0
ll floor_sum(ll n, ll m, ll a, ll b) {
    if (n <= 0) return 0;
    ll ans = 0;
    auto pull = [&](ll &x, ll w) {
        ll q = floor_div(x, m);
        ans += q * w;
        x -= q * m;
    };
    while (true) {
        pull(a, n * (n - 1) / 2);
        pull(b, n);
        ll y = a * n + b;
        if (y < m) return ans;
        n = y / m;
        b = y % m;
        swap(a, m);
    }
}

```

9.3 Miller Rabin

```

bool _miller_rabin_test(ll n, ll d, ll s, ll a) {
    ll x = bin_pow_mod(a, d, n);
    for (int i = 0; i < s; ++i) {
        ll y = ((__int128_t)x * x) % n;
        if (y == 1 && x != 1) {
            return false;
        }

        x = y;
    }
    if (x != 1) {
        return false;
    }
    return true;
}

```

```

bool is_prime_ml(ll n) {
    if (n <= 1) {
        return false;
    }
    // all primes
    vector<ll> as = {2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37};
}

```

```

    ll d = n - 1;
    ll s = 0;
    while ((d & 1) == 0) {
        ++s;
        d >>= 1;
    }
    for (ll a : as) {
        if (n == a) {
            return true;
        }
        if (n % a == 0) {
            return false;
        }
        if (!_miller_rabin_test(n, d, s, a)) {
            return false;
        }
    }
    return true;
}

```

10 Strings

10.1 LCP

```

// p - suffix massive output
// c - suffix massive classes
vector<ll> calc_lcp(ll n, const string& s, const vector<ll>& c, const
vector<ll>& p) {
    vector<ll> lcp(n - 1, 0);

    ll pref = 0;

    for (int i = 0; i < n - 1; ++i) {
        ll pos = c[i];
        ll j = p[pos - 1];
        while (i + pref < n && j + pref < n && s[i + pref] == s[j + pref]
    ) {
            ++pref;
        }
        lcp[pos - 1] = pref;
        pref = max(0ll, pref - 1);
    }
}

```

```

    return lcp;
}

```

10.2 Prefix Function

```

vector<ll> prefix_function(string s) {
    ll n = s.size();
    vector<ll> p(n, 0);
    for (int i = 1; i < n; ++i) {
        ll k = p[i - 1];
        while (k > 0 && s[i] != s[k])
            k = p[k - 1];
        if (s[i] == s[k])
            ++k;
        p[i] = k;
    }
    return p;
}

```

10.3 Suffix Massive

```

void radix_sort(vector<pair<pair<ll, ll>, ll>>& prs) {
    ll n = prs.size();
    vector<ll> cnt(n, 0);
    for (auto mem : prs) {
        cnt[mem.first.first]++;
    }
    vector<ll> ptr(n, 0);
    for (int i = 1; i < n; ++i) {
        ptr[i] = ptr[i - 1] + cnt[i - 1];
    }

    vector<pair<pair<ll, ll>, ll>> new_prs(n);

    for (auto mem : prs) {
        ll i = mem.first.first;

        new_prs[ptr[i]++] = mem;
    }
    prs = new_prs;
}

vector<ll> suffix_array(string s) {
}

```



```

s += '$';

ll n = s.size();

vector<ll> p(n), c(n);

{ // k == 0
    vector<pair<ll, ll>> prs(n);
    for (int i = 0; i < n; ++i) {
        prs[i] = {s[i], i};
    }
    sort(all(prs));
    for (int i = 0; i < n; ++i) {
        p[i] = prs[i].second;
    }

    c[p[0]] = 0;
    for (int i = 1; i < n; ++i) {
        if (prs[i].first == prs[i - 1].first) {
            c[p[i]] = c[p[i - 1]];
        } else {
            c[p[i]] = c[p[i - 1]] + 1;
        }
    }
}

ll k = 0;

while ((1ll << k) < n) {
    vector<pair<pair<ll, ll>, ll>> prs(n);
    for (int i = 0; i < n; ++i) {
        ll t = p[i];
        ll j = ((t - (1ll << k)) % n + n) % n;
        prs[i] = {{c[j], c[t]}, j};
    }
    radix_sort(prs);

    for (int i = 0; i < n; ++i) {
        p[i] = prs[i].second;
    }
}

```

```

c[p[0]] = 0;
for (int i = 1; i < n; ++i) {
    if (prs[i].first == prs[i - 1].first) {
        c[p[i]] = c[p[i - 1]];
    } else {
        c[p[i]] = c[p[i - 1]] + 1;
    }
}

++k;
}

vector<ll> ans;
ans.reserve((int)n - 1);
for (int i = 1; i < n; ++i)
    ans.push_back(p[i]);
return ans;
}

```

10.4 Z Function

```

vector<ll> z_function(string s) {
    ll n = s.size();
    vector<ll> z(n, 0);
    ll r = 0;
    for (int i = 1; i < n; ++i) {
        if (z[i - r] < r + z[r] - i)
            z[i] = z[i - r];
        else {
            z[i] = max(r + z[r] - i, 0ll);
            while (i + z[i] < n && s[i + z[i]] == s[z[i]])
                ++z[i];
            r = i;
        }
    }
    return z;
}

```