

ICPC 2026

PROBLEM	READ	SOLVED	WRITTEN	OPENED	COMMENT
A					
B					
C					
D					
E					
F					
G					
H					
I					
J					
K					
L					
M					
N					

Time	Andrey	Taisia	Timofey
0:30			
1:00			
1:30			
2:00			
2:30			
3:00			
3:30			
4:00			
4:30			
5:00			

Contents

1	Combinatorics	2
1.1	Gray Code	2
2	Convolutions	2
2.1	FFT MOD	2
2.2	FFT	3
2.3	FHT	3
2.4	SOS DP	4
3	Data Structures	4
3.1	Centroid Decomposition	4
3.2	DSU	5
3.3	Disjoint Sparse Table	6
3.4	Fenwick 2D	6
3.5	Fenwick Tree	7
3.6	HLD	7
3.7	Ordered Set	8
3.8	Persistent DSU	9
3.9	Prefix Automate	9
3.10	Segment Tree Mass Simple	10
3.11	Segment Tree Mass	11
3.12	Segment Tree Simple	13
3.13	Segment Tree	13
3.14	Sparse Table	14
3.15	Treap	15
4	Flows	16
4.1	Dinic	16
5	Graphs	17
5.1	2 SAT	17
5.2	Euler Path	18
5.3	Hopcroft Karp	18
5.4	Hungarian	19
5.5	Initial Pairing	20
5.6	Kuhn	21
6	Number Theory	21
6.1	Eratosthenes	21
6.2	Miller Rabin	21
7	Strings	22
7.1	Prefix Function	22

7.2 Z Function 22

1 Combinatorics

1.1 Gray Code

```
inline ll g(ll n) {
    return n ^ (n >> 1);
}
```

2 Convolutions

2.1 FFT MOD

```
const ll ROOT = 31;
const ll REV_ROOT = rev(ROOT);
const int ROOT_PW = (1ll << 23);

int bit_rev(int num, int lg_n) {
    int res = 0;
    for (int i = 0; i < lg_n; ++i)
        if (num & (1 << i))
            res |= 1 << (lg_n - 1 - i);
    return res;
}

void fft_inpl(vector<ll>& a, bool invert) {
    int n = a.size();
    int lg_n = 0;
    while ((1 << lg_n) < n)
        ++lg_n;

    for (int i = 0; i < n; ++i) {
        if (i < bit_rev(i, lg_n))
            swap(a[i], a[bit_rev(i, lg_n)]);
    }

    for (int len = 2; len <= n; len <= 1) {
        ll w = invert ? REV_ROOT : ROOT;
```

```
for (int i = len; i < ROOT_PW; i <= 1)
    w = (w * w) % MOD;
for (int i = 0; i < n; i += len) {
    ll wn = 1;
    for (int j = 0; j < len / 2; ++j) {
        ll u = a[i + j], v = (a[i + j + len / 2] * wn) % MOD;
        a[i + j] = u + v < MOD ? u + v : u + v - MOD;
        a[i + j + len / 2] = u - v >= 0 ? u - v : u - v + MOD;
        wn *= w;
        wn %= MOD;
    }
}

if (invert) {
    int nrev = rev(n);
    for (int i = 0; i < n; ++i) {
        a[i] *= nrev;
        a[i] %= MOD;
    }
}

vector<ll> vect_mult(const vector<ll>& a, const vector<ll>& b) {
    ll sz = a.size() + b.size() - 1;
    ll n = 1;
    while (n < sz) {
        n <= 1;
    }

    vector<ll> fa(n, 0), fb(n, 0);
    for (int i = 0; i < n; ++i) {
        if (i < a.size()) {
            fa[i] = a[i];
        }
        if (i < b.size()) {
            fb[i] = b[i];
        }
    }

    fft_inpl(fa, false);
    fft_inpl(fb, false);
    for (int i = 0; i < n; ++i) {
        fa[i] *= fb[i];
        fa[i] %= MOD;
    }
}
```

```

    }
    fft_inpl(fa, true);

    vector<ll> mult(sz);
    for (int i = 0; i < sz; ++i) {
        mult[i] = fa[i];
    }
    return mult;
}

```

2.2 FFT

```

int bit_rev(int num, int lg_n) {
    int res = 0;
    for (int i = 0; i < lg_n; ++i)
        if (num & (1 << i))
            res |= 1 << (lg_n - 1 - i);
    return res;
}

// FFT
void fft_inpl(vector<comp>& a, bool invert) {
    int n = a.size();
    int lg_n = 0;
    while ((1 << lg_n) < n)
        ++lg_n;

    for (int i = 0; i < n; ++i) {
        if (i < bit_rev(i, lg_n)) {
            swap(a[i], a[bit_rev(i, lg_n)]);
        }
    }

    for (int len = 2; len <= n; len <<= 1) {
        double ang = 2 * PI / len * (invert ? -1 : 1);
        comp w(cos(ang), sin(ang));
        for (int i = 0; i < n; i += len) {
            comp wn(1);
            for (int j = 0; j < len / 2; ++j) {
                comp u = a[i + j], v = a[i + j + len / 2] * wn;
                a[i + j] = u + v;
                a[i + j + len / 2] = u - v;
                wn *= w;
            }
        }
    }
}

```

```

    }
    if (invert) {
        for (int i = 0; i < n; ++i) {
            a[i] /= n;
        }
    }
}

vector<ll> vect_mult(const vector<ll>& a, const vector<ll>& b) {
    ll sz = a.size() + b.size() - 1;
    ll n = 1;
    while (n < sz) {
        n <<= 1;
    }

    vector<comp> fa(n, 0), fb(n, 0);
    for (int i = 0; i < n; ++i) {
        if (i < a.size()) {
            fa[i] = comp(a[i], 0);
        }
        if (i < b.size()) {
            fb[i] = comp(b[i], 0);
        }
    }

    fft_inpl(fa, false);
    fft_inpl(fb, false);
    for (int i = 0; i < n; ++i) {
        fa[i] *= fb[i];
    }
    fft_inpl(fa, true);

    vector<ll> mult(sz);
    for (int i = 0; i < sz; ++i) {
        mult[i] = round(fa[i].real());
    }
    return mult;
}

```

2.3 FHT

```

inline ll soft_mod(ll a) {
    return a >= MOD ? a - MOD : a;
}

```

```

}

void FHT(vector<ll>& a) {
    ll sz = a.size();
    for (int mid = 1; mid < sz; mid <= 1) {
        for (int i = 0; i < sz; i += mid << 1) {
            for (int j = 0; j < mid; ++j) {
                ll x = a[i + j];
                ll y = a[i + j + mid];
                a[i + j] = soft_mod(x + y);
                a[i + j + mid] = soft_mod(x - y + MOD);
            }
        }
    }
}

vector<ll> xor_mult(vector<ll> a, vector<ll> b) {
    FHT(a);
    FHT(b);
    ll n = a.size();
    vector<ll> c(n);

    for (int i = 0; i < n; ++i) {
        c[i] = (a[i] * b[i]) % MOD;
    }

    FHT(c);
    ll revn = bin_pow(n, MOD - 2);
    for (int i = 0; i < n; ++i) {
        c[i] *= revn;
        c[i] %= MOD;
    }
    return c;
}

```

2.4 SOS DP

```

void sos(vector<ll>& dp) {
    ll n = dp.size();
    ll k = 0;
    while ((1ll << k) < n) {
        ++k;
    }
}

```

```

    for (int j = 0; j < k; ++j) {
        for (int i = 0; i < n; ++i) {
            if (i & (1ll << j)) {
                dp[i] += dp[i ^ (1ll << j)];
            }
        }
    }
}

void revsos(vector<ll>& dp) {
    ll n = dp.size();

    ll k = 0;
    while ((1ll << k) < n) {
        ++k;
    }

    for (int j = k - 1; j >= 0; --j) {
        for (int i = 0; i < n; ++i) {
            if (i & (1ll << j)) {
                dp[i] -= dp[i ^ (1ll << j)];
            }
        }
    }
}

```

3 Data Structures

3.1 Centroid Decomposition

```

struct CentroidDecomp {
    ll n;
    vector<ll> parent;

    void calc_sizes(ll v, vector<char>& used, vector<vector<ll>>& g,
vector<ll>& s) {
        s[v] = 1;
        used[v] = 1;

        for (ll u : g[v]) {
            if (!used[u]) {
                calc_sizes(u, used, g, s);
                s[v] += s[u];
            }
        }
    }
}

```

```

    }
}

ll find_centroid(ll v, vector<char>& used, vector<vector<ll>>& g,
vector<ll>& s, ll sz) {
    used[v] = 1;

    for (ll u : g[v]) {
        if (!used[u]) {
            if (s[u] > sz / 2) {
                return find_centroid(u, used, g, s, sz);
            }
        }
    }

    return v;
}

void set_parent(ll v, vector<char>& used, vector<vector<ll>>& g, ll
cent) {
    if (v != cent)
        parent[v] = cent;
    used[v] = 1;

    for (ll u : g[v]) {
        if (!used[u]) {
            set_parent(u, used, g, cent);
        }
    }
}

CentroidDecomp(ll N, vector<vector<ll>>& g) {
    n = N;
    parent.assign(n, -1);

    vector<char> cused(n, 0);
    vector<ll> s(n, 0);
    ll cnt_used = 0;

    while (cnt_used < n) {
        vector<char> sused = cused, used = cused, pused = cused;

        for (int i = 0; i < n; ++i) {

```

```

            if (!sused[i]) {
                calc_sizes(i, sused, g, s);
                ll cent = find_centroid(i, used, g, s, s[i]);

                cused[cent] = 1;
                ++cnt_used;
                set_parent(i, pused, g, cent);
            }
        }
    }
};

```

3.2 DSU

```

struct DSU {
    ll n;
    vector<ll> prev, size;

    DSU(ll N) : n(N) {
        prev.assign(n, -1);
        size.assign(n, 1);
    }

    ll root(ll a) {
        ll aa = a;
        while (prev[aa] != -1)
            aa = prev[aa];

        while (prev[aa] != -1) {
            ll last = prev[aa];
            prev[aa] = a;
            aa = last;
        }
        return a;
    }

    bool connected(ll a, ll b) {
        return root(a) == root(b);
    }

    bool unite(ll a, ll b) {
        a = root(a);
        b = root(b);

```

```

    if (a == b)
        return false;
    if (size[a] < size[b])
        swap(a, b);
    prev[b] = a;
    size[a] += size[b];
    return true;
}
};

```

3.3 Disjoint Sparse Table

```

struct DisjointSparseTable {
    vector<vector<ll>> dp;

    ll neutral() {
        return 0;
    }
    ll merge(ll a, ll b) {
        return a + b;
    }

    DisjointSparseTable() {}

    DisjointSparseTable(const vector<ll>& a) {
        ll n = (ll)a.size();
        ll k = 0;
        ll nn = 1;
        while (nn <= n) {
            ++k;
            nn <<= 1;
        }

        dp.assign((int)k, vector<ll>((int)n + 1, neutral()));

        ll t = 0;
        for (ll len = 1; len <= n; len <<= 1, ++t) {
            for (ll cent = len; cent <= n; cent += len * 2) {
                // left part (including cent-1)
                dp[(int)t][(int)(cent - 1)] = a[(int)(cent - 1)];
                for (ll i = cent - 2; i >= cent - len; --i) {
                    dp[(int)t][(int)i] = merge(a[(int)i], dp[(int)t][(int)
                    )(i + 1)]);
                }
            }
        }
    }
};

```

```

    }

    // right part: dp[t][cent] is neutral for empty prefix
    dp[(int)t][(int)cent] = neutral();
    for (ll i = cent + 1; i < min(cent + len, n + 1); ++i) {
        dp[(int)t][(int)i] = merge(dp[(int)t][(int)(i - 1)],
        a[(int)(i - 1)]);
    }
}

// query on [l, r)
ll query(ll l, ll r) {
    if (r <= 1)
        return neutral();
    ll t = 63 - __builtin_clzll((ull)(1 ^ r));
    return merge(dp[(int)t][(int)l], dp[(int)t][(int)r]);
}
};

```

3.4 Fenwick 2D

```

template <class T>
struct Fenwick2D {
    ll n = 0, m = 0;
    vector<vector<T>> bit;

    Fenwick2D() = default;
    Fenwick2D(int n_, int m_) {
        init(n_, m_);
    }

    void init(int n_, int m_) {
        n = n_;
        m = m_;
        bit.assign((int)n + 1, vector<T>((int)m + 1, T{}));
    }

    // add delta at (x, y), 0-indexed
    void add(ll x, ll y, T delta) {
        for (ll i = x + 1; i <= n; i += i & -i)
            for (ll j = y + 1; j <= m; j += j & -j)
                bit[i][j] += delta;
    }
};

```

```

}

// sum over [0..x] x [0..y], 0-indexed; returns 0 if x<0 or y<0
T sum_prefix(ll x, ll y) const {
    if (x < 0 || y < 0)
        return T{};
    T res{};
    for (ll i = x + 1; i > 0; i -= i & -i)
        for (ll j = y + 1; j > 0; j -= j & -j)
            res += bit[i][j];
    return res;
}

// sum over rectangle [x1..x2] x [y1..y2], inclusive, 0-indexed
T sum_rect(ll x1, ll y1, ll x2, ll y2) const {
    return sum_prefix(x2, y2) - sum_prefix(x1 - 1, y2) - sum_prefix(
x2, y1 - 1) + sum_prefix(x1 - 1, y1 - 1);
}
};

```

3.5 Fenwick Tree

```

struct FenwickTree {
    vector<ll> tree;
    ll n;

    FenwickTree(ll N) {
        n = N;
        tree.assign(n, 0);
    }

    ll F(ll x) {
        return x & (x + 1);
    }

    ll H(ll x) {
        return x | (x + 1);
    }

    // [0, r)
    ll query(ll r) {
        if (r > n) {
            r = n;
        }
    }
}

```

```

--r;
ll ans = 0;
while (r >= 0) {
    ans ^= tree[r];
    r = F(r) - 1;
}
return ans;
}

// [l, r)
ll query(ll l, ll r) {
    return query(r) ^ query(l);
}

void add(ll id, ll val) {
    while (id < n) {
        tree[id] ^= val;
        id = H(id);
    }
}
};

```

3.6 HLD

```

struct HLD {
    ll n;
    vector<ll> top, pos, h, par;

    ll gpos = 0;

    SegmentTree st;

    void calc_sizes(ll v, vector<char>& used, const vector<vector<ll>>& g
, vector<ll>& s) {
        s[v] = 1;
        used[v] = 1;

        for (ll u : g[v]) {
            if (!used[u]) {
                calc_sizes(u, used, g, s);
                s[v] += s[u];
            }
        }
    }
}

```

```

void build_dec(ll v, ll p, ll pr, vector<char>& used, const vector<
vector<ll>>& g, vector<ll>& s) {
    used[v] = 1;
    pos[v] = gpos++;
    top[pos[v]] = pos[p];
    par[pos[v]] = pos[pr];
    if (pr != v)
        h[pos[v]] = h[pos[pr]] + 1;

    vector<ll> child;

    for (ll u : g[v]) {
        if (!used[u]) {
            child.push_back(u);
        }
    }

    for (int i = 1; i < child.size(); ++i) {
        if (s[child[i]] > s[child[0]]) {
            swap(child[i], child[0]);
        }
    }

    if (!child.empty()) {
        build_dec(child[0], p, v, used, g, s);
        for (int i = 1; i < child.size(); ++i) {
            build_dec(child[i], child[i], v, used, g, s);
        }
    }
}

HLD(ll N, const vector<vector<ll>>& g, const vector<ll>& a) {
    n = N;

    top.resize(n, 0);
    pos.resize(n, 0);
    h.resize(n, 0);
    par.resize(n, 0);
    vector<char> used(n, 0);
    vector<ll> s(n, 0);

    calc_sizes(0, used, g, s);
    used.assign(n, 0);

```

```

    build_dec(0, 0, 0, used, g, s);

    vector<ll> pa(n, 0);
    for (int i = 0; i < n; ++i) {
        pa[pos[i]] = a[i];
    }

    st = SegmentTree(pa);
}

ll query(ll u, ll v) {
    ll ans = 0;

    u = pos[u];
    v = pos[v];

    ll pu = top[u];
    ll pv = top[v];

    while (pu != pv) {
        if (h[pu] >= h[pv]) {
            ans += st.query(pu, u + 1).sum;
            u = par[pu];
            pu = top[u];
        } else {
            ans += st.query(pv, v + 1).sum;
            v = par[pv];
            pv = top[v];
        }
    }
    ans += st.query(min(u, v), max(u, v) + 1).sum;

    return ans;
}

void change(ll u, ll val) {
    u = pos[u];
    st.change(u, val);
}
};

```

3.7 Ordered Set

```
#include <ext/pb_ds/assoc_container.hpp>
```



```
#include <ext/pb_ds/tree_policy.hpp>

using namespace __gnu_pbds;

template <class T, class Compare = std::less<T>>
using ordered_set = tree<
    T,
    null_type,
    Compare,
    rb_tree_tag,
    tree_order_statistics_node_update>;
```

3.8 Persistent DSU

```
struct PersistentDSU {
    ll n;
    vector<ll> prev, size;

    PersistentDSU(ll N) : n(N) {
        prev.assign(n, -1);
        size.assign(n, 1);
    }

    ll root(ll a) {
        while (prev[a] != -1)
            a = prev[a];
        return a;
    }

    bool connected(ll a, ll b) {
        return root(a) == root(b);
    }

    vector<pair<ll, ll>> changes; //

    bool unite(ll a, ll b) {
        a = root(a);
        b = root(b);
        if (a == b)
            return false;
        if (size[a] < size[b])
            swap(a, b);
        prev[b] = a;
        size[a] += size[b];
    }
};
```

```
changes.push_back({b, a});
return true;
}

bool rollback() {
    if (changes.empty())
        return false;
    pair<ll, ll> ba = changes.back();
    changes.pop_back();
    prev[ba.first] = -1;
    size[ba.second] -= size[ba.first];
    return true;
}
};
```

3.9 Prefix Automate

```
struct PrefixAutomate {
    const static int A = 26;

    struct Node {
        int next[A] = {-1};
        int link = -1;

        int prev = -1;
        int pe = -1;

        int has = 0;
    };

    vector<Node> tree;

    PrefixAutomate() {
        tree.push_back(Node());
    }

    void add(const string& s) {
        int v = 0;
        for (char c : s) {
            int e = c - 'a';
            if (tree[v].next[e] == -1) {
                tree[v].next[e] = tree.size();
                tree.push_back(Node());
                tree.back().prev = v;
            }
        }
    }
};
```

```

        tree.back().pe = e;
    }
    v = tree[v].next[e];
}
tree[v].has = 1;
}

void addVect(const vector<string>& vs) {
    for (const auto& s : vs) {
        add(s);
    }
}

void del(const string& s) {
    int v = 0;
    for (char c : s) {
        int e = c - 'a';
        if (tree[v].next[e] == -1) {
            return;
        }
        v = tree[v].next[e];
    }
    tree[v].has = 0;
}

void ahoCorasick() {
    queue<int> que;

    tree[0].prev = 0;
    tree[0].pe = -1;

    tree[0].link = 0;
    for (int i = 0; i < A; ++i) {
        if (tree[0].next[i] == -1) {
            tree[0].next[i] = 0;
        } else {
            que.push(tree[0].next[i]);
        }
    }

    while (!que.empty()) {
        int v = que.front();
        que.pop();

```

```

        if (tree[v].link == -1) {
            if (v == 0 || tree[v].prev == 0)
                tree[v].link = 0;
            else
                tree[v].link = tree[tree[v].prev].next[tree[v].pe];
        }

        for (int i = 0; i < A; ++i) {
            if (tree[v].next[i] == -1) {
                tree[v].next[i] = tree[tree[v].link].next[i];
            } else {
                que.push(tree[v].next[i]);
            }
        }
    }
}
};

```

3.10 Segment Tree Mass Simple

```

struct SegmentTreeMassSimple {
    struct Node {
        ll size, val, inc;

        Node(ll Val = 0, ll Size = 0, ll Inc = 0) {
            val = Val;
            size = Size;
            inc = Inc;
        }
    };

    ll n;
    vector<Node> tree;

    Node merge(Node n1, Node n2) {
        return Node(n1.val + n2.val, n1.size + n2.size);
    }

    SegmentTreeMassSimple(const vector<ll>& start) {
        n = start.size();

        tree.resize(n * 2);

        for (int i = 0; i < n; ++i) {

```

```

        tree[i + n] = Node(start[i], 1, 0);
    }

    for (int i = n - 1; i >= 0; --i) {
        tree[i] = merge(tree[i << 1], tree[i << 1 | 1]);
    }
}

void apply(ll i, ll val) {
    tree[i].val += val * tree[i].size;
    tree[i].inc += val;
}

void push(ll i) {
    if (i > 1) {
        push(i >> 1);
    }
    if (i < n) {
        apply(i << 1, tree[i].inc);
        apply(i << 1 | 1, tree[i].inc);
        tree[i].inc = 0;
    }
}

// fix node i and all parents
void fix(ll i) {
    push(i);
    while (i > 1) {
        ll j = i >> 1;
        tree[j] = merge(tree[j << 1], tree[j << 1 | 1]);
        i = j;
    }
}

Node query(ll l, ll r) {
    l += n;
    r += n;

    Node ans1, ansr;

    push(l);
    push(r - 1);

    while (r > l) {

```

```

        if (l & 1) {
            ans1 = merge(ans1, tree[l++]);
        }
        if (r & 1) {
            ansr = merge(tree[--r], ansr);
        }

        l >>= 1;
        r >>= 1;
    }

    return merge(ans1, ansr);
}

void change(ll l, ll r, ll inc) {
    l += n;
    r += n;

    ll l0 = l, r0 = r;

    push(l);
    push(r - 1);

    while (r > l) {
        if (l & 1) {
            apply(l++, inc);
        }
        if (r & 1) {
            apply(--r, inc);
        }

        l >>= 1;
        r >>= 1;
    }

    fix(l0);
    fix(r0 - 1);
}
};

```

3.11 Segment Tree Mass

```

struct SegmentTreeMass {
    struct Node {

```

```

    ll sum = 0;
    ll add = 0;

    Node(ll Sum = 0, ll Add = 0) {
        sum = Sum;
        add = Add;
    }
};

Node neutral = Node();
ll n;
vector<Node> tree;

SegmentTreeMass(const vector<ll>& start) {
    n = start.size();
    tree.resize(4 * n + 3);
    init(start);
}

SegmentTreeMass(ll N) {
    n = N;
    tree.resize(4 * n + 3);
    vector<ll> start(n, 0);
    init(start);
}

Node merge(Node n1, Node n2) {
    return Node(n1.sum + n2.sum);
}

void fix(ll v, ll l, ll r) {
    tree[v] = merge(tree[v * 2 + 1], tree[v * 2 + 2]);
}

void apply(ll v, ll l, ll r, ll val) {
    tree[v].add += val;
    tree[v].sum += val * (r - l);
}

void push(ll v, ll l, ll r) {
    ll m = (r + l) / 2;

    apply(v * 2 + 1, l, m, tree[v].add);
    apply(v * 2 + 2, m, r, tree[v].add);

```

```

    tree[v].add = 0;
}

void init(ll v, ll l, ll r, const vector<ll>& start) {
    if (l + 1 == r) {
        tree[v] = Node(start[l], 0);
        return;
    }

    ll m = (r + l) / 2;
    init(v * 2 + 1, l, m, start);
    init(v * 2 + 2, m, r, start);
    fix(v, l, r);
}

void init(const vector<ll>& start) {
    init(0, 0, n, start);
}

// [l: r)
Node query(ll v, ll l, ll r, ll ql, ll qr) {
    if (ql <= l && r <= qr) {
        return tree[v];
    }
    if (r <= ql || qr <= l) {
        return neutral;
    }

    ll m = (r + l) / 2;
    push(v, l, r);
    return merge(query(v * 2 + 1, l, m, ql, qr), query(v * 2 + 2, m,
r, ql, qr));
}

Node query(ll ql, ll qr) {
    return query(0, 0, n, ql, qr);
}

void add(ll v, ll l, ll r, ll ql, ll qr, ll val) {
    if (ql <= l && r <= qr) {
        apply(v, l, r, val);
        return;
    }
    if (r <= ql || qr <= l) {

```

```

        return;
    }

    ll m = (r + 1) / 2;
    push(v, l, r);
    add(v * 2 + 1, l, m, ql, qr, val);
    add(v * 2 + 2, m, r, ql, qr, val);
    fix(v, l, r);
}

void add(ll ql, ll qr, ll val) {
    add(0, 0, n, ql, qr, val);
}
};

```

3.12 Segment Tree Simple

```

struct SegmentTreeSimple {
    ll n;
    vector<ll> tree;

    SegmentTreeSimple(ll N) {
        n = N;
        tree.resize(n * 2);
    }

    SegmentTreeSimple(const vector<ll>& start) {
        n = start.size();
        tree.resize(n * 2);

        for (int i = 0; i < n; ++i) {
            tree[i + n] = start[i];
        }
        for (int i = n - 1; i > 0; --i) {
            tree[i] = tree[i << 1] + tree[i << 1 | 1];
        }
    }

    void change(ll i, ll val) {
        i += n;
        tree[i] = val;
        while (i > 1) {
            tree[i >> 1] = tree[i] + tree[i ^ 1];
            i >>= 1;
        }
    }
};

```

```

    }

    ll query(ll l, ll r) {
        ll ans = 0;

        l += n;
        r += n;

        while (l < r) {
            if (l & 1) {
                ans += tree[l++];
            }
            if (r & 1) {
                ans += tree[--r];
            }

            l >>= 1;
            r >>= 1;
        }

        return ans;
    }
};

```

3.13 Segment Tree

```

struct SegmentTree {
    struct Node {
        ll sum;

        Node(ll Sum = 0) : sum(Sum) {}
    };

    Node neutral = Node();

    ll n;
    vector<Node> tree;

    void init(ll v, ll l, ll r, const vector<ll>& start) {
        if (l + 1 == r) {
            tree[v] = Node(start[l]);
            return;
        }
    }
};

```

```

    }

    ll m = (l + r) / 2;

    init(v * 2 + 1, l, m, start);
    init(v * 2 + 2, m, r, start);
    tree[v] = merge(tree[v * 2 + 1], tree[v * 2 + 2]);
}

SegmentTree() {
}

SegmentTree(const vector<ll>& start) {
    n = start.size();
    tree.resize(n * 4 + 3);
    init(0, 0, n, start);
}

Node merge(Node n1, Node n2) {
    return Node(n1.sum + n2.sum);
}

Node query(ll v, ll l, ll r, ll ql, ll qr) {
    if (ql <= l && r <= qr)
        return tree[v];
    if (qr <= l || r <= ql)
        return neutral;

    ll m = (l + r) / 2;
    return merge(query(v * 2 + 1, l, m, ql, qr), query(v * 2 + 2, m,
r, ql, qr));
}

Node query(ll ql, ll qr) {
    return query(0, 0, n, ql, qr);
}

void change(ll v, ll l, ll r, ll id, ll val) {
    if (l + 1 == r && l == id) {
        tree[v] = Node(val);
        return;
    }
    if (r <= id || id < l) {
        return;
    }

```

```

    }

    ll m = (l + r) / 2;
    change(v * 2 + 1, l, m, id, val);
    change(v * 2 + 2, m, r, id, val);
    tree[v] = merge(tree[v * 2 + 1], tree[v * 2 + 2]);
}

void change(ll id, ll val) {
    change(0, 0, n, id, val);
}

};

```

3.14 Sparse Table

```

template <class T>
struct SparseTable {
    ll n, k;
    vector<T> a;
    vector<vector<T>> sparse;
    vector<ll> length;

    SparseTable(vector<T>& start) {
        n = start.size();
        k = 0;
        for (ll d = 1; d <= n; d *= 2, ++k) {
        }
        a.assign(start.begin(), start.end());
        sparse.assign(n, vector<T>(k));
        countSparse();
        precalc();
    }

    void precalc() {
        length.assign(n + 1, 0);
        ll t = 0;
        for (int l = 1; l <= n; ++l) {
            if ((1ll << (t + 1)) < l)
                ++t;
            length[l] = t;
        }
    }

    void countSparse() {

```

```

    for (int i = 0; i < n; ++i) {
        sparse[i][0] = a[i];
    }
    for (int j = 1; j < k; ++j) {
        for (int i = 0; i < n; ++i) {
            ll d = (1ll << (j - 1));
            sparse[i][j] = max(sparse[i][j - 1], sparse[min(n - 1, i
+ d)][j - 1]);
        }
    }

T query(ll l, ll r) {
    ll t = length[r - 1];

    ll d = (1ll << t);

    return max(sparse[l][t], sparse[r - d][t]);
}
};

```

3.15 Treap

```

struct Treap {
    Treap* left;
    Treap* right;
    ll x;
    unsigned int y;
    unsigned int size;
    ll dp;

    Treap(ll val = 0) {
        left = nullptr;
        right = nullptr;
        size = 1;
        x = val;
        y = mersenne();
        update(this);
    }

    friend ll get_dp(Treap* node) {
        if (node == nullptr)
            return 0;
        return node->dp;
    }
}

```

```

}

friend unsigned int get_size(Treap* node) {
    if (node == nullptr)
        return 0;
    return node->size;
}

friend void update(Treap* node) {
    if (node == nullptr)
        return;
    node->size = 1 + get_size(node->left) + get_size(node->right);
    node->dp = max({node->x, get_dp(node->left), get_dp(node->right)
});
}

// split by size
friend pair<Treap*, Treap*> split_k(Treap* node, unsigned int k) {
    if (node == nullptr)
        return {nullptr, nullptr};
    if (get_size(node->left) < k) {
        auto res = split_k(node->right, k - get_size(node->left) - 1)
;
        node->right = res.first;
        update(node);
        return {node, res.second};
    } else {
        auto res = split_k(node->left, k);
        node->left = res.second;
        update(node);
        return {res.first, node};
    }
}

// split by dp: dp in left < k
friend pair<Treap*, Treap*> split_dp(Treap* node, unsigned int k) {
    if (node == nullptr)
        return {nullptr, nullptr};
    if (get_dp(node) < k) {
        auto res = split_dp(node->right, k);
        node->right = res.first;
        update(node);
        return {node, res.second};
    } else {

```

```

    auto res = split_dp(node->left, k);
    node->left = res.second;
    update(node);
    return {res.first, node};
}

friend Treap* merge(Treap* left, Treap* right) {
    if (left == nullptr)
        return right;
    if (right == nullptr)
        return left;
    if (left->y > right->y) {
        left->right = merge(left->right, right);
        update(left);
        return left;
    } else {
        right->left = merge(left, right->left);
        update(right);
        return right;
    }
}

friend Treap* insert(Treap* node, unsigned int pos, ll val) {
    auto res = split_k(node, pos);
    Treap* tr = new Treap(val);
    return merge(merge(res.first, tr), res.second);
}

friend Treap* erase(Treap* node, unsigned int pos) {
    auto res = split_k(node, pos + 1);
    auto left_res = split_k(res.first, pos);
    return merge(left_res.first, res.second);
}

// return {element, root}
friend pair<Treap*, Treap*> kth_element(Treap* node, unsigned int k)
{
    if (get_size(node) < k)
        return {nullptr, node};
    auto res = split_k(node, k + 1);
    auto left_res = split_k(res.first, k);
    return {left_res.second, merge(left_res.first, merge(left_res.
second, res.second))};
}

```

```

}

// return sub segment [l, r) and remaineng Treap [0, l) + [r + 1,
size)
friend pair<Treap*, Treap*> cut(Treap* node, unsigned int l, unsigned
int r) {
    auto res = split_k(node, r);
    auto left_res = split_k(res.first, l);
    return {left_res.second, merge(left_res.first, res.second)};
}
};

```

4 Flows

4.1 Dinic

```

struct FlowSolver {
    struct DinicEdge {
        ll a, b, cap, flow;
    };

    vector<DinicEdge> edges;
    vector<vector<ll>> g;
    ll n;

    FlowSolver(ll N) {
        n = N;
        g.resize(n);
    }

    void add_edge(ll u, ll v, ll w) {
        g[u].push_back(edges.size());
        edges.push_back({u, v, w, 0});
        g[v].push_back(edges.size());
        edges.push_back({v, u, 0, 0});
    }

    bool bfs(ll s, ll t, vector<ll>& d) {
        queue<ll> q;
        d.assign(n, -1);
        d[s] = 0;
        q.push(s);
    }
}

```



```

while (!q.empty()) {
    ll v = q.front();
    q.pop();

    for (ll id : g[v]) {
        ll u = edges[id].b;
        if (d[u] == -1) {
            if (edges[id].cap > edges[id].flow) {
                d[u] = d[v] + 1;
                q.push(u);
            }
        }
    }
}

return d[t] != -1;
}

ll dfs(ll v, ll t, ll flow, vector<ll>& d, vector<ll>& ptr) {
    if (flow == 0) {
        return 0;
    }
    if (v == t) {
        return flow;
    }

    for (; ptr[v] < g[v].size(); ++ptr[v]) {
        ll id = g[v][ptr[v]];
        ll u = edges[id].b;

        if (d[u] == d[v] + 1) {
            ll add_flow = dfs(u, t, min(flow, edges[id].cap - edges[
id].flow), d, ptr);
            if (add_flow > 0) {
                edges[id].flow += add_flow;
                edges[id ^ 1].flow -= add_flow;
                return add_flow;
            }
        }
    }

    return 0;
}

ll dinic(ll s, ll t) {

```

```

    ll flow = 0;
    vector<ll> d;
    while (bfs(s, t, d)) {
        vector<ll> ptr(n, 0);
        while (ll add_flow = dfs(s, t, inf, d, ptr)) {
            flow += add_flow;
        }
    }
    return flow;
}
};

```

5 Graphs

5.1 2 SAT

```

struct SATSolver {
    ll n;
    vector<vector<ll>> g, gt;
    vector<char> used;
    vector<ll> order, comp;

    void init(ll N) {
        n = N;
        g.assign((int)(2 * n), {});
        gt.assign((int)(2 * n), {});
    }

    // literal: var in [0..n), val=false -> 2*var, val=true -> 2*var+1
    ll lit(ll var, ll val) { return 2 * var + (val ? 1 : 0); }
    ll neg(ll x) { return x ^ 1; }

    void add_imp(ll a, ll b) {
        g[(int)a].push_back(b);
        gt[(int)b].push_back(a);
    }

    // (a_var is a_val) OR (b_var is b_val)
    void add_or(ll a_var, ll a_val, ll b_var, ll b_val) {
        ll a = lit(a_var, a_val);
        ll b = lit(b_var, b_val);
        add_imp(neg(a), b);
        add_imp(neg(b), a);
    }
}

```

```

}

void dfs1(ll v) {
    used[(int)v] = 1;
    for (ll to : g[(int)v]) if (!used[(int)to]) dfs1(to);
    order.push_back(v);
}

void dfs2(ll v, ll cl) {
    comp[(int)v] = cl;
    for (ll to : gt[(int)v]) if (comp[(int)to] == -1) dfs2(to, cl);
}

// returns empty vector if unsat; otherwise assignment[i] in {0,1}
vector<ll> solve() {
    used.assign((int)(2 * n), 0);
    order.clear();
    for (ll i = 0; i < 2 * n; ++i) if (!used[(int)i]) dfs1(i);

    comp.assign((int)(2 * n), -1);
    ll j = 0;
    for (ll i = 2 * n - 1; i >= 0; --i) {
        ll v = order[(int)i];
        if (comp[(int)v] == -1) dfs2(v, j++);
    }

    vector<ll> ans((int)n);
    for (ll i = 0; i < n; ++i) {
        if (comp[(int)(2 * i)] == comp[(int)(2 * i + 1)]) return {};
        ans[(int)i] = (comp[(int)(2 * i)] < comp[(int)(2 * i + 1)]);
    }
    return ans;
}
};

```

5.2 Euler Path

```

void cycle(ll prev, ll v, vector<vector<pair<ll, ll>>>& g, vector<ll>&
ans) {
    while (!g[v].empty()) {
        auto iu = g[v].back();
        ll u = iu.second;
        g[v].pop_back();
        cycle(iu.first, u, g, ans);
    }
}

```

```

}
if (prev >= 0)
    ans.push_back(prev);
}

```

5.3 Hopcroft Karp

```

struct HopcroftKarp {
    ll n1, n2;
    vector<vector<ll>> g;
    vector<ll> dist;
    vector<ll> mt1, mt2;

    void init(ll N1, ll N2) {
        n1 = N1;
        n2 = N2;
        g.assign((int)n1, {});
        mt1.assign((int)n1, -1);
        mt2.assign((int)n2, -1);
        dist.assign((int)n1, 0);
    }

    void add_edge(ll u, ll v) {
        // u in [0..n1), v in [0..n2)
        g[(int)u].push_back(v);
    }

    bool bfs() {
        queue<ll> q;
        for (ll i = 0; i < n1; ++i) {
            if (mt1[(int)i] == -1) {
                dist[(int)i] = 0;
                q.push(i);
            } else {
                dist[(int)i] = -1;
            }
        }

        bool found = false;
        while (!q.empty()) {
            ll v = q.front();
            q.pop();

            for (ll to : g[(int)v]) {

```

```

    ll u = mt2[(int)to];
    if (u == -1) {
        found = true;
    } else if (dist[(int)u] == -1) {
        dist[(int)u] = dist[(int)v] + 1;
        q.push(u);
    }
}
}
return found;
}

bool dfs(ll v) {
    for (ll to : g[(int)v]) {
        ll u = mt2[(int)to];
        if (u == -1 || (dist[(int)u] == dist[(int)v] + 1 && dfs(u)))
        {
            mt1[(int)v] = to;
            mt2[(int)to] = v;
            return true;
        }
    }
    dist[(int)v] = -1;
    return false;
}

ll solve() {
    ll matching = 0;
    while (bfs()) {
        for (ll i = 0; i < n1; ++i) {
            if (mt1[(int)i] == -1) {
                if (dfs(i)) {
                    ++matching;
                }
            }
        }
    }
    return matching;
}
};

```

5.4 Hungarian

// a size is (n + 1) x (m + 1), 1-indexing

```

// n <= m; if n < m than a[i][j] must be >= 0
pair<ll, vector<int>> hungarian(const vector<vector<ll>>& a, int n, int m)
{
    vector<ll> u(n + 1, 0), v(m + 1, 0);
    vector<int> p(m + 1, 0), way(m + 1, 0);
    for (int i = 1; i <= n; ++i) {
        int j0 = 0;
        p[j0] = i;

        vector<char> used(m + 1, 0);
        vector<ll> minv(m + 1, inf);
        do {
            used[j0] = true;
            int i0 = p[j0];
            int j1 = -1, delta = inf;

            // run step of dfs from i0
            for (int j = 1; j <= m; ++j) {
                if (used[j]) {
                    continue;
                }

                int cur = a[i0][j] - u[i0] - v[j];
                if (cur < minv[j]) {
                    minv[j] = cur;
                    way[j] = j0;
                }
                if (minv[j] < delta) {
                    delta = minv[j];
                    j1 = j;
                }
            }

            // update potentials
            for (int j = 0; j <= m; ++j) {
                if (used[j]) {
                    u[p[j]] += delta;
                    v[j] -= delta;
                } else {
                    minv[j] -= delta;
                }
            }

            j0 = j1;
        } while (j1 != -1);
    }
}

```

```

    } while (p[j0] != 0);

    while (j0) {
        int j1 = way[j0];
        p[j0] = p[j1];
        j0 = j1;
    }

    return {-v[0], p};
}

```

5.5 Initial Pairing

```

int init_pairing(int n1, int n2, const vector<vector<int>>& g, vector<int>
>& mt, vector<int>& rmt) {
    auto PACK = [](int x, int y) { return ((1l)x << 30) + y; };
    auto SUNPACK = [](int x) {
        const static ll mask = (1ll << 30) - 1;
        return x & mask;
    };

    vector<int> deg(n1, 0);
    vector<vector<int>> ng(n1);
    vector<vector<pair<int, int>>> rg(n2);
    vector<int> next(n1, 0);
    set<ll> que;
    for (int i = 0; i < n1; ++i) {
        for (auto j : g[i]) {
            ++deg[i];
            rg[j].push_back({i, ng[i].size()});
            ng[i].push_back(j);
        }
        que.insert(PACK(deg[i], i));
    }

    int pairing = 0;

    while (!que.empty()) {
        auto res = *que.begin();
        que.erase(res);

        int i = SUNPACK(res);
        if (deg[i] == 0) {

```

```

            continue;
        }

        while (ng[i][next[i]] == -1) {
            ++next[i];
        }
        int j = ng[i][next[i]++];

        deg[i] = 0;
        for (auto ks : rg[j]) {
            int k = ks.first;
            int sz = ks.second;
            if (deg[k] != 0) {
                ng[k][sz] = -1;
                que.erase(PACK(deg[k], k));
                --deg[k];
                que.insert(PACK(deg[k], k));
            }
        }
        mt[j] = i;
        rmt[i] = j;
        ++pairing;
    }
    return pairing;
}

vector<int> fast_kuhn(int n1, int n2, vector<vector<int>>& g) {
    vector<char> used(n1, 0);
    vector<int> mt(n2, -1), rmt(n1, -1);

    init_pairing(n1, n2, g, mt, rmt);

    int mark = 0;

    for (int run = 1; run;) {
        ++mark;
        run = 0;
        for (int i = 0; i < n1; ++i) {
            if (rmt[i] == -1 && kuhn_dfs(i, used, mark, g, mt)) {
                run = 1;
            }
        }
    }

    for (int j = 0; j < n2; ++j) {

```

```

        if (mt[j] != -1) {
            rmt[mt[j]] = j;
        }
    }
}

```

```

return mt;
}

```

5.6 Kuhn

```

bool kuhn_dfs(int v, vector<char>& used, char mark, vector<vector<int>>&
g, vector<int>& mt) {
    if (used[v] == mark) {
        return false;
    }
    used[v] = mark;

    for (int u : g[v]) {
        if (mt[u] == -1 || kuhn_dfs(mt[u], used, mark, g, mt)) {
            mt[u] = v;
            return true;
        }
    }
    return false;
}

vector<int> kuhn(int n1, int n2, vector<vector<int>>& g) {
    vector<char> used(n1, 0);
    vector<int> mt(n2, -1);

    int mark = 1;

    for (int i = 0; i < n1; ++i) {
        if (kuhn_dfs(i, used, mark, g, mt)) {
            ++mark;
        }
    }

    return mt;
}

```

6 Number Theory

6.1 Eratosthenes

```

void erat(ll N, vector<ll>& primes, vector<ll>& mi) {
    mi.assign(N, 0);
    for (int i = 2; i < N; ++i) {
        if (mi[i] == 0) {
            primes.push_back(i);
            mi[i] = i;

            for (int j = 0; j < primes.size() && primes[j] <= mi[i] && i *
primes[j] < N; ++j) {
                mi[primes[j] * i] = primes[j];
            }
        }
    }
}

```

6.2 Miller Rabin

```

bool _miller_rabin_test(ll n, ll d, ll s, ll a) {
    ll x = bin_pow_mod(a, d, n);
    for (int i = 0; i < s; ++i) {
        ll y = ((__int128_t)x * x) % n;
        if (y == 1 && x != 1) {
            return false;
        }
        x = y;
    }
    if (x != 1) {
        return false;
    }
    return true;
}

bool is_prime_ml(ll n) {
    if (n <= 1) {
        return false;
    }
    // all primes

```

```

vector<ll> as = {2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37};
ll d = n - 1;
ll s = 0;
while ((d & 1) == 0) {
    ++s;
    d >>= 1;
}
for (ll a : as) {
    if (n == a) {
        return true;
    }
    if (n % a == 0) {
        return false;
    }
    if (!_miller_rabin_test(n, d, s, a)) {
        return false;
    }
}
return true;
}

```

7 Strings

7.1 Prefix Function

```

vector<ll> prefix_function(string s) {
    ll n = s.size();
    vector<ll> p(n, 0);

```

```

    for (int i = 1; i < n; ++i) {
        ll k = p[i - 1];
        while (k > 0 && s[i] != s[k])
            k = p[k - 1];
        if (s[i] == s[k])
            ++k;
        p[i] = k;
    }
    return p;
}

```

7.2 Z Function

```

vector<ll> z_function(string s) {
    ll n = s.size();
    vector<ll> z(n, 0);
    ll r = 0;
    for (int i = 1; i < n; ++i) {
        if (z[i - r] < r + z[r] - i)
            z[i] = z[i - r];
        else {
            z[i] = max(r + z[r] - i, 0ll);
            while (i + z[i] < n && s[i + z[i]] == s[z[i]])
                ++z[i];
            r = i;
        }
    }
    return z;
}

```