Nocturnal++

Sign in to your account

Email

you@university.edu

Password

••••••••

Sign In

Don't have an account? **Sign Up**

Create Account

First Name

John

Last Name

Dev

Email

you@university.edu

Password

Min. 8 characters

Profile Information

School

University of South Carolina

Major

Computer Science

Grad Year

2027

Create Account

Already have an account? **Sign In**

Welcome, John

Streak: 12 days

Solved: 4/6

Rank: #4,287

Continue: Maximum Subarray MEDIUM · Array →

Recent Questions

See All →

Status	Title	Difficulty	Category	Success
✓	Two Sum	Easy	Array	52%
✓	Reverse Linked List	Easy	Linked List	62%
	Big-O of Nested Loops	Easy	Big-O	69%
	Merge Two Sorted Lists	Medium	Linked List	47%
✓	Maximum Subarray	Medium	Array	45%
	Explain O(log n)	Easy	Big-O	69%

Progress

Easy 3/3

Medium 1/3

Hard 0/2

Question Library

8 questions available

Difficulty: All | Easy | Medium | Hard

Category: All | Big-O | Array | Linked List

	Title	Type	Difficulty	Category	Success
✓	Two Sum	Coding	Easy	Array	52%
✓	Reverse Linked List	Coding	Easy	Linked List	62%
○	Big-O of Nested Loops	Multiple Choice	Easy	Big-O	69%
○	Merge Two Sorted Lists	Coding	Medium	Linked List	47%
✓	Maximum Subarray	Coding	Medium	Array	45%
○	Explain O(log n)	Short Answer	Easy	Big-O	69%
○	Detect Cycle in Linked List	Coding	Medium	Linked List	45%
○	Trapping Rain Water	Coding	Hard	Array	22%

Two Sum

Easy · Coding · Array · 52% success · 2,841 attempts

Problem | Answers (2) | Discussion

PROBLEM

Given an array of integers nums and an integer target, return indices of the two numbers such that they add up to target.
You may assume each input has exactly one solution.

EXAMPLE

Input: nums = [2,7,11,15], target = 9 Output: [0,1]
Explanation: nums[0] + nums[1] == 9

CONSTRAINTS

$2 \le$ nums.length $\le 10^4$ · Only one valid answer exists

HINT [Click to reveal]

Top Answer by AlgoMaster ▲ 39 ▼

```
def twoSum(nums, target):
    seen = {}
    for i, num in enumerate(nums):
        comp = target - num
        if comp in seen: return [seen[comp], i]
        seen[num] = i
```

Hash map approach. O(n) time, O(n) space.

Comments: "Great explanation!" - CodeNewbie | "What about duplicates?" - Learner99
Reply: "O(n) is the optimal tradeoff here." - DSA_Pro

Add a comment...

Post

Bookmarked Questions

3 saved questions

Title	Difficulty	Category	Saved
Two Sum	Easy	Array	★
Maximum Subarray	Medium	Array	★
Trapping Rain Water	Hard	Array	★

J

John Dev

john@university.edu

Contributor

Stats | Account Details | Bookmarks

Streak **12 days**	Rank **#4,287**
Solved **4**	Upvotes **156**

Difficulty Breakdown

Easy 3/3

Medium 1/3

Hard 0/2

Account Details

School	University of South Carolina
Major	Computer Science
Graduation Year	2027
Email	john@university.edu
Role	Contributor
Resume URL	Not uploaded

Edit Profile

Settings

Account | Profile | Password

Account Settings

First Name

John

Last Name

Dev

Email

john@university.edu

Save Changes

Danger Zone

Permanently delete your account and all data.

Delete Account