Splunk CIM Data Model — Field Catalog

Purpose: a catalog of every Splunk Common Information Model (CIM) field, by data model and dataset — to reconcile a generated or third-party add-on field-for-field against what the model actually defines.

Source: `splunk_data_model_objects_fields_870.csv` (Splunk CIM 8.7.0)
Generated: October 17, 2026
Scope: 1519 fields · 27 models · 139 datasets

Status: `Req` = required · `Rec` = recommended (the dataset should populate it) · `Opt` = optional.
Tags match events into a dataset (not sourcetype); a tag not listed here pulls events into *no* known dataset.
Child datasets (dotted names) list only the fields they add and also inherit the parent's fields + tag constraint.
Fields described "Auto-set by ES asset/identity correlation" must **not** be extracted by an add-on.
`(Eval)`/`(Rex)`/`(Lookup)` = the model derives the field that way.

Models

- Alerts — 1 dataset(s), 30 fields
- Application_State (deprecated) — 4 dataset(s), 25 fields
- Authentication — 1 dataset(s), 41 fields
- Certificates — 2 dataset(s), 47 fields
- Change — 4 dataset(s), 49 fields
- Change_Analysis (deprecated) — 3 dataset(s), 40 fields
- Compute_Inventory — 9 dataset(s), 57 fields
- DLP — 1 dataset(s), 37 fields
- Data_Access — 1 dataset(s), 41 fields
- Databases — 8 dataset(s), 76 fields
- Email — 2 dataset(s), 54 fields
- Endpoint — 5 dataset(s), 198 fields
- Event_Signatures — 1 dataset(s), 9 fields
- Interprocess_Messaging — 1 dataset(s), 35 fields
- Intrusion_Detection — 1 dataset(s), 36 fields
- JVM — 7 dataset(s), 46 fields
- Malware — 2 dataset(s), 45 fields
- Network_Resolution — 1 dataset(s), 32 fields
- Network_Sessions — 2 dataset(s), 29 fields
- Network_Traffic — 1 dataset(s), 66 fields
- Performance — 9 dataset(s), 49 fields
- Splunk_Audit — 6 dataset(s), 79 fields
- Ticket_Management — 4 dataset(s), 28 fields
- Updates — 2 dataset(s), 22 fields
- Vulnerabilities — 1 dataset(s), 46 fields
- Web — 2 dataset(s), 46 fields

Alerts

Alerts

Object Alerts · **Parent** BaseEvent · **Fields** 30 · **Tags** alert
Constraint (`cim_Alerts_indexes`) tag=alert

Field	St	Type	Description
app	Rec	string	The system, service, or application that generated the alert event. Examples incl… (Eval)
dest	Rec	string	The object that is the 'target' of the alert event. Examples include an email add… (Eval)
severity	Rec	string	The severity of the alert event. Note: This field is a string. Specific values ar… (Eval)
signature_id	Rec	string	The vendor specific policy or rule that generated the alert event, such as 'Polic… (Eval)
src	Rec	string	The object that is the 'actor' of the alert event. You can alias or extract this… (Eval)
type	Rec	string	The alert event type. (Eval)
user	Rec	string	The user involved in the alert event. (Eval)
body	Opt	string	This field is deprecated in favor of 'description'.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
description	Opt	string	The description of the alert event.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_type	Opt	string	The type of the destination object, such as 'instance', 'storage', 'firewall'.
id	Opt	string	The unique identifier of the alert event.
mitre_technique_id	Opt	string	The MITRE ATT&CK technique ID of the alert event, searchable at https://attack.mi…
severity_id	Opt	string	The numeric or vendor specific severity indicator corresponding to the event seve…
signature	Opt	string	The human-friendly title of the alert event, such as 'API GetAccountPasswordPolic…
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_type	Opt	string	The type of the source object, such as 'instance', 'storage', 'firewall'.
subject	Opt	string	This field is deprecated in favor of 'signature'.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_name	Opt	string	The user_name of user involved in the alert event. (Eval)
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
vendor_account	Opt	string	The account associated with the alert event.
vendor_region	Opt	string	The data center region involved in the alert event, such as us-west-2.

Prescribed values
severity = critical, high, medium, low, informational, unknown
type = alarm, alert, event, task, warning, unknown

Application_State

All_Application_State

Object All_Application_State · **Parent** BaseEvent · **Fields** 14 · **Tags** listening, port, process, report, service
Constraint (`cim_Application_State_indexes`) (tag=listening tag=port) OR (tag=process tag=report) OR (tag=service tag=report)

Field	St	Type	Description
dest	Rec	string	The compute resource where the service is installed. You can alias this from more... (Eval)
process	Rec	string	The name of a process or service file, such as sqlsrvr.exe or httpd. Note: This f... (Eval)
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_requires_av	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
dest_should_timesync	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_update	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
process_name	Opt	string	The name of a process. (Rex)
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user	Opt	string	The user account the service is running as, such as System or httpdsvc.
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

All_Application_State.Ports

Object Ports · **Parent** All_Application_State · **Fields** 3 · **Tags** listening, port
Constraint tag=listening tag=port

Field	St	Type	Description
dest_port	Rec	number	Network ports communicated to by the process, such as 53. (Eval)
transport	Rec	string	The network ports listened to by the application process, such as tcp, udp, etc. (Eval)
transport_dest_port	Opt	string	Calculated as transport/dest_port, such as tcp/53. (Eval)

All_Application_State.Processes

Object Processes · **Parent** All_Application_State · **Fields** 4 · **Tags** process, report
Constraint tag=process tag=report

Field	St	Type	Description
cpu_load_mhz	Opt	number	CPU Load in megahertz.
cpu_load_percent	Opt	number	CPU Load in percent.
cpu_time	Opt	string	CPU Time.
mem_used	Opt	number	Memory used in bytes.

All_Application_State.Services

Object Services · **Parent** All_Application_State · **Fields** 4 · **Tags** service, report
Constraint tag=service tag=report

Field	St	Type	Description
service	Rec	string	The name of the service, such as SQL Server or Apache Web Server. Note: This fiel… (Eval)
service_id	Rec	string	A numeric indicator for a service. (Eval)
start_mode	Rec	string	The start mode for the service. (Eval)
status	Rec	string	The status of the service. (Eval)

Prescribed values
start_mode = disabled, manual, auto
status = critical, started, stopped, warning

Authentication

Authentication

Object Authentication · **Parent** BaseEvent · **Fields** 41 · **Tags** authentication
Constraint (`cim_Authentication_indexes`) tag=authentication NOT (action=success user=*$)

Field	St	Type	Description
action	Rec	string	The action performed on the resource. (Eval)
app	Rec	string	The application involved in the event, such as ssh, splunk, win:local. (Eval)
dest	Rec	string	The target involved in the authentication. You can alias this from more specific… (Eval)
src	Rec	string	The source involved in the authentication. In the case of endpoint protection aut… (Eval)
src_user	Rec	string	In privilege escalation events, src_user represents the user who initiated the pr… (Eval)
user	Rec	string	The name of the user involved in the event, or who initiated the event. For authe… (Eval)
authentication_method	Opt	string	The method used to authenticate the request such as SAML, FIDO, or MFA.
authentication_service	Opt	string	The service used to authenticate the request such as Okta, or ActiveDirectory
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
dest_nt_domain	Opt	string	The name of the Active Directory used by the authentication target, if applicable.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
duration	Opt	number	The amount of time for the completion of the authentication event, in seconds.
process	Opt	string	Full path and the name of the executable for the process that attempted the logon...
reason	Opt	string	The human-readable message associated with the authentication action (success or...
reason_id	Opt	string	The reason why logon failed. For example "0xC0000234".
response_time	Opt	number	The amount of time it took to receive a response in the authentication event, in...
result	Opt	string	The result of the authentication attempt for audittrailv2 sourcetypes. (Eval)
session_id	Opt	string	The unique identifier assigned to the login session.
signature	Opt	string	A human-readable signature name.
signature_id	Opt	string	The unique identifier or event code of the event signature.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_nt_domain	Opt	string	The name of the Active Directory used by the authentication source, if applicable.
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_id	Opt	string	The unique id of the user who initiated the privilege escalation. This field is u...
src_user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_role	Opt	string	The role of the user who initiated the privilege escalation. This field is unnece...
src_user_type	Opt	string	The type of the user who initiated the privilege escalation. This field is unnece...
tag	Opt	string	This automatically generated field is used to access tags from within data models...

Field	St	Type	Description
user_agent	Opt	string	The user agent through which the request was made, such as Mozilla/5.0 (Macintosh...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_id	Opt	string	The unique id of the user involved in the event. For authentication privilege esc...
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_role	Opt	string	The role of the user involved in the event, or who initiated the event. For authe...
user_type	Opt	string	The type of the user involved in the event or who initiated the event, such as IA...
vendor_account	Opt	string	The account that manages the user that initiated the request.

Prescribed values
action = success, failure, pending, error

Certificates

All_Certificates

Object All_Certificates · **Parent** BaseEvent · **Fields** 15 · **Tags** certificate
Constraint (`cim_Certificates_indexes`) tag=certificate

Field	St	Type	Description
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest	Opt	string	The target in the certificate management event.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	The category of the target, such as email_server or SOX-compliant. This field is...
dest_port	Opt	number	The port number of the target.
dest_priority	Opt	string	The priority of the target.
duration	Opt	number	The amount of time for the completion of the certificate management event, in sec...
response_time	Opt	number	The amount of time it took, in seconds, to receive a response in the certificate...

Field	St	Type	Description
src	Opt	string	The source involved in the certificate management event. You can alias this from...
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	The category of the certificate management source, such as email_server or SOX-co...
src_port	Opt	number	The port number of the source.
src_priority	Opt	string	The priority of the certificate management source.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
transport	Opt	string	The transport protocol of the Network Traffic involved with this certificate.

All_Certificates.SSL

Object SSL · **Parent** All_Certificates · **Fields** 32 · **Tags** ssl, tls
Constraint (tag=ssl OR tag=tls)

Field	St	Type	Description
ssl_end_time	Rec	timestamp	The expiry time of the certificate.
ssl_hash	Rec	string	The hash of the certificate. (Eval)
ssl_issuer	Rec	string	The certificate issuer's RFC2253 Distinguished Name. (Eval)
ssl_issuer_common_name	Rec	string	The certificate issuer's common name. (Eval)
ssl_issuer_email_domain	Rec	string	The domain name contained within the certificate issuer's email address. (Rex)
ssl_serial	Rec	string	The certificate's serial number.
ssl_start_time	Rec	timestamp	This is the start date and time for this certificate's validity.
ssl_subject	Rec	string	The certificate owner's RFC2253 Distinguished Name. (Eval)
ssl_subject_common_name	Rec	string	The certificate subject's common name. (Eval)
ssl_subject_email_domain	Rec	string	The domain name contained within the certificate subject's email address. (Rex)
ssl_engine	Opt	string	The name of the signature engine that created the certificate.

Field	St	Type	Description
ssl_is_valid	Opt	boolean	Indicator of whether the ssl certificate is valid or not. (Eval)
ssl_issuer_email	Opt	string	The certificate issuer's email address.
ssl_issuer_locality	Opt	string	The certificate issuer's locality.
ssl_issuer_organization	Opt	string	The certificate issuer's organization.
ssl_issuer_state	Opt	string	The certificate issuer's state of residence.
ssl_issuer_street	Opt	string	The certificate issuer's street address.
ssl_issuer_unit	Opt	string	The certificate issuer's organizational unit.
ssl_name	Opt	string	The name of the ssl certificate.
ssl_policies	Opt	string	The Object Identification Numbers of the certificate's policies in a comma separa…
ssl_publickey	Opt	string	The certificate's public key.
ssl_publickey_algorithm	Opt	string	The algorithm used to create the public key.
ssl_session_id	Opt	string	The session identifier for this certificate.
ssl_signature_algorithm	Opt	string	The algorithm used by the Certificate Authority to sign the certificate.
ssl_subject_email	Opt	string	The certificate owner's e-mail address.
ssl_subject_locality	Opt	string	The certificate owner's locality.
ssl_subject_organization	Opt	string	The certificate owner's organization.
ssl_subject_state	Opt	string	The certificate owner's state of residence.
ssl_subject_street	Opt	string	The certificate owner's street address.
ssl_subject_unit	Opt	string	The certificate owner's organizational unit.
ssl_validity_window	Opt	number	The length of time, in seconds, for which this certificate is valid. (Eval)
ssl_version	Opt	string	The ssl version of this certificate.

Prescribed values

ssl_is_valid = true, false, 1, 0

Change

All_Changes

Object All_Changes · **Parent** BaseEvent · **Fields** 32 · **Tags** change

Constraint (`cim_Change_indexes`) tag=change

Field	St	Type	Description
action	Rec	string	The action attempted on the resource, regardless of success or failure. (Eval)
change_type	Rec	string	The type of change, such as filesystem or AAA (authentication, authorization, and... (Eval)
command	Rec	string	The command that initiated the change. (Eval)
dest	Rec	string	The resource where change occurred. You can alias this from more specific fields... (Eval)
dvc	Rec	string	The device that reported the change, if applicable, such as a FIP or CIM server... (Eval)
object	Rec	string	Name of the affected object on the resource, such as a router interface, user acc... (Eval)
object_attrs	Rec	string	The attributes that were updated on the updated resource object, if applicable. (Eval)
object_category	Rec	string	Generic name for the class of the updated resource object. Expected values may be... (Eval)
object_id	Rec	string	The unique updated resource object ID as presented to the system, if applicable... (Eval)
object_path	Rec	string	The path of the modified resource object, if applicable, such as a file, director... (Eval)
result	Rec	string	The vendor-specific result of a change, or clarification of an action status. For... (Eval)
result_id	Rec	string	A result indicator for an action status. (Eval)
src	Rec	string	The resource where the change was originated. You can alias this from more specif... (Eval)
status	Rec	string	Status of the update. (Eval)
user	Rec	string	The user or entity performing the change. For account changes, this is the accoun... (Eval)
vendor_product	Rec	string	The vendor and product or service that detected the change. This field can be aut... (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user_agent	Opt	string	The user agent through which the request was made, such as Mozilla/5.0 (Macintosh...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_name	Opt	string	The user name of the user or entity performing the change. For account changes, t... (Eval)
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_type	Opt	string	The type of the user involved in the event or who initiated the event, such as IA...
vendor_account	Opt	string	The account associated with the change.
vendor_region	Opt	string	The data center region where the change occurred, such as us-west-2.

Prescribed values
action = acl_modified, cleared, created, deleted, modified, stopped, lockout, read, logoff, updated, started, restarted, unlocked
status = success, failure

All_Changes.Network_Changes

Object Network_Changes · **Parent** All_Changes · **Fields** 7 · **Tags** network
Constraint tag=network

Field	St	Type	Description
dest_ip_range	Opt	string	For network events, the outgoing traffic for a specific destination IP address ra...
dest_port_range	Opt	string	For network events, this field represents destination port or range. For example...
direction	Opt	string	For network events, this field represents whether the traffic is inbound or outbo...
protocol	Opt	string	This field represents the protocol for the network event rule.
rule_action	Opt	string	For network events, this field represents whether to allow or deny traffic.

Field	St	Type	Description
src_ip_range	Opt	string	For network events, this field represents the incoming traffic from a specific so…
src_port_range	Opt	string	For network events, this field represents source port or range. For example, 80 o…

All_Changes.Account_Management

Object Account_Management · **Parent** All_Changes · **Fields** 8 · **Tags** account
Constraint tag=account

Field	St	Type	Description
dest_nt_domain	Rec	string	The NT domain of the destination, if applicable. (Eval)
src_nt_domain	Rec	string	The NT domain of the source, if applicable. (Eval)
src_user	Rec	string	For account changes, the user or entity performing the change. (Eval)
src_user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_name	Opt	string	For account changes, the user name of the user or entity performing the change. (Eval)
src_user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_type	Opt	string	For account management events, this should represent the type of the user changed…

All_Changes.Instance_Changes

Object Instance_Changes · **Parent** All_Changes · **Fields** 2 · **Tags** instance
Constraint tag=instance

Field	St	Type	Description
image_id	Rec	string	For create instance events, this field represents the image ID used for creating… (Eval)
instance_type	Rec	string	For create instance events, this field represents the type of instance to build s… (Eval)

Change_Analysis

All_Changes

Object All_Changes · **Parent** BaseEvent · **Fields** 26 · **Tags** change
Constraint (`cim_Change_Analysis_indexes`) tag=change

Field	St	Type	Description
action	Rec	string	The action performed on the resource. (Eval)
change_type	Rec	string	The type of change, such as filesystem or AAA (authentication, authorization, and... (Eval)
command	Rec	string	The command that initiated the change. (Eval)
dest	Rec	string	The resource where change occurred. You can alias this from more specific fields... (Eval)
dvc	Rec	string	The device that reported the change, if applicable, such as a FIP or CIM server... (Eval)
object	Rec	string	Name of the affected object on the resource, such as a router interface, user acc... (Eval)
object_attrs	Rec	string	The attributes that were updated on the updated resource object, if applicable. (Eval)
object_category	Rec	string	Generic name for the class of the updated resource object. Expected values may be... (Eval)
object_id	Rec	string	The unique updated resource object ID as presented to the system, if applicable... (Eval)
object_path	Rec	string	The path of the modified resource object, if applicable, such as a file, director... (Eval)
result	Rec	string	The vendor-specific result of a change, or clarification of an action status. For... (Eval)
result_id	Rec	string	A result indicator for an action status. (Eval)
src	Rec	string	The resource where the change was originated. You can alias this from more specif... (Eval)
status	Rec	string	Status of the update. (Eval)
user	Rec	string	The user or entity performing the change. For account changes, this is the accoun... (Eval)
vendor_product	Rec	string	The vendor and product or service that detected the change. This field can be aut... (Eval)
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values
action = acl_modified, cleared, created, deleted, modified, read, stopped, updated
change_type = restart
object_category = directory, file, group, registry, user
result = lockout
status = success, failure

Endpoint_Changes.Filesystem_Changes

Object Filesystem_Changes · **Parent** Endpoint_Changes · **Fields** 8
Constraint (object_category=file OR object_category=directory)

Field	St	Type	Description
file_access_time	Rec	timestamp	The time the file (the object of the event) was accessed. (Eval)
file_acl	Rec	string	Access controls associated with the file affected by the event. (Eval)
file_create_time	Rec	timestamp	The time the file (the object of the event) was created. (Eval)
file_hash	Rec	string	A cryptographic identifier assigned to the file object affected by the event. (Eval)
file_modify_time	Rec	timestamp	The time the file (the object of the event) was altered. (Eval)
file_name	Rec	string	The name of the file that is the object of the event (without location informatio... (Eval)
file_path	Rec	string	The location of the file that is the object of the event, in local file and direc... (Eval)
file_size	Rec	number	The size of the file that is the object of the event, in kilobytes. (Eval)

All_Changes.Account_Management

Object Account_Management · **Parent** All_Changes · **Fields** 6 · **Tags** account
Constraint tag=account

Field	St	Type	Description
dest_nt_domain	Rec	string	The NT domain of the destination, if applicable. (Eval)

Field	St	Type	Description
src_nt_domain	Rec	string	The NT domain of the source, if applicable. (Eval)
src_user	Rec	string	For account changes, the user or entity performing the change. (Eval)
src_user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Compute_Inventory

All_Inventory

Object All_Inventory · **Parent** BaseEvent · **Fields** 14 · **Tags** inventory, cpu, memory, network, storage, system, version, user, virtual
Constraint (`cim_Compute_Inventory_indexes`) tag=inventory (tag=cpu OR tag=memory OR tag=network OR tag=storage OR (tag=system tag=version) OR tag=user OR tag=virtual)

Field	St	Type	Description
dest	Rec	string	The system where the data originated, the source of the event. You can alias this... (Eval)
vendor_product	Rec	string	The vendor and product name of the resource, such as Cisco Catalyst 3850. This fi... (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
description	Opt	string	The description of the inventory system.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	The priority of the system where the data originated.
enabled	Opt	boolean	Indicates whether the resource is enabled or disabled.
family	Opt	string	The product family of the resource, such as 686_64 or RISC.
hypervisor_id	Opt	string	The hypervisor identifier, if applicable.
serial	Opt	string	The serial number of the resource.
status	Opt	string	The current reported state of the resource.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
version	Opt	string	The version of a computer resource, such as 2008r2 or 3.0.0.

All_Inventory.CPU

Object `CPU` · **Parent** `All_Inventory` · **Fields** 3 · **Tags** `cpu`
Constraint `tag=cpu`

Field	St	Type	Description
`cpu_cores`	Rec	number	The number of CPU cores reported by the resource (total, not per CPU).
`cpu_count`	Rec	number	The number of CPUs reported by the resource.
`cpu_mhz`	Rec	number	The maximum speed of the CPU reported by the resource (in megahertz).

`All_Inventory.Memory`

Object `Memory` · **Parent** `All_Inventory` · **Fields** 1 · **Tags** `memory`
Constraint `tag=memory`

Field	St	Type	Description
`mem`	Rec	number	The total amount of memory installed in or allocated to the resource, in megabyte…

`All_Inventory.Network`

Object `Network` · **Parent** `All_Inventory` · **Fields** 12 · **Tags** `network`
Constraint `tag=network`

Field	St	Type	Description
`dns`	Rec	string	The domain name server for the resource.
`interface`	Rec	string	The network interfaces of the computing resource, such as eth0, eth1 or Wired Eth…
`ip`	Rec	string	The network addresses of the computing resource, such as 192.168.1.1 or E80:0000:…
`mac`	Rec	string	A MAC (media access control) address associated with the resource, such as 06:10:…
`name`	Rec	string	A name field provided in some data sources.
`dest_ip`	Opt	string	The IP address for the system that the data is going to.
`inline_nat`	Opt	string	Identifies whether the resource is a network address translation pool.
`lb_method`	Opt	string	The load balancing method used by the computing resource such as method, round ro…
`node`	Opt	string	Represents a node hit.
`node_port`	Opt	number	The number of the destination port on the server that you requested from.
`src_ip`	Opt	string	The IP address for the system from which the data originates.

Field	St	Type	Description
vip_port	Opt	number	The port number for the virtual IP address (VIP). A VIP allows multiple MACs to u…

All_Inventory.Storage

Object Storage · **Parent** All_Inventory · **Fields** 14 · **Tags** storage
Constraint tag=storage

Field	St	Type	Description
mount	Rec	string	The path at which a storage resource is mounted.
storage	Rec	number	The amount of storage capacity allocated to the resource, in megabytes.
array	Opt	string	The array that the storage resource is a member of, if applicable.
blocksize	Opt	number	The block size used by the storage resource, in kilobytes.
cluster	Opt	string	The index cluster that the resource is a member of, if applicable.
fd_max	Opt	number	The maximum number of file descriptors available.
latency	Opt	number	The latency reported by the resource, in milliseconds.
parent	Opt	string	A higher level object that this resource is owned by, if applicable.
read_blocks	Opt	number	The maximum possible number of blocks read per second during a polling period.
read_latency	Opt	number	For a polling period, the average amount of time elapsed until a read request is…
read_ops	Opt	number	The total number of read operations in the polling period.
write_blocks	Opt	number	The maximum possible number of blocks written per second during a polling period.
write_latency	Opt	number	For a polling period, the average amount of time elapsed until a write request is…
write_ops	Opt	number	The total number of write operations in the polling period.

All_Inventory.OS

Object OS · **Parent** All_Inventory · **Fields** 1 · **Tags** system, version
Constraint tag=system tag=version

Field	St	Type	Description
os	Rec	string	The operating system of the resource, such as Microsoft Windows Server 2008r2. Th… (Eval)

All_Inventory.User

Object User · **Parent** All_Inventory · **Fields** 8 · **Tags** user
Constraint tag=user

Field	St	Type	Description
interactive	Rec	boolean	Indicates whether a locally defined account on a resource can be interactively lo... (Eval)
password	Rec	string	Displays the stored password(s) for a locally defined account, if it has any. For... (Eval)
user	Rec	string	The full name of a locally defined account. (Eval)
shell	Opt	string	Indicates the shell program used by a locally defined account.
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_id	Opt	number	The user identification for a locally defined account.
user_priority	Opt	string	The priority of a locally-defined account.

All_Inventory.Virtual_OS

Object Virtual_OS · **Parent** All_Inventory · **Fields** 1 · **Tags** virtual
Constraint tag=virtual

Field	St	Type	Description
hypervisor	Rec	string	The hypervisor parent of a virtual guest OS.

Virtual_OS.Snapshot

Object Snapshot · **Parent** Virtual_OS · **Fields** 3 · **Tags** snapshot
Constraint tag=snapshot

Field	St	Type	Description
size	Rec	number	The snapshot file size, in megabytes.
snapshot	Rec	string	The name of a snapshot file.
time	Opt	timestamp	The time at which the snapshot was taken.

DLP

DLP_Incidents

Object DLP_Incidents · **Parent** BaseEvent · **Fields** 37 · **Tags** dlp, incident
Constraint (`cim_DLP_indexes`) tag=dlp tag=incident

Field	St	Type	Description
action	Rec	string	The action taken by the DLP device. (Eval)
category	Rec	string	The category of the DLP event. (Eval)
dest	Rec	string	The target of the DLP event. (Eval)
dlp_type	Rec	string	The type of DLP system that generated the event. (Eval)
dvc	Rec	string	The device that reported the DLP event. (Eval)
object	Rec	string	The name of the affected object. (Eval)
object_category	Rec	string	The category of the affected object. (Eval)
object_path	Rec	string	The path of the affected object. (Eval)
severity	Rec	string	The severity of the DLP event. (Eval)
signature	Rec	string	The name of the DLP event. (Eval)
src	Rec	string	The source of the DLP event. (Eval)
src_user	Rec	string	The source user of the DLP event. (Eval)
user	Rec	string	The target user of the DLP event. (Eval)
vendor_product	Rec	string	The vendor and product name of the DLP system. (Eval)
app	Opt	string	The application involved in the event.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_zone	Opt	string	The zone of the DLP target.
dvc_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_zone	Opt	string	The zone of the DLP device.
severity_id	Opt	string	The numeric or vendor specific severity indicator corresponding to the event seve…
signature_id	Opt	string	The unique identifier or event code of the event signature.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
src_user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_zone	Opt	string	The zone of the DLP source.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Data_Access

Data_Access

Object Data_Access · **Parent** BaseEvent · **Fields** 41 · **Tags** data, access
Constraint (`cim_Data_Access_indexes`) tag=data tag=access

Field	St	Type	Description
action	Rec	string	The data access action taken by the user. (Eval)
app	Rec	string	The system, service, or application that generated the data access event. Example... (Eval)
dest	Rec	string	The destination where the data resides or where it is being accessed, such as the... (Eval)
object	Rec	string	Resource object name on which the action was performed by a user. (Eval)
object_attrs	Rec	string	The attributes that were updated on the updated resource object, if applicable. (Eval)
object_category	Rec	string	Generic name for the class of the updated resource object. Expected values may be... (Eval)
object_id	Rec	string	The unique updated resource object ID as presented to the system, if applicable... (Eval)
object_size	Rec	string	The size of the modified resource object. (Eval)
signature	Rec	string	A human-readable signature name.
src	Rec	string	The endpoint client host. (Eval)

Field	St	Type	Description
user	Rec	string	The user involved in the event, or who initiated the event. (Eval)
user_name	Rec	string	The user name of the user or entity performing the change. For account changes, t… (Eval)
vendor_account	Rec	string	The account that manages the user that initiated the request. (Eval)
vendor_product	Rec	string	The vendor and product name of the vendor. (Eval)
application_id	Opt	string	Application ID of the user
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_name	Opt	string	Name of the destination as defined by the Vendor.
dest_type	Opt	string	The type of the destination object, such as 'instance', 'storage', 'firewall', 'p…
dest_url	Opt	string	Url of the product, application or object.
dvc	Opt	string	The device that reported the data access event.
dvc_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
email	Opt	string	The email address of the user involved in the event, or who initiated the event.
object_path	Opt	string	The path of the modified resource object, if applicable, such as a file, director…
owner	Opt	string	Resource owner.
owner_email	Opt	string	Email of the resource owner.
owner_id	Opt	string	ID of the owner as defined by the vendor.
parent_object	Opt	string	Parent of the object name on which the action was performed by a user.
parent_object_category	Opt	string	Object category of the parent object on which action was performed by a user.
parent_object_id	Opt	string	Object id of the parent object on which the action was performed by a user.
signature_id	Opt	string	The unique identifier or event code of the event signature.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_agent	Opt	string	The user agent through which the request was made, such as Mozilla/5.0 (Macintosh…

Field	St	Type	Description
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_email	Opt	string	The email address of the user involved in the event, or who initiated the event.
user_group	Opt	string	The group of the user involved in the event, or who initiated the event.
user_id	Opt	string	The unique id of the user involved in the event. For authentication privilege esc…
user_role	Opt	string	The role of the user involved in the event, or who initiated the event.
user_type	Opt	string	The type of the user involved in the event or who initiated the event, such as IA…
vendor_product_id	Opt	string	The vendor and product name ID as defined by the vendor.
vendor_region	Opt	string	The data center region where the change occurred, such as us-west-2.

Prescribed values
action = accepted, commented, copied, created, deleted, disabled, downloaded, enabled, forwarded, granted, invited, locked, modified, moved, read, restarted, revoked, shared, started, stopped, uncommented, undeleted, unlocked, unshared, uploaded
object_category = collaboration, file, folder, comment, task, note

---

Databases

All_Databases

Object All_Databases · **Parent** BaseEvent · **Fields** 18 · **Tags** database
Constraint (`cim_Databases_indexes`) tag=database

Field	St	Type	Description
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest	Opt	string	The destination of the database event. You can alias this from more specific fiel…
dest_bunit	Opt	string	The business unit of the destination.
dest_category	Opt	string	The category of the destination.
dest_priority	Opt	string	The priority of the destination.
duration	Opt	number	The amount of time for the completion of the database event, in seconds.

Field	St	Type	Description
object	Opt	string	The name of the database object.
response_time	Opt	number	The amount of time it took to receive a response in the database event, in second…
src	Opt	string	The source of the database event. You can alias this from more specific fields, s…
src_bunit	Opt	string	The business unit of the source.
src_category	Opt	string	The category of the source.
src_priority	Opt	string	The priority of the source.
tag	Opt	string	This automatically generated field is used to access tags from within data models…
user	Opt	string	Name of the database process user.
user_bunit	Opt	string	The business unit of the user.
user_category	Opt	string	The category associated with the user.
user_priority	Opt	string	The priority of the user.
vendor_product	Opt	string	The vendor and product name of the database system. This field can be automatical… (Eval)

All_Databases.Database_Instance

Object Database_Instance · **Parent** All_Databases · **Fields** 4 · **Tags** instance
Constraint tag=instance

Field	St	Type	Description
instance_name	Opt	string	The name of the database instance.
instance_version	Opt	string	The version of the database instance.
process_limit	Opt	number	The maximum number of processes that the database instance can handle.
session_limit	Opt	number	The maximum number of sessions that the database instance can handle.

Database_Instance.Instance_Stats

Object Instance_Stats · **Parent** Database_Instance · **Fields** 19 · **Tags** stats
Constraint tag=stats

Field	St	Type	Description
availability	Opt	string	The status of the database server.

Field	St	Type	Description
avg_executions	Opt	number	The average number of executions for the database instance.
dump_area_used	Opt	string	The amount of the database dump area that has been used.
instance_reads	Opt	number	The total number of reads for the database instance.
instance_writes	Opt	number	The total number of writes for the database instance.
number_of_users	Opt	number	The total number of users for the database instance.
processes	Opt	number	The number of processes currently running for the database instance.
sessions	Opt	number	The total number of sessions currently in use for the database instance.
sga_buffer_cache_size	Opt	number	The total size of the buffer cache for the database instance, in bytes.
sga_buffer_hit_limit	Opt	number	The maximum number of buffers that can be hit in the database instance without fi…
sga_data_dict_hit_ratio	Opt	number	The hit-to-miss ratio for the database instance's data dictionary.
sga_fixed_area_size	Opt	number	The size of the fixed area (also referred to as the fixed SGA) for the database i…
sga_free_memory	Opt	number	The total amount of free memory in the database instance SGA, in bytes.
sga_library_cache_size	Opt	number	The total library cache size for the database instance, in bytes.
sga_redo_log_buffer_size	Opt	number	The total size of the redo log buffer for the database instance, in bytes.
sga_shared_pool_size	Opt	number	The total size of the shared pool for this database instance, in bytes.
sga_sql_area_size	Opt	number	The total size of the SQL area for this database instance, in bytes.
start_time	Opt	timestamp	The total amount of uptime for the database instance.
tablespace_used	Opt	string	The total amount of tablespace used for the database instance, in bytes.

Prescribed values

availability = Available, Not Available

Database_Instance.Session_Info

Object Session_Info · **Parent** Database_Instance · **Fields** 15 · **Tags** session
Constraint tag=session

Field	St	Type	Description
buffer_cache_hit_ratio	Opt	number	The percentage of logical reads from the buffer during the session (1-physical re…
commits	Opt	number	The number of commits per second performed by the user associated with the sessio…
cpu_used	Opt	number	The number of CPU centiseconds used by the session. Divide this value by 100 to g…
cursor	Opt	number	The number of the cursor currently in use by the session.
elapsed_time	Opt	number	The total amount of time elapsed since the user started the session by logging in…
logical_reads	Opt	number	The total number of consistent gets and database block gets performed during the…
machine	Opt	string	The name of the logical host associated with the database instance.
memory_sorts	Opt	number	The total number of memory sorts performed during the session.
physical_reads	Opt	number	The total number of physical reads performed during the session.
seconds_in_wait	Opt	number	The seconds_in_wait depends on the value of wait_time. If wait_time = 0, seconds_…
session_id	Opt	string	The unique id that identifies the session.
session_status	Opt	string	The current status of the session.
table_scans	Opt	number	Number of table scans performed during the session.
wait_state	Opt	string	Provides the current wait state for the session. Can indicate that the session is…
wait_time	Opt	number	When wait_time = 0, the session is waiting. When wait_time has a nonzero value, i…

Prescribed values
session_status = Online, Offline
wait_state = WAITING, WAITED UNKNOWN, WAITED SHORT TIME, WAITED KNOWN TIME

Database_Instance.Lock_Info

Object `Lock_Info` · **Parent** `Database_Instance` · **Fields** 7 · **Tags** `lock`
Constraint `tag=lock`

Field	St	Type	Description
`last_call_minute`	Opt	number	Represents the amount of time elapsed since the session_status changed to its cur…
`lock_mode`	Opt	string	The mode of the lock on the object.
`lock_session_id`	Opt	string	The session identifier of the locked object.
`logon_time`	Opt	number	The database logon time for the session.
`obj_name`	Opt	string	The name of the locked object.
`os_pid`	Opt	string	The process identifier for the operating system.
`serial_num`	Opt	string	The serial number of the object.

`All_Databases.Database_Query`

Object `Database_Query` · **Parent** `All_Databases` · **Fields** 4 · **Tags** `query`
Constraint `tag=query`

Field	St	Type	Description
`query`	Opt	string	The full database query.
`query_id`	Opt	string	The identifier for the database query.
`query_time`	Opt	timestamp	The time the system initiated the database query.
`records_affected`	Opt	number	The number of records affected by the database query.

`Database_Query.Tablespace`

Object `Tablespace` · **Parent** `Database_Query` · **Fields** 5 · **Tags** `tablespace`
Constraint `tag=tablespace`

Field	St	Type	Description
`free_bytes`	Opt	number	The total amount of free space in the tablespace, in bytes.
`tablespace_name`	Opt	string	The name of the tablespace.
`tablespace_reads`	Opt	number	The number of tablespace reads carried out by the query.
`tablespace_status`	Opt	string	The status of the tablespace.
`tablespace_writes`	Opt	number	The number of tablespace writes carried out by the query.

Prescribed values
`tablespace_status` = Offline, Online, Read Only

`Database_Query.Query_Stats`

Object `Query_Stats` · **Parent** `Database_Query` · **Fields** 4 · **Tags** `stats`
Constraint `tag=stats`

Field	St	Type	Description
`indexes_hit`	Opt	string	The names of the indexes hit by the database query.
`query_plan_hit`	Opt	string	The name of the query plan hit by the query.
`stored_procedures_called`	Opt	string	The names of the stored procedures called by the query.
`tables_hit`	Opt	string	The names of the tables hit by the query.

Email

`All_Email`

Object `All_Email` · **Parent** `BaseEvent` · **Fields** 49 · **Tags** `email`
Constraint `(`cim_Email_indexes`) tag=email`

Field	St	Type	Description
`action`	Rec	string	Action taken by the reporting device. (Eval)
`dest`	Rec	string	The endpoint system to which the message was delivered. You can alias this from m… (Eval)
`recipient`	Rec	string	The recipient email addresses. (Eval)
`recipient_domain`	Rec	string	The domain name contained within the recipient email addresses. (Rex)
`src`	Rec	string	The system that sent the message. You can alias this from more specific fields, s… (Eval)
`src_user`	Rec	string	The email address of the message sender. (Eval)
`src_user_domain`	Rec	string	The domain name contained within the email address of the message sender. (Rex)
`vendor_product`	Rec	string	The vendor and product of the email server used for the email transaction. This f… (Eval)
`cim_entity_zone`	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
`delay`	Opt	number	Total sending delay in milliseconds.
`dest_bunit`	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
`dest_category`	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
`dest_priority`	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
`duration`	Opt	number	The amount of time for the completion of the messaging event, in seconds.

Field	St	Type	Description
file_hash	Opt	string	The hashes for the files attached to the message, if any exist. Deprecated in fav…
file_hashes	Opt	string	The hashes for the files attached to the message, if any exist.
file_name	Opt	string	The names of the files attached to the message, if any exist.
file_size	Opt	number	The size of the files attached the message, in bytes.
internal_message_id	Opt	string	Host-specific unique message identifier (such as aid in sendmail, IMI in Domino…
message_id	Opt	string	The globally-unique message identifier.
message_info	Opt	string	Additional information about the message.
orig_dest	Opt	string	The original destination host of the message. The message destination host can ch…
orig_recipient	Opt	string	The original recipient of the message. The message recipient can change when the…
orig_src	Opt	string	The original source of the message.
process	Opt	string	The name of the email executable that carries out the message transaction, such a…
process_id	Opt	number	The numeric identifier of the process invoked to send the message.
protocol	Opt	string	The email protocol involved, such as SMTP or RPC.
recipient_count	Opt	number	The total number of intended message recipients. (Eval)
recipient_status	Opt	string	The recipient delivery status, if available.
response_time	Opt	number	The amount of time it took to receive a response in the messaging event, in secon…
retries	Opt	number	The number of times that the message was automatically resent because it was boun…
return_addr	Opt	string	The return address for the message.
size	Opt	number	The size of the message, in bytes.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
src_user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
status_code	Opt	string	The status code associated with the message.
subject	Opt	string	The subject of the message.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
url	Opt	string	The URL associated with the message, if any.
user	Opt	string	The user context for the process. This is not the email address for the sender. F...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
xdelay	Opt	string	Extended delay information for the message transaction. May contain details of al...
xref	Opt	string	An external reference. Can contain message IDs or recipient addresses from relate...

Prescribed values
action = delivered, blocked, quarantined, deleted
protocol = smtp, imap, pop3, mapi

All_Email.Filtering

Object Filtering · **Parent** All_Email · **Fields** 5 · **Tags** filter
Constraint tag=filter

Field	St	Type	Description
signature	Rec	string	The name of the filter applied.
filter_action	Opt	string	The status produced by the filter, such as 'accepted', 'rejected', or 'dropped'.
filter_score	Opt	number	Numeric indicator assigned to specific emails by an email filter.
signature_extra	Opt	string	Any additional information about the filter.
signature_id	Opt	string	The id associated with the filter name.

Endpoint

Ports

Object `Ports` · **Parent** `BaseSearch` · **Fields** 33
Constraint *(none — derived dataset; inherits parent)*

Field	St	Type	Description
`dest`	Rec	string	The endpoint for which the port is listening on. (Eval)
`dest_port`	Rec	number	Network port listening on the endpoint, such as 53.
`src`	Rec	string	The "remote" system connected to the listening port (if applicable). (Eval)
`src_port`	Rec	number	The "remote" port connected to the listening port (if applicable). (Eval)
`transport`	Rec	string	The network transport protocol associated with the listening port, such as tcp, u…
`user`	Rec	string	The user account associated with the listening port. (Eval)
`vendor_product`	Rec	string	The vendor and product name of the Endpoint solution that reported the event, suc… (Eval)
`_time`	Opt	timestamp	The event timestamp expressed in Unix time.
`cim_entity_zone`	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
`creation_time`	Opt	timestamp	The time at which the network port started listening on the endpoint.
`dest_bunit`	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
`dest_category`	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
`dest_priority`	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
`dest_requires_av`	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
`dest_should_timesync`	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
`dest_should_update`	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
`host`	Opt	string	The host associated with the search.
`process_guid`	Opt	string	The globally unique identifier of the process assigned by the vendor_product.
`process_id`	Opt	string	The numeric identifier of the process assigned by the operating system.

Field	St	Type	Description
source	Opt	string	The source associated with the search.
sourcetype	Opt	string	The source type associated with the search.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_requires_av	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
src_should_timesync	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
src_should_update	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
state	Opt	string	The status of the listening port, such as established, listening, etc.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
transport_dest_port	Opt	string	Calculated as transport/dest_port, such as tcp/53.
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Processes

Object Processes · **Parent** BaseSearch · **Fields** 43
Constraint *(none — derived dataset; inherits parent)*

Field	St	Type	Description
dest	Rec	string	The endpoint for which the process was spawned. (Eval)
loaded_file	Rec	string	The file that was loaded. (Eval)
original_file_name	Rec	string	Original name of the file, not including path. Sometimes this field is similar to... (Eval)

Field	St	Type	Description
parent_process	Rec	string	The full command string of the parent process (Eval)
parent_process_name	Rec	string	The friendly name of the parent process, such as notepad.exe. (Eval)
process	Rec	string	The full command string of the spawned process. Such as C:\WINDOWS\system32\cmd.e... (Eval)
process_name	Rec	string	The friendly name of the process, such as notepad.exe. (Eval)
user	Rec	string	The current user linked to the running process. (Eval)
vendor_product	Rec	string	The vendor and product name of the Endpoint solution that reported the event, suc... (Eval)
_time	Opt	timestamp	The event timestamp expressed in Unix time.
action	Opt	string	The action taken by the endpoint.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
cpu_load_percent	Opt	number	CPU load consumed by the process (in percent).
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_is_expected	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_requires_av	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_timesync	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_update	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
host	Opt	string	The host associated with the search.
mem_used	Opt	number	Memory used by the process (in bytes).
os	Opt	string	The operating system of the resource, such as Microsoft Windows Server 2008r2.

Field	St	Type	Description
parent_process_exec	Opt	string	The executable name of the parent process.
parent_process_guid	Opt	string	The globally unique identifier of the parent process assigned by the vendor_produ…
parent_process_hash	Opt	string	The digest(s) of the parent process, such as , , etc.
parent_process_id	Opt	number	The numeric identifier of the parent process assigned by the operating system.
parent_process_path	Opt	string	The file path of the parent process, such as C:\Windows\System32\notepad.exe.
parent_user	Opt	string	The original user under which the process was created. This field is extracted fo… (Eval)
process_current_directory	Opt	string	The current working directory used to spawn the process.
process_exec	Opt	string	The executable name of the process.
process_guid	Opt	string	The globally unique identifier of the process assigned by the vendor_product.
process_hash	Opt	string	The digest(s) of the process, such as , , etc.
process_id	Opt	number	The numeric identifier of the process assigned by the operating system.
process_integrity_level	Opt	string	The integrity level of the process.
process_path	Opt	string	The file path of the process, such as C:\Windows\System32\notepad.exe.
source	Opt	string	The source associated with the search.
sourcetype	Opt	string	The source type associated with the search.
tag	Opt	string	This automatically generated field is used to access tags from within data models…
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_id	Opt	string	The unique identifier of the user account which spawned the process.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values
`process_integrity_level` = protected process, system, high, medium high, medium, low, untrusted

Services

Object `Services` · **Parent** `BaseSearch` · **Fields** 37
Constraint *(none — derived dataset; inherits parent)*

Field	St	Type	Description
`dest`	Rec	string	The endpoint for which the service is installed. (Eval)
`service`	Rec	string	The full service name. (Eval)
`service_id`	Rec	string	The unique identifier of the service assigned by the operating system.. (Eval)
`service_name`	Rec	string	The friendly service name. (Eval)
`start_mode`	Rec	string	The start mode for the service. (Eval)
`status`	Rec	string	The status of the service. (Eval)
`user`	Rec	string	The user account associated with the service. (Eval)
`vendor_product`	Rec	string	The vendor and product name of the Endpoint solution that reported the event, suc... (Eval)
`_time`	Opt	timestamp	The event timestamp expressed in Unix time.
`cim_entity_zone`	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
`description`	Opt	string	The description of the service.
`dest_bunit`	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
`dest_category`	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
`dest_is_expected`	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
`dest_priority`	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
`dest_requires_av`	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
`dest_should_timesync`	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
dest_should_update	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
host	Opt	string	The host associated with the search.
process_guid	Opt	string	The globally unique identifier of the process assigned by the vendor_product.
process_id	Opt	string	The numeric identifier of the process assigned by the operating system.
service_dll	Opt	string	The dynamic link library associated with the service.
service_dll_hash	Opt	string	The digest(s) of the dynamic link library associated with the service, such as <m...
service_dll_path	Opt	string	The file path to the dynamic link library assocatied with the service, such as C:...
service_dll_signature_exists	Opt	boolean	Whether or not the dynamic link library associated with the service has a digital...
service_dll_signature_verified	Opt	boolean	Whether or not the dynamic link library associated with the service has had it's...
service_exec	Opt	string	The executable name of the service.
service_hash	Opt	string	The digest(s) of the service, such as , , etc.
service_path	Opt	string	The file path of the service, such as C:\WINDOWS\system32\svchost.exe.
service_signature_exists	Opt	boolean	Whether or not the service has a digitally signed signature.
service_signature_verified	Opt	boolean	Whether or not the service has had it's digitally signed signature verified.
source	Opt	string	The source associated with the search.
sourcetype	Opt	string	The source type associated with the search.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values
`start_mode` = disabled, manual, auto
`status` = critical, started, stopped, warning, installed

Filesystem

Object `Filesystem` · **Parent** `BaseSearch` · **Fields** 43
Constraint *(none — derived dataset; inherits parent)*

Field	St	Type	Description
action	Rec	string	The action performed on the resource. (Eval)
dest	Rec	string	The endpoint pertaining to the filesystem activity. (Eval)
file_access_time	Rec	timestamp	The time the file (the object of the event) was accessed.
file_acl	Rec	string	Access controls associated with the file affected by the event. (Eval)
file_create_time	Rec	timestamp	The time the file (the object of the event) was created.
file_hash	Rec	string	A cryptographic identifier assigned to the file object affected by the event. Dep… (Eval)
file_hashes	Rec	string	A cryptographic identifier assigned to the file object affected by the event. (Eval)
file_modify_time	Rec	timestamp	The time the file (the object of the event) was altered.
file_name	Rec	string	The name of the file, such as notepad.exe. (Eval)
file_path	Rec	string	The path of the file, such as C:\Windows\System32\notepad.exe. (Eval)
file_size	Rec	number	The size of the file that is the object of the event, in kilobytes. (Eval)
process	Rec	string	The full command string of the spawned process. Such as C:\WINDOWS\system32\cmd.e… (Eval)
process_name	Rec	string	The friendly name of the process, such as notepad.exe. (Eval)
user	Rec	string	The user account associated with the filesystem access. (Eval)
vendor_product	Rec	string	The vendor and product name of the Endpoint solution that reported the event, suc… (Eval)
_time	Opt	timestamp	The event timestamp expressed in Unix time.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_requires_av	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_timesync	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_update	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
host	Opt	string	The host associated with the search.
image	Opt	string	The binary file path or name that is tied to a process ID (PID) in events like pr…
parent_process	Opt	string	The full command string of the parent process (Eval)
parent_process_exec	Opt	string	The executable name of the parent process.
parent_process_guid	Opt	string	The globally unique identifier of the parent process assigned by the vendor_produ…
parent_process_hash	Opt	string	The digest(s) of the parent process, such as , , etc.
parent_process_id	Opt	number	The numeric identifier of the parent process assigned by the operating system.
parent_process_name	Opt	string	The friendly name of the parent process, such as notepad.exe. (Eval)
parent_process_path	Opt	string	The file path of the parent process, such as C:\Windows\System32\notepad.exe.
process_exec	Opt	string	The executable name of the process.
process_guid	Opt	string	The globally unique identifier of the process assigned by the vendor_product.
process_hash	Opt	string	The digest(s) of the process, such as , , etc.
process_id	Opt	string	The numeric identifier of the process assigned by the operating system.
process_path	Opt	string	The file path of the process, such as C:\Windows\System32\notepad.exe.

Field	St	Type	Description
source	Opt	string	The source associated with the search.
sourcetype	Opt	string	The source type associated with the search.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values
action = acl_modified, created, deleted, modified, read

Registry

Object Registry · **Parent** BaseSearch · **Fields** 42
Constraint *(none — derived dataset; inherits parent)*

Field	St	Type	Description
action	Rec	string	The action performed on the resource. (Eval)
dest	Rec	string	The endpoint pertaining to the registry events. (Eval)
process	Rec	string	The full command string of the spawned process. Such as C:\WINDOWS\system32\cmd.e... (Eval)
process_name	Rec	string	The friendly name of the process, such as notepad.exe. (Eval)
registry_key_name	Rec	string	The name of the registry key, such as PrinterDriverData. (Eval)
registry_path	Rec	string	The path to the registry value, such as \win\directory\directory2{676235CD-B656-... (Eval)
registry_value_data	Rec	string	The unaltered registry value. (Eval)
registry_value_name	Rec	string	The name of the registry value. (Eval)
registry_value_type	Rec	string	The type of the registry value. (Eval)
user	Rec	string	The user account associated with the registry access. (Eval)
vendor_product	Rec	string	The vendor and product name of the Endpoint solution that reported the event, suc... (Eval)

Field	St	Type	Description
_time	Opt	timestamp	The event timestamp expressed in Unix time.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_requires_av	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_timesync	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_update	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
host	Opt	string	The host associated with the search.
image	Opt	string	The binary file path or name that is tied to a process ID (PID) in events like pr...
parent_process	Opt	string	The full command string of the parent process (Eval)
parent_process_exec	Opt	string	The executable name of the parent process.
parent_process_guid	Opt	string	The globally unique identifier of the parent process assigned by the vendor_produ...
parent_process_hash	Opt	string	The digest(s) of the parent process, such as , , etc.
parent_process_id	Opt	number	The numeric identifier of the parent process assigned by the operating system.
parent_process_name	Opt	string	The friendly name of the parent process, such as notepad.exe. (Eval)
parent_process_path	Opt	string	The file path of the parent process, such as C:\Windows\System32\notepad.exe.
process_exec	Opt	string	The executable name of the process.
process_guid	Opt	string	The globally unique identifier of the process assigned by the vendor_product.
process_hash	Opt	string	The digest(s) of the process, such as , , etc.

Field	St	Type	Description
process_id	Opt	string	The numeric identifier of the process assigned by the operating system.
process_path	Opt	string	The file path of the process, such as C:\Windows\System32\notepad.exe.
registry_hive	Opt	string	The logical grouping of registry keys, subkeys, and values.
registry_value_text	Opt	string	The textual representation of registry_value_data (if applicable).
source	Opt	string	The source associated with the search.
sourcetype	Opt	string	The source type associated with the search.
status	Opt	string	The outcome of the registry action.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values

action = created, deleted, modified, read
registry_value_type = REG_BINARY, REG_DWORD, REG_DWORD_LITTLE_ENDIAN, REG_DWORD_BIG_ENDIAN, REG_EXPAND_SZ, REG_LINK, REG_MULTI_SZ, REG_NONE, REG_QWORD, REG_QWORD_LITTLE_ENDIAN, REG_SZ
registry_hive = HKEY_CURRENT_CONFIG, HKEY_CURRENT_USER, HKEY_LOCAL_MACHINE\SAM, HKEY_LOCAL_MACHINE\Security, HKEY_LOCAL_MACHINE\Software, HKEY_LOCAL_MACHINE\System, HKEY_USERS.DEFAULT
status = failure, success

Event_Signatures

Signatures

Object Signatures · **Parent** BaseEvent · **Fields** 9 · **Tags** track_event_signatures
Constraint (`cim_Event_Signatures_indexes`) tag=track_event_signatures (signature=* OR signature_id=*)

Field	St	Type	Description
vendor_product	Rec	string	The vendor and product name of the technology that reported the event, such as Ca... (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest	Opt	string	System affected by the signature.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
signature	Opt	string	The human readable event name.
signature_id	Opt	string	The event name identifier (as supplied by the vendor).
tag	Opt	string	This automatically generated field is used to access tags from within data models...

Interprocess_Messaging

All_Messaging

Object All_Messaging · **Parent** BaseEvent · **Fields** 35 · **Tags** messaging
Constraint (`cim_Interprocess_Messaging_indexes`) tag=messaging

Field	St	Type	Description
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest	Opt	string	The destination of the message. You can alias this from more specific fields, suc... (Eval)
dest_bunit	Opt	string	The business unit of the destination.
dest_category	Opt	string	The type of message destination.
dest_priority	Opt	string	The priority of the destination.
duration	Opt	number	The number of seconds from message call to message response. Can be derived by ge...
endpoint	Opt	string	The endpoint that the message accessed during the RPC (remote procedure call) tra...
endpoint_version	Opt	string	The version of the endpoint accessed during the RPC (remote procedure call) trans...
message	Opt	string	A command or reference that an RPC (remote procedure call) reads or responds to.

Field	St	Type	Description
message_consumed_time	Opt	timestamp	The time that the RPC (remote procedure call) read the message and was prepared t…
message_correlation_id	Opt	string	The message correlation identification value.
message_delivered_time	Opt	timestamp	The time that the message producer sent the message.
message_delivery_mode	Opt	string	The message delivery mode. Possible values depend on the type of message-oriented…
message_expiration_time	Opt	timestamp	The time that the message expired.
message_id	Opt	string	The message identification.
message_priority	Opt	string	The priority of the message. Important jobs that the message queue should answer…
message_properties	Opt	string	An arbitrary list of message properties. The set of properties displayed depends…
message_received_time	Opt	timestamp	The time that the message was received by a message-oriented middleware (MOM) sol…
message_redelivered	Opt	boolean	Indicates whether or not the message was redelivered.
message_reply_dest	Opt	string	The name of the destination for replies to the message.
message_type	Opt	string	The type of message, such as call or reply.
parameters	Opt	string	Arguments that have been passed to an endpoint by a REST call or something simila…
payload	Opt	string	The message payload.
payload_type	Opt	string	The type of payload in the message. The payload type can be text (such as json, x…
request_payload	Opt	string	The content of the message request.
request_payload_type	Opt	string	The type of payload in the message request. The payload type can be text (such as…
request_sent_time	Opt	timestamp	The time that the message request was sent.
response_code	Opt	string	The response status code sent by the receiving server. Ranges between 200 and 404.
response_payload_type	Opt	string	The type of payload in the message response. The payload type can be text (such a…
response_received_time	Opt	timestamp	The time that the message response was received.

Field	St	Type	Description
response_time	Opt	number	The amount of time it took to receive a response, in seconds.
return_message	Opt	string	The response status message sent by the message server.
rpc_protocol	Opt	string	The protocol that the message server uses for remote procedure calls (RPC). Possi…
status	Opt	boolean	The status of the message response.
tag	Opt	string	This automatically generated field is used to access tags from within data models…

Prescribed values

dest_category = queue, topic
status = pass, fail

Intrusion_Detection

IDS_Attacks

Object IDS_Attacks · **Parent** BaseEvent · **Fields** 36 · **Tags** ids, attack
Constraint (`cim_Intrusion_Detection_indexes`) tag=ids tag=attack

Field	St	Type	Description
category	Rec	string	The vendor-provided category of the triggered signature, such as spyware. Note: T… (Eval)
dest	Rec	string	The destination of the attack detected by the intrusion detection system (IDS). Y… (Eval)
dvc	Rec	string	The device that detected the intrusion event. You can alias this from more specif… (Eval)
ids_type	Rec	string	The type of IDS that generated the event. (Eval)
severity	Rec	string	The severity of the network protection event. Note: This field is a string. Use s… (Eval)
signature	Rec	string	The name of the intrusion detected on the client (the src), such as PlugAndPlay_B… (Eval)
src	Rec	string	The source involved in the attack detected by the IDS. You can alias this from mo… (Eval)
user	Rec	string	The user involved with the intrusion detection event. (Eval)
vendor_product	Rec	string	The vendor and product name of the IDS or IPS system that detected the vulnerabil… (Eval)

Field	St	Type	Description
action	Opt	string	The action taken by the intrusion detection system (IDS).
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_ip	Opt	string	The IP address of the destination.
dest_port	Opt	number	The destination port of the intrusion.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_type	Opt	string	The type of the destination object, such as 'instance', 'storage', 'firewall'.
dvc_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
file_hash	Opt	string	A cryptographic identifier assigned to the file object affected by the event. Dep…
file_hashes	Opt	string	A cryptographic identifier assigned to the file object affected by the event.
file_name	Opt	string	The name of the file, such as notepad.exe.
file_path	Opt	string	The path of the file, such as C:\Windows\System32\notepad.exe.
severity_id	Opt	string	The numeric or vendor specific severity indicator corresponding to the event seve…
signature_id	Opt	string	The unique identifier or event code of the event signature.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_ip	Opt	string	The ip address of the source.
src_port	Opt	number	The port number of the source.
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
tag	Opt	string	This automatically generated field is used to access tags from within data models…
transport	Opt	string	The OSI layer 4 (transport) protocol of the intrusion, in lower case.
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values

ids_type = network, host, application, wireless
severity = critical, high, medium, low, informational
action = allowed, blocked

JVM

JVM

Object JVM · **Parent** BaseEvent · **Fields** 3 · **Tags** jvm
Constraint (`cim_JVM_indexes`) tag=jvm

Field	St	Type	Description
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
jvm_description	Opt	string	A description field provided in some data sources.
tag	Opt	string	This automatically generated field is used to access tags from within data models...

JVM.Threading

Object Threading · **Parent** JVM · **Fields** 12 · **Tags** threading
Constraint tag=threading

Field	St	Type	Description
cm_enabled	Opt	boolean	Indicates whether thread contention monitoring is enabled.
cm_supported	Opt	boolean	Indicates whether the JVM supports thread contention monitoring.
cpu_time_enabled	Opt	boolean	Indicates whether thread CPU time measurement is enabled.
cpu_time_supported	Opt	boolean	Indicates whether the Java virtual machine supports CPU time measurement for the...
current_cpu_time	Opt	number	CPU-space time taken by the JVM, in seconds.
current_user_time	Opt	number	User-space time taken by the JVM, in seconds.
daemon_thread_count	Opt	number	The JVM's current daemon count.
omu_supported	Opt	boolean	Indicates whether the JVM supports monitoring of object monitor usage.
peak_thread_count	Opt	number	The JVM's peak thread count.

Field	St	Type	Description
synch_supported	Opt	boolean	Indicates whether the JVM supports monitoring of ownable synchronizer usage.
thread_count	Opt	number	The JVM's current thread count.
threads_started	Opt	number	The total number of threads started in the JVM.

Prescribed values
cm_enabled = true, false, 1, 0
cm_supported = true, false, 1, 0
cpu_time_enabled = true, false, 1, 0
cpu_time_supported = true, false, 1, 0
omu_supported = true, false, 1, 0
synch_supported = true, false, 1, 0

JVM.Runtime

Object Runtime · **Parent** JVM · **Fields** 5 · **Tags** runtime
Constraint tag=runtime

Field	St	Type	Description
process_name	Opt	string	Process name of the JVM process.
start_time	Opt	timestamp	Start time of the JVM process.
uptime	Opt	number	Uptime of the JVM process, in seconds.
vendor_product	Opt	string	The JVM product or service. This field can be automatically populated by the the… (Eval)
version	Opt	string	Version of the JVM.

JVM.OS

Object OS · **Parent** JVM · **Fields** 13 · **Tags** os
Constraint tag=os

Field	St	Type	Description
committed_memory	Opt	number	Amount of memory committed to the JVM, in bytes.
cpu_time	Opt	number	Amount of CPU time taken by the JVM, in seconds.
free_physical_memory	Opt	number	Amount of free physical memory remaining to the JVM, in bytes.
free_swap	Opt	number	Amount of free swap memory remaining to the JVM, in bytes.
max_file_descriptors	Opt	number	Maximum file descriptors available to the JVM.

Field	St	Type	Description
open_file_descriptors	Opt	number	Number of file descriptors opened by the JVM.
os	Opt	string	OS that the JVM is running on.
os_architecture	Opt	string	OS architecture that the JVM is running on.
os_version	Opt	string	OS version that the JVM is running on.
physical_memory	Opt	number	Physical memory available to the OS that the JVM is running on, in bytes.
swap_space	Opt	number	Swap memory space available to the OS that the JVM is running on, in bytes.
system_load	Opt	number	System load of the OS that the JVM is running on.
total_processors	Opt	number	Total processor cores available to the OS that the JVM is running on.

JVM.Compilation

Object Compilation · **Parent** JVM · **Fields** 1 · **Tags** compilation
Constraint tag=compilation

Field	St	Type	Description
compilation_time	Opt	number	Time taken by JIT compilation, in seconds.

JVM.Classloading

Object Classloading · **Parent** JVM · **Fields** 3 · **Tags** classloading
Constraint tag=classloading

Field	St	Type	Description
current_loaded	Opt	number	The current count of classes loaded in the JVM.
total_loaded	Opt	number	The total count of classes loaded in the JVM.
total_unloaded	Opt	number	The total count of classes unloaded from the JVM.

JVM.Memory

Object Memory · **Parent** JVM · **Fields** 9 · **Tags** memory
Constraint tag=memory

Field	St	Type	Description
heap_committed	Opt	number	Committed amount of heap memory used by the JVM, in bytes.
heap_initial	Opt	number	Initial amount of heap memory used by the JVM, in bytes.

Field	St	Type	Description
heap_max	Opt	number	Maximum amount of heap memory used by the JVM, in bytes.
heap_used	Opt	number	Heap memory used by the JVM, in bytes.
non_heap_committed	Opt	number	Committed amount of non-heap memory used by the JVM, in bytes.
non_heap_initial	Opt	number	Initial amount of non-heap memory used by the JVM, in bytes.
non_heap_max	Opt	number	Maximum amount of non-heap memory used by the JVM, in bytes.
non_heap_used	Opt	number	Non-heap memory used by the JVM, in bytes.
objects_pending	Opt	number	Number of objects pending in the JVM.

Malware

Malware_Attacks

Object Malware_Attacks · **Parent** BaseEvent · **Fields** 32 · **Tags** malware, attack
Constraint (`cim_Malware_indexes`) tag=malware tag=attack

Field	St	Type	Description
action	Rec	string	The action taken by the reporting device. (Eval)
category	Rec	string	The category of the malware event, such as keylogger or ad-supported program. Not… (Eval)
date	Rec	string	The date of the malware event. (Eval)
dest	Rec	string	The system that was affected by the malware event. You can alias this from more s… (Eval)
dest_nt_domain	Rec	string	The NT domain of the destination, if applicable. (Eval)
severity	Rec	string	The severity of the network protection event. Note: This field is a string. Use s… (Eval)
signature	Rec	string	The name of the malware infection detected on the client (the dest), such as Troj… (Eval)
user	Rec	string	The user involved in the malware event. (Eval)
vendor_product	Rec	string	The vendor and product name of the endpoint protection system, such as Symantec A… (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
dest_ip	Opt	string	The IP address of the destination.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_requires_av	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
file_hash	Opt	string	The hash of the file with suspected malware. Deprecated in favor of 'file_hashes'.
file_hashes	Opt	string	The hash of the file with suspected malware.
file_name	Opt	string	The name of the file with suspected malware.
file_path	Opt	string	The full file path of the file with suspected malware.
severity_id	Opt	string	The numeric or vendor specific severity indicator corresponding to the event seve…
signature_id	Opt	string	The unique identifier or event code of the event signature.
src	Opt	string	The source of the endpoint event, such as a DAT file relay server. You can alias…
src_bunit	Opt	string	The business unit of the source.
src_category	Opt	string	The category of the source.
src_ip	Opt	string	The ip address of the source.
src_priority	Opt	string	The priority of the source.
src_user	Opt	string	The reported sender of an email-based attack.
tag	Opt	string	This automatically generated field is used to access tags from within data models…
url	Opt	string	A URL containing more information about the vulnerability.
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values

action = allowed, blocked, deferred

severity = critical, high, medium, low, informational

Malware_Operations

Object Malware_Operations · **Parent** BaseSearch · **Fields** 13

Constraint *(none — derived dataset; inherits parent)*

Field	St	Type	Description
dest	Rec	string	The system where the malware operations event occurred. (Eval)
dest_nt_domain	Rec	string	The NT domain of the dest system, if applicable. (Eval)
product_version	Rec	string	The product version of the malware operations product.
signature_version	Rec	string	The version of the malware signature bundle in a signature update operations even…
vendor_product	Rec	string	The vendor product name of the malware operations product. (Eval)
_time	Opt	timestamp	The event timestamp expressed in Unix time.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_ip	Opt	string	The IP address of the destination.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_requires_av	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
tag	Opt	string	This automatically generated field is used to access tags from within data models…

Network_Resolution

DNS

Object DNS · **Parent** BaseEvent · **Fields** 32 · **Tags** network, resolution, dns
Constraint (`cim_Network_Resolution_indexes`) tag=network tag=resolution tag=dns

Field	St	Type	Description
answer	Rec	string	Resolved address for the query. (Eval)
dest	Rec	string	The destination of the network resolution event. You can alias this from more spe… (Eval)
message_type	Rec	string	Type of DNS message. (Eval)
query	Rec	string	The domain which needs to be resolved. Applies to messages of type 'Query'. (Eval)
reply_code	Rec	string	The return code for the response. For details, see the Domain Name System Paramet… (Lookup)

Field	St	Type	Description
reply_code_id	Rec	string	The numerical id or name of a return code. For details, see the Domain Name Syste... (Eval)
vendor_product	Rec	string	The vendor product name of the DNS server. The Splunk platform can derive this fi... (Eval)
additional_answer_count	Opt	number	Number of entries in the 'additional' section of the DNS message.
answer_count	Opt	number	Number of entries in the answer section of the DNS message. (Eval)
authority_answer_count	Opt	number	Number of entries in the 'authority' section of the DNS message.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	The business unit of the destination.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_ip	Opt	string	The IP address of the destination.
dest_port	Opt	number	The destination port number.
dest_priority	Opt	string	The priority of the destination, if applicable.
duration	Opt	number	The time taken by the network resolution event, in seconds.
name	Opt	string	The name of the DNS event.
query_count	Opt	number	Number of entries that appear in the 'Questions' section of the DNS query. (Eval)
query_type	Opt	string	Number of entries that appear in the 'Questions' section of the DNS query.
record_type	Opt	string	The DNS resource record type. For details, see the List of DNS record types on on...
response_time	Opt	number	The amount of time it took to receive a response in the network resolution event...
src	Opt	string	The source of the network resolution event. You can alias this from more specific...
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
src_ip	Opt	string	The ip address of the source.
src_port	Opt	number	The port number of the source.
src_priority	Opt	string	The priority of the source.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
transaction_id	Opt	number	The unique numerical transaction id of the network resolution event.
transport	Opt	string	The transport protocol used by the network resolution event.
ttl	Opt	number	The time-to-live of the network resolution event, in seconds.

Prescribed values
message_type = Query, Response
reply_code = No Error, Format Error, Server Failure, Non-Existent Domain, etc.
reply_code_id = 0, NoError, 1, FormErr, 2, ServFail, 3, NXDomain, etc.
query_type = Query, IQuery, Status, Notify, Update, A, MX, NS, PTR

Network_Sessions

All_Sessions

Object All_Sessions · **Parent** BaseEvent · **Fields** 27 · **Tags** network, session
Constraint (`cim_Network_Sessions_indexes`) tag=network tag=session

Field	St	Type	Description
dest_dns	Rec	string	The domain name system address of the destination for a network session event. (Eval)
dest_ip	Rec	string	The internal IP address allocated to the client initializing a network session. F... (Eval)
dest_mac	Rec	string	The internal MAC address of the network session client. For DHCP events, this is... (Eval)
dest_nt_host	Rec	string	The NetBIOS name of the client initializing a network session. (Eval)
dvc	Rec	string	The device that reported the session event. You can alias this from more specific... (Eval)
user	Rec	string	The user in a network session event, where applicable. For example, a VPN session... (Eval)

Field	St	Type	Description
vendor_product	Rec	string	The full name of the Dynamic Host Configuration Protocol (DHCP) or DNS server inv... (Eval)
action	Opt	string	The action taken by the reporting device.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	The business unit of the destination.
dest_category	Opt	string	The category of the destination.
dest_priority	Opt	string	The priority of the destination.
duration	Opt	number	The amount of time for the completion of the network session event, in seconds.
response_time	Opt	number	The amount of time it took to receive a response in the network session event, in...
signature	Opt	string	An indication of the type of network session event.
signature_id	Opt	string	The unique identifier or event code of the event signature.
src_bunit	Opt	string	The business unit of the source.
src_category	Opt	string	The category of the source.
src_dns	Opt	string	The external domain name of the client initializing a network session. Not applic...
src_ip	Opt	string	The IP address of the client initializing a network session. Not applicable for D...
src_mac	Opt	string	The MAC address of the client initializing a network session. Not applicable for...
src_nt_host	Opt	string	The NetBIOS name of the client initializing a network session. Not applicable for...
src_priority	Opt	string	The priority of the source.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user_bunit	Opt	string	The business unit associated with the user.
user_category	Opt	string	The category of the user.
user_priority	Opt	string	The priority of the user.

Prescribed values

action = started, blocked, ended

All_Sessions.DHCP

Object `DHCP` · **Parent** `All_Sessions` · **Fields** 2 · **Tags** `dhcp`
Constraint `tag=dhcp`

Field	St	Type	Description
`lease_duration`	Opt	number	The duration of the Dynamic Host Configuration Protocol (DHCP) lease, in seconds.
`lease_scope`	Opt	string	The consecutive range of possible IP addresses that the Dynamic Host Configuratio…

Network_Traffic

`All_Traffic`

Object `All_Traffic` · **Parent** `BaseEvent` · **Fields** 66 · **Tags** `network`, `communicate`
Constraint `(`cim_Network_Traffic_indexes`) tag=network tag=communicate`

Field	St	Type	Description
`action`	Rec	string	The action taken by the network device. (Eval)
`bytes`	Rec	number	Total count of bytes handled by this device/interface (bytes_in + bytes_out). (Eval)
`bytes_in`	Rec	number	How many bytes this device/interface received. (Eval)
`bytes_out`	Rec	number	How many bytes this device/interface transmitted. (Eval)
`dest`	Rec	string	The destination of the network traffic (the remote host). You can alias this from… (Eval)
`dest_port`	Rec	number	The destination port of the network traffic. Note: Do not translate the value of… (Eval)
`dvc`	Rec	string	The device that reported the traffic event. You can alias this from more specific… (Eval)
`rule`	Rec	string	The rule name that defines the action that was taken in the event. Note: Use rule… (Eval)
`src`	Rec	string	The source of the network traffic (the client requesting the connection). You can… (Eval)
`src_port`	Rec	number	The source port of the network traffic. Note: Do not translate the value of this… (Eval)
`transport`	Rec	string	The OSI layer 4 (transport) protocol of the traffic observed, in lower case. (Eval)
`user`	Rec	string	The user that requested the traffic flow. (Eval)
`vendor_product`	Rec	string	The vendor and product of the device generating the network event. This field can… (Eval)

Field	St	Type	Description
app	Opt	string	The application protocol of the traffic.
channel	Opt	number	The 802.11 channel used by a wireless network.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_interface	Opt	string	The interface that is listening remotely or receiving packets locally. Can also b…
dest_ip	Opt	string	The IP address of the destination.
dest_mac	Opt	string	The destination TCP/IP layer 2 Media Access Control (MAC) address of a packet's d…
dest_priority	Opt	string	The destination priority, if applicable.
dest_translated_ip	Opt	string	The NATed IPv4 or IPv6 address to which a packet has been sent.
dest_translated_port	Opt	number	The NATed port to which a packet has been sent. Note: Do not translate the values…
dest_zone	Opt	string	The network zone of the destination.
direction	Opt	string	The direction the packet is traveling.
duration	Opt	number	The amount of time for the completion of the network event, in seconds.
dvc_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_ip	Opt	string	The ip address of the device.
dvc_mac	Opt	string	The device TCP/IP layer 2 Media Access Control (MAC) address of a packet's destin…
dvc_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_zone	Opt	string	The network zone of the device.
flow_id	Opt	string	Unique identifier for this traffic stream, such as a netflow, jflow, or cflow.
icmp_code	Opt	string	The RFC 2780 or RFC 4443 human-readable code value of the traffic, such as Destin…
icmp_type	Opt	number	The RFC 2780 or RFC 4443 numeric value of the traffic. See the ICMP Type Numbers…

Field	St	Type	Description
packets	Opt	number	The total count of packets handled by this device/interface (packets_in + packets... (Eval)
packets_in	Opt	number	The total count of packets received by this device/interface. (Eval)
packets_out	Opt	number	The total count of packets transmitted by this device/interface. (Eval)
process_guid	Opt	string	The globally unique identifier of the process assigned by the vendor_product.
process_id	Opt	string	The numeric identifier of the process assigned by the operating system.
protocol	Opt	string	The OSI layer 3 (network) protocol of the traffic observed, in lower case. For ex...
protocol_version	Opt	string	Version of the OSI layer 3 protocol, in lower case.
response_time	Opt	number	The amount of time it took to receive a response in the network event, in seconds.
rule_id	Opt	string	The vendor-specific unique identifier of the rule. Examples: 0x00011f0000011f00...
session_id	Opt	string	The session identifier. Multiple transactions build a session.
src_bunit	Opt	string	The business unit of the network traffic source.
src_category	Opt	string	The category of the network traffic source.
src_interface	Opt	string	The interface that is listening locally or sending packets remotely. Can also be...
src_ip	Opt	string	The ip address of the source.
src_mac	Opt	string	The source TCP/IP layer 2 Media Access Control (MAC) address of a packet's destin...
src_priority	Opt	string	The priority of the source, if applicable.
src_translated_ip	Opt	string	The NATed IPv4 or IPv6 address from which a packet has been sent.
src_translated_port	Opt	number	The NATed port from which a packet has been sent. Note: Do not translate the valu...
src_zone	Opt	string	The network zone of the source.
ssid	Opt	string	The 802.11 service set identifier (ssid) assigned to a wireless session.

Field	St	Type	Description
tag	Opt	string	This automatically generated field is used to access tags from within data models...
tcp_flag	Opt	string	The TCP flag or multiple flags specified in the event.
tos	Opt	string	The combination of source and destination IP ToS (type of service) values in the...
ttl	Opt	number	The 'time to live' of a packet or diagram, in seconds.
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
vendor_account	Opt	string	The account associated with the network traffic.
vlan	Opt	string	The virtual local area network (VLAN) specified in the record.
wifi	Opt	string	The wireless standard(s) in use, such as 802.11a, 802.11b, 802.11g, or 802.11n.

Prescribed values
action = allowed, blocked, teardown
transport = tcp, udp, icmp
direction = inbound, outbound
icmp_type = 0-254
tcp_flag = SYN, ACK, FIN, RST, URG, PSH

Performance

All_Performance

Object All_Performance · **Parent** BaseEvent · **Fields** 10 · **Tags** performance, cpu, facilities, memory, storage, network, os, time, synchronize, uptime
Constraint (`cim_Performance_indexes`) tag=performance (tag=cpu OR tag=facilities OR tag=memory OR tag=storage OR tag=network OR (tag=os ((tag=time tag=synchronize) OR tag=uptime)))

Field	St	Type	Description
dest	Rec	string	The system where the event occurred, usually a facilities resource such as a rack... (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
dest_priority	Opt	string	The priority of the system where the performance event occurred.
dest_should_timesync	Opt	boolean	Indicates whether or not the system where the performance event occurred should t...
dest_should_update	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
hypervisor_id	Opt	string	The ID of the virtualization hypervisor.
resource_type	Opt	string	The type of facilities resource involved in the performance event, such as a rack...
tag	Opt	string	This automatically generated field is used to access tags from within data models...

All_Performance.CPU

Object CPU · **Parent** All_Performance · **Fields** 4 · **Tags** cpu
Constraint tag=cpu

Field	St	Type	Description
cpu_load_percent	Rec	number	The amount of CPU load reported by the controller in percentage points.
cpu_load_mhz	Opt	number	The amount of CPU load reported by the controller in megahertz.
cpu_time	Opt	number	The number of CPU seconds consumed by processes.
cpu_user_percent	Opt	number	Percentage of CPU user time consumed by processes.

All_Performance.Facilities

Object Facilities · **Parent** All_Performance · **Fields** 3 · **Tags** facilities
Constraint tag=facilities

Field	St	Type	Description
temperature	Rec	number	Average temperature of the facilities resource, in degrees Celsius.
fan_speed	Opt	number	The speed of the cooling fan in the facilities resource, in rotations per second.
power	Opt	number	Amount of power consumed by the facilities resource, in kW.

All_Performance.Memory

Object Memory · **Parent** All_Performance · **Fields** 7 · **Tags** memory
Constraint tag=memory

Field	St	Type	Description
mem	Rec	number	The total amount of memory capacity reported by the resource, in megabytes.
mem_free	Rec	number	The free amount of memory reported by the resource, in megabytes.
mem_used	Rec	number	The used amount of memory reported by the resource, in megabytes.
mem_committed	Opt	number	The committed amount of memory reported by the resource, in megabytes.
swap	Opt	number	The total swap space size, in megabytes, if applicable.
swap_free	Opt	number	The free swap space size, in megabytes, if applicable.
swap_used	Opt	number	The used swap space size, in megabytes, if applicable.

All_Performance.Storage

Object Storage · **Parent** All_Performance · **Fields** 19 · **Tags** storage
Constraint tag=storage

Field	St	Type	Description
storage_free	Rec	number	The free amount of storage capacity reported by the resource, in megabytes.
storage_free_percent	Rec	number	The percentage of storage capacity reported by the resource that is free.
storage_used	Rec	number	The used amount of storage capacity reported by the resource, in megabytes.
storage_used_percent	Rec	number	The percentage of storage capacity reported by the resource that is used.
array	Opt	string	The array that the resource is a member of, if applicable.
blocksize	Opt	number	Block size used by the storage resource, in kilobytes.
cluster	Opt	string	The cluster that the resource is a member of, if applicable.
fd_max	Opt	number	The maximum number of available file descriptors.
fd_used	Opt	number	The current number of open file descriptors.
latency	Opt	number	The latency reported by the resource, in milliseconds.
mount	Opt	string	The mount point of a storage resource.
parent	Opt	string	A generic indicator of hierarchy. For instance, a disk event might include the ar…
read_blocks	Opt	number	Number of blocks read.
read_latency	Opt	number	The latency of read operations, in milliseconds.

Field	St	Type	Description
read_ops	Opt	number	Number of read operations.
storage	Opt	number	The total amount of storage capacity reported by the resource, in megabytes.
write_blocks	Opt	number	The number of blocks written by the resource.
write_latency	Opt	number	The latency of write operations, in milliseconds.
write_ops	Opt	number	The total number of write operations processed by the resource.

All_Performance.Network

Object Network · **Parent** All_Performance · **Fields** 2 · **Tags** network
Constraint tag=network

Field	St	Type	Description
thruput	Rec	string	The current throughput reported by the service, in bytes.
thruput_max	Opt	number	The maximum possible throughput reported by the service, in bytes.

All_Performance.OS

Object OS · **Parent** All_Performance · **Fields** 2 · **Tags** os
Constraint tag=os

Field	St	Type	Description
signature	Rec	string	The event description signature, if available.
signature_id	Opt	string	The unique identifier or event code of the event signature.

OS.Timesync

Object Timesync · **Parent** OS · **Fields** 1 · **Tags** time, synchronize
Constraint tag=time tag=synchronize

Field	St	Type	Description
action	Rec	string	The result of a time sync event. (Eval)

Prescribed values
action = success, failure

OS.Uptime

Object Uptime · **Parent** OS · **Fields** 1 · **Tags** uptime
Constraint tag=uptime

Field	St	Type	Description
uptime	Rec	string	The uptime of the compute resource, in seconds. (Eval)

Splunk_Audit

> Internal Splunk audit/telemetry model — populated by Splunk; vendor add-ons normally do not map here.

Datamodel_Acceleration

Object Datamodel_Acceleration · **Parent** BaseSearch · **Fields** 18
Constraint *(none — derived dataset; inherits parent)*

Field	St	Type	Description
access_count	Opt	number	The number of times the data model summary has been accessed since it was created.
access_time	Opt	timestamp	The timestamp of the most recent access of the data model summary.
app	Opt	string	The application context in which the data model summary was accessed.
buckets	Opt	number	The number of index buckets spanned by the data model acceleration summary.
buckets_size	Opt	number	The total size of the buckets spanned by the data model acceleration summary.
complete	Opt	number	The percentage of the data model summary that is currently complete.
cron	Opt	string	The cron expression used to accelerate the data model.
datamodel	Opt	string	The name of the data model accelerated.
digest	Opt	string	A hash of the current data model contents.
earliest	Opt	timestamp	The earliest time that the data model summary was accessed.
is_inprogress	Opt	boolean	Indicates whether the data model acceleration is currently in progress.
last_error	Opt	string	The text of the last error reported during the data model acceleration.
last_sid	Opt	string	The search id of the last acceleration attempt.
latest	Opt	timestamp	The most recent acceleration timestamp of the data model.
mod_time	Opt	timestamp	The timestamp of the most recent modification to the data model acceleration.

Field	St	Type	Description
retention	Opt	number	The length of time that data model accelerations are retained, in seconds.
size	Opt	number	The amount of storage space the data model's acceleration summary takes up, in by…
summary_id	Opt	string	The unique id of the data model acceleration summary.

Prescribed values
is_inprogress = true, false, 1, 0

Search_Activity

Object Search_Activity · **Parent** BaseEvent · **Fields** 15
Constraint index=_audit action=search search_id=*

Field	St	Type	Description
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
datamodel	Opt	string	The name of the datamodel (for datamodel acceleration searches). (Eval)
info	Opt	string	The action of the search (granted, completed, cancelled, failed).
savedsearch_name	Opt	string	The name of the saved search. (Eval)
search	Opt	string	The SPL search syntax. (Eval)
search_alias	Opt	string	Short description of the type of search being run, such as the name of the search… (Eval)
search_et	Opt	string	The earliest time of the search.
search_id	Opt	string	The ID of the search. (Eval)
search_lt	Opt	string	The latest time of the search.
search_type	Opt	string	The type of search. (Eval)
total_run_time	Opt	string	The total run time of the search.
user	Opt	string	The name of the user who ran the search. (Rex)
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Scheduler_Activity

Object Scheduler_Activity · **Parent** BaseSearch · **Fields** 14
Constraint *(none — derived dataset; inherits parent)*

Field	St	Type	Description
_time	Opt	timestamp	The event timestamp expressed in Unix time.
app	Opt	string	The app context in which the scheduled search was run.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
host	Opt	string	The host on which the scheduled search was run.
savedsearch_name	Opt	string	The name of the saved search.
sid	Opt	string	The search id.
source	Opt	string	The source associated with the scheduled search.
sourcetype	Opt	string	The source type associated with the scheduled search.
splunk_server	Opt	string	The Splunk Server on which the scheduled search runs.
status	Opt	string	The status of the scheduled search.
user	Opt	string	The user who scheduled the search.
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

View_Activity

Object `View_Activity` · **Parent** `BaseEvent` · **Fields** 9
Constraint `index=_internal sourcetype=splunk_web_access method=GET status=200`

Field	St	Type	Description
app	Req	string	The app name which contains the view.
view	Req	string	The name of the view.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
spent	Opt	number	The amount of time spent loading the view (in milliseconds).
uri	Opt	string	The uniform resource identifier of the view activity.
user	Opt	string	The username of the user who accessed the view.
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Web_Service_Errors

Object `Web_Service_Errors` · **Parent** `BaseSearch` · **Fields** 5
Constraint *(none — derived dataset; inherits parent)*

Field	St	Type	Description
`_time`	Opt	timestamp	The event timestamp expressed in Unix time.
`cim_entity_zone`	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
`host`	Opt	string	The host on which the web service error occurred.
`source`	Opt	string	The source where the web service error occurred.
`sourcetype`	Opt	string	The source type associated with the web service error.

`Modular_Actions`

Object `Modular_Actions` · **Parent** `BaseEvent` · **Fields** 18 · **Tags** `modaction`
Constraint `tag=modaction`

Field	St	Type	Description
`action_mode`	Opt	string	Specifies whether the action was executed as an ad hoc action or from a saved sea…
`action_name`	Opt	string	The name of the action. (Eval)
`action_status`	Opt	string	The status of the action. For example, 'success' or 'failure'.
`app`	Opt	string	The app ID of the app or add-on that owns the action.
`cim_entity_zone`	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
`component`	Opt	string	The component of the modular action script involved in the event. Often used in c…
`duration`	Opt	number	How long the action took to complete, in milliseconds.
`orig_rid`	Opt	string	The rid value of a source action result, automatically added to an event if it is…
`orig_sid`	Opt	string	The original sid value of a source action, automatically added to an event if it…
`rid`	Opt	string	The id associated with the result of a specific sid. By default, this is the row…
`search_name`	Opt	string	The name of the correlation search that triggered the action. Blank for ad hoc ac…
`sid`	Opt	string	The search id, automatically assigned by splunkd. (Eval)
`signature`	Opt	string	The logging string associated with alert action introspection events. (Eval)

Field	St	Type	Description
user	Opt	string	The user who triggered an ad hoc alert. Not relevant for actions triggered by sea… (Eval)
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
worker	Opt	string	The worker performing the action. (Eval)

Prescribed values
action_mode = saved, adhoc

Ticket_Management

All_Ticket_Management

Object All_Ticket_Management · **Parent** BaseEvent · **Fields** 25 · **Tags** ticketing
Constraint (`cim_Ticket_Management_indexes`) tag=ticketing

Field	St	Type	Description
affect_dest	Opt	string	Destinations affected by the service request.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
comments	Opt	string	Comments about the service request.
description	Opt	string	The description of the service request.
dest	Opt	string	The destination of the service request. You can alias this from more specific fie… (Eval)
dest_bunit	Opt	string	The business unit of the destination.
dest_category	Opt	string	The category of the destination.
dest_priority	Opt	string	The priority of the destination.
priority	Opt	string	The relative priority of the service request.
severity	Opt	string	The relative severity of the service request.
severity_id	Opt	string	The numeric or vendor specific severity indicator corresponding to the event seve…
splunk_id	Opt	string	The unique identifier of the service request as it pertains to Splunk. For exampl…
splunk_realm	Opt	string	The Splunk application or use case associated with the unique identifier (splunk_…

Field	St	Type	Description
src_user	Opt	string	The user or entity that created or triggered the service request, if applicable.
src_user_bunit	Opt	string	The business unit associated with the user or entity that triggered the service r…
src_user_category	Opt	string	The category associated with the user or entity that triggered the service reques…
src_user_priority	Opt	string	The priority associated with the user or entity that triggered the service reques…
status	Opt	string	The relative status of the service request.
tag	Opt	string	This automatically generated field is used to access tags from within data models…
ticket_id	Opt	string	An identification name, code, or number for the service request. (Eval)
time_submitted	Opt	timestamp	The time that the src_user submitted the service request.
user	Opt	string	The name of the user or entity that is assigned to carry out the service request…
user_bunit	Opt	string	The business unit associated with the user or entity that is assigned to carry ou…
user_category	Opt	string	The category associated with the user or entity that is assigned to carry out the…
user_priority	Opt	string	The priority of the user or entity that is assigned to carry out the service requ…

All_Ticket_Management.Change

Object Change · **Parent** All_Ticket_Management · **Fields** 1 · **Tags** change
Constraint tag=change

Field	St	Type	Description
change	Opt	string	Designation for a request for change (RFC) that is raised to modify an IT service… (Eval)

All_Ticket_Management.Incident

Object Incident · **Parent** All_Ticket_Management · **Fields** 1 · **Tags** incident
Constraint tag=incident

Field	St	Type	Description
incident	Opt	string	The incident that triggered the service request. Can be a rare occurrence, or som… (Eval)

All_Ticket_Management.Problem

Object Problem · **Parent** All_Ticket_Management · **Fields** 1 · **Tags** problem
Constraint tag=problem

Field	St	Type	Description
problem	Opt	string	When multiple occurrences of related incidents are observed, they are collectivel… (Eval)

Updates

Updates

Object Updates · **Parent** BaseEvent · **Fields** 17 · **Tags** update, status
Constraint (`cim_Updates_indexes`) tag=update tag=status

Field	St	Type	Description
dest	Rec	string	The system that is affected by the patch change. You can alias this from more spe… (Eval)
signature	Rec	string	The name of the patch requirement detected on the client (the dest), such as MS08… (Eval)
signature_id	Rec	string	The ID of the patch requirement detected on the client (the src). Note: Use signa… (Eval)
status	Rec	string	Indicates the status of a given patch requirement. (Eval)
vendor_product	Rec	string	The vendor and product of the patch monitoring product, such as Lumension Patch M… (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_should_update	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dvc	Opt	string	The device that detected the patch event, such as a patching or configuration man…
file_hash	Opt	string	The checksum of the patch package that was installed or attempted. Deprecated in…

Field	St	Type	Description
file_hashes	Opt	string	The checksum of the patch package that was installed or attempted.
file_name	Opt	string	The name of the patch package that was installed or attempted.
severity	Opt	string	The severity associated with the patch event.
severity_id	Opt	string	The numeric or vendor specific severity indicator corresponding to the event seve…
tag	Opt	string	This automatically generated field is used to access tags from within data models…

Prescribed values
status = available, installed, invalid, restart required, failure
severity = critical, high, medium, low, informational

Update_Errors

Object Update_Errors · **Parent** BaseSearch · **Fields** 5
Constraint *(none — derived dataset; inherits parent)*

Field	St	Type	Description
_time	Opt	timestamp	The event timestamp expressed in Unix time.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
host	Opt	string	The host associated with the search.
source	Opt	string	The source associated with the search.
sourcetype	Opt	string	The source type associated with the search.

Vulnerabilities

Vulnerabilities

Object Vulnerabilities · **Parent** BaseEvent · **Fields** 46 · **Tags** vulnerability, report
Constraint (`cim_Vulnerabilities_indexes`) tag=vulnerability tag=report

Field	St	Type	Description
category	Rec	string	The category of the discovered vulnerability, such as DoS. Note: This field is a… (Eval)
cve	Rec	string	The identifier provided in the Common Vulnerabilities and Exposures index (search… (Eval)

Field	St	Type	Description
dest	Rec	string	The host with the discovered vulnerability. You can alias this from more specific… (Eval)
dvc	Rec	string	The system that discovered the vulnerability. You can alias this from more specif… (Eval)
severity	Rec	string	The severity of the vulnerability detection event. Specific values are required… (Eval)
signature	Rec	string	The name of the vulnerability detected on the host, such as HPSBMU02785 SSRT10052… (Eval)
vendor_product	Rec	string	The vendor and product that detected the vulnerability. This field can be automat… (Eval)
affected_component_type	Opt	string	The type of component affected by the vulnerability, based on the NIST CPE 2.3 ta…
affected_product	Opt	string	The name of the product affected by the vulnerability. Distinct from vendor_produ…
affected_product_version	Opt	string	The specific version of the affected product (e.g., 1.0.0, 2.3.1). Provides granu…
bugtraq	Opt	string	The identifier in the vulnerability database provided by the Security Focus websi… (Eval)
cert	Opt	string	The identifier in the vulnerability database provided by the US Computer Emergenc… (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
cvss	Opt	number	Numeric indicator of the common vulnerability scoring system.
cvss_attack_complexity	Opt	string	Describes conditions beyond the attacker's control that must exist to exploit the…
cvss_attack_vector	Opt	string	Reflects the context by which vulnerability exploitation is possible.
cvss_availability_impact	Opt	string	Measures the impact to availability of the impacted component.
cvss_base_score	Opt	number	The CVSS base score. Distinct from the existing cvss field, which represents a co…
cvss_confidentiality_impact	Opt	string	Measures the impact to confidentiality of information resources.
cvss_exploitability_score	Opt	number	CVSS sub-score reflecting the exploitability characteristics of the vulnerability.

Field	St	Type	Description
cvss_impact_score	Opt	number	CVSS sub-score reflecting the potential impact of a successful exploit on the aff…
cvss_integrity_impact	Opt	string	Measures the impact to integrity of a successfully exploited vulnerability.
cvss_privileges_required	Opt	string	The level of privileges an attacker must possess before successfully exploiting t…
cvss_scope	Opt	string	Captures whether a vulnerability impacts resources beyond its means.
cvss_user_interaction	Opt	string	Captures the requirement for a human user other than the attacker to participate…
cvss_vector_string	Opt	string	The full CVSS vector string representing all base metrics in compact machine-read…
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
is_known_exploited	Opt	boolean	Indicates whether the vulnerability is listed in a known exploited vulnerabilitie…
msft	Opt	string	The Microsoft Security Advisory number (http://technet.microsoft.com/en-us/securi… (Eval)
mskb	Opt	string	The Microsoft Knowledge Base article number (http://support.microsoft.com/kb/). (Eval)
severity_id	Opt	string	The numeric or vendor specific severity indicator corresponding to the event seve…
signature_id	Opt	string	The unique identifier or event code of the event signature.

Field	St	Type	Description
tag	Opt	string	This automatically generated field is used to access tags from within data models...
url	Opt	string	The URL involved in the discovered vulnerability.
user	Opt	string	The user involved in the discovered vulnerability.
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
vuln_modified_time	Opt	timestamp	The timestamp when the CVE record was last modified in the vulnerability database...
vuln_published_time	Opt	timestamp	The timestamp when the CVE was first published in the vulnerability database (e.g...
xref	Opt	string	A cross-reference identifier associated with the vulnerability. In most cases, th... (Eval)

Prescribed values
severity = critical, high, medium, low, informational
affected_component_type = application, hardware, operating system
cvss_attack_complexity = Low, High
cvss_attack_vector = Network, Adjacent, Local, Physical
cvss_availability_impact = None, Low, High
cvss_confidentiality_impact = None, Low, High
cvss_integrity_impact = None, Low, High
cvss_privileges_required = None, Low, High
cvss_scope = Unchanged, Changed
cvss_user_interaction = None, Required

Web

Web

Object Web · **Parent** BaseEvent · **Fields** 43 · **Tags** web
Constraint (`cim_Web_indexes`) tag=web

Field	St	Type	Description
action	Rec	string	The action taken by the server or proxy. (Eval)

Field	St	Type	Description
bytes	Rec	number	The total number of bytes transferred (bytes_in + bytes_out). (Eval)
bytes_in	Rec	number	The number of inbound bytes transferred. (Eval)
bytes_out	Rec	number	The number of outbound bytes transferred. (Eval)
dest	Rec	string	The destination of the network traffic (the remote host). You can alias this from... (Eval)
http_content_type	Rec	string	The content-type of the requested HTTP resource. (Eval)
http_method	Rec	string	The HTTP method used in the request. (Eval)
http_referrer	Rec	string	The HTTP referrer used in the request. The W3C specification and many implementat... (Eval)
http_referrer_domain	Rec	string	The domain name contained within the HTTP referrer used in the request. (Rex)
http_user_agent	Rec	string	The user agent used in the request. (Eval)
src	Rec	string	The source of the network traffic (the client requesting the connection). (Eval)
status	Rec	string	The HTTP response code indicating the status of the proxy request. (Eval)
url	Rec	string	The URL of the requested HTTP resource. (Eval)
url_domain	Rec	string	The domain name contained within the URL of the requested HTTP resource. (Rex)
user	Rec	string	The user that requested the HTTP resource. (Eval)
vendor_product	Rec	string	The vendor and product of the proxy server, such as Squid Proxy Server. This fiel... (Eval)
app	Opt	string	The application detected or hosted by the server/site such as wordpress, splunk...
cached	Opt	boolean	Indicates whether the event data is cached or not.
category	Opt	string	The category of traffic, such as may be provided by a proxy server.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
cookie	Opt	string	The cookie file recorded in the event.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_ip	Opt	string	The IP address of the destination.
dest_port	Opt	number	The destination port of the web traffic.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
duration	Opt	number	The time taken by the proxy event, in milliseconds.
http_user_agent_length	Opt	number	The length of the user agent used in the request. (Eval)
response_time	Opt	number	The amount of time it took to receive a response, if applicable, in milliseconds.
signature	Opt	string	A human-readable signature name, e.g. a threat category.
signature_id	Opt	string	The unique identifier or event code of the event signature.
site	Opt	string	The virtual site which services the request, if applicable.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_ip	Opt	string	The ip address of the source.
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
uri_path	Opt	string	The path of the resource served by the webserver or proxy.
uri_query	Opt	string	The path of the resource requested by the client.
url_length	Opt	number	The length of the URL. (Eval)
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values

`http_method` = GET, PUT, POST, DELETE, HEAD, OPTIONS, CONNECT, TRACE

`status` = 100, 101, 102, 200, 201, 202, 203, 204, 205, 206, 207, 208, 226, 300, 301, 302, 303, 304, 305, 306, 307, 308, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 422, 423, 424, 426, 428, 429, 431, 500, 501, 502, 503, 504, 505, 506, 507, 508, 510, 511

`cached` = true, false, 1, 0

`Web.Storage`

Object `Storage` · **Parent** `Web` · **Fields** 3 · **Tags** `storage`

Constraint `tag=storage`

Field	St	Type	Description
`error_code`	Opt	string	The error code that occurred while accessing the storage account.
`operation`	Opt	string	The operation performed on the storage account.
`storage_name`	Opt	string	The name of the bucket or storage account.

Splunk CIM 8.7.0 reference (`splunk_data_model_objects_fields_870.csv`) · October 17, 2026 · Machine Data Insights Inc. — Data Refinery