

Splunk CIM Data Model — Field Catalog

Purpose: a catalog of every Splunk Common Information Model (CIM) field, by data model and dataset — to reconcile a generated or third-party add-on field-for-field against what the model actually defines.

Source: [splunk_data_model_objects_fields_850.csv](#) (Splunk CIM 8.5.0)

Generated: May 19, 2026

Scope: 1474 fields · 27 models · 139 datasets

Status: **Req** = required · **Rec** = recommended (the dataset should populate it) · **Opt** = optional.

Tags match events into a dataset (not sourcetype); a tag not listed here pulls events into *no* known dataset.

Child datasets (dotted names) list only the fields they add and also inherit the parent's fields + tag constraint. Fields described "Auto-set by ES asset/identity correlation" must **not** be extracted by an add-on.

(Eval)/(Rex)/(Lookup) = the model derives the field that way.

Models

- [Alerts](#) — 1 dataset(s), 30 fields
 - [Application_State](#) — 4 dataset(s), 25 fields
 - [Authentication](#) — 1 dataset(s), 41 fields
 - [Certificates](#) — 2 dataset(s), 47 fields
 - [Change](#) — 4 dataset(s), 49 fields
 - [Change_Analysis](#) — 3 dataset(s), 40 fields
 - [Compute_Inventory](#) — 9 dataset(s), 57 fields
 - [DLP](#) — 1 dataset(s), 37 fields
 - [Data_Access](#) — 1 dataset(s), 41 fields
 - [Databases](#) — 8 dataset(s), 76 fields
 - [Email](#) — 2 dataset(s), 53 fields
 - [Endpoint](#) — 5 dataset(s), 177 fields
 - [Event_Signatures](#) — 1 dataset(s), 9 fields
 - [Interprocess_Messaging](#) — 1 dataset(s), 35 fields
 - [Intrusion_Detection](#) — 1 dataset(s), 35 fields
 - [JVM](#) — 7 dataset(s), 46 fields
 - [Malware](#) — 2 dataset(s), 44 fields
 - [Network_Resolution](#) — 1 dataset(s), 32 fields
 - [Network_Sessions](#) — 2 dataset(s), 29 fields
 - [Network_Traffic](#) — 1 dataset(s), 66 fields
 - [Performance](#) — 9 dataset(s), 49 fields
 - [Splunk_Audit](#) — 6 dataset(s), 79 fields
 - [Ticket_Management](#) — 4 dataset(s), 28 fields
 - [Updates](#) — 2 dataset(s), 21 fields
 - [Vulnerabilities](#) — 1 dataset(s), 28 fields
 - [Web](#) — 2 dataset(s), 44 fields
-

Alerts

Alerts

Object Alerts · **Parent** BaseEvent · **Fields** 30 · **Tags** alert

Constraint (`cim\_Alerts\_indexes`) tag=alert

Field	St	Type	Description
app	Rec	string	The system, service, or application that generated the alert event. Examples incl... (Eval)
dest	Rec	string	The object that is the 'target' of the alert event. Examples include an email add... (Eval)
severity	Rec	string	The severity of the alert event. Note: This field is a string. Specific values ar... (Eval)
signature_id	Rec	string	The vendor specific policy or rule that generated the alert event, such as 'Polic... (Eval)
src	Rec	string	The object that is the 'actor' of the alert event. You can alias or extract this... (Eval)
type	Rec	string	The alert event type. (Eval)
user	Rec	string	The user involved in the alert event. (Eval)
body	Opt	string	This field is deprecated in favor of 'description'.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
description	Opt	string	The description of the alert event.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_type	Opt	string	The type of the destination object, such as 'instance', 'storage', 'firewall'.
id	Opt	string	The unique identifier of the alert event.
mitre_technique_id	Opt	string	The MITRE ATT&CK technique ID of the alert event, searchable at https://attack.mitre.org
severity_id	Opt	string	The numeric or vendor specific severity indicator corresponding to the event seve...
signature	Opt	string	The human-friendly title of the alert event, such as 'API GetAccountPasswordPolic...
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
<code>src_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>src_type</code>	Opt	string	The type of the source object, such as 'instance', 'storage', 'firewall'.
<code>subject</code>	Opt	string	This field is deprecated in favor of 'signature'.
<code>tag</code>	Opt	string	This automatically generated field is used to access tags from within data models...
<code>user_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_name</code>	Opt	string	The user_name of user involved in the alert event. (Eval)
<code>user_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>vendor_account</code>	Opt	string	The account associated with the alert event.
<code>vendor_region</code>	Opt	string	The data center region involved in the alert event, such as us-west-2.

Prescribed values

`severity` = critical, high, medium, low, informational, unknown

`type` = alarm, alert, event, task, warning, unknown

Application_State

All_Application_State

Object All_Application_State · **Parent** BaseEvent · **Fields** 14 · **Tags** listening, port, process, report, service

Constraint (`cim\_Application\_State\_indexes`) (tag=listening tag=port) OR (tag=process tag=report) OR (tag=service tag=report)

Field	St	Type	Description
<code>dest</code>	Rec	string	The compute resource where the service is installed. You can alias this from more... (Eval)
<code>process</code>	Rec	string	The name of a process or service file, such as sqlsrvr.exe or httpd. Note: This f... (Eval)
<code>dest_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_requires_av</code>	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
dest_should_timesync	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_update	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
process_name	Opt	string	The name of a process. (Rex)
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user	Opt	string	The user account the service is running as, such as System or httpdsvc.
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

All_Application_State.Ports

Object [Ports](#) · **Parent** [All_Application_State](#) · **Fields** 3 · **Tags** [listening](#), [port](#)
Constraint [tag=listening](#) [tag=port](#)

Field	St	Type	Description
dest_port	Rec	number	Network ports communicated to by the process, such as 53. (Eval)
transport	Rec	string	The network ports listened to by the application process, such as tcp, udp, etc. (Eval)
transport_dest_port	Opt	string	Calculated as transport/dest_port, such as tcp/53. (Eval)

All_Application_State.Processes

Object [Processes](#) · **Parent** [All_Application_State](#) · **Fields** 4 · **Tags** [process](#), [report](#)
Constraint [tag=process](#) [tag=report](#)

Field	St	Type	Description
cpu_load_mhz	Opt	number	CPU Load in megahertz.
cpu_load_percent	Opt	number	CPU Load in percent.
cpu_time	Opt	string	CPU Time.
mem_used	Opt	number	Memory used in bytes.

All_Application_State.Services

Object [Services](#) · **Parent** [All_Application_State](#) · **Fields** 4 · **Tags** [service](#), [report](#)
Constraint [tag=service](#) [tag=report](#)

Field	St	Type	Description
service	Rec	string	The name of the service, such as SQL Server or Apache Web Server. Note: This fiel... (Eval)
service_id	Rec	string	A numeric indicator for a service. (Eval)
start_mode	Rec	string	The start mode for the service. (Eval)
status	Rec	string	The status of the service. (Eval)

Prescribed values

[start_mode](#) = disabled, manual, auto

[status](#) = critical, started, stopped, warning

Authentication

Authentication

Object [Authentication](#) · **Parent** [BaseEvent](#) · **Fields** 41 · **Tags** [authentication](#)

Constraint (``cim_Authentication_indexes``) [tag=authentication](#) NOT ([action=success](#) [user=*\\$](#))

Field	St	Type	Description
action	Rec	string	The action performed on the resource. (Eval)
app	Rec	string	The application involved in the event, such as ssh, splunk, win:local. (Eval)
dest	Rec	string	The target involved in the authentication. You can alias this from more specific... (Eval)
src	Rec	string	The source involved in the authentication. In the case of endpoint protection aut... (Eval)
src_user	Rec	string	In privilege escalation events, src_user represents the user who initiated the pr... (Eval)
user	Rec	string	The name of the user involved in the event, or who initiated the event. For authe... (Eval)
authentication_method	Opt	string	The method used to authenticate the request such as SAML, FIDO, or MFA.
authentication_service	Opt	string	The service used to authenticate the request such as Okta, or ActiveDirectory
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
dest_nt_domain	Opt	string	The name of the Active Directory used by the authentication target, if applicable.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
duration	Opt	number	The amount of time for the completion of the authentication event, in seconds.
process	Opt	string	Full path and the name of the executable for the process that attempted the logon...
reason	Opt	string	The human-readable message associated with the authentication action (success or...
reason_id	Opt	string	The reason why logon failed. For example "0xC0000234".
response_time	Opt	number	The amount of time it took to receive a response in the authentication event, in...
result	Opt	string	The result of the authentication attempt for audittrailv2 sourcetypes. (Eval)
session_id	Opt	string	The unique identifier assigned to the login session.
signature	Opt	string	A human-readable signature name.
signature_id	Opt	string	The unique identifier or event code of the event signature.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_nt_domain	Opt	string	The name of the Active Directory used by the authentication source, if applicable.
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_id	Opt	string	The unique id of the user who initiated the privilege escalation. This field is u...
src_user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_role	Opt	string	The role of the user who initiated the privilege escalation. This field is unnece...
src_user_type	Opt	string	The type of the user who initiated the privilege escalation. This field is unnece...
tag	Opt	string	This automatically generated field is used to access tags from within data models...

Field	St	Type	Description
<code>user_agent</code>	Opt	string	The user agent through which the request was made, such as Mozilla/5.0 (Macintosh...
<code>user_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_id</code>	Opt	string	The unique id of the user involved in the event. For authentication privilege esc...
<code>user_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_role</code>	Opt	string	The role of the user involved in the event, or who initiated the event. For authe...
<code>user_type</code>	Opt	string	The type of the user involved in the event or who initiated the event, such as IA...
<code>vendor_account</code>	Opt	string	The account that manages the user that initiated the request.

Prescribed values

`action` = success, failure, pending, error

Certificates

All_Certificates

Object All_Certificates · **Parent** BaseEvent · **Fields** 15 · **Tags** certificate

Constraint (`cim\_Certificates\_indexes`) tag=certificate

Field	St	Type	Description
<code>cim_entity_zone</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest</code>	Opt	string	The target in the certificate management event.
<code>dest_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_category</code>	Opt	string	The category of the target, such as email_server or SOX-compliant. This field is...
<code>dest_port</code>	Opt	number	The port number of the target.
<code>dest_priority</code>	Opt	string	The priority of the target.
<code>duration</code>	Opt	number	The amount of time for the completion of the certificate management event, in sec...
<code>response_time</code>	Opt	number	The amount of time it took, in seconds, to receive a response in the certificate...

Field	St	Type	Description
<code>src</code>	Opt	string	The source involved in the certificate management event. You can alias this from...
<code>src_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>src_category</code>	Opt	string	The category of the certificate management source, such as email_server or SOX-co...
<code>src_port</code>	Opt	number	The port number of the source.
<code>src_priority</code>	Opt	string	The priority of the certificate management source.
<code>tag</code>	Opt	string	This automatically generated field is used to access tags from within data models...
<code>transport</code>	Opt	string	The transport protocol of the Network Traffic involved with this certificate.

All_Certificates.SSL

Object `SSL` · **Parent** `All_Certificates` · **Fields** 32 · **Tags** `ssl`, `tls`

Constraint (`tag=ssl` OR `tag=tls`)

Field	St	Type	Description
<code>ssl_end_time</code>	Rec	timestamp	The expiry time of the certificate.
<code>ssl_hash</code>	Rec	string	The hash of the certificate. (Eval)
<code>ssl_issuer</code>	Rec	string	The certificate issuer's RFC2253 Distinguished Name. (Eval)
<code>ssl_issuer_common_name</code>	Rec	string	The certificate issuer's common name. (Eval)
<code>ssl_issuer_email_domain</code>	Rec	string	The domain name contained within the certificate issuer's email address. (Rex)
<code>ssl_serial</code>	Rec	string	The certificate's serial number.
<code>ssl_start_time</code>	Rec	timestamp	This is the start date and time for this certificate's validity.
<code>ssl_subject</code>	Rec	string	The certificate owner's RFC2253 Distinguished Name. (Eval)
<code>ssl_subject_common_name</code>	Rec	string	The certificate subject's common name. (Eval)
<code>ssl_subject_email_domain</code>	Rec	string	The domain name contained within the certificate subject's email address. (Rex)
<code>ssl_engine</code>	Opt	string	The name of the signature engine that created the certificate.

Field	St	Type	Description
ssl_is_valid	Opt	boolean	Indicator of whether the ssl certificate is valid or not. (Eval)
ssl_issuer_email	Opt	string	The certificate issuer's email address.
ssl_issuer_locality	Opt	string	The certificate issuer's locality.
ssl_issuer_organization	Opt	string	The certificate issuer's organization.
ssl_issuer_state	Opt	string	The certificate issuer's state of residence.
ssl_issuer_street	Opt	string	The certificate issuer's street address.
ssl_issuer_unit	Opt	string	The certificate issuer's organizational unit.
ssl_name	Opt	string	The name of the ssl certificate.
ssl_policies	Opt	string	The Object Identification Numbers of the certificate's policies in a comma separa...
ssl_publickey	Opt	string	The certificate's public key.
ssl_publickey_algorithm	Opt	string	The algorithm used to create the public key.
ssl_session_id	Opt	string	The session identifier for this certificate.
ssl_signature_algorithm	Opt	string	The algorithm used by the Certificate Authority to sign the certificate.
ssl_subject_email	Opt	string	The certificate owner's e-mail address.
ssl_subject_locality	Opt	string	The certificate owner's locality.
ssl_subject_organization	Opt	string	The certificate owner's organization.
ssl_subject_state	Opt	string	The certificate owner's state of residence.
ssl_subject_street	Opt	string	The certificate owner's street address.
ssl_subject_unit	Opt	string	The certificate owner's organizational unit.
ssl_validity_window	Opt	number	The length of time, in seconds, for which this certificate is valid. (Eval)
ssl_version	Opt	string	The ssl version of this certificate.

Prescribed values

ssl_is_valid = true, false, 1, 0

Change

All_Changes

Object All_Changes · **Parent** BaseEvent · **Fields** 32 · **Tags** change

Constraint (`cim\_Change\_indexes`) tag=change

Field	St	Type	Description
action	Rec	string	The action attempted on the resource, regardless of success or failure. (Eval)
change_type	Rec	string	The type of change, such as filesystem or AAA (authentication, authorization, and... (Eval)
command	Rec	string	The command that initiated the change. (Eval)
dest	Rec	string	The resource where change occurred. You can alias this from more specific fields... (Eval)
dvc	Rec	string	The device that reported the change, if applicable, such as a FIP or CIM server... (Eval)
object	Rec	string	Name of the affected object on the resource, such as a router interface, user acc... (Eval)
object_attrs	Rec	string	The attributes that were updated on the updated resource object, if applicable. (Eval)
object_category	Rec	string	Generic name for the class of the updated resource object. Expected values may be... (Eval)
object_id	Rec	string	The unique updated resource object ID as presented to the system, if applicable... (Eval)
object_path	Rec	string	The path of the modified resource object, if applicable, such as a file, director... (Eval)
result	Rec	string	The vendor-specific result of a change, or clarification of an action status. For... (Eval)
result_id	Rec	string	A result indicator for an action status. (Eval)
src	Rec	string	The resource where the change was originated. You can alias this from more specif... (Eval)
status	Rec	string	Status of the update. (Eval)
user	Rec	string	The user or entity performing the change. For account changes, this is the accoun... (Eval)
vendor_product	Rec	string	The vendor and product or service that detected the change. This field can be aut... (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user_agent	Opt	string	The user agent through which the request was made, such as Mozilla/5.0 (Macintosh...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_name	Opt	string	The user name of the user or entity performing the change. For account changes, t... (Eval)
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_type	Opt	string	The type of the user involved in the event or who initiated the event, such as IA...
vendor_account	Opt	string	The account associated with the change.
vendor_region	Opt	string	The data center region where the change occurred, such as us-west-2.

Prescribed values

action = acl_modified, cleared, created, deleted, modified, stopped, lockout, read, logoff, updated, started, restarted, unlocked

status = success, failure

All_Changes.Network_Changes

Object Network_Changes · **Parent** All_Changes · **Fields** 7 · **Tags** network

Constraint tag=network

Field	St	Type	Description
dest_ip_range	Opt	string	For network events, the outgoing traffic for a specific destination IP address ra...
dest_port_range	Opt	string	For network events, this field represents destination port or range. For example...
direction	Opt	string	For network events, this field represents whether the traffic is inbound or outbo...
protocol	Opt	string	This field represents the protocol for the network event rule.
rule_action	Opt	string	For network events, this field represents whether to allow or deny traffic.

Field	St	Type	Description
src_ip_range	Opt	string	For network events, this field represents the incoming traffic from a specific so...
src_port_range	Opt	string	For network events, this field represents source port or range. For example, 80 o...

All_Changes.Account_Management

Object Account_Management · **Parent** All_Changes · **Fields** 8 · **Tags** account

Constraint tag=account

Field	St	Type	Description
dest_nt_domain	Rec	string	The NT domain of the destination, if applicable. (Eval)
src_nt_domain	Rec	string	The NT domain of the source, if applicable. (Eval)
src_user	Rec	string	For account changes, the user or entity performing the change. (Eval)
src_user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_name	Opt	string	For account changes, the user name of the user or entity performing the change. (Eval)
src_user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_type	Opt	string	For account management events, this should represent the type of the user changed...

All_Changes.Instance_Changes

Object Instance_Changes · **Parent** All_Changes · **Fields** 2 · **Tags** instance

Constraint tag=instance

Field	St	Type	Description
image_id	Rec	string	For create instance events, this field represents the image ID used for creating... (Eval)
instance_type	Rec	string	For create instance events, this field represents the type of instance to build s... (Eval)

Change_Analysis

All_Changes

Object All_Changes · **Parent** BaseEvent · **Fields** 26 · **Tags** change

Constraint (`cim\_Change\_Analysis\_indexes`) tag=change

Field	St	Type	Description
action	Rec	string	The action performed on the resource. (Eval)
change_type	Rec	string	The type of change, such as filesystem or AAA (authentication, authorization, and... (Eval)
command	Rec	string	The command that initiated the change. (Eval)
dest	Rec	string	The resource where change occurred. You can alias this from more specific fields... (Eval)
dvc	Rec	string	The device that reported the change, if applicable, such as a FIP or CIM server... (Eval)
object	Rec	string	Name of the affected object on the resource, such as a router interface, user acc... (Eval)
object_attrs	Rec	string	The attributes that were updated on the updated resource object, if applicable. (Eval)
object_category	Rec	string	Generic name for the class of the updated resource object. Expected values may be... (Eval)
object_id	Rec	string	The unique updated resource object ID as presented to the system, if applicable... (Eval)
object_path	Rec	string	The path of the modified resource object, if applicable, such as a file, director... (Eval)
result	Rec	string	The vendor-specific result of a change, or clarification of an action status. For... (Eval)
result_id	Rec	string	A result indicator for an action status. (Eval)
src	Rec	string	The resource where the change was originated. You can alias this from more specif... (Eval)
status	Rec	string	Status of the update. (Eval)
user	Rec	string	The user or entity performing the change. For account changes, this is the accoun... (Eval)
vendor_product	Rec	string	The vendor and product or service that detected the change. This field can be aut... (Eval)
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values

action = acl_modified, cleared, created, deleted, modified, read, stopped, updated

change_type = restart

object_category = directory, file, group, registry, user

result = lockout

status = success, failure

Endpoint_Changes.Filesystem_Changes

Object Filesystem_Changes · **Parent** Endpoint_Changes · **Fields** 8

Constraint (object_category=file OR object_category=directory)

Field	St	Type	Description
file_access_time	Rec	timestamp	The time the file (the object of the event) was accessed. (Eval)
file_acl	Rec	string	Access controls associated with the file affected by the event. (Eval)
file_create_time	Rec	timestamp	The time the file (the object of the event) was created. (Eval)
file_hash	Rec	string	A cryptographic identifier assigned to the file object affected by the event. (Eval)
file_modify_time	Rec	timestamp	The time the file (the object of the event) was altered. (Eval)
file_name	Rec	string	The name of the file that is the object of the event (without location informatio... (Eval)
file_path	Rec	string	The location of the file that is the object of the event, in local file and direc... (Eval)
file_size	Rec	number	The size of the file that is the object of the event, in kilobytes. (Eval)

All_Changes.Account_Management

Object Account_Management · **Parent** All_Changes · **Fields** 6 · **Tags** account

Constraint tag=account

Field	St	Type	Description
dest_nt_domain	Rec	string	The NT domain of the destination, if applicable. (Eval)

Field	St	Type	Description
src_nt_domain	Rec	string	The NT domain of the source, if applicable. (Eval)
src_user	Rec	string	For account changes, the user or entity performing the change. (Eval)
src_user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Compute_Inventory

All_Inventory

Object All_Inventory · **Parent** BaseEvent · **Fields** 14 · **Tags** inventory, cpu, memory, network, storage, system, version, user, virtual

Constraint (`cim\_Compute\_Inventory\_indexes`) tag=inventory (tag=cpu OR tag=memory OR tag=network OR tag=storage OR (tag=system tag=version) OR tag=user OR tag=virtual)

Field	St	Type	Description
dest	Rec	string	The system where the data originated, the source of the event. You can alias this... (Eval)
vendor_product	Rec	string	The vendor and product name of the resource, such as Cisco Catalyst 3850. This fi... (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
description	Opt	string	The description of the inventory system.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	The priority of the system where the data originated.
enabled	Opt	boolean	Indicates whether the resource is enabled or disabled.
family	Opt	string	The product family of the resource, such as 686_64 or RISC.
hypervisor_id	Opt	string	The hypervisor identifier, if applicable.
serial	Opt	string	The serial number of the resource.
status	Opt	string	The current reported state of the resource.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
version	Opt	string	The version of a computer resource, such as 2008r2 or 3.0.0.

All_Inventory.CPU

Object CPU · **Parent** All_Inventory · **Fields** 3 · **Tags** cpu**Constraint** tag=cpu

Field	St	Type	Description
cpu_cores	Rec	number	The number of CPU cores reported by the resource (total, not per CPU).
cpu_count	Rec	number	The number of CPUs reported by the resource.
cpu_mhz	Rec	number	The maximum speed of the CPU reported by the resource (in megahertz).

All_Inventory.Memory

Object Memory · **Parent** All_Inventory · **Fields** 1 · **Tags** memory**Constraint** tag=memory

Field	St	Type	Description
mem	Rec	number	The total amount of memory installed in or allocated to the resource, in megabyte...

All_Inventory.Network

Object Network · **Parent** All_Inventory · **Fields** 12 · **Tags** network**Constraint** tag=network

Field	St	Type	Description
dns	Rec	string	The domain name server for the resource.
interface	Rec	string	The network interfaces of the computing resource, such as eth0, eth1 or Wired Eth...
ip	Rec	string	The network addresses of the computing resource, such as 192.168.1.1 or E80:0000:....
mac	Rec	string	A MAC (media access control) address associated with the resource, such as 06:10:....
name	Rec	string	A name field provided in some data sources.
dest_ip	Opt	string	The IP address for the system that the data is going to.
inline_nat	Opt	string	Identifies whether the resource is a network address translation pool.
lb_method	Opt	string	The load balancing method used by the computing resource such as method, round ro...
node	Opt	string	Represents a node hit.
node_port	Opt	number	The number of the destination port on the server that you requested from.
src_ip	Opt	string	The IP address for the system from which the data originates.

Field	St	Type	Description
<code>vip_port</code>	Opt	number	The port number for the virtual IP address (VIP). A VIP allows multiple MACs to u...

All_Inventory.Storage

Object `Storage` · **Parent** `All_Inventory` · **Fields** 14 · **Tags** `storage`

Constraint `tag=storage`

Field	St	Type	Description
<code>mount</code>	Rec	string	The path at which a storage resource is mounted.
<code>storage</code>	Rec	number	The amount of storage capacity allocated to the resource, in megabytes.
<code>array</code>	Opt	string	The array that the storage resource is a member of, if applicable.
<code>blocksize</code>	Opt	number	The block size used by the storage resource, in kilobytes.
<code>cluster</code>	Opt	string	The index cluster that the resource is a member of, if applicable.
<code>fd_max</code>	Opt	number	The maximum number of file descriptors available.
<code>latency</code>	Opt	number	The latency reported by the resource, in milliseconds.
<code>parent</code>	Opt	string	A higher level object that this resource is owned by, if applicable.
<code>read_blocks</code>	Opt	number	The maximum possible number of blocks read per second during a polling period.
<code>read_latency</code>	Opt	number	For a polling period, the average amount of time elapsed until a read request is...
<code>read_ops</code>	Opt	number	The total number of read operations in the polling period.
<code>write_blocks</code>	Opt	number	The maximum possible number of blocks written per second during a polling period.
<code>write_latency</code>	Opt	number	For a polling period, the average amount of time elapsed until a write request is...
<code>write_ops</code>	Opt	number	The total number of write operations in the polling period.

All_Inventory.OS

Object `OS` · **Parent** `All_Inventory` · **Fields** 1 · **Tags** `system`, `version`

Constraint `tag=system` `tag=version`

Field	St	Type	Description
<code>os</code>	Rec	string	The operating system of the resource, such as Microsoft Windows Server 2008r2. Th... (Eval)

All_Inventory.User

Object User · **Parent** All_Inventory · **Fields** 8 · **Tags** user

Constraint tag=user

Field	St	Type	Description
interactive	Rec	boolean	Indicates whether a locally defined account on a resource can be interactively lo... (Eval)
password	Rec	string	Displays the stored password(s) for a locally defined account, if it has any. For... (Eval)
user	Rec	string	The full name of a locally defined account. (Eval)
shell	Opt	string	Indicates the shell program used by a locally defined account.
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_id	Opt	number	The user identification for a locally defined account.
user_priority	Opt	string	The priority of a locally-defined account.

All_Inventory.Virtual_OS

Object Virtual_OS · **Parent** All_Inventory · **Fields** 1 · **Tags** virtual

Constraint tag=virtual

Field	St	Type	Description
hypervisor	Rec	string	The hypervisor parent of a virtual guest OS.

Virtual_OS.Snapshot

Object Snapshot · **Parent** Virtual_OS · **Fields** 3 · **Tags** snapshot

Constraint tag=snapshot

Field	St	Type	Description
size	Rec	number	The snapshot file size, in megabytes.
snapshot	Rec	string	The name of a snapshot file.
time	Opt	timestamp	The time at which the snapshot was taken.

DLP

DLP_Incidents

Object DLP_Incidents · **Parent** BaseEvent · **Fields** 37 · **Tags** dlp, incident

Constraint (`cim\_DLP\_indexes`) tag=dlp tag=incident

Field	St	Type	Description
action	Rec	string	The action taken by the DLP device. (Eval)
category	Rec	string	The category of the DLP event. (Eval)
dest	Rec	string	The target of the DLP event. (Eval)
dlp_type	Rec	string	The type of DLP system that generated the event. (Eval)
dvc	Rec	string	The device that reported the DLP event. (Eval)
object	Rec	string	The name of the affected object. (Eval)
object_category	Rec	string	The category of the affected object. (Eval)
object_path	Rec	string	The path of the affected object. (Eval)
severity	Rec	string	The severity of the DLP event. (Eval)
signature	Rec	string	The name of the DLP event. (Eval)
src	Rec	string	The source of the DLP event. (Eval)
src_user	Rec	string	The source user of the DLP event. (Eval)
user	Rec	string	The target user of the DLP event. (Eval)
vendor_product	Rec	string	The vendor and product name of the DLP system. (Eval)
app	Opt	string	The application involved in the event.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_zone	Opt	string	The zone of the DLP target.
dvc_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_zone	Opt	string	The zone of the DLP device.
severity_id	Opt	string	The numeric or vendor specific severity indicator corresponding to the event seve...
signature_id	Opt	string	The unique identifier or event code of the event signature.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
src_user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_zone	Opt	string	The zone of the DLP source.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Data_Access

Data_Access

Object Data_Access · **Parent** BaseEvent · **Fields** 41 · **Tags** data, access

Constraint (`cim\_Data\_Access\_indexes`) tag=data tag=access

Field	St	Type	Description
action	Rec	string	The data access action taken by the user. (Eval)
app	Rec	string	The system, service, or application that generated the data access event. Example... (Eval)
dest	Rec	string	The destination where the data resides or where it is being accessed, such as the... (Eval)
object	Rec	string	Resource object name on which the action was performed by a user. (Eval)
object_attrs	Rec	string	The attributes that were updated on the updated resource object, if applicable. (Eval)
object_category	Rec	string	Generic name for the class of the updated resource object. Expected values may be... (Eval)
object_id	Rec	string	The unique updated resource object ID as presented to the system, if applicable... (Eval)
object_size	Rec	string	The size of the modified resource object. (Eval)
signature	Rec	string	A human-readable signature name.
src	Rec	string	The endpoint client host. (Eval)

Field	St	Type	Description
user	Rec	string	The user involved in the event, or who initiated the event. (Eval)
user_name	Rec	string	The user name of the user or entity performing the change. For account changes, t... (Eval)
vendor_account	Rec	string	The account that manages the user that initiated the request. (Eval)
vendor_product	Rec	string	The vendor and product name of the vendor. (Eval)
application_id	Opt	string	Application ID of the user
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_name	Opt	string	Name of the destination as defined by the Vendor.
dest_type	Opt	string	The type of the destination object, such as 'instance', 'storage', 'firewall', 'p...
dest_url	Opt	string	Url of the product, application or object.
dvc	Opt	string	The device that reported the data access event.
dvc_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
email	Opt	string	The email address of the user involved in the event, or who initiated the event.
object_path	Opt	string	The path of the modified resource object, if applicable, such as a file, director...
owner	Opt	string	Resource owner.
owner_email	Opt	string	Email of the resource owner.
owner_id	Opt	string	ID of the owner as defined by the vendor.
parent_object	Opt	string	Parent of the object name on which the action was performed by a user.
parent_object_category	Opt	string	Object category of the parent object on which action was performed by a user.
parent_object_id	Opt	string	Object id of the parent object on which the action was performed by a user.
signature_id	Opt	string	The unique identifier or event code of the event signature.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_agent	Opt	string	The user agent through which the request was made, such as Mozilla/5.0 (Macintosh...

Field	St	Type	Description
<code>user_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_email</code>	Opt	string	The email address of the user involved in the event, or who initiated the event.
<code>user_group</code>	Opt	string	The group of the user involved in the event, or who initiated the event.
<code>user_id</code>	Opt	string	The unique id of the user involved in the event. For authentication privilege esc...
<code>user_role</code>	Opt	string	The role of the user involved in the event, or who initiated the event.
<code>user_type</code>	Opt	string	The type of the user involved in the event or who initiated the event, such as IA...
<code>vendor_product_id</code>	Opt	string	The vendor and product name ID as defined by the vendor.
<code>vendor_region</code>	Opt	string	The data center region where the change occurred, such as us-west-2.

Prescribed values

`action` = accepted, commented, copied, created, deleted, disabled, downloaded, enabled, forwarded, granted, invited, locked, modified, moved, read, restarted, revoked, shared, started, stopped, uncommented, undeleted, unlocked, unshared, uploaded

`object_category` = collaboration, file, folder, comment, task, note

Databases

All_Databases

Object `All_Databases` · **Parent** `BaseEvent` · **Fields** 18 · **Tags** `database`

Constraint (``cim_Databases_indexes``) `tag=database`

Field	St	Type	Description
<code>cim_entity_zone</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest</code>	Opt	string	The destination of the database event. You can alias this from more specific fiel...
<code>dest_bunit</code>	Opt	string	The business unit of the destination.
<code>dest_category</code>	Opt	string	The category of the destination.
<code>dest_priority</code>	Opt	string	The priority of the destination.
<code>duration</code>	Opt	number	The amount of time for the completion of the database event, in seconds.

Field	St	Type	Description
object	Opt	string	The name of the database object.
response_time	Opt	number	The amount of time it took to receive a response in the database event, in second...
src	Opt	string	The source of the database event. You can alias this from more specific fields, s...
src_bunit	Opt	string	The business unit of the source.
src_category	Opt	string	The category of the source.
src_priority	Opt	string	The priority of the source.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user	Opt	string	Name of the database process user.
user_bunit	Opt	string	The business unit of the user.
user_category	Opt	string	The category associated with the user.
user_priority	Opt	string	The priority of the user.
vendor_product	Opt	string	The vendor and product name of the database system. This field can be automatical... (Eval)

All_Databases.Database_Instance

Object [Database_Instance](#) · **Parent** [All_Databases](#) · **Fields** 4 · **Tags** [instance](#)
Constraint tag=instance

Field	St	Type	Description
instance_name	Opt	string	The name of the database instance.
instance_version	Opt	string	The version of the database instance.
process_limit	Opt	number	The maximum number of processes that the database instance can handle.
session_limit	Opt	number	The maximum number of sessions that the database instance can handle.

Database_Instance.Instance_Stats

Object [Instance_Stats](#) · **Parent** [Database_Instance](#) · **Fields** 19 · **Tags** [stats](#)
Constraint tag=stats

Field	St	Type	Description
availability	Opt	string	The status of the database server.

Field	St	Type	Description
avg_executions	Opt	number	The average number of executions for the database instance.
dump_area_used	Opt	string	The amount of the database dump area that has been used.
instance_reads	Opt	number	The total number of reads for the database instance.
instance_writes	Opt	number	The total number of writes for the database instance.
number_of_users	Opt	number	The total number of users for the database instance.
processes	Opt	number	The number of processes currently running for the database instance.
sessions	Opt	number	The total number of sessions currently in use for the database instance.
sga_buffer_cache_size	Opt	number	The total size of the buffer cache for the database instance, in bytes.
sga_buffer_hit_limit	Opt	number	The maximum number of buffers that can be hit in the database instance without fi...
sga_data_dict_hit_ratio	Opt	number	The hit-to-miss ratio for the database instance's data dictionary.
sga_fixed_area_size	Opt	number	The size of the fixed area (also referred to as the fixed SGA) for the database i...
sga_free_memory	Opt	number	The total amount of free memory in the database instance SGA, in bytes.
sga_library_cache_size	Opt	number	The total library cache size for the database instance, in bytes.
sga_redo_log_buffer_size	Opt	number	The total size of the redo log buffer for the database instance, in bytes.
sga_shared_pool_size	Opt	number	The total size of the shared pool for this database instance, in bytes.
sga_sql_area_size	Opt	number	The total size of the SQL area for this database instance, in bytes.
start_time	Opt	timestamp	The total amount of uptime for the database instance.
tablespace_used	Opt	string	The total amount of tablespace used for the database instance, in bytes.

Prescribed values

availability = Available, Not Available

Database_Instance.Session_Info

Object Session_Info · **Parent** Database_Instance · **Fields** 15 · **Tags** session

Constraint tag=session

Field	St	Type	Description
buffer_cache_hit_ratio	Opt	number	The percentage of logical reads from the buffer during the session (1-physical re...
commits	Opt	number	The number of commits per second performed by the user associated with the sessio...
cpu_used	Opt	number	The number of CPU centiseconds used by the session. Divide this value by 100 to g...
cursor	Opt	number	The number of the cursor currently in use by the session.
elapsed_time	Opt	number	The total amount of time elapsed since the user started the session by logging in...
logical_reads	Opt	number	The total number of consistent gets and database block gets performed during the...
machine	Opt	string	The name of the logical host associated with the database instance.
memory_sorts	Opt	number	The total number of memory sorts performed during the session.
physical_reads	Opt	number	The total number of physical reads performed during the session.
seconds_in_wait	Opt	number	The seconds_in_wait depends on the value of wait_time. If wait_time = 0, seconds_...
session_id	Opt	string	The unique id that identifies the session.
session_status	Opt	string	The current status of the session.
table_scans	Opt	number	Number of table scans performed during the session.
wait_state	Opt	string	Provides the current wait state for the session. Can indicate that the session is...
wait_time	Opt	number	When wait_time = 0, the session is waiting. When wait_time has a nonzero value, i...

Prescribed values

session_status = Online, Offline

wait_state = WAITING, WAITED UNKNOWN, WAITED SHORT TIME, WAITED KNOWN TIME

Database_Instance.Lock_Info

Object `Lock_Info` · **Parent** `Database_Instance` · **Fields** 7 · **Tags** `lock`
Constraint `tag=lock`

Field	St	Type	Description
<code>last_call_minute</code>	Opt	number	Represents the amount of time elapsed since the session_status changed to its cur...
<code>lock_mode</code>	Opt	string	The mode of the lock on the object.
<code>lock_session_id</code>	Opt	string	The session identifier of the locked object.
<code>logon_time</code>	Opt	number	The database logon time for the session.
<code>obj_name</code>	Opt	string	The name of the locked object.
<code>os_pid</code>	Opt	string	The process identifier for the operating system.
<code>serial_num</code>	Opt	string	The serial number of the object.

`All_Databases.Database_Query`

Object `Database_Query` · **Parent** `All_Databases` · **Fields** 4 · **Tags** `query`
Constraint `tag=query`

Field	St	Type	Description
<code>query</code>	Opt	string	The full database query.
<code>query_id</code>	Opt	string	The identifier for the database query.
<code>query_time</code>	Opt	timestamp	The time the system initiated the database query.
<code>records_affected</code>	Opt	number	The number of records affected by the database query.

`Database_Query.Tablespace`

Object `Tablespace` · **Parent** `Database_Query` · **Fields** 5 · **Tags** `tablespace`
Constraint `tag=tablespace`

Field	St	Type	Description
<code>free_bytes</code>	Opt	number	The total amount of free space in the tablespace, in bytes.
<code>tablespace_name</code>	Opt	string	The name of the tablespace.
<code>tablespace_reads</code>	Opt	number	The number of tablespace reads carried out by the query.
<code>tablespace_status</code>	Opt	string	The status of the tablespace.
<code>tablespace_writes</code>	Opt	number	The number of tablespace writes carried out by the query.

Prescribed values

`tablespace_status` = Offline, Online, Read Only

`Database_Query.Query_Stats`

Object Query_Stats · **Parent** Database_Query · **Fields** 4 · **Tags** stats

Constraint tag=stats

Field	St	Type	Description
indexes_hit	Opt	string	The names of the indexes hit by the database query.
query_plan_hit	Opt	string	The name of the query plan hit by the query.
stored_procedures_called	Opt	string	The names of the stored procedures called by the query.
tables_hit	Opt	string	The names of the tables hit by the query.

Email

All_Email

Object All_Email · **Parent** BaseEvent · **Fields** 48 · **Tags** email

Constraint (`cim\_Email\_indexes`) tag=email

Field	St	Type	Description
action	Rec	string	Action taken by the reporting device. (Eval)
dest	Rec	string	The endpoint system to which the message was delivered. You can alias this from m... (Eval)
recipient	Rec	string	The recipient email addresses. (Eval)
recipient_domain	Rec	string	The domain name contained within the recipient email addresses. (Rex)
src	Rec	string	The system that sent the message. You can alias this from more specific fields, s... (Eval)
src_user	Rec	string	The email address of the message sender. (Eval)
src_user_domain	Rec	string	The domain name contained within the email address of the message sender. (Rex)
vendor_product	Rec	string	The vendor and product of the email server used for the email transaction. This f... (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
delay	Opt	number	Total sending delay in milliseconds.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
duration	Opt	number	The amount of time for the completion of the messaging event, in seconds.

Field	St	Type	Description
file_hash	Opt	string	The hashes for the files attached to the message, if any exist.
file_name	Opt	string	The names of the files attached to the message, if any exist.
file_size	Opt	number	The size of the files attached the message, in bytes.
internal_message_id	Opt	string	Host-specific unique message identifier (such as aid in sendmail, IMI in Domino...
message_id	Opt	string	The globally-unique message identifier.
message_info	Opt	string	Additional information about the message.
orig_dest	Opt	string	The original destination host of the message. The message destination host can ch...
orig_recipient	Opt	string	The original recipient of the message. The message recipient can change when the...
orig_src	Opt	string	The original source of the message.
process	Opt	string	The name of the email executable that carries out the message transaction, such a...
process_id	Opt	number	The numeric identifier of the process invoked to send the message.
protocol	Opt	string	The email protocol involved, such as SMTP or RPC.
recipient_count	Opt	number	The total number of intended message recipients. (Eval)
recipient_status	Opt	string	The recipient delivery status, if available.
response_time	Opt	number	The amount of time it took to receive a response in the messaging event, in secon...
retries	Opt	number	The number of times that the message was automatically resent because it was boun...
return_addr	Opt	string	The return address for the message.
size	Opt	number	The size of the message, in bytes.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
status_code	Opt	string	The status code associated with the message.

Field	St	Type	Description
subject	Opt	string	The subject of the message.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
url	Opt	string	The URL associated with the message, if any.
user	Opt	string	The user context for the process. This is not the email address for the sender. F...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
xdelay	Opt	string	Extended delay information for the message transaction. May contain details of al...
xref	Opt	string	An external reference. Can contain message IDs or recipient addresses from relate...

Prescribed values

action = delivered, blocked, quarantined, deleted

protocol = smtp, imap, pop3, mapi

All_Email.Filtering

Object Filtering · Parent All_Email · Fields 5 · Tags filter

Constraint tag=filter

Field	St	Type	Description
signature	Rec	string	The name of the filter applied.
filter_action	Opt	string	The status produced by the filter, such as 'accepted', 'rejected', or 'dropped'.
filter_score	Opt	number	Numeric indicator assigned to specific emails by an email filter.
signature_extra	Opt	string	Any additional information about the filter.
signature_id	Opt	string	The id associated with the filter name.

Endpoint

Ports

Object Ports · Parent BaseSearch · Fields 29

Constraint (none — derived dataset; inherits parent)

Field	St	Type	Description
dest	Rec	string	The endpoint for which the port is listening on. (Eval)
dest_port	Rec	number	Network port listening on the endpoint, such as 53.
src	Rec	string	The "remote" system connected to the listening port (if applicable). (Eval)
src_port	Rec	number	The "remote" port connected to the listening port (if applicable). (Eval)
transport	Rec	string	The network transport protocol associated with the listening port, such as tcp, u...
user	Rec	string	The user account associated with the listening port. (Eval)
vendor_product	Rec	string	The vendor and product name of the Endpoint solution that reported the event, suc... (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
creation_time	Opt	timestamp	The time at which the network port started listening on the endpoint.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_requires_av	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_timesync	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_update	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
process_guid	Opt	string	The globally unique identifier of the process assigned by the vendor_product.
process_id	Opt	string	The numeric identifier of the process assigned by the operating system.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
<code>src_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>src_requires_av</code>	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
<code>src_should_timesync</code>	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
<code>src_should_update</code>	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
<code>state</code>	Opt	string	The status of the listening port, such as established, listening, etc.
<code>tag</code>	Opt	string	This automatically generated field is used to access tags from within data models...
<code>transport_dest_port</code>	Opt	string	Calculated as transport/dest_port, such as tcp/53.
<code>user_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Processes

Object [Processes](#) · **Parent** [BaseSearch](#) · **Fields** 39

Constraint (*none* — *derived dataset; inherits parent*)

Field	St	Type	Description
<code>dest</code>	Rec	string	The endpoint for which the process was spawned. (Eval)
<code>loaded_file</code>	Rec	string	The file that was loaded. (Eval)
<code>original_file_name</code>	Rec	string	Original name of the file, not including path. Sometimes this field is similar to... (Eval)
<code>parent_process</code>	Rec	string	The full command string of the parent process (Eval)
<code>parent_process_name</code>	Rec	string	The friendly name of the parent process, such as notepad.exe. (Eval)
<code>process</code>	Rec	string	The full command string of the spawned process. Such as C:\WINDOWS\system32\cmd.e... (Eval)

Field	St	Type	Description
process_name	Rec	string	The friendly name of the process, such as notepad.exe. (Eval)
user	Rec	string	The current user linked to the running process. (Eval)
vendor_product	Rec	string	The vendor and product name of the Endpoint solution that reported the event, suc... (Eval)
action	Opt	string	The action taken by the endpoint.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
cpu_load_percent	Opt	number	CPU load consumed by the process (in percent).
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_is_expected	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_requires_av	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_timesync	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_update	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
mem_used	Opt	number	Memory used by the process (in bytes).
os	Opt	string	The operating system of the resource, such as Microsoft Windows Server 2008r2.
parent_process_exec	Opt	string	The executable name of the parent process.
parent_process_guid	Opt	string	The globally unique identifier of the parent process assigned by the vendor_produ...
parent_process_hash	Opt	string	The digest(s) of the parent process, such as , , etc.
parent_process_id	Opt	number	The numeric identifier of the parent process assigned by the operating system.
parent_process_path	Opt	string	The file path of the parent process, such as C:\Windows\System32\notepad.exe.

Field	St	Type	Description
parent_user	Opt	string	The original user under which the process was created. This field is extracted fo... (Eval)
process_current_directory	Opt	string	The current working directory used to spawn the process.
process_exec	Opt	string	The executable name of the process.
process_guid	Opt	string	The globally unique identifier of the process assigned by the vendor_product.
process_hash	Opt	string	The digest(s) of the process, such as , , etc.
process_id	Opt	number	The numeric identifier of the process assigned by the operating system.
process_integrity_level	Opt	string	The integrity level of the process.
process_path	Opt	string	The file path of the process, such as C:\Windows\System32\notepad.exe.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_id	Opt	string	The unique identifier of the user account which spawned the process.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values

process_integrity_level = protected process, system, high, medium high, medium, low, untrusted

Services

Object [Services](#) · **Parent** [BaseSearch](#) · **Fields** 33

Constraint (*none* — *derived dataset; inherits parent*)

Field	St	Type	Description
dest	Rec	string	The endpoint for which the service is installed. (Eval)
service	Rec	string	The full service name. (Eval)
service_id	Rec	string	The unique identifier of the service assigned by the operating system.. (Eval)

Field	St	Type	Description
service_name	Rec	string	The friendly service name. (Eval)
start_mode	Rec	string	The start mode for the service. (Eval)
status	Rec	string	The status of the service. (Eval)
user	Rec	string	The user account associated with the service. (Eval)
vendor_product	Rec	string	The vendor and product name of the Endpoint solution that reported the event, suc... (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
description	Opt	string	The description of the service.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_is_expected	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_requires_av	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_timesync	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_update	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
process_guid	Opt	string	The globally unique identifier of the process assigned by the vendor_product.
process_id	Opt	string	The numeric identifier of the process assigned by the operating system.
service_dll	Opt	string	The dynamic link library associated with the service.
service_dll_hash	Opt	string	The digest(s) of the dynamic link library associated with the service, such as <m...
service_dll_path	Opt	string	The file path to the dynamic link library associatied with the service, such as C:...

Field	St	Type	Description
<code>service_dll_signature_exists</code>	Opt	boolean	Whether or not the dynamic link library associated with the service has a digital...
<code>service_dll_signature_verified</code>	Opt	boolean	Whether or not the dynamic link library associated with the service has had it's...
<code>service_exec</code>	Opt	string	The executable name of the service.
<code>service_hash</code>	Opt	string	The digest(s) of the service, such as , , etc.
<code>service_path</code>	Opt	string	The file path of the service, such as C:\WINDOWS\system32\svchost.exe.
<code>service_signature_exists</code>	Opt	boolean	Whether or not the service has a digitally signed signature.
<code>service_signature_verified</code>	Opt	boolean	Whether or not the service has had it's digitally signed signature verified.
<code>tag</code>	Opt	string	This automatically generated field is used to access tags from within data models...
<code>user_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values

`start_mode` = disabled, manual, auto

`status` = critical, started, stopped, warning, installed

Filesystem

Object `Filesystem` · **Parent** `BaseSearch` · **Fields** 38

Constraint (*none* — *derived dataset; inherits parent*)

Field	St	Type	Description
<code>action</code>	Rec	string	The action performed on the resource. (Eval)
<code>dest</code>	Rec	string	The endpoint pertaining to the filesystem activity. (Eval)
<code>file_access_time</code>	Rec	timestamp	The time the file (the object of the event) was accessed.
<code>file_acl</code>	Rec	string	Access controls associated with the file affected by the event. (Eval)
<code>file_create_time</code>	Rec	timestamp	The time the file (the object of the event) was created.

Field	St	Type	Description
file_hash	Rec	string	A cryptographic identifier assigned to the file object affected by the event. (Eval)
file_modify_time	Rec	timestamp	The time the file (the object of the event) was altered.
file_name	Rec	string	The name of the file, such as notepad.exe. (Eval)
file_path	Rec	string	The path of the file, such as C:\Windows\System32\notepad.exe. (Eval)
file_size	Rec	number	The size of the file that is the object of the event, in kilobytes. (Eval)
process	Rec	string	The full command string of the spawned process. Such as C:\WINDOWS\system32\cmd.e... (Eval)
process_name	Rec	string	The friendly name of the process, such as notepad.exe. (Eval)
user	Rec	string	The user account associated with the filesystem access. (Eval)
vendor_product	Rec	string	The vendor and product name of the Endpoint solution that reported the event, suc... (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_requires_av	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_timesync	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_update	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
image	Opt	string	The binary file path or name that is tied to a process ID (PID) in events like pr...
parent_process	Opt	string	The full command string of the parent process (Eval)
parent_process_exec	Opt	string	The executable name of the parent process.

Field	St	Type	Description
parent_process_guid	Opt	string	The globally unique identifier of the parent process assigned by the vendor_produ...
parent_process_hash	Opt	string	The digest(s) of the parent process, such as , , etc.
parent_process_id	Opt	number	The numeric identifier of the parent process assigned by the operating system.
parent_process_name	Opt	string	The friendly name of the parent process, such as notepad.exe. (Eval)
parent_process_path	Opt	string	The file path of the parent process, such as C:\Windows\System32\notepad.exe.
process_exec	Opt	string	The executable name of the process.
process_guid	Opt	string	The globally unique identifier of the process assigned by the vendor_product.
process_hash	Opt	string	The digest(s) of the process, such as , , etc.
process_id	Opt	string	The numeric identifier of the process assigned by the operating system.
process_path	Opt	string	The file path of the process, such as C:\Windows\System32\notepad.exe.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values

action = acl_modified, created, deleted, modified, read

Registry

Object Registry · **Parent** BaseSearch · **Fields** 38

Constraint (none — derived dataset; inherits parent)

Field	St	Type	Description
action	Rec	string	The action performed on the resource. (Eval)
dest	Rec	string	The endpoint pertaining to the registry events. (Eval)

Field	St	Type	Description
process	Rec	string	The full command string of the spawned process. Such as C:\WINDOWS\system32\cmd.e... (Eval)
process_name	Rec	string	The friendly name of the process, such as notepad.exe. (Eval)
registry_key_name	Rec	string	The name of the registry key, such as PrinterDriverData. (Eval)
registry_path	Rec	string	The path to the registry value, such as \win\directory\directory2{676235CD-B656-... (Eval)
registry_value_data	Rec	string	The unaltered registry value. (Eval)
registry_value_name	Rec	string	The name of the registry value. (Eval)
registry_value_type	Rec	string	The type of the registry value. (Eval)
user	Rec	string	The user account associated with the registry access. (Eval)
vendor_product	Rec	string	The vendor and product name of the Endpoint solution that reported the event, suc... (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_requires_av	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_timesync	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
dest_should_update	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
image	Opt	string	The binary file path or name that is tied to a process ID (PID) in events like pr...
parent_process	Opt	string	The full command string of the parent process (Eval)
parent_process_exec	Opt	string	The executable name of the parent process.
parent_process_guid	Opt	string	The globally unique identifier of the parent process assigned by the vendor_produ...
parent_process_hash	Opt	string	The digest(s) of the parent process, such as , , etc.
parent_process_id	Opt	number	The numeric identifier of the parent process assigned by the operating system.
parent_process_name	Opt	string	The friendly name of the parent process, such as notepad.exe. (Eval)

Field	St	Type	Description
parent_process_path	Opt	string	The file path of the parent process, such as C:\Windows\System32\notepad.exe.
process_exec	Opt	string	The executable name of the process.
process_guid	Opt	string	The globally unique identifier of the process assigned by the vendor_product.
process_hash	Opt	string	The digest(s) of the process, such as , , etc.
process_id	Opt	string	The numeric identifier of the process assigned by the operating system.
process_path	Opt	string	The file path of the process, such as C:\Windows\System32\notepad.exe.
registry_hive	Opt	string	The logical grouping of registry keys, subkeys, and values.
registry_value_text	Opt	string	The textual representation of registry_value_data (if applicable).
status	Opt	string	The outcome of the registry action.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values

action = created, deleted, modified, read

registry_value_type = REG_BINARY, REG_DWORD, REG_DWORD_LITTLE_ENDIAN, REG_DWORD_BIG_ENDIAN, REG_EXPAND_SZ, REG_LINK, REG_MULTI_SZ, REG_NONE, REG_QWORD, REG_QWORD_LITTLE_ENDIAN, REG_SZ

registry_hive = HKEY_CURRENT_CONFIG, HKEY_CURRENT_USER, HKEY_LOCAL_MACHINE\SAM, HKEY_LOCAL_MACHINE\Security, HKEY_LOCAL_MACHINE\Software, HKEY_LOCAL_MACHINE\System, HKEY_USERS.DEFAULT

status = failure, success

Event_Signatures

Signatures

Object Signatures · **Parent** BaseEvent · **Fields** 9 · **Tags** track_event_signatures

Constraint (`cim\_Event\_Signatures\_indexes`) tag=track_event_signatures (signature=* OR signature_id=*)

Field	St	Type	Description
vendor_product	Rec	string	The vendor and product name of the technology that reported the event, such as Ca... (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest	Opt	string	System affected by the signature.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
signature	Opt	string	The human readable event name.
signature_id	Opt	string	The event name identifier (as supplied by the vendor).
tag	Opt	string	This automatically generated field is used to access tags from within data models...

Interprocess_Messaging

All_Messaging

Object All_Messaging · **Parent** BaseEvent · **Fields** 35 · **Tags** messaging

Constraint (`cim\_Interprocess\_Messaging\_indexes`) tag=messaging

Field	St	Type	Description
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest	Opt	string	The destination of the message. You can alias this from more specific fields, suc... (Eval)
dest_bunit	Opt	string	The business unit of the destination.
dest_category	Opt	string	The type of message destination.
dest_priority	Opt	string	The priority of the destination.
duration	Opt	number	The number of seconds from message call to message response. Can be derived by ge...
endpoint	Opt	string	The endpoint that the message accessed during the RPC (remote procedure call) tra...
endpoint_version	Opt	string	The version of the endpoint accessed during the RPC (remote procedure call) trans...
message	Opt	string	A command or reference that an RPC (remote procedure call) reads or responds to.

Field	St	Type	Description
message_consumed_time	Opt	timestamp	The time that the RPC (remote procedure call) read the message and was prepared t...
message_correlation_id	Opt	string	The message correlation identification value.
message_delivered_time	Opt	timestamp	The time that the message producer sent the message.
message_delivery_mode	Opt	string	The message delivery mode. Possible values depend on the type of message-oriented...
message_expiration_time	Opt	timestamp	The time that the message expired.
message_id	Opt	string	The message identification.
message_priority	Opt	string	The priority of the message. Important jobs that the message queue should answer...
message_properties	Opt	string	An arbitrary list of message properties. The set of properties displayed depends...
message_received_time	Opt	timestamp	The time that the message was received by a message-oriented middleware (MOM) sol...
message_redelivered	Opt	boolean	Indicates whether or not the message was redelivered.
message_reply_dest	Opt	string	The name of the destination for replies to the message.
message_type	Opt	string	The type of message, such as call or reply.
parameters	Opt	string	Arguments that have been passed to an endpoint by a REST call or something simila...
payload	Opt	string	The message payload.
payload_type	Opt	string	The type of payload in the message. The payload type can be text (such as json, x...
request_payload	Opt	string	The content of the message request.
request_payload_type	Opt	string	The type of payload in the message request. The payload type can be text (such as...
request_sent_time	Opt	timestamp	The time that the message request was sent.
response_code	Opt	string	The response status code sent by the receiving server. Ranges between 200 and 404.
response_payload_type	Opt	string	The type of payload in the message response. The payload type can be text (such a...
response_received_time	Opt	timestamp	The time that the message response was received.

Field	St	Type	Description
<code>response_time</code>	Opt	number	The amount of time it took to receive a response, in seconds.
<code>return_message</code>	Opt	string	The response status message sent by the message server.
<code>rpc_protocol</code>	Opt	string	The protocol that the message server uses for remote procedure calls (RPC). Possi...
<code>status</code>	Opt	boolean	The status of the message response.
<code>tag</code>	Opt	string	This automatically generated field is used to access tags from within data models...

Prescribed values

`dest_category` = queue, topic

`status` = pass, fail

Intrusion_Detection

IDS_Attacks

Object `IDS_Attacks` · **Parent** `BaseEvent` · **Fields** 35 · **Tags** `ids`, `attack`

Constraint (``cim_Intrusion_Detection_indexes``) `tag=ids` `tag=attack`

Field	St	Type	Description
<code>category</code>	Rec	string	The vendor-provided category of the triggered signature, such as spyware. Note: T... (Eval)
<code>dest</code>	Rec	string	The destination of the attack detected by the intrusion detection system (IDS). Y... (Eval)
<code>dvc</code>	Rec	string	The device that detected the intrusion event. You can alias this from more specif... (Eval)
<code>ids_type</code>	Rec	string	The type of IDS that generated the event. (Eval)
<code>severity</code>	Rec	string	The severity of the network protection event. Note: This field is a string. Use s... (Eval)
<code>signature</code>	Rec	string	The name of the intrusion detected on the client (the src), such as PlugAndPlay_B... (Eval)
<code>src</code>	Rec	string	The source involved in the attack detected by the IDS. You can alias this from mo... (Eval)
<code>user</code>	Rec	string	The user involved with the intrusion detection event. (Eval)
<code>vendor_product</code>	Rec	string	The vendor and product name of the IDS or IPS system that detected the vulnerabil... (Eval)

Field	St	Type	Description
action	Opt	string	The action taken by the intrusion detection system (IDS).
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_ip	Opt	string	The IP address of the destination.
dest_port	Opt	number	The destination port of the intrusion.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_type	Opt	string	The type of the destination object, such as 'instance', 'storage', 'firewall'.
dvc_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
file_hash	Opt	string	A cryptographic identifier assigned to the file object affected by the event.
file_name	Opt	string	The name of the file, such as notepad.exe.
file_path	Opt	string	The path of the file, such as C:\Windows\System32\notepad.exe.
severity_id	Opt	string	The numeric or vendor specific severity indicator corresponding to the event seve...
signature_id	Opt	string	The unique identifier or event code of the event signature.
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_ip	Opt	string	The ip address of the source.
src_port	Opt	number	The port number of the source.
src_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
transport	Opt	string	The OSI layer 4 (transport) protocol of the intrusion, in lower case.
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values

ids_type = network, host, application, wireless

severity = critical, high, medium, low, informational

action = allowed, blocked

JVM

JVM

Object JVM · **Parent** BaseEvent · **Fields** 3 · **Tags** jvm

Constraint (`cim\_JVM\_indexes`) tag=jvm

Field	St	Type	Description
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
jvm_description	Opt	string	A description field provided in some data sources.
tag	Opt	string	This automatically generated field is used to access tags from within data models...

JVM.Threading

Object Threading · **Parent** JVM · **Fields** 12 · **Tags** threading

Constraint tag=threading

Field	St	Type	Description
cm_enabled	Opt	boolean	Indicates whether thread contention monitoring is enabled.
cm_supported	Opt	boolean	Indicates whether the JVM supports thread contention monitoring.
cpu_time_enabled	Opt	boolean	Indicates whether thread CPU time measurement is enabled.
cpu_time_supported	Opt	boolean	Indicates whether the Java virtual machine supports CPU time measurement for the...
current_cpu_time	Opt	number	CPU-space time taken by the JVM, in seconds.
current_user_time	Opt	number	User-space time taken by the JVM, in seconds.
daemon_thread_count	Opt	number	The JVM's current daemon count.
omu_supported	Opt	boolean	Indicates whether the JVM supports monitoring of object monitor usage.
peak_thread_count	Opt	number	The JVM's peak thread count.
synch_supported	Opt	boolean	Indicates whether the JVM supports monitoring of ownable synchronizer usage.
thread_count	Opt	number	The JVM's current thread count.

Field	St	Type	Description
<code>threads_started</code>	Opt	number	The total number of threads started in the JVM.

Prescribed values

`cm_enabled` = true, false, 1, 0

`cm_supported` = true, false, 1, 0

`cpu_time_enabled` = true, false, 1, 0

`cpu_time_supported` = true, false, 1, 0

`omu_supported` = true, false, 1, 0

`synch_supported` = true, false, 1, 0

JVM.Runtime

Object `Runtime` · **Parent** `JVM` · **Fields** 5 · **Tags** `runtime`

Constraint `tag=runtime`

Field	St	Type	Description
<code>process_name</code>	Opt	string	Process name of the JVM process.
<code>start_time</code>	Opt	timestamp	Start time of the JVM process.
<code>uptime</code>	Opt	number	Uptime of the JVM process, in seconds.
<code>vendor_product</code>	Opt	string	The JVM product or service. This field can be automatically populated by the the... (Eval)
<code>version</code>	Opt	string	Version of the JVM.

JVM.OS

Object `OS` · **Parent** `JVM` · **Fields** 13 · **Tags** `os`

Constraint `tag=os`

Field	St	Type	Description
<code>committed_memory</code>	Opt	number	Amount of memory committed to the JVM, in bytes.
<code>cpu_time</code>	Opt	number	Amount of CPU time taken by the JVM, in seconds.
<code>free_physical_memory</code>	Opt	number	Amount of free physical memory remaining to the JVM, in bytes.
<code>free_swap</code>	Opt	number	Amount of free swap memory remaining to the JVM, in bytes.
<code>max_file_descriptors</code>	Opt	number	Maximum file descriptors available to the JVM.
<code>open_file_descriptors</code>	Opt	number	Number of file descriptors opened by the JVM.
<code>os</code>	Opt	string	OS that the JVM is running on.
<code>os_architecture</code>	Opt	string	OS architecture that the JVM is running on.

Field	St	Type	Description
os_version	Opt	string	OS version that the JVM is running on.
physical_memory	Opt	number	Physical memory available to the OS that the JVM is running on, in bytes.
swap_space	Opt	number	Swap memory space available to the OS that the JVM is running on, in bytes.
system_load	Opt	number	System load of the OS that the JVM is running on.
total_processors	Opt	number	Total processor cores available to the OS that the JVM is running on.

JVM.Compilation

Object [Compilation](#) · **Parent** [JVM](#) · **Fields** 1 · **Tags** [compilation](#)
Constraint [tag=compilation](#)

Field	St	Type	Description
compilation_time	Opt	number	Time taken by JIT compilation, in seconds.

JVM.Classloading

Object [Classloading](#) · **Parent** [JVM](#) · **Fields** 3 · **Tags** [classloading](#)
Constraint [tag=classloading](#)

Field	St	Type	Description
current_loaded	Opt	number	The current count of classes loaded in the JVM.
total_loaded	Opt	number	The total count of classes loaded in the JVM.
total_unloaded	Opt	number	The total count of classes unloaded from the JVM.

JVM.Memory

Object [Memory](#) · **Parent** [JVM](#) · **Fields** 9 · **Tags** [memory](#)
Constraint [tag=memory](#)

Field	St	Type	Description
heap_committed	Opt	number	Committed amount of heap memory used by the JVM, in bytes.
heap_initial	Opt	number	Initial amount of heap memory used by the JVM, in bytes.
heap_max	Opt	number	Maximum amount of heap memory used by the JVM, in bytes.
heap_used	Opt	number	Heap memory used by the JVM, in bytes.

Field	St	Type	Description
<code>non_heap_committed</code>	Opt	number	Committed amount of non-heap memory used by the JVM, in bytes.
<code>non_heap_initial</code>	Opt	number	Initial amount of non-heap memory used by the JVM, in bytes.
<code>non_heap_max</code>	Opt	number	Maximum amount of non-heap memory used by the JVM, in bytes.
<code>non_heap_used</code>	Opt	number	Non-heap memory used by the JVM, in bytes.
<code>objects_pending</code>	Opt	number	Number of objects pending in the JVM.

Malware

Malware_Attacks

Object `Malware_Attacks` · **Parent** `BaseEvent` · **Fields** 31 · **Tags** `malware`, `attack`

Constraint (``cim_Malware_indexes``) `tag=malware tag=attack`

Field	St	Type	Description
<code>action</code>	Rec	string	The action taken by the reporting device. (Eval)
<code>category</code>	Rec	string	The category of the malware event, such as keylogger or ad-supported program. Not... (Eval)
<code>date</code>	Rec	string	The date of the malware event. (Eval)
<code>dest</code>	Rec	string	The system that was affected by the malware event. You can alias this from more s... (Eval)
<code>dest_nt_domain</code>	Rec	string	The NT domain of the destination, if applicable. (Eval)
<code>severity</code>	Rec	string	The severity of the network protection event. Note: This field is a string. Use s... (Eval)
<code>signature</code>	Rec	string	The name of the malware infection detected on the client (the dest), such as Troj... (Eval)
<code>user</code>	Rec	string	The user involved in the malware event. (Eval)
<code>vendor_product</code>	Rec	string	The vendor and product name of the endpoint protection system, such as Symantec A... (Eval)
<code>cim_entity_zone</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_ip</code>	Opt	string	The IP address of the destination.
<code>dest_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
<code>dest_requires_av</code>	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
<code>file_hash</code>	Opt	string	The hash of the file with suspected malware.
<code>file_name</code>	Opt	string	The name of the file with suspected malware.
<code>file_path</code>	Opt	string	The full file path of the file with suspected malware.
<code>severity_id</code>	Opt	string	The numeric or vendor specific severity indicator corresponding to the event seve...
<code>signature_id</code>	Opt	string	The unique identifier or event code of the event signature.
<code>src</code>	Opt	string	The source of the endpoint event, such as a DAT file relay server. You can alias...
<code>src_bunit</code>	Opt	string	The business unit of the source.
<code>src_category</code>	Opt	string	The category of the source.
<code>src_ip</code>	Opt	string	The ip address of the source.
<code>src_priority</code>	Opt	string	The priority of the source.
<code>src_user</code>	Opt	string	The reported sender of an email-based attack.
<code>tag</code>	Opt	string	This automatically generated field is used to access tags from within data models...
<code>url</code>	Opt	string	A URL containing more information about the vulnerability.
<code>user_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values

`action` = allowed, blocked, deferred

`severity` = critical, high, medium, low, informational

Malware_Operations

Object `Malware_Operations` · **Parent** `BaseSearch` · **Fields** 13

Constraint (*none — derived dataset; inherits parent*)

Field	St	Type	Description
<code>dest</code>	Rec	string	The system where the malware operations event occurred. (Eval)
<code>dest_nt_domain</code>	Rec	string	The NT domain of the dest system, if applicable. (Eval)
<code>product_version</code>	Rec	string	The product version of the malware operations product.

Field	St	Type	Description
<code>signature_version</code>	Rec	string	The version of the malware signature bundle in a signature update operations even...
<code>vendor_product</code>	Rec	string	The vendor product name of the malware operations product. (Eval)
<code>_time</code>	Opt	timestamp	The event timestamp expressed in Unix time.
<code>cim_entity_zone</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_ip</code>	Opt	string	The IP address of the destination.
<code>dest_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_requires_av</code>	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
<code>tag</code>	Opt	string	This automatically generated field is used to access tags from within data models...

Network_Resolution

DNS

Object `DNS` · **Parent** `BaseEvent` · **Fields** 32 · **Tags** `network`, `resolution`, `dns`

Constraint (``cim_Network_Resolution_indexes``) `tag=network` `tag=resolution` `tag=dns`

Field	St	Type	Description
<code>answer</code>	Rec	string	Resolved address for the query. (Eval)
<code>dest</code>	Rec	string	The destination of the network resolution event. You can alias this from more spe... (Eval)
<code>message_type</code>	Rec	string	Type of DNS message. (Eval)
<code>query</code>	Rec	string	The domain which needs to be resolved. Applies to messages of type 'Query'. (Eval)
<code>reply_code</code>	Rec	string	The return code for the response. For details, see the Domain Name System Paramet... (Lookup)
<code>reply_code_id</code>	Rec	string	The numerical id or name of a return code. For details, see the Domain Name Syste... (Eval)
<code>vendor_product</code>	Rec	string	The vendor product name of the DNS server. The Splunk platform can derive this fi... (Eval)
<code>additional_answer_count</code>	Opt	number	Number of entries in the 'additional' section of the DNS message.

Field	St	Type	Description
answer_count	Opt	number	Number of entries in the answer section of the DNS message. (Eval)
authority_answer_count	Opt	number	Number of entries in the 'authority' section of the DNS message.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_bunit	Opt	string	The business unit of the destination.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_ip	Opt	string	The IP address of the destination.
dest_port	Opt	number	The destination port number.
dest_priority	Opt	string	The priority of the destination, if applicable.
duration	Opt	number	The time taken by the network resolution event, in seconds.
name	Opt	string	The name of the DNS event.
query_count	Opt	number	Number of entries that appear in the 'Questions' section of the DNS query. (Eval)
query_type	Opt	string	Number of entries that appear in the 'Questions' section of the DNS query.
record_type	Opt	string	The DNS resource record type. For details, see the List of DNS record types on on...
response_time	Opt	number	The amount of time it took to receive a response in the network resolution event...
src	Opt	string	The source of the network resolution event. You can alias this from more specific...
src_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
src_ip	Opt	string	The ip address of the source.
src_port	Opt	number	The port number of the source.
src_priority	Opt	string	The priority of the source.
tag	Opt	string	This automatically generated field is used to access tags from within data models...

Field	St	Type	Description
<code>transaction_id</code>	Opt	number	The unique numerical transaction id of the network resolution event.
<code>transport</code>	Opt	string	The transport protocol used by the network resolution event.
<code>ttl</code>	Opt	number	The time-to-live of the network resolution event, in seconds.

Prescribed values

`message_type` = Query, Response

`reply_code` = No Error, Format Error, Server Failure, Non-Existent Domain, etc.

`reply_code_id` = 0, NoError, 1, FormErr, 2, ServFail, 3, NXDomain, etc.

`query_type` = Query, IQuery, Status, Notify, Update, A, MX, NS, PTR

Network_Sessions

All_Sessions

Object `All_Sessions` · **Parent** `BaseEvent` · **Fields** 27 · **Tags** `network`, `session`

Constraint (``cim_Network_Sessions_indexes``) `tag=network` `tag=session`

Field	St	Type	Description
<code>dest_dns</code>	Rec	string	The domain name system address of the destination for a network session event. (Eval)
<code>dest_ip</code>	Rec	string	The internal IP address allocated to the client initializing a network session. F... (Eval)
<code>dest_mac</code>	Rec	string	The internal MAC address of the network session client. For DHCP events, this is... (Eval)
<code>dest_nt_host</code>	Rec	string	The NetBIOS name of the client initializing a network session. (Eval)
<code>dvc</code>	Rec	string	The device that reported the session event. You can alias this from more specific... (Eval)
<code>user</code>	Rec	string	The user in a network session event, where applicable. For example, a VPN session... (Eval)
<code>vendor_product</code>	Rec	string	The full name of the Dynamic Host Configuration Protocol (DHCP) or DNS server inv... (Eval)
<code>action</code>	Opt	string	The action taken by the reporting device.
<code>cim_entity_zone</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_bunit</code>	Opt	string	The business unit of the destination.

Field	St	Type	Description
<code>dest_category</code>	Opt	string	The category of the destination.
<code>dest_priority</code>	Opt	string	The priority of the destination.
<code>duration</code>	Opt	number	The amount of time for the completion of the network session event, in seconds.
<code>response_time</code>	Opt	number	The amount of time it took to receive a response in the network session event, in...
<code>signature</code>	Opt	string	An indication of the type of network session event.
<code>signature_id</code>	Opt	string	The unique identifier or event code of the event signature.
<code>src_bunit</code>	Opt	string	The business unit of the source.
<code>src_category</code>	Opt	string	The category of the source.
<code>src_dns</code>	Opt	string	The external domain name of the client initializing a network session. Not applic...
<code>src_ip</code>	Opt	string	The IP address of the client initializing a network session. Not applicable for D...
<code>src_mac</code>	Opt	string	The MAC address of the client initializing a network session. Not applicable for...
<code>src_nt_host</code>	Opt	string	The NetBIOS name of the client initializing a network session. Not applicable for...
<code>src_priority</code>	Opt	string	The priority of the source.
<code>tag</code>	Opt	string	This automatically generated field is used to access tags from within data models...
<code>user_bunit</code>	Opt	string	The business unit associated with the user.
<code>user_category</code>	Opt	string	The category of the user.
<code>user_priority</code>	Opt	string	The priority of the user.

Prescribed values

`action` = started, blocked, ended

All_Sessions.DHCP

Object DHCP · **Parent** All_Sessions · **Fields** 2 · **Tags** dhcp

Constraint tag=dhcp

Field	St	Type	Description
<code>lease_duration</code>	Opt	number	The duration of the Dynamic Host Configuration Protocol (DHCP) lease, in seconds.

Field	St	Type	Description
lease_scope	Opt	string	The consecutive range of possible IP addresses that the Dynamic Host Configuratio...

Network_Traffic

All_Traffic

Object All_Traffic · **Parent** BaseEvent · **Fields** 66 · **Tags** network, communicate
Constraint (`cim\_Network\_Traffic\_indexes`) tag=network tag=communicate

Field	St	Type	Description
action	Rec	string	The action taken by the network device. (Eval)
bytes	Rec	number	Total count of bytes handled by this device/interface (bytes_in + bytes_out). (Eval)
bytes_in	Rec	number	How many bytes this device/interface received. (Eval)
bytes_out	Rec	number	How many bytes this device/interface transmitted. (Eval)
dest	Rec	string	The destination of the network traffic (the remote host). You can alias this from... (Eval)
dest_port	Rec	number	The destination port of the network traffic. Note: Do not translate the value of... (Eval)
dvc	Rec	string	The device that reported the traffic event. You can alias this from more specific... (Eval)
rule	Rec	string	The rule name that defines the action that was taken in the event. Note: Use rule... (Eval)
src	Rec	string	The source of the network traffic (the client requesting the connection). You can... (Eval)
src_port	Rec	string	The source port of the network traffic. Note: Do not translate the value of this... (Eval)
transport	Rec	string	The OSI layer 4 (transport) protocol of the traffic observed, in lower case. (Eval)
user	Rec	string	The user that requested the traffic flow. (Eval)
vendor_product	Rec	string	The vendor and product of the device generating the network event. This field can... (Eval)
app	Opt	string	The application protocol of the traffic.
channel	Opt	number	The 802.11 channel used by a wireless network.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_interface	Opt	string	The interface that is listening remotely or receiving packets locally. Can also b...
dest_ip	Opt	string	The IP address of the destination.
dest_mac	Opt	string	The destination TCP/IP layer 2 Media Access Control (MAC) address of a packet's d...
dest_priority	Opt	string	The destination priority, if applicable.
dest_translated_ip	Opt	string	The NATed IPv4 or IPv6 address to which a packet has been sent.
dest_translated_port	Opt	number	The NATed port to which a packet has been sent. Note: Do not translate the values...
dest_zone	Opt	string	The network zone of the destination.
direction	Opt	string	The direction the packet is traveling.
duration	Opt	number	The amount of time for the completion of the network event, in seconds.
dvc_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_ip	Opt	string	The ip address of the device.
dvc_mac	Opt	string	The device TCP/IP layer 2 Media Access Control (MAC) address of a packet's destin...
dvc_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_zone	Opt	string	The network zone of the device.
flow_id	Opt	string	Unique identifier for this traffic stream, such as a netflow, jflow, or cflow.
icmp_code	Opt	string	The RFC 2780 or RFC 4443 human-readable code value of the traffic, such as Destin...
icmp_type	Opt	number	The RFC 2780 or RFC 4443 numeric value of the traffic. See the ICMP Type Numbers...
packets	Opt	number	The total count of packets handled by this device/interface (packets_in + packets... (Eval)
packets_in	Opt	number	The total count of packets received by this device/interface. (Eval)

Field	St	Type	Description
packets_out	Opt	number	The total count of packets transmitted by this device/interface. (Eval)
process_guid	Opt	string	The globally unique identifier of the process assigned by the vendor_product.
process_id	Opt	string	The numeric identifier of the process assigned by the operating system.
protocol	Opt	string	The OSI layer 3 (network) protocol of the traffic observed, in lower case. For ex...
protocol_version	Opt	string	Version of the OSI layer 3 protocol, in lower case.
response_time	Opt	number	The amount of time it took to receive a response in the network event, in seconds.
rule_id	Opt	string	The vendor-specific unique identifier of the rule. Examples: 0x00011f0000011f00...
session_id	Opt	string	The session identifier. Multiple transactions build a session.
src_bunit	Opt	string	The business unit of the network traffic source.
src_category	Opt	string	The category of the network traffic source.
src_interface	Opt	string	The interface that is listening locally or sending packets remotely. Can also be...
src_ip	Opt	string	The ip address of the source.
src_mac	Opt	string	The source TCP/IP layer 2 Media Access Control (MAC) address of a packet's destin...
src_priority	Opt	string	The priority of the source, if applicable.
src_translated_ip	Opt	string	The NATed IPv4 or IPv6 address from which a packet has been sent.
src_translated_port	Opt	number	The NATed port from which a packet has been sent. Note: Do not translate the valu...
src_zone	Opt	string	The network zone of the source.
ssid	Opt	string	The 802.11 service set identifier (ssid) assigned to a wireless session.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
tcp_flag	Opt	string	The TCP flag or multiple flags specified in the event.
tos	Opt	string	The combination of source and destination IP ToS (type of service) values in the...

Field	St	Type	Description
<code>ttl</code>	Opt	number	The 'time to live' of a packet or diagram, in seconds.
<code>user_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>vendor_account</code>	Opt	string	The account associated with the network traffic.
<code>vlan</code>	Opt	string	The virtual local area network (VLAN) specified in the record.
<code>wifi</code>	Opt	string	The wireless standard(s) in use, such as 802.11a, 802.11b, 802.11g, or 802.11n.

Prescribed values

`action` = allowed, blocked, teardown

`transport` = tcp, udp, icmp

`direction` = inbound, outbound

`icmp_type` = 0-254

`tcp_flag` = SYN, ACK, FIN, RST, URG, PSH

Performance

All_Performance

Object `All_Performance` · **Parent** `BaseEvent` · **Fields** 10 · **Tags** `performance`, `cpu`, `facilities`, `memory`, `storage`, `network`, `os`, `time`, `synchronize`, `uptime`

Constraint (``cim_Performance_indexes``) `tag=performance (tag=cpu OR tag=facilities OR tag=memory OR tag=storage OR tag=network OR (tag=os ((tag=time tag=synchronize) OR tag=uptime)))`

Field	St	Type	Description
<code>dest</code>	Rec	string	The system where the event occurred, usually a facilities resource such as a rack... (Eval)
<code>cim_entity_zone</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_priority</code>	Opt	string	The priority of the system where the performance event occurred.
<code>dest_should_timesync</code>	Opt	boolean	Indicates whether or not the system where the performance event occurred should t...
<code>dest_should_update</code>	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
hypervisor_id	Opt	string	The ID of the virtualization hypervisor.
resource_type	Opt	string	The type of facilities resource involved in the performance event, such as a rack...
tag	Opt	string	This automatically generated field is used to access tags from within data models...

All_Performance.CPU

Object CPU · **Parent** All_Performance · **Fields** 4 · **Tags** cpu

Constraint tag=cpu

Field	St	Type	Description
cpu_load_percent	Rec	number	The amount of CPU load reported by the controller in percentage points.
cpu_load_mhz	Opt	number	The amount of CPU load reported by the controller in megahertz.
cpu_time	Opt	number	The number of CPU seconds consumed by processes.
cpu_user_percent	Opt	number	Percentage of CPU user time consumed by processes.

All_Performance.Facilities

Object Facilities · **Parent** All_Performance · **Fields** 3 · **Tags** facilities

Constraint tag=facilities

Field	St	Type	Description
temperature	Rec	number	Average temperature of the facilities resource, in degrees Celsius.
fan_speed	Opt	number	The speed of the cooling fan in the facilities resource, in rotations per second.
power	Opt	number	Amount of power consumed by the facilities resource, in kW.

All_Performance.Memory

Object Memory · **Parent** All_Performance · **Fields** 7 · **Tags** memory

Constraint tag=memory

Field	St	Type	Description
mem	Rec	number	The total amount of memory capacity reported by the resource, in megabytes.
mem_free	Rec	number	The free amount of memory reported by the resource, in megabytes.
mem_used	Rec	number	The used amount of memory reported by the resource, in megabytes.

Field	St	Type	Description
mem_committed	Opt	number	The committed amount of memory reported by the resource, in megabytes.
swap	Opt	number	The total swap space size, in megabytes, if applicable.
swap_free	Opt	number	The free swap space size, in megabytes, if applicable.
swap_used	Opt	number	The used swap space size, in megabytes, if applicable.

All_Performance.Storage

Object Storage · **Parent** All_Performance · **Fields** 19 · **Tags** storage

Constraint tag=storage

Field	St	Type	Description
storage_free	Rec	number	The free amount of storage capacity reported by the resource, in megabytes.
storage_free_percent	Rec	number	The percentage of storage capacity reported by the resource that is free.
storage_used	Rec	number	The used amount of storage capacity reported by the resource, in megabytes.
storage_used_percent	Rec	number	The percentage of storage capacity reported by the resource that is used.
array	Opt	string	The array that the resource is a member of, if applicable.
blocksize	Opt	number	Block size used by the storage resource, in kilobytes.
cluster	Opt	string	The cluster that the resource is a member of, if applicable.
fd_max	Opt	number	The maximum number of available file descriptors.
fd_used	Opt	number	The current number of open file descriptors.
latency	Opt	number	The latency reported by the resource, in milliseconds.
mount	Opt	string	The mount point of a storage resource.
parent	Opt	string	A generic indicator of hierarchy. For instance, a disk event might include the ar...
read_blocks	Opt	number	Number of blocks read.
read_latency	Opt	number	The latency of read operations, in milliseconds.
read_ops	Opt	number	Number of read operations.
storage	Opt	number	The total amount of storage capacity reported by the resource, in megabytes.
write_blocks	Opt	number	The number of blocks written by the resource.

Field	St	Type	Description
<code>write_latency</code>	Opt	number	The latency of write operations, in milliseconds.
<code>write_ops</code>	Opt	number	The total number of write operations processed by the resource.

All_Performance.Network

Object `Network` · **Parent** `All_Performance` · **Fields** 2 · **Tags** `network`

Constraint `tag=network`

Field	St	Type	Description
<code>throughput</code>	Rec	string	The current throughput reported by the service, in bytes.
<code>throughput_max</code>	Opt	number	The maximum possible throughput reported by the service, in bytes.

All_Performance.OS

Object `OS` · **Parent** `All_Performance` · **Fields** 2 · **Tags** `os`

Constraint `tag=os`

Field	St	Type	Description
<code>signature</code>	Rec	string	The event description signature, if available.
<code>signature_id</code>	Opt	string	The unique identifier or event code of the event signature.

OS.Timesync

Object `Timesync` · **Parent** `OS` · **Fields** 1 · **Tags** `time`, `synchronize`

Constraint `tag=time` `tag=synchronize`

Field	St	Type	Description
<code>action</code>	Rec	string	The result of a time sync event. (Eval)

Prescribed values

`action` = success, failure

OS.Uptime

Object `Uptime` · **Parent** `OS` · **Fields** 1 · **Tags** `uptime`

Constraint `tag=uptime`

Field	St	Type	Description
<code>uptime</code>	Rec	string	The uptime of the compute resource, in seconds. (Eval)

Splunk_Audit

Internal Splunk audit/telemetry model — populated by Splunk; vendor add-ons normally do not map here.

Datamodel_Acceleration

Object `Datamodel_Acceleration` · **Parent** `BaseSearch` · **Fields** 18

Constraint (*none* — *derived dataset; inherits parent*)

Field	St	Type	Description
<code>access_count</code>	Opt	number	The number of times the data model summary has been accessed since it was created.
<code>access_time</code>	Opt	timestamp	The timestamp of the most recent access of the data model summary.
<code>app</code>	Opt	string	The application context in which the data model summary was accessed.
<code>buckets</code>	Opt	number	The number of index buckets spanned by the data model acceleration summary.
<code>buckets_size</code>	Opt	number	The total size of the buckets spanned by the data model acceleration summary.
<code>complete</code>	Opt	number	The percentage of the data model summary that is currently complete.
<code>cron</code>	Opt	string	The cron expression used to accelerate the data model.
<code>datamodel</code>	Opt	string	The name of the data model accelerated.
<code>digest</code>	Opt	string	A hash of the current data model contents.
<code>earliest</code>	Opt	timestamp	The earliest time that the data model summary was accessed.
<code>is_inprogress</code>	Opt	boolean	Indicates whether the data model acceleration is currently in progress.
<code>last_error</code>	Opt	string	The text of the last error reported during the data model acceleration.
<code>last_sid</code>	Opt	string	The search id of the last acceleration attempt.
<code>latest</code>	Opt	timestamp	The most recent acceleration timestamp of the data model.
<code>mod_time</code>	Opt	timestamp	The timestamp of the most recent modification to the data model acceleration.
<code>retention</code>	Opt	number	The length of time that data model accelerations are retained, in seconds.
<code>size</code>	Opt	number	The amount of storage space the data model's acceleration summary takes up, in by...
<code>summary_id</code>	Opt	string	The unique id of the data model acceleration summary.

Prescribed values`is_inprogress` = true, false, 1, 0**Search_Activity****Object** `Search_Activity` · **Parent** `BaseEvent` · **Fields** 15**Constraint** `index=_audit action=search search_id=*`

Field	St	Type	Description
<code>cim_entity_zone</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>datamodel</code>	Opt	string	The name of the datamodel (for datamodel acceleration searches). (Eval)
<code>info</code>	Opt	string	The action of the search (granted, completed, cancelled, failed).
<code>savedsearch_name</code>	Opt	string	The name of the saved search. (Eval)
<code>search</code>	Opt	string	The SPL search syntax. (Eval)
<code>search_alias</code>	Opt	string	Short description of the type of search being run, such as the name of the search... (Eval)
<code>search_et</code>	Opt	string	The earliest time of the search.
<code>search_id</code>	Opt	string	The ID of the search. (Eval)
<code>search_lt</code>	Opt	string	The latest time of the search.
<code>search_type</code>	Opt	string	The type of search. (Eval)
<code>total_run_time</code>	Opt	string	The total run time of the search.
<code>user</code>	Opt	string	The name of the user who ran the search. (Rex)
<code>user_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Scheduler_Activity**Object** `Scheduler_Activity` · **Parent** `BaseSearch` · **Fields** 14**Constraint** *(none — derived dataset; inherits parent)*

Field	St	Type	Description
<code>_time</code>	Opt	timestamp	The event timestamp expressed in Unix time.
<code>app</code>	Opt	string	The app context in which the scheduled search was run.
<code>cim_entity_zone</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>host</code>	Opt	string	The host on which the scheduled search was run.

Field	St	Type	Description
<code>savedsearch_name</code>	Opt	string	The name of the saved search.
<code>sid</code>	Opt	string	The search id.
<code>source</code>	Opt	string	The source associated with the scheduled search.
<code>sourcetype</code>	Opt	string	The source type associated with the scheduled search.
<code>splunk_server</code>	Opt	string	The Splunk Server on which the scheduled search runs.
<code>status</code>	Opt	string	The status of the scheduled search.
<code>user</code>	Opt	string	The user who scheduled the search.
<code>user_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

View_Activity

Object `View_Activity` · **Parent** `BaseEvent` · **Fields** 9

Constraint `index=_internal` `sourcetype=splunk_web_access` `method=GET` `status=200`

Field	St	Type	Description
<code>app</code>	Req	string	The app name which contains the view.
<code>view</code>	Req	string	The name of the view.
<code>cim_entity_zone</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>spent</code>	Opt	number	The amount of time spent loading the view (in milliseconds).
<code>uri</code>	Opt	string	The uniform resource identifier of the view activity.
<code>user</code>	Opt	string	The username of the user who accessed the view.
<code>user_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Web_Service_Errors

Object `Web_Service_Errors` · **Parent** `BaseSearch` · **Fields** 5

Constraint *(none — derived dataset; inherits parent)*

Field	St	Type	Description
<code>_time</code>	Opt	timestamp	The event timestamp expressed in Unix time.
<code>cim_entity_zone</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
host	Opt	string	The host on which the web service error occurred.
source	Opt	string	The source where the web service error occurred.
sourcetype	Opt	string	The source type associated with the web service error.

Modular_Actions

Object [Modular_Actions](#) · **Parent** [BaseEvent](#) · **Fields** 18 · **Tags** [modaction](#)

Constraint [tag=modaction](#)

Field	St	Type	Description
action_mode	Opt	string	Specifies whether the action was executed as an ad hoc action or from a saved sea...
action_name	Opt	string	The name of the action. (Eval)
action_status	Opt	string	The status of the action. For example, 'success' or 'failure'.
app	Opt	string	The app ID of the app or add-on that owns the action.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
component	Opt	string	The component of the modular action script involved in the event. Often used in c...
duration	Opt	number	How long the action took to complete, in milliseconds.
orig_rid	Opt	string	The rid value of a source action result, automatically added to an event if it is...
orig_sid	Opt	string	The original sid value of a source action, automatically added to an event if it...
rid	Opt	string	The id associated with the result of a specific sid. By default, this is the row...
search_name	Opt	string	The name of the correlation search that triggered the action. Blank for ad hoc ac...
sid	Opt	string	The search id, automatically assigned by splunkd. (Eval)
signature	Opt	string	The logging string associated with alert action introspection events. (Eval)
user	Opt	string	The user who triggered an ad hoc alert. Not relevant for actions triggered by sea... (Eval)
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Field	St	Type	Description
<code>worker</code>	Opt	string	The worker performing the action. (Eval)

Prescribed values

`action_mode` = saved, adhoc

Ticket_Management

All_Ticket_Management

Object All_Ticket_Management · **Parent** BaseEvent · **Fields** 25 · **Tags** ticketing

Constraint (`cim\_Ticket\_Management\_indexes`) tag=ticketing

Field	St	Type	Description
<code>affect_dest</code>	Opt	string	Destinations affected by the service request.
<code>cim_entity_zone</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>comments</code>	Opt	string	Comments about the service request.
<code>description</code>	Opt	string	The description of the service request.
<code>dest</code>	Opt	string	The destination of the service request. You can alias this from more specific fie... (Eval)
<code>dest_bunit</code>	Opt	string	The business unit of the destination.
<code>dest_category</code>	Opt	string	The category of the destination.
<code>dest_priority</code>	Opt	string	The priority of the destination.
<code>priority</code>	Opt	string	The relative priority of the service request.
<code>severity</code>	Opt	string	The relative severity of the service request.
<code>severity_id</code>	Opt	string	The numeric or vendor specific severity indicator corresponding to the event seve...
<code>splunk_id</code>	Opt	string	The unique identifier of the service request as it pertains to Splunk. For exampl...
<code>splunk_realm</code>	Opt	string	The Splunk application or use case associated with the unique identifier (splunk_...
<code>src_user</code>	Opt	string	The user or entity that created or triggered the service request, if applicable.
<code>src_user_bunit</code>	Opt	string	The business unit associated with the user or entity that triggered the service r...
<code>src_user_category</code>	Opt	string	The category associated with the user or entity that triggered the service reques...

Field	St	Type	Description
<code>src_user_priority</code>	Opt	string	The priority associated with the user or entity that triggered the service request...
<code>status</code>	Opt	string	The relative status of the service request.
<code>tag</code>	Opt	string	This automatically generated field is used to access tags from within data models...
<code>ticket_id</code>	Opt	string	An identification name, code, or number for the service request. (Eval)
<code>time_submitted</code>	Opt	timestamp	The time that the src_user submitted the service request.
<code>user</code>	Opt	string	The name of the user or entity that is assigned to carry out the service request...
<code>user_bunit</code>	Opt	string	The business unit associated with the user or entity that is assigned to carry ou...
<code>user_category</code>	Opt	string	The category associated with the user or entity that is assigned to carry out the...
<code>user_priority</code>	Opt	string	The priority of the user or entity that is assigned to carry out the service requ...

All_Ticket_Management.Change

Object Change · **Parent** All_Ticket_Management · **Fields** 1 · **Tags** change

Constraint tag=change

Field	St	Type	Description
<code>change</code>	Opt	string	Designation for a request for change (RFC) that is raised to modify an IT service... (Eval)

All_Ticket_Management.Incident

Object Incident · **Parent** All_Ticket_Management · **Fields** 1 · **Tags** incident

Constraint tag=incident

Field	St	Type	Description
<code>incident</code>	Opt	string	The incident that triggered the service request. Can be a rare occurrence, or som... (Eval)

All_Ticket_Management.Problem

Object Problem · **Parent** All_Ticket_Management · **Fields** 1 · **Tags** problem

Constraint tag=problem

Field	St	Type	Description
<code>problem</code>	Opt	string	When multiple occurrences of related incidents are observed, they are collectivel... (Eval)

Updates

Updates

Object `Updates` · **Parent** `BaseEvent` · **Fields** 16 · **Tags** `update`, `status`

Constraint (``cim_Updates_indexes``) `tag=update` `tag=status`

Field	St	Type	Description
<code>dest</code>	Rec	string	The system that is affected by the patch change. You can alias this from more spe... (Eval)
<code>signature</code>	Rec	string	The name of the patch requirement detected on the client (the dest), such as MS08... (Eval)
<code>signature_id</code>	Rec	string	The ID of the patch requirement detected on the client (the src). Note: Use signa... (Eval)
<code>status</code>	Rec	string	Indicates the status of a given patch requirement. (Eval)
<code>vendor_product</code>	Rec	string	The vendor and product of the patch monitoring product, such as Lumension Patch M... (Eval)
<code>cim_entity_zone</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_should_update</code>	Opt	boolean	Auto-set by ES asset/identity correlation — do not extract.
<code>dvc</code>	Opt	string	The device that detected the patch event, such as a patching or configuration man...
<code>file_hash</code>	Opt	string	The checksum of the patch package that was installed or attempted.
<code>file_name</code>	Opt	string	The name of the patch package that was installed or attempted.
<code>severity</code>	Opt	string	The severity associated with the patch event.
<code>severity_id</code>	Opt	string	The numeric or vendor specific severity indicator corresponding to the event seve...
<code>tag</code>	Opt	string	This automatically generated field is used to access tags from within data models...

Prescribed values

status = available, installed, invalid, restart required, failure

severity = critical, high, medium, low, informational

Update_Errors

Object `Update_Errors` · **Parent** `BaseSearch` · **Fields** 5

Constraint (*none* — *derived dataset; inherits parent*)

Field	St	Type	Description
<code>_time</code>	Opt	timestamp	The event timestamp expressed in Unix time.
<code>cim_entity_zone</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>host</code>	Opt	string	The host associated with the search.
<code>source</code>	Opt	string	The source associated with the search.
<code>sourcetype</code>	Opt	string	The source type associated with the search.

Vulnerabilities

Vulnerabilities

Object `Vulnerabilities` · **Parent** `BaseEvent` · **Fields** 28 · **Tags** `vulnerability`, `report`

Constraint (``cim_vulnerabilities_indexes``) `tag=vulnerability` `tag=report`

Field	St	Type	Description
<code>category</code>	Rec	string	The category of the discovered vulnerability, such as DoS. Note: This field is a... (Eval)
<code>cve</code>	Rec	string	The identifier provided in the Common Vulnerabilities and Exposures index (search... (Eval)
<code>dest</code>	Rec	string	The host with the discovered vulnerability. You can alias this from more specific... (Eval)
<code>dvc</code>	Rec	string	The system that discovered the vulnerability. You can alias this from more specif... (Eval)
<code>severity</code>	Rec	string	The severity of the vulnerability detection event. Specific values are required... (Eval)
<code>signature</code>	Rec	string	The name of the vulnerability detected on the host, such as HPSBMU02785 SSRT10052... (Eval)
<code>vendor_product</code>	Rec	string	The vendor and product that detected the vulnerability. This field can be automat... (Eval)
<code>bugtraq</code>	Opt	string	The identifier in the vulnerability database provided by the Security Focus websi... (Eval)

Field	St	Type	Description
cert	Opt	string	The identifier in the vulnerability database provided by the US Computer Emergenc... (Eval)
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
cvss	Opt	number	Numeric indicator of the common vulnerability scoring system.
dest_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dest_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
dvc_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
msft	Opt	string	The Microsoft Security Advisory number (http://technet.microsoft.com/en-us/securi...) (Eval)
mskb	Opt	string	The Microsoft Knowledge Base article number (http://support.microsoft.com/kb/). (Eval)
severity_id	Opt	string	The numeric or vendor specific severity indicator corresponding to the event seve...
signature_id	Opt	string	The unique identifier or event code of the event signature.
tag	Opt	string	This automatically generated field is used to access tags from within data models...
url	Opt	string	The URL involved in the discovered vulnerability.
user	Opt	string	The user involved in the discovered vulnerability.
user_bunit	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_category	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
user_priority	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
xref	Opt	string	A cross-reference identifier associated with the vulnerability. In most cases, th... (Eval)

Prescribed values

severity = critical, high, medium, low, informational

Web

Web

Object [Web](#) · **Parent** [BaseEvent](#) · **Fields** 41 · **Tags** [web](#)

Constraint (``cim_web_indexes``) `tag=web`

Field	St	Type	Description
action	Rec	string	The action taken by the server or proxy. (Eval)
bytes	Rec	number	The total number of bytes transferred (bytes_in + bytes_out). (Eval)
bytes_in	Rec	number	The number of inbound bytes transferred. (Eval)
bytes_out	Rec	number	The number of outbound bytes transferred. (Eval)
dest	Rec	string	The destination of the network traffic (the remote host). You can alias this from... (Eval)
http_content_type	Rec	string	The content-type of the requested HTTP resource. (Eval)
http_method	Rec	string	The HTTP method used in the request. (Eval)
http_referrer	Rec	string	The HTTP referrer used in the request. The W3C specification and many implementat... (Eval)
http_referrer_domain	Rec	string	The domain name contained within the HTTP referrer used in the request. (Rex)
http_user_agent	Rec	string	The user agent used in the request. (Eval)
src	Rec	string	The source of the network traffic (the client requesting the connection). (Eval)
status	Rec	string	The HTTP response code indicating the status of the proxy request. (Eval)
url	Rec	string	The URL of the requested HTTP resource. (Eval)
url_domain	Rec	string	The domain name contained within the URL of the requested HTTP resource. (Rex)
user	Rec	string	The user that requested the HTTP resource. (Eval)
vendor_product	Rec	string	The vendor and product of the proxy server, such as Squid Proxy Server. This fiel... (Eval)
app	Opt	string	The application detected or hosted by the server/site such as wordpress, splunk...
cached	Opt	boolean	Indicates whether the event data is cached or not.
category	Opt	string	The category of traffic, such as may be provided by a proxy server.
cim_entity_zone	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
cookie	Opt	string	The cookie file recorded in the event.

Field	St	Type	Description
<code>dest_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>dest_ip</code>	Opt	string	The IP address of the destination.
<code>dest_port</code>	Opt	number	The destination port of the web traffic.
<code>dest_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>duration</code>	Opt	number	The time taken by the proxy event, in milliseconds.
<code>http_user_agent_length</code>	Opt	number	The length of the user agent used in the request. (Eval)
<code>response_time</code>	Opt	number	The amount of time it took to receive a response, if applicable, in milliseconds.
<code>site</code>	Opt	string	The virtual site which services the request, if applicable.
<code>src_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>src_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>src_ip</code>	Opt	string	The ip address of the source.
<code>src_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>tag</code>	Opt	string	This automatically generated field is used to access tags from within data models...
<code>uri_path</code>	Opt	string	The path of the resource served by the webserver or proxy.
<code>uri_query</code>	Opt	string	The path of the resource requested by the client.
<code>url_length</code>	Opt	number	The length of the URL. (Eval)
<code>user_bunit</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_category</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.
<code>user_priority</code>	Opt	string	Auto-set by ES asset/identity correlation — do not extract.

Prescribed values

`http_method` = GET, PUT, POST, DELETE, HEAD, OPTIONS, CONNECT, TRACE

status = 100, 101, 102, 200, 201, 202, 203, 204, 205, 206, 207, 208, 226, 300, 301, 302, 303, 304, 305, 306, 307, 308, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 422, 423, 424, 426, 428, 429, 431, 500, 501, 502, 503, 504, 505, 506, 507, 508, 510, 511

cached = true, false, 1, 0

Web.Storage

Object Storage · **Parent** Web · **Fields** 3 · **Tags** storage
Constraint tag=storage

Field	St	Type	Description
error_code	Opt	string	The error code that occurred while accessing the storage account.
operation	Opt	string	The operation performed on the storage account.
storage_name	Opt	string	The name of the bucket or storage account.