

---

# Machine Listening for Music and Sound Analysis

## Lecture 3 – Music Information Retrieval I

---

Dr.-Ing. Jakob Abeßer

Fraunhofer IDMT

Jakob.abesser@idmt.fraunhofer.de

<https://machinelisting.github.io>

---

# Overview

---

- Music Information Retrieval
- Music Tagging
- Music Similarity
- Tempo Estimation

# Music Information Retrieval

## Examples

### ■ Examples:

#### ■ Musical Instrument



AUD-1



AUD-2

#### ■ Musical Genre / Tempo



AUD-3



AUD-4

# Music Information Retrieval

## Motivation

- Large music collections
- Mobile device apps / instruments
- Music industry shifts almost completely to online products & services
- Growing market of music streaming services




Fig. 1




Fig. 2

---

# Music Information Retrieval

## Typical Research Tasks


---

- What's that song again? Who's singing that?
  - Audio identification
- I want to learn that song on my instrument!
  - Automatic music transcription
- What songs are similar? How to generate a playlist?
  - Audio similarity search
- How to organize my music? Which genre / style?
  - Audio classification

# Music Information Retrieval

## Research Landscape

- Interdisciplinary research community since 2000
- Conferences
  - ISMIR (International Society for Music Information Retrieval)
  - IEEE ICASSP, DAFx, AES, ICMC, SMC
- MIREX competition (Music Information Retrieval Evaluation eXchange)



---

# Music Information Retrieval


## Research Landscape

---

- MIR @ Fraunhofer IDMT
  - Semantic music technologies (SMT) group
    - Staff + PhD / master / bachelor students + interns
- National / international research groups
  - International Audio Laboratories Erlangen, Germany
  - Centre for Digital Music, Queen Mary University, London, UK
  - Universitat Pompeu Fabra, Barcelona, Spain
  - Institute for music/acoustic research and coordination (IRCAM), Paris, France
  - USA, China, Taiwan, Japan, Korea, etc.

# Music Information Retrieval

## Research Task Taxonomy






---

# Music Information Retrieval

## Case Studies

---

- MIR 1 lecture
  - Music tagging / music similarity → general tasks
  - Tempo estimation → rhythm
- MIR 2 lecture
  - Pitch detection → pitch / tonality
  - Source separation & instrument recognition → timbre
- Teaching Concept



---

# Music Tagging

## Introduction

---

### ■ Tags

- Textual (objective / subjective) annotations of songs

- Examples

- Instruments (drums, bass, guitar, vocals ...)
- Genre (classical, electro, hip hop)
- Mood (mellow, romantic, angry, happy)
- Miscellaneous (noise, loud, ambient)


### ■ Challenge

- Music pieces change their characteristics over time
  - E.g.: trumpet plays only in the chorus (jazz)

# Music Tagging


## Traditional Approach

- Audio feature engineering & music domain knowledge
- Standard classification methods (GMM, SVM, kNN)



# Music Tagging

## Novel Approaches



(a) Feature engineering (MFCC)

(b) Low-level feature

(c) Joint feature learning & classification (CNN)

(d) End-to-end learning

Fig. 3

# Music Tagging

## Novel Approaches

- Joint representation learning & classification using CNNs
  - Input: spectrograms (2D) or audio samples (1D end-to-end)
- Integrate musical knowledge in network design (e.g., filter shapes)




Fig. 4

# Music Tagging

## Novel Approaches

### ■ End-to-end Learning

- Model input is low-level representation (audio waveform)
- No pre-processing / assumptions required
- Not restricted to spectral magnitudes → can model phase!
- Requires large amounts of training data




Fig. 6

# Music Tagging

## Novel Approaches

### ■ Transfer Learning

- Pre-train model on source task (lot of data available)
- Fine-tune model on target task (only little data available)




Fig. 5

- Source model (CNN) → Target model (embeddings + shallow classifier)

# Music Similarity

## Introduction

- Music → inherently multi-dimensional
- Challenge
  - Large music databases
  - Incomplete / missing metadata
- Query by example → general retrieval approach
  - Retrieval most similar song  $S$  given a query song  $Q$




Fig. 7



# Music Similarity

## Introduction

### ■ Retrieval tasks

- Music fingerprinting (retrieve title, artist, e.g., Shazam app)
- Cover song identification (similar text, chord progressions ...)
- Music replacement (similar style, instrumentation)

### ■ Specificity of different tasks




Fig. 8

# Music Similarity

## Traditional Approaches

- Different dimensions of music similarity

- Melodic similarity (pitch contours)




- Timbral similarity (instrumentation)




— Piano — Guitar — Vocals

- Structural / harmonic similarity (segments, chords)




- Rhythmic similarity (patterns)



# Music Similarity

## Novel Approaches


- Metric learning
  - Model (abstract) notion of similarity between data instances
    - Pair-wise distance between feature representations
- Training → Preserve similarity in the feature space
  - Proximity between similar instances
  - Distance between dissimilar instances
- Distance measures (Euclidean, cosine)
- Query  $Q$  → Ranked list of most similar items ( $S_i$ )



# Music Similarity

## Novel Approaches

- Disentanglement learning
  - Similarity → multiple semantic concepts (e.g., genre, instrument, mood)
    - learnt jointly
    - remain separable in the embedding space
- Improves tagging (classification) and recommendation (similarity)




# Music Similarity

## Novel Approaches

### ■ Triplet-based Training

#### ■ Conditional Similarity Networks (CSN) [Lee, 2020]



# Tempo Detection

## Introduction

- Tempo [beats / minute]
- Frequency with which humans tap along the beat




Fig. 11

- Beat tracking
- Estimating precise beat positions





Fig. 12



FMP Notebooks

# Tempo Detection

## Introduction

- Note onsets → note beginning times
  - Clearly defined for plucked string and percussion instruments
  - Ambiguous for wind & brass instruments
- Onset detection
  - Onset detection function
  - Peak picking




Fig. 13

Audio samples  
↓  
Onset detection  
function & peaks




Fig. 14

# Tempo Detection

## Traditional Methods

- Predominant local pulse (PLP)
  - Correlation with local (windowed) periodic patterns
- Tempogram [Grosche & Müller, 2009]
  - Local likelihood of different tempo candidates
  - Allows to follow tempo changes (classical music)



FMP Notebooks





Fig. 15



# Tempo Detection


## Novel Methods

### ■ Approach [Böck et al., 2015]




### ■ Signal representation

- Stacking of 3 STFT magnitude spectrograms (N=1024, 2048, 4096)
- Log-amplitude & log-frequency



(a) Input audio signal




(b) Input to the neural network

Fig. 17


# Tempo Detection

## Novel Methods

- Neural Network
  - Recurrent (bi-directional LSTM) layer
  - Outputs beat activation function
- Comb filter bank
  - Multiple comb filters → detect periodicities
- Estimate tempo from histogram maximum



(c) Neural network output (beat activation function)



(f) Weighted histogram with summed maxima

Fig. 18

# Tempo Detection

## Novel Methods

- Approach [Schreiber & Müller, 2018]
  - Sample rate ~ 11 kHz, 40-band mel spectrogram
- Tempo estimation → classification (256 classes: 30 – 285 bpm)
- Neural Network
  - 3 layers (short filters) → onsets
  - 4 multi-filter modules (parallel conv layers) → compress along frequency & find periodicities
  - Dense layers → tempo classification




Fig. 19

---

# Summary

---

- Music Information Retrieval
  - Music Tagging
  - Music Similarity
  - Tempo Estimation
- 
- Main trends
    - Adapt (data-driven) deep learning methods to music domain
    - Incorporate music domain knowledge

---

# References

---

- Böck, S., Krebs, F., & Widmer, G. (2015). Accurate tempo estimation based on recurrent neural networks and resonating comb filters. *Proceedings of the International Society for Music Information Retrieval Conference (ISMIR)*, 625–631.
- Grosche, P., & Müller, M. (2009). A mid-level representation for capturing dominant tempo and pulse information in music recordings. *Proceedings of the International Society for Music Information Retrieval Conference (ISMIR)*, 189–194.
- Lee, J., Bryan, N. J., Salamon, J., Jin, Z., & Nam, J. (2020). Disentangled Multidimensional Metric Learning for Music Similarity. *Proceedings of the IEEE International Conference on Acoustics, Speech, and Signal Processing (ICASSP)*, 6–10. Barcelona, Spain.
- Lee, J., Bryan, N. J., Salamon, J., Jin, Z., & Nam, J. (2020). Metric learning vs classification for disentangled music representation learning. *Proceedings of the International Society for Music Information Retrieval Conference (ISMIR)*, 439–445. Montréal, Canada.
- Müller, M. (2021). *Fundamentals of Music Processing - Using Python and Jupyter Notebooks* (2nd ed.). Springer.
- Nam, J., Choi, K., Lee, J., Chou, S. Y., & Yang, Y. H. (2019). Deep Learning for Audio-Based Music Classification and Tagging: Teaching Computers to Distinguish Rock from Bach. *IEEE Signal Processing Magazine*, 36(1), 41–51.
- Pons, J., Nieto, O., Prockup, M., Schmidt, E., Ehrmann, A., & Serra, X. (2018). End-to-End Learning for Music Audio Tagging at Scale. *Proceedings of the International Society for Music Information Retrieval (ISMIR)2*, 637–644. Paris, France.

---

# References

---

Ribecky, S. (2021). *Disentanglement Representation Learning for Music Annotation and Music Similarity*. Technische Universität Ilmenau.

Schreiber, H., & Müller, M. (2018). A Single-Step Approach to Musical Tempo Estimation using a Convolutional Neural Network. *Proceedings of the International Society for Music Information Retrieval Conference (ISMIR)*, 98–105. Paris, France.

Won, M., Chun, S., Nieto, O., & Serra, X. (2020). Data-Driven Harmonic Filters for Audio Representation Learning. *Proceedings of the IEEE International Conference on Acoustics, Speech, and Signal Processing (ICASSP)*, 536–540. Barcelona, Spain.

---

# Images

---

Fig. 1: <https://www.synchtank.com/wp-content/uploads/2018/06/1476277072027.jpg>

Fig. 2: [https://miro.medium.com/max/800/1\\*cC1KOdyzst1nazak42cBdg.jpeg](https://miro.medium.com/max/800/1*cC1KOdyzst1nazak42cBdg.jpeg)

Fig. 3: [Nam, 2019], p. 42, Fig. 1

Fig. 4: [Won, 2020], p. 537, Fig. 1a

Fig. 5: [Nam, 2019], p. 48, Fig. 4

Fig. 6: [Pons, 2018], p. 639, Fig. 2 (top left)

Fig. 7: [Lee, 2020, ICASSP], p. 1, Fig. 1

Fig. 8: [Ribecky, 2021], p. 26, Fig. 2.11

Fig. 9: [Lee, 2020, ISMIR], p. 1, Fig. 1

Fig. 10: [Lee, 2020, ICASSP], p. 2, Fig. 2

Fig. 11: [Müller, 2021], p. 309, chapter 6 (cover image)

Fig. 12: [Müller, 2021], p. 310, Fig. 6.1(b)

Fig. 13: [Müller, 2021], p. 311, Fig. 6.2

Fig. 14: [Müller, 2021], p. 313, Fig. 6.3(a)&(b)

---

# Images

---

Fig. 15: [Grosche & Müller, 2009], p. 2, Fig. 1(e-g) & p. 3, Fig. 2 (a)

Fig. 16: [Böck et al., 2015], p. 2, Fig. 1

Fig. 17: [Böck et al., 2015], p. 3, Fig. 2 (a) & (b)

Fig. 18: [Böck et al., 2015], p. 3, Fig. 2 (c) & (f)

Fig. 19: [Schreiber & Müller, 2018], p. 3, Fig. 2



---

# Sounds

---

**AUD-1:** Mr Smith – Black Top (2021), <https://freemusicarchive.org/music/mr-smith/studio-city/black-top>

**AUD-2:** Crowander – Humbug (2021), <https://freemusicarchive.org/music/crowander/from-the-piano-solo-piano/humbug>

**AUD-3:** Bumy Goldson: Keep Walking (2021), <https://freemusicarchive.org/music/bumy-goldson/parlor/keep-walking>

**AUD-4:** Cloudjumper: Mocking the god (2016),  
[https://freemusicarchive.org/music/Cloudjumper/Memories\\_of\\_Snow/05\\_Cloudjumper\\_-\\_Mocking\\_the\\_gods](https://freemusicarchive.org/music/Cloudjumper/Memories_of_Snow/05_Cloudjumper_-_Mocking_the_gods)

---

# Thank you!

---

■ Any questions?

Dr.-Ing. Jakob Abeßer

Fraunhofer IDMT

Jakob.abesser@idmt.fraunhofer.de

<https://machinelisting.github.io>