

Homework 12 sample solution

Due 10/14/16

October 11, 2016

Stirling Numbers of the Second Kind, represented as $S(n, k)$, count (among other things) the number of ways to divide n objects into exactly k nonempty piles. For example, there are 7 ways to divide four objects into two piles:

$\{1, 2, 3\}$	$\{4\}$
$\{1, 2, 4\}$	$\{3\}$
$\{1, 3, 4\}$	$\{2\}$
$\{2, 3, 4\}$	$\{1\}$
$\{1, 2\}$	$\{3, 4\}$
$\{1, 3\}$	$\{2, 4\}$
$\{1, 4\}$	$\{2, 3\}$

Stirling Numbers of the Second Kind can be calculated using the following recurrence relation:

$$S(n, k) = \begin{cases} 1, & \text{if } k = 1 \text{ or } k = n \\ kS(n-1, k) + S(n-1, k-1), & \text{otherwise} \end{cases}$$

Use this recurrence to answer the questions below. If you are interested why this recurrence is true, you may see the footnote¹ below; *however*, you do not need to understand why this works in order to solve the problem.

1. Describe a naïve recursive algorithm that computes $S(n, k)$ using this recurrence.

See below

2. What map implementation would you use for a memoized dynamic programming solution to this problem and why?

2D array (direct map), because the recursive function has two arguments whose values change

¹When adding one element to go from $n-1$ to n , the new element can either go in a pile by itself or be added to an existing pile. There are $S(n-1, k-1)$ ways to put these $n-1$ elements into $k-1$ piles, and we can create the k^{th} pile by putting the new element by itself. On the other hand, there are $S(n-1, k)$ ways to put the $n-1$ elements into k piles, and we can add the new element to any of the k piles. There's only one way to put everything into one pile, and the only way to put n elements into n piles is to put everything in its own pile.

3. Describe a memoized dynamic programming solution to this problem.

Naïve algorithm

Memoized algorithm

```
Input:  $n$ : number of objects
Input:  $k$ : number of piles
Output:  $S(n, k)$ : number of ways to divide  $n$  objects into  $k$  nonempty
        piles
1 Algorithm: MemoStirling2
2 if  $S[n, k] > 0$  then
3   | return  $S[n, k]$ 
4 elseif  $k = 1$  or  $k = n$  then
5   |  $S[n, k] = 1$ 
6   | return 1
7 else
8   |  $S[n, k] = k \cdot \text{MemoStirling2}(n - 1, k) + \text{MemoStirling2}(n - 1, k - 1)$ 
9   | return  $S[n, k]$ 
10  | return  $k \cdot \text{Stirling2}(n - 1, k) + \text{Stirling2}(n - 1, k - 1)$ 
11 end
```

```
Input:  $n$ : number of objects
Input:  $k$ : number of piles
Output:  $S(n, k)$ : number of ways to divide  $n$  objects into  $k$  nonempty
        piles
1 Algorithm: Stirling2DynProg
2  $S = \text{Array}(n, k)$ 
3 Initialize  $S$  to 0
4 return MemoStirling2( $n, k$ )
```