

物質安全資料表 (Safety Data Sheet)

Revised date : 05.09.2018 page 1 of 5

1:物品與廠商資料

(IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY/UNDERTAKING)

1.1 物品鑑別(Product identifier):

物品名稱(Product name): 8克壓縮一氧化二氮充填鋼瓶(8 g N2O chargers)

化學符號 (Chemical formula): Nitrous oxide (N2O)

CAS: 10024-97-2 EC:233-032-0

Index Number: N/A

1.2 製造商或供應商名稱、地址及電話(Details of the supplier of the safety data sheet):

元翎精密工業股份有限公司(Mosa Industrial Corp.)

63247台灣雲林縣虎尾鎮科虎三路18號 (18, Kehu 3Rd. Huwei, Yunlin 63247, Taiwan)

網址:www.twmosa.com Phone: +886 5 6361867 Fax: +886 5 6312770

1.3 緊急聯絡電話(Emergency telephone Number): +886 5 6361867

2: 危害辨識資料(HAZARDS IDENTIFICATION)

所處環境之氧含量低於19.5%時,可能會導致窒息。與一氧化二氮接觸可能引起噁心和呼吸困難,濃度過高時可能會導致血管擴張,及循環衰竭。警告!壓力容器應避免陽光直射,不可暴露在溫度超過50°C(122°F)的環境;防止兒童碰觸玩耍;不可使用強大外力打開氣體鋼瓶。

Oxygen levels below 19.5% may cause asphyxia. Nitrogen oxide exposure can cause nausea and respiratory problems. High concentrations may cause vasodilation leading to circulatory collapse.

Warning! Pressurized container; protect from sunlight; do not expose to temperatures exceeding 50°C (122° F); keep out the reach of children; never dispose of full container, never force open.

3: 成分辨識資料(COMPOSITION/INFORMATION ON INGREDIENTS)

物質(Substance)

/ 調劑(Preparation):

物質(Substance)

化學名稱(Chemical name) 一氧化二氮(Nitrous oxide)

化學文摘社登記號碼(CAS number):

EC Number (from EINECS)

曲 (CAS number): EINECS)
10024-97-2 233-032-0

標誌(Symbol)



UN Number: UN1070

4: 急救措施(FIRST AID MEASURES)

4.1 急救措施的說明(Description of first aid measures)

4.1.1 吸 入(Inhalation): 搬運患者到有新鮮空氣的地方,如果患者呼吸困難,需提供氧氣;如果患者沒有

呼吸,需立即進行心肺復甦術,並立即送醫。

Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical

attention.

4.1.2 食 入(Ingestion): 由於氣態,正常情況下預計不會發生。

Not expected under normal conditions due to gaseous state.

4.1.3 皮膚接觸: 立即將患部浸泡於溫度低於40度之溫水浴中,不可使用乾的火源烤,如果是大

(Skin Contact) 區域凍傷,脫去衣服使用溫水淋浴,立即送醫。。

Wash affected area with soap and water; if irritation persists, seek medical

attention.



Mosa Industrial Corp.

物質安全資料表 (Safety Data Sheet)

page 2 of 5

4.1.4 眼睛接觸 (Eye Contact): 檢查並去除隱形眼鏡,以乾淨的水沖洗眼睛15分鐘,同時保持眼瞼張開。如果

有持續刺激威需立即就醫。

Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical

5: 滅火措施(FIRE-FIGHTING MEASURES)

5.1 具體危害(Specific Hazards):

曝露於高温燒灼可能造成容器破裂或爆炸。

Exposure to fire may cause containers to rupture/explode.

5.2 一般危害(General Hazards):

此產品為不易燃及不可燃物。燃燒時產物包括碳、氫、氧化合物及一氧化碳。

Product is not flammable or combustible. Products of combustion include compounds of carbon, hydrogen and oxygen, including carbon monoxide.

5.3 滅火介質(Extinguishing Media):

非燃性物質但會助燃,使用嫡合發火源之減火劑。

Carbon dioxide, water, water fog, dry chemical, chemical foam.

5.4 異常火災和爆炸危險(Unusual Fire and Explosion Hazards):

當氣瓶暴露在極端熱密閉空間內易導致爆炸。此高壓力的氣體鋼瓶,不要在靠近熱源的地方使用或存放。 Closed containers can explode due to buildup of pressure when exposed to extreme heat. Contents under pressure. Do not use or store near heat sources.

5.5 有害燃燒產物(Hazardous Combustion Products):

煙霧,煙霧或蒸汽,碳的氧化物。

Smoke, fumes or vapors, oxides of carbon.

6: 洩漏處理方法(ACCIDENTAL RELEASE MEASURES)

6.1 個人的預防措施 (Personal precautions):

迅速撤離災區,必要時戴上自給式呼吸器。除非災區被證明是安全的否則不可進入。並確保充足的空氣流通。 Evacuate area. Wear self-contained breathing apparatus whenentering area unless atmosphere is proved to be safe. Ensureadequate air ventilation.

6.2 環境保護措施 (Environmental precautions):

嘗試停止洩漏。防止洩漏流入下水道,地下室或任何地方,過度的積累可能會造成危險。

Try to stop release. Prevent from entering sewers, basements andworkpits, or any place where its accumulation can be angerous.

6.3 清理方法 (Clean up methods):

通風良好的地方 Ventilated area.

7: 安全處置與儲存方法(HANDLING AND STORAGE)

安全處置 (Handling): 不使用時請保持容器密閉,保護氣瓶避免招受碰撞;防止儲存於高溫處,遠離熱

源。不可刺穿氣瓶。並不要試圖填充容器;遠離陽光直射和熱源。

Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures, keep away from sources of heat. Do not puncture container. Do not attempt to refill container. Keep away from direct sunlight and heat.



Mosa Industrial Corp.

物質安全資料表 (Safety Data Sheet)

page 3 of 5

6160 lbf/in2 at 212 °F

6815 lbf/in2 at 230 °F

儲存 (Storage): 不可加熱,使用時最高環境溫度請勿超過50°C (122°F)。並儲存在陰涼、乾燥

的場所。(Do not heat. Maximum environmental temperature in use not to

exceed 50°C (122°F). Store in a cool and dry location.)

鋼瓶材料:

(Packaging materials)

可回收鋼材 (Recyclable steel)

推薦使用 (Recommended

使用原來的盛裝容器 (Use original container.)

use):

8: 暴露預防措施(EXPOSURE CONTROL/PERSONAL PROTECTION)

工程控制: 通風良好避免濃度累積,工作區應監測含氧量以確認氧氣濃度高於19.5%。

(Engineering controls) The use of local exhaust ventilation is required to control emissions near the

source. Provide mechanical ventilation of confined spaces.

個人防護: 確保足夠的通風。同時進行處理氣瓶工作需配戴手套和防護鞋。

(Personal protection) Ensure adequate ventilation. Carry working gloves and protection

9: 物理及化學性質(PHYSICAL AND CHEMICAL PROPERTIES)

·氧化二氢的物理和化學性質 Physical and chemical properties of N2O (E942--99% N2O)

1 atm下的氣體壓力

(Gas density at 1 atm):

58.5 kg/cm2 at 20°C

比重(Relative density (air=1)):

1.53 at 20°C

熔點(Melting point (N2O Sublimes)):

- 90.86° C (- 132° F)

沸點(Boiling point):

):

- 88.48° C (- 127° F)

溶解度(水中) (Solubility (H20)):

1.50 g/L at 15 °C, 100 kPa

氣味和外觀(Odor and appearance): 無色,微甜味的氣體 (A colorless, odorless gas)

Parameter of 8g N2O charger	公制單位 <u>(METRIC UNITS)</u>	英制單位(<u>US / IMPERIAL UNITS)</u>
總長(Overall Length (approx)):	65 mm	2.56 in
瓶身外徑(Body Diameter):	18 mm	0.709 in
頸部外徑(Neck Diameter):	8.7 mm	0.343 in
內容積(Internal Volume (approx)):	10.3 ml min.	0.63 in³ min.
N2O淨重(Net weight of N2O (appro	x)): 8 g	0.32 oz
空瓶重量(Tare wt. of charger (appro	ox)): 21 g	0.84 oz
總重 (Gross wt. of charger (approx)): 29 g	1.16 oz
爆破壓(Bursting pressure):	>500 bar	>7250 lbf/in²
壓力/溫度 在充填密度為 0.78kg/liter的狀況下(Pressure / Temperature Characteristics at filling density of 0.78 kg/liter	52 bar at 20 °C	750 lbf/in ² at 68 °F
	185 bar at 50 °C	2680 lbf/in ² at 122 °F
	290 bar at 70 °C	4200 lbf/in ² at 158 °F

425 bar at 100 °C

470 bar at 110 °C



MOSa Industrial Corp.

物質安全資料表 (Safety Data Sheet)

page 4 of 5

10: 安定性及反應性(STABILITY AND RELIABILITY)

安定性 (Stability): 正常狀況下安定 (The product is stable.)

應避免之物質:

燃性、自燃性、碳氫類如油脂、醇類等。

(Materials to avoid)

如果正確處理和儲存不會發生分解。在發生火災時,可能會產生碳,烴類,煙霧

危險的分解物: (Hazardous Decomposition

或蒸氣和煙霧氧化物。

Products)

Decomposition will not occur if handled and stored properly. In case of a fire.

oxides of carbon, hydrocarbons, fumes or vapors, and smoke may be

11: 毒性資料(TOXICOLOGICAL INFORMATION)

一般 (General)

從這個產品並無任何已知的毒性效應。

No known toxicological effects from this product.

急毒性 (Acute toxicity)

會造成窒息、人體會因急速缺氧造成受傷甚至死亡。

N2O can cause rapid circulatory insufficiency. Symptoms are headache, nausea and vomiting, which may lead to unconsciousness.

12: 生態資料(ECOLOGICAL INFORMATION)

沒有任何數據顯示這種材料對環境有不利影響。無論是化學需氧量或生化耗氧量數據都適用。基於該產品的化 學成分,它是假設的混合物,可以在數量有限的一個水土不服生物廢物處理廠系統治療。然而,這樣的待遇應 進行評估,並批准為每個特定的生物系統。在這種混合物的成分沒有被列為海洋污染物。

No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.

13: 廢棄處置方法(DISPOSAL CONSIDERATIONS)

廢棄處置方法(Waste Disposal Method):

參考相關法規處理 (Never dump at sea. Inform waste disposal contractor of material to be disposed of zincplated and chrome stabilised steel. Never dispose of a filled cylinder.)

14: 運送資料(TRANSPORT INFORMATION)

無危險性(Non hazardous)

2.2 運輸危害分類(Class)

聯合國編號(UN No.) **UN 1070**

標示(Title): 小型氣體容器(Receptacles, small, containing gas (gas cartridges))

小型容器, 僅裝有無毒性成份氣體, 且容器之容量不超過1000毫升, 不可燃

燒、不可重覆充填、没有釋放裝置。

(Receptacles with capacity not exceeding 1000 ml containing only non-toxic

constituents, non-flammable, without release device, not refillable.



元翎精密工業股份有限公司 Mosa Industrial Corp.

物質安全資料表 (Safety Data Sheet)

page 5 of 5

15: 法規資料(REGULATORY INFORMATION)

CAS編號確定該產品的成分均存在歐洲現有商業化學物質清單。

Components of this product identified by CAS numbers are on the European Inventory of Existing Commercial Chemical Substances.

危險符號 (Hazard symbol(s)):

歐盟法規 (EU Regulations):

分類 (Classification): 有害 (Harmful)

風險短述 (Risk Phrases): R20- 過量吸入有害 (Harmful by inhalation.)

安全短述 (Safety Phrases): \$38 - 在通風不足的情況下,應佩戴合適的呼吸供給設備

使主短弧 (Salety Phrases): (In case of insufficient ventilation, wear suitable respiratory equipment.)

内容物 (Contains): 一氧化二氮 (N2O)

16: 其他資料(OTHER INFORMATION)

特殊毒性試驗尚未進行在此產品上。我們的危險性評估的基礎來自於類似的產品、技術文獻,和專業經驗。 Specific toxicity tests have not been conducted on this product. Our hazard evaluation is based on Information from similar products, the ingredients, technical literature, and/or professional experience.

製表單位 (Tabulation)	公司(Company):	元翎精密工業股份有限公司(Mosa Industrial Corp.)		
	地址(Address):	台灣雲林縣虎尾鎮科虎三路18號 (18, Kehu 3Rd. Huwei, Yunlin 63247, Taiwan)		
	電話(Phone):	886 5 6361867	傳真(FAX):	886-5-6313607
製表	人(Tabulator)	R&D 黃育修(Ben)	版次(Revision):	3