

# Contents

|          |   |          |
|----------|---|----------|
| <b>1</b> | <b>Tengwar Formal Unicode/AAT: Graphite and AAT options</b> | <b>1</b> |
| 1.1      | Character Alternatives . . . . .                            | 2        |
| 1.1.1    | Descending W-Tengwa . . . . .                               | 2        |
| 1.1.2    | Tilde Bar . . . . .   | 2        |
| 1.1.3    | Circumflex A-Tehta . . . . .                                | 2        |
| 1.1.4    | Swash Sa-Rince . . . . .                                    | 2        |
| 1.2      | Osse Hook . . . . .   | 2        |
| 1.3      | Carrier Diacritic (for ‘Full Writing’) . . . . .            | 3        |
| 1.4      | Osse Diacritic (for ‘Full Writing’) . . . . .               | 3        |
| <b>2</b> | <b>Sample Text</b>  | <b>5</b> |
| 2.1      | Graphite . . . . .  | 5        |
| 2.2      | AAT . . . . .   | 5        |

## 1 Tengwar Formal Unicode/AAT: Graphite and AAT options

Here are samples of the different options. The options are specified by adding something to the font name in the `\font` command. The extended font names are all given in this document. A font specification will look like this:

```
\font\bla="font (/GR):feature=value(;feature=value) "
```

In this specification, the part `bla` is a string of your choice. On Mac OS X, the part `/GR` is optional. It tells X<sub>Y</sub>TeX to use the Graphite information. If you leave it away, it will use the AAT information, which only works on Mac OS X. Note that you can define as many features as you like:

```
\font\myformal="Tengwar Formal Unicode/GR:204=1;207=2"
```

After this `\font` command has been defined, you can use `\myformal` as a command, for instance as follows:

```
\myformal ac̣eo ɹonɹp̣ \normalfont
```

This will look like this: ac̣eo ɹonɹp̣

## 1.1 Character Alternatives

### 1.1.1 Descending W-Tengwa

Default

λcζo 2onτp

"Tengwar Formal Unicode/GR:204=1"

λcΞo 2onTpn

"Tengwar Formal Unicode/AAT:Character Alternatives=Descending  
W-Tengwa;"

λcΞo 2onTpn

### 1.1.2 Tilde Bar

Default

ပြည်ထောင်စု

"Tengwar Formal Unicode/GR:209=1"

ပြည်ထောင်စု

"Tengwar Formal Unicode/AAT:Character Alternatives=Tilde Bar"

ပြည်ထောင်စု

### 1.1.3 Circumflex A-Tehta

Default

 $\ddot{p}\ddot{p}$ 

"Tengwar Formal Unicode/GR:210=1"

 $\hat{p}\hat{p}$ 

"Tengwar Formal Unicode/AAT:Character Alternatives=Circumflex  
A-Tehta"

řř

#### 1.1.4 Swash Sa-Rince

Default

բարձր շահնակ:

"Tengwar Formal Unicode/GR:211=1"

*Handwritten signature*

"Tengwar Formal Unicode/AAT:Character Alternatives=Swash  
Sa-Rince"

բարձրագույն խաղաղարար

## 1.2 Osse Hook

Default

 $c\tau, c$

## Word Final

"Tengwar Formal Unicode/GR:207=1"

ꞨꞬ

"Tengwar Formal Unicode/AAT:Osse Hook=Word Final"

ꞨꞬ

## Always

"Tengwar Formal Unicode/GR:207=2"

ꞨꞬ

"Tengwar Formal Unicode/AAT:Osse Hook=Always"

ꞨꞬ

## 1.3 Carrier Diacritic (for ‘Full Writing’)

Default

ꞨꞬ Ꞩ

## Dot

"Tengwar Formal Unicode/GR:213=1"

ꞨꞬ Ꞩ

"Tengwar Formal Unicode/AAT:Carrier Diacritic (for 'Full Writing')=Dot"

ꞨꞬ Ꞩ Ꞩ

## Acute

"Tengwar Formal Unicode/GR:213=2"

ꞨꞬ Ꞩ

"Tengwar Formal Unicode/AAT:Carrier Diacritic (for 'Full Writing')=Acute"

ꞨꞬ Ꞩ

## 1.4 Osse Diacritic (for ‘Full Writing’)

Default

ꞨꞬ ꞨꞬ ꞨꞬ

## Dot on Ambiguous Osse

"Tengwar Formal Unicode/GR:214=1"

ꞨꞬ ꞨꞬ ꞨꞬ

"Tengwar Formal Unicode/AAT:Osse Diacritic (for 'Full Writing')=Dot on Ambiguous Osse"

ḣcȳλcȷp

### **Dot on every osse**

"Tengwar Formal Unicode/GR:214=2"

ḣcȳλcȷp

"Tengwar Formal Unicode/AAT:Osse Diacritic (for 'Full Writing')=Dot on Every Osse"

ḣcȳλcȷp

## 2 Sample Text

## 2.1 Graphite

[illegible]

## 2.2 AAT

[illegible]