

termiteOS Documentation

Release alpha

Nacho Mas

CONTENTS

1	Introduction	3
2	Architecture	5
3	License	7
4	Technical information	9
Index		25

 $A\ telescope\ Operating\ System\ base\ on\ zmq\ and\ Protocol\ Buffers.\ Documentation\ https://nachoplus.github.io/termiteOS/index.html$

CONTENTS 1

2 CONTENTS

INTRODUCTION

Termite OS is a modular, adaptable, easily extendable telescope operating system developed primarily, but not exclusively, in python.

It wants to answer to several limitations that most of the commercial mount controllers have. It wants to be a platform where you can incorporate all kinds of functionalities that the professional or amateur astronomer may need in a simple way.

Posible use case:

- To motorize a DIY mount or retrofit a old one.
- Make your telescope be able to track the ISS or any other satellite.
- Implement new protocol commands.
- New native protocols, i.e. indilib
- Control over the objects catalogs built into your telescope.
- Integrate pointing model in your mount.
- Connect a GPS to your mount and use his data for location and time.
- Define the horizon of your observatory.
- WiFi or Bluetooth access to your mount
- Develope new motion estrategies.

With termiteOS you will address all this things and more.

Termite OS is a work in progress but much of the functionality is already available:

- Stepper controller using Raspberry PI and the integrated DRV8825 widely used in the 3D printer world
- · LX200 command set
- Slew and celestial track
- · Satellite tracking

Ongoing funtionality:

- · Arduino base hardware
- BLDC motors
- Servo motors
- Web interface
- Constellation pointing

CHAPTER

TWO

ARCHITECTURE

Each termiteOS functionality is implemented as a separate program called a'node'. The nodes communicate each other using the zmq protocol. The organization between the nodes is hierarchical thus a node can have several children but has only one parent or none in the case of the'root node'.

ZMQ (http://zeromq.org/) is used for transport and on https://developers.google.com/protocol-buffers/ for message definitions and serialization.

Each node has its own ZMQ port and a set of commands and responds to through that port. Each node opens connections with its parent node and with all its children so that messages can be exchanged.

These nodes can run on the same or different CPUs taking advantage of all the features of the ZMQ protocol.

CHAPTER THREE

LICENSE

GPL3 Copyright (c) July 2018 Nacho Mas

Logo made with https://www.designevo.com/en/ DesignEvo

8

CHAPTER

FOUR

TECHNICAL INFORMATION

Launcher

• Launcher program launch a set of node following the instruction in yaml file

This program allow to launch at once all nodes needed for a specific hardware/funtionality.

Example of a yaml configuration file:

```
simple:
type: telescope
host: localhost
port: 5000
nodes:
    - LX200:
        type: tcpproxy
         host: localhost
         port: 5001
         params: {'tcpport':6001,'End':'#'}
    - tracker:
         type: TLEtracker
         host: localhost
         port: 5002
         nodes:
            - trackertcp:
                 type: tcpproxy
                 host: localhost
                 port: 5003
                 params: {'tcpport':6003}
```

This example is equivalent to run on the command shell all following commands:

```
miteTelescope --port 5000 --name simple
mitetcpproxy --port 5001 --name LX200 --parent_host localhost --parent_port 5000 --params {'tc}
miteTLEtracker --port 5002 --name tracker --parent_host localhost --parent_port 5000
mitetcpproxy --port 5003 --name trackertcp --parent_host localhost --parent_port 5002 --params
```

You can find other examples in 'termoteOS/machines/'

Command line:

miteLaunch

Launch all nodes defined in YAMLFILE

```
miteLaunch [OPTIONS] YAMLFILE
```

Arguments

YAMLFILE

Required argument

API

```
Launch tools to run a rig. Run several daemons at once
```

```
termiteOS.launch.launchmachine (yamlfile)
Launch an arragement of daemons defined in a yaml file

termiteOS.launch.launchnode (nodedict, parent_host='', parent_port=False)
Launch a node defined in dictionary. Called recursively

termiteOS.launch.run_in_separate_process (func, *args, **kwds)
Run function in a separate process. To background executables
```

Nodes

Nodes are separate programs. The nodes communicate each other using the zmq protocol. The organization between the nodes is hierarchical thus a node can have several children but has only one parent or none in the case of the root node.

Nodes are based on http://zeromq.org/ for transport and on https://developers.google.com/protocol-buffers/ for message definitions and serialization.

Each node has its own ZMQ port and a set of commands and responds to through that port. Each node opens connections with its parent node and with all its children so that messages can be exchanged.

These nodes can run on the same or different CPUs taking advantage of all the features of the ZMQ protocol.

All nodes are derive from nodeSkull base class which implements all the comunication logic and basic commands.

TLEtracker

• TLEtracker node calculate satellite TLE speed and RA/DEC and send to the mount

With this node the mount is able to follow any object with TLE.

Command line:

miteTLEtracker

Launch a TLEtracker node

```
miteTLEtracker [OPTIONS]
```

Options

```
--name <name>
    module name
--port <port>
    Port listen
--parent_host <parent_host>
    Parent host to connect to. If False the node become a ROOTHUB
```

```
--parent_port <parent_port>
    Parent port to connect to

TLEtracker commands
```

follow

Follow satellite

help

Print help text. Do nothing. Normaly overloaded by a child class

ls

list the node commands

nodes

list the children nodes:

param arg (None)

returns a python list all children node names

ping

None

tree

Print all self and children nodes availabled commands

```
param arg (None)
```

returns a string contain all commands

hub

• hub node has not own commands. Only used to connect other nodes

Command line:

miteHub

Launch a hub node

```
miteHub [OPTIONS]
```

Options

```
--name <name>
    module name

--port <port>
    Port listen

--parent_host <parent_host>
    Parent host to connect to. If False the node become a ROOTHUB

--parent_port <parent_port>
    Parent port to connect to
```

hub commands

```
help
Print help text. Do nothing. Normaly overloaded by a child class

ls
list the node commands

nodes
list the children nodes:
param arg (None)
returns a python list all children node names

ping
None

Tree
Print all self and children nodes availabled commands
param arg (None)
```

joystick

• joystick node to manual move the mount with a joystick

returns a string contain all commands

Command line:

miteJoy

Launch a joystick node

```
miteJoy [OPTIONS]
```

Options

```
--name <name>
    module name

--port <port>
    Port listen

--parent_host <parent_host>
    Parent host to connect to. If False the node become a ROOTHUB

--parent_port <parent_port>
    Parent port to connect to
```

joystick commands

help

Print help text. Do nothing. Normaly overloaded by a child class

ls

```
list the node commands
```

nodes

list the children nodes:

```
param arg (None)
```

returns a python list all children node names

ping

None

tree

Print all self and children nodes availabled commands

```
param arg (None)
```

returns a string contain all commands

tcpproxy

• tcproxy node acts as a proxy connector between other node and an especific TCP port

All commands recived throught the TCP port are relay to the myCmdPort port of the node conected to.

Using this node allow us to connect to a specific node (the parent node of tcpproxy node) with a regular *telnet host* port

Command line:

mitetcpproxy

Launch a tepproxy node

```
mitetcpproxy [OPTIONS]
```

Options

```
--name <name>
    module name

--port <port>
    Port listen

--parent_host <parent_host>
    Parent host to connect to. If False the node become a ROOTHUB

--parent_port <parent_port>
    Parent port to connect to

--params <params>
    Dictionary with extra parameters default={"tcpport":6001,"End":"#"}
```

tcpproxy commands

help

Print help text. Do nothing. Normaly overloaded by a child class

ls

```
list the node commands
nodes
     list the children nodes:
           param arg (None)
           returns a python list all children node names
ping
      None
tree
      Print all self and children nodes availabled commands
           param arg (None)
```

returns a string contain all commands

Telescope

• **telescope** node implement a telescope mount basic commands (goto,slew,track..)

Two axis equatorial mount telescope.

Command line:

miteTelescope

Launch a telescope node

```
miteTelescope [OPTIONS]
```

Options

```
--name <name>
    module name
--port <port>
     Port listen
--parent_host cparent_host>
     Parent host to connect to. If False the node become a ROOTHUB
--parent_port <parent_port>
     Parent port to connect to
```

telescope commands

ack

None

align2target

None

firware date

None

firware_ver

```
None
getLocalDate
     None
getLocalTime\\
     None
getSideralTime
     None
getTargetDEC
     None
getTargetRA
     None
{\bf getTelescopeDEC}
     None
getTelescopeRA
     None
help
     Print help text. Do nothing. Normaly overloaded by a child class
info
     None
ls
     list the node commands
nodes
     list the children nodes:
          param arg (None)
          returns a python list all children node names
ping
     None
pulseE
     None
pulseN
     None
pulseS
     None
pulseW
     None
set Max Slew Rate \\
     None
setTargetDEC
```

None

```
setTargetRA
     None
slew
     None
slewRate
     None
stopSlew
     None
tree
     Print all self and children nodes availabled commands
           param arg (None)
          returns a string contain all commands
Node commands
TLEtracker commands
follow
     Follow satellite
help
     Print help text. Do nothing. Normaly overloaded by a child class
ls
     list the node commands
nodes
     list the children nodes:
          param arg (None)
          returns a python list all children node names
ping
     None
tree
     Print all self and children nodes availabled commands
           param arg (None)
          returns a string contain all commands
costellation commands
follow
     None
help
     Print help text. Do nothing. Normaly overloaded by a child class
ls
```

```
list the node commands
nodes
     list the children nodes:
           param arg (None)
           returns a python list all children node names
ping
      None
tree
      Print all self and children nodes availabled commands
           param arg (None)
           returns a string contain all commands
hub commands
help
     Print help text. Do nothing. Normaly overloaded by a child class
ls
      list the node commands
nodes
      list the children nodes:
           param arg (None)
           returns a python list all children node names
ping
      None
tree
      Print all self and children nodes availabled commands
           param arg (None)
           returns a string contain all commands
joystick commands
help
     Print help text. Do nothing. Normaly overloaded by a child class
ls
      list the node commands
nodes
      list the children nodes:
           param arg (None)
           returns a python list all children node names
ping
      None
```

```
tree
     Print all self and children nodes availabled commands
          param arg (None)
          returns a string contain all commands
tcpproxy commands
help
     Print help text. Do nothing. Normaly overloaded by a child class
ls
     list the node commands
nodes
     list the children nodes:
          param arg (None)
          returns a python list all children node names
ping
     None
tree
     Print all self and children nodes availabled commands
          param arg (None)
          returns a string contain all commands
telescope commands
ack
     None
align2target
     None
firware date
     None
firware_ver
     None
getLocalDate
     None
getLocalTime
     None
getSideralTime
     None
getTargetDEC
```

None

```
None
getTelescopeDEC
     None
getTelescopeRA
     None
help
     Print help text. Do nothing. Normaly overloaded by a child class
info
     None
ls
     list the node commands
nodes
     list the children nodes:
          param arg (None)
          returns a python list all children node names
ping
     None
pulseE
     None
pulseN
     None
pulseS
     None
pulseW
     None
set Max Slew Rate \\
     None
setTargetDEC\\
     None
setTargetRA
     None
slew
     None
slewRate
     None
stopSlew
     None
tree
```

Print all self and children nodes availabled commands

param arg (None)

returns a string contain all commands

Drivers


Drivers interact with the real hardware and normaly are used in the **node** code.

Motors

Raspberry Drivers

rpiDRV8825Hat

This is a DIY Raspberry Pi Hat base on the popular stepper control chip DRV8825



API DIY DRV8825 driver Hat interface.

This board has two DRV8825 able to driver 2 motors See hardware on termiteOS/driver/rpi/hardware

INTERFACE TO OTHER MODULES:

- motorBeta
- pinout
- microsteps
- clutch()
- reset()
- sleep()
- set_microsteps(microsteps)
- sync(motorBeta)

This class define the PIN mapping and basic methods for the rpiDVR8825 Hat

Note: Posible values of driverID can be 0 or 1.

clutch (ON_OFF)

Engage or Disengage(free spinnig) the motors

fault (gpio, level, tick)

Callback function to check internal driver faults

```
reset (ON_OFF)
    Reset the driver circuit

set_dir (dir)
    Set the direction of motion

set_microsteps (microsteps)
    Set microstepping mode of the driver

sleep (ON_OFF)
    Sleep or wake up the driver circuit

stepcounter (gpio, level, tick)
    Callback function to update internal position counter

sync (position)
    Set the actual internal position == position

test ()
    Test the Hat sending steps
```

rpiSpeedPWM

A PWM driver

API Raspberry PWM motor driver.

INTERFACE:

- inherits several methods from rpiDRV8825Hut base class
 - betaMotor
 - pinout
 - microsteps
 - clutch()
 - reset()
 - sleep()
 - set_microsteps(microsteps)
 - sync(position)
- Own methods:
 - setSpeed (radians/seconds)
 - setRPM(RPM)
 - SetPoint(setpoint)
 - goto() -> absolute SetPoint
 - move() -> relative SetPoint
 - stop()
 - isStopped
 - gotoEnd
 - pos

4.3. Drivers 21

```
class termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM(driverID, microsteps, FullTurn-
                                                                    Steps, gear=1, name='Axis',
                                                                     raspberry='localhost')
     This class do the PWM control calling the underlying pigpiod daemon.
     Note: Up to dates only PID control is implemented.
     SetPoint (setpoint)
          Establish the _SetPoint value
     clutch(ON_OFF)
          Engage or Disengage(free spinnig) the motors
     fault (gpio, level, tick)
          Callback function to check internal driver faults
     goto (setpoint, blocking=False)
          Absolute movement
     gotoEnd
          True if the axis finally arrive to destination(_SetPoint), False otherwise
     isStopped
          True if is stopped, False otherwise
     move (relsetpoint)
          Relative movement
     pos
          Actual position (Corrected motorBeta)
     rampUp (v, deltaT, out_min=-750, out_max=750)
          Limit motor speed changes to avoid axis stalling
     reset (ON OFF)
          Reset the driver circuit
     run (*args, **kwargs)
     setRPM(rpm)
          Set and start PWM to obtain rpm
      setSpeed(v)
          Set and start PWM to obtain radians/seconds
      set_dir(dir)
          Set the direction of motion
      set_microsteps (microsteps)
          Set microstepping mode of the driver
     sleep(ON OFF)
          Sleep or wake up the driver circuit
     stepcounter (gpio, level, tick)
          Callback function to update internal position counter
     stop()
          Not implemented
      stopPWM()
          Stop PWM generation without any check
     sync (newposition)
          Establish newposition as current possition (motorBeta)
```

```
test()
    Test the Hat sending steps

trackSpeed(trackSpeed)
    Set axis track speed. Track speed*timestep is add to the _SetPoint value
termiteOS.drivers.rpi.rpiSpeedPWM.threaded(fn)
    Multithread wrapper. Used as a function decorator
```

Miscellaneus

TBD

Indices and tables

- genindex
- modindex
- search

Symbols					
-name <name></name>	isStopped (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM attribute), 22				
miteHub command line option, 11 miteJoy command line option, 12	attribute), 22				
mitetoproxy command line option, 13	L				
miteTelescope command line option, 14	launchmachine() (in module termiteOS.launch), 10				
miteTLEtracker command line option, 10	launchnode() (in module termiteOS.launch), 10				
-params <params></params>	M				
mitetcpproxy command line option, 13					
-parent_host <pre> parent_host <pre> parent_host</pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre>	miteHub command line option —name <name>, 11</name>				
miteHub command line option, 11 miteJoy command line option, 12	-parent_host <parent_host>, 11</parent_host>				
mitetoproxy command line option, 12	-parent_port <parent_nost 11<="" <,="" td=""></parent_nost>				
miteTelescope command line option, 14	-port <port>, 11</port>				
miteTLEtracker command line option, 10	miteJoy command line option				
-parent_port <parent_port></parent_port>	-name <name>, 12</name>				
miteHub command line option, 11	<pre>-parent_host <parent_host>, 12</parent_host></pre>				
miteJoy command line option, 12	-parent_port <pre></pre>				
mitetcpproxy command line option, 13	-port <port>, 12 mital aurah command line ention</port>				
miteTelescope command line option, 14	miteLaunch command line option YAMLFILE, 10				
miteTLEtracker command line option, 10 –port <port></port>	mitetopproxy command line option				
miteHub command line option, 11	-name <name>, 13</name>				
miteJoy command line option, 12	-params <params>, 13</params>				
mitetcpproxy command line option, 13	-parent_host <parent_host>, 13</parent_host>				
miteTelescope command line option, 14	<pre>-parent_port <parent_port>, 13</parent_port></pre>				
miteTLEtracker command line option, 10	-port <port>, 13</port>				
С	miteTelescope command line option				
	-name <name>, 14</name>				
clutch() (termiteOS.drivers.rpi.rpiDRV8825Hat.rpiDRV8825Hatparent_host <parent_host>, 14</parent_host>					
method), 20	1.4				
clutch() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedP method), 22	miteTLEtracker command line option				
method), 22	-name <name>, 10</name>				
F	<pre>-parent_host <parent_host>, 10</parent_host></pre>				
fault() (termiteOS.drivers.rpi.rpiDRV8825Hat.rpiDRV88	25Hat -parent_port <parent_port>, 10 -port <port>, 10</port></parent_port>				
method), 20 fault() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPW	move() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM				
method), 22	method), 22				
	P				
G	nos (termiteOS drivers rni rniSpeedPWM rniSpeedPWM				
goto() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM attribute), 22 method), 22					
gotoEnd (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM					
attribute), 22	rampUp() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM method), 22				

```
reset() (termiteOS.drivers.rpi.rpiDRV8825Hat.rpiDRV8825Hat.speed() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM
         method), 20
                                                              method), 23
reset() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM
         method), 22
rpiDRV8825Hat
                      (class
                                             termi-
                                                    YAMLFILE
         teOS.drivers.rpi.rpiDRV8825Hat), 20
                                                         miteLaunch command line option, 10
rpiSpeedPWM
                     (class
                                   in
                                             termi-
         teOS.drivers.rpi.rpiSpeedPWM), 21
run() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM
         method), 22
run_in_separate_process()
                                  module
                           (in
                                             termi-
         teOS.launch), 10
S
set_dir() (termiteOS.drivers.rpi.rpiDRV8825Hat.rpiDRV8825Hat
         method), 21
set_dir() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM
         method), 22
set_microsteps()
                                            (termi-
         teOS.drivers.rpi.rpiDRV8825Hat.rpiDRV8825Hat
         method), 21
set_microsteps()
         teOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM
         method), 22
SetPoint() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM
         method), 22
setRPM() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM
         method), 22
setSpeed() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM
         method), 22
sleep() (termiteOS.drivers.rpi.rpiDRV8825Hat.rpiDRV8825Hat
         method), 21
sleep() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM
         method), 22
stepcounter() (termiteOS.drivers.rpi.rpiDRV8825Hat.rpiDRV8825Hat
         method), 21
stepcounter() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM
         method), 22
stop() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM
         method), 22
stopPWM() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM
         method), 22
sync() (termiteOS.drivers.rpi.rpiDRV8825Hat.rpiDRV8825Hat
         method), 21
sync() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM
         method), 22
Т
termiteOS.drivers.rpi.rpiDRV8825Hat (module), 20
termiteOS.drivers.rpi.rpiSpeedPWM (module), 21
termiteOS.launch (module), 10
test() (termiteOS.drivers.rpi.rpiDRV8825Hat.rpiDRV8825Hat
         method), 21
test() (termiteOS.drivers.rpi.rpiSpeedPWM.rpiSpeedPWM
         method), 22
threaded()
                  (in
                             module
                                             termi-
```

26 Index

teOS.drivers.rpi.rpiSpeedPWM), 23