

Podstawy baz danych


Projekt konferencje

Agnieszka Dutka, Maciek Trątnowiecki

AGH, Styczeń 2020

Objaśnienie schematu bazy

- Clients - Reprezentuje klientów chcących opłacić miejsca na konferencjach i warsztatach. Klientem może być zarówno firma, jak i osoba prywatna. W zależności od tego dane klienta reprezentowane są przez odpowiednią relację w bazie.
- Companies - Jeśli klient jest firmą, przechowuje jego dane.
- Participants - Jeśli klient jest osobą prywatną, przechowuje jego dane.
- Conferences - Reprezentuje konferencję z którą powiązane są odpowiednie dni konferencyjne, oraz warsztaty.
- Conference_days - Reprezentuje pojedynczy dzień konferencji. Powiązana jest z nim ustalona opłata za uczestnictwo. Zniżki obowiązujące w zależności od daty rejestracji zawarte są w relacji Early_Signup_Discounts.
- Early_Signup_Discounts - Odpowiada za informację o tabeli zniżek na dany dzień konferencyjny. Pojedyncza zniżka przechowywana jest w krotce z atrybutami w postaci procentowej obniżki ceny standardowej, oraz ostatniego dnia w którym obowiązuje.
- Conference_day_reservations - Realizuje rezerwacje na poszczególny dzień konferencji. Każda rezerwacja powiązana jest z klientem, który ją opłaca. Za powiązanie rezerwacji z uczestnikiem odpowiada osobna relacja. Zawiera także pole due_price określające termin płatności. Atrybut active odpowiada za możliwość rezygnacji z podjętej rezerwacji (uznaliśmy, że usuwanie krotki z bazy może nie być optymalnym rozwiązaniem, jako że zawarte w niej dane mogą jeszcze być przydatne z punktu widzenia logiki biznesowej). Atrybuty adult_seats i student_seats służą do liczenia kosztu podjęcia rezerwacji przed powiązaniem jej z uczestnikami konferencji.
- Conference_day_registration - Wiąże rezerwację z uczestnikami konferencji. Atrybut is_student informuje, czy danemu uczestnikowi przysługuje zniżka studencka.
- Payments - Przechowuje informacje o wpływach pieniężnych powiązanych z daną rejestracją.
- Workshops - Reprezentuje warsztaty odbywające się w trakcie odpowiednich dni konferencyjnych.
- Workshops_reservations - Opisuje rezerwacje na warsztaty w sposób analogiczny do rezerwacji na konferencje.
- Workshops_registrations - Łączy rezerwację z uczestnikami w sposób analogiczny do dni konferencyjnych.



Implementacja

```
1000 -- tables
1001 -- Table: Clients
1002 CREATE TABLE Clients (
1003     id int NOT NULL IDENTITY,
1004     zip_code varchar(6) NOT NULL,
1005     city varchar(30) NOT NULL,
1006     address varchar(100) NOT NULL,
1007     CONSTRAINT Clients_pk PRIMARY KEY (id)
1008 );
1009
1010 -- Table: Companies
1011 CREATE TABLE Companies (
1012     companyName varchar(100) NOT NULL,
1013     nip nvarchar(15) NOT NULL CHECK ((nip not like '%[^0-9]%' ) and (LEN(nip) = 10) and (nip
1014     not like '0%' or nip like '1%')),
1015     phone varchar(20) NOT NULL,
1016     clients_id int NOT NULL,
1017     email varchar(100) NOT NULL CHECK (email like '%_@_%._%'),
1018     CONSTRAINT unique_nip UNIQUE (nip),
1019     CONSTRAINT checkNip CHECK (dbo.IsValidNip(nip) = 1),
1020     CONSTRAINT Companies_pk PRIMARY KEY (clients_id)
1021 );
1022
1023 -- Table: Conference_day_registration
1024 CREATE TABLE Conference_day_registration (
1025     reservation_id int NOT NULL,
1026     Participant_id int NOT NULL,
1027     is_student bit NOT NULL DEFAULT 0,
1028     CONSTRAINT Conference_day_registration_pk PRIMARY KEY (reservation_id ,Participant_id)
1029 );
1030
1031 -- Table: Conference_day_reservations
1032 CREATE TABLE Conference_day_reservations (
1033     reservation_id int NOT NULL IDENTITY,
1034     conference_day_id int NOT NULL,
1035     clients_id int NOT NULL,
1036     reservation_date datetime NOT NULL DEFAULT GETDATE() ,
1037     active bit NOT NULL DEFAULT 1,
1038     due_price datetime NOT NULL DEFAULT DATEADD(week, 2, GETDATE()) CHECK (due_price >=
1039     GETDATE()),
1040     adult_seats int NOT NULL DEFAULT 0 CHECK (adult_seats >= 0),
1041     student_seats int NOT NULL DEFAULT 0 CHECK (student_seats >= 0),
1042     CONSTRAINT Conference_day_reservations_pk PRIMARY KEY (reservation_id)
1043 );
1044
1045 -- Table: Conference_days
1046 CREATE TABLE Conference_days (
1047     conference_day_id int NOT NULL IDENTITY,
1048     conference_id int NOT NULL,
1049     date date NOT NULL DEFAULT GETDATE() ,
1050     standard_price money NOT NULL DEFAULT 0 CHECK (standard_price >= 0),
1051     student_discount decimal(4,4) NOT NULL DEFAULT 0 CHECK (student_discount >= 0),
1052     number_of_seats int NOT NULL DEFAULT 0 CHECK (number_of_seats >= 0),
1053     CONSTRAINT Conference_days_pk PRIMARY KEY (conference_day_id)
1054 );
1055
1056 -- Table: Conferences
1057 CREATE TABLE Conferences (
1058     Conference_id int NOT NULL IDENTITY,
1059     name varchar(100) NOT NULL,
1060     description text NULL,
1061     CONSTRAINT Conferences_pk PRIMARY KEY (Conference_id)
1062 );
1063
1064 -- Table: Early_signup_discounts
1065 CREATE TABLE Early_signup_discounts (
1066     discount_id int NOT NULL IDENTITY,
1067     conference_day_id int NOT NULL,
1068     end_date datetime NOT NULL,
1069     discount decimal(4,4) NOT NULL DEFAULT 0,
1070     CONSTRAINT Early_signup_discounts_pk PRIMARY KEY (discount_id)
1071 );
1072
1073 -- Table: Participants
```

```

1072 CREATE TABLE Participants (
      participant_id int NOT NULL IDENTITY,
1074      clients_id int NULL DEFAULT Null,
      name varchar(100) NOT NULL,
1076      surname varchar(100) NOT NULL,
      email varchar(100) NOT NULL CHECK (email like '%_@_%._%'),
1078      phone varchar(20) NOT NULL,
      CONSTRAINT Participants-pk PRIMARY KEY (participant_id)
1080 );

1082 — Table: Payments
CREATE TABLE Payments (
1084      payment_id int NOT NULL IDENTITY,
      reservation_id int NOT NULL,
1086      in_date datetime NOT NULL,
      value money NOT NULL,
1088      CONSTRAINT Payments-pk PRIMARY KEY (payment_id)
);

1090 — Table: Workshop-registration
1092 CREATE TABLE Workshop-registration (
      Participant_id int NOT NULL,
1094      reservation_id int NOT NULL,
      CONSTRAINT Workshop-registration-pk PRIMARY KEY (Participant_id, reservation_id)
1096 );

1098 — Table: Workshop-reservations
CREATE TABLE Workshop-reservations (
1100      reservation_id int NOT NULL IDENTITY,
      workshop_id int NOT NULL,
1102      reservation_date datetime NOT NULL DEFAULT GETDATE(),
      due_price datetime NOT NULL DEFAULT DATEADD(week, 2, GETDATE()) CHECK (due_price >=
GETDATE()),
1104      nr_of_seats int NOT NULL DEFAULT 0 CHECK (nr_of_seats >= 0),
      Conference_day_res_id int NOT NULL,
1106      active bit NOT NULL DEFAULT 1,
      CONSTRAINT Workshop-reservations-pk PRIMARY KEY (reservation_id)
1108 );

1110 — Table: Workshops
CREATE TABLE Workshops (
1112      workshop_id int NOT NULL IDENTITY,
      conference_day_id int NOT NULL,
1114      start_time datetime NOT NULL,
      end_time datetime NOT NULL CHECK (end_time >= GETDATE()),
1116      topic text NOT NULL,
      price money NOT NULL CHECK (price >= 0),
1118      number_of_seats int NOT NULL DEFAULT 0 CHECK (number_of_seats >= 0),
      CONSTRAINT Workshops-pk PRIMARY KEY (workshop_id)
1120 );

1122 — foreign keys
— Reference: Companies_Clients (table: Companies)
1124 ALTER TABLE Companies ADD CONSTRAINT Companies_Clients
      FOREIGN KEY (clients_id)
1126      REFERENCES Clients (id);

1128 — Reference: Conference_day_registration_Conference_day_reservations (table:
      Conference_day_registration)
ALTER TABLE Conference_day_registration ADD CONSTRAINT
      Conference_day_registration_Conference_day_reservations
1130      FOREIGN KEY (reservation_id)
      REFERENCES Conference_day_reservations (reservation_id)
1132      ON DELETE CASCADE;

1134 — Reference: Conference_day_registration_Participants (table: Conference_day_registration)
ALTER TABLE Conference_day_registration ADD CONSTRAINT
      Conference_day_registration_Participants
1136      FOREIGN KEY (Participant_id)
      REFERENCES Participants (participant_id)
1138      ON DELETE CASCADE;

1140 — Reference: Conference_day_reservations_Clients (table: Conference_day_reservations)
ALTER TABLE Conference_day_reservations ADD CONSTRAINT Conference_day_reservations_Clients
1142      FOREIGN KEY (clients_id)
      REFERENCES Clients (id);

```

```

1144  — Reference: Conference_day_reservations_Conference_days (table: Conference_day_reservations)
1146  ALTER TABLE Conference_day_reservations ADD CONSTRAINT
      Conference_day_reservations_Conference_days
      FOREIGN KEY (conference_day_id)
1148  REFERENCES Conference_days (conference_day_id)
      ON DELETE CASCADE;
1150
1150  — Reference: Conference_days_Conferences (table: Conference_days)
1152  ALTER TABLE Conference_days ADD CONSTRAINT Conference_days_Conferences
      FOREIGN KEY (conference_id)
1154  REFERENCES Conferences (Conference_id)
      ON DELETE CASCADE;
1156
1156  — Reference: Discounts_Conference_days (table: Early_signup_discounts)
1158  ALTER TABLE Early_signup_discounts ADD CONSTRAINT Discounts_Conference_days
      FOREIGN KEY (conference_day_id)
1160  REFERENCES Conference_days (conference_day_id)
      ON DELETE CASCADE;
1162
1162  — Reference: Participants_Clients (table: Participants)
1164  ALTER TABLE Participants ADD CONSTRAINT Participants_Clients
      FOREIGN KEY (clients_id)
1166  REFERENCES Clients (id)
      ON DELETE SET NULL;
1168
1168  — Reference: Payments_Conference_day_reservations (table: Payments)
1170  ALTER TABLE Payments ADD CONSTRAINT Payments_Conference_day_reservations
      FOREIGN KEY (reservation_id)
1172  REFERENCES Conference_day_reservations (reservation_id);
1174
1174  — Reference: Workshop_registration_Participants (table: Workshop_registration)
1176  ALTER TABLE Workshop_registration ADD CONSTRAINT Workshop_registration_Participants
      FOREIGN KEY (Participant_id)
      REFERENCES Participants (participant_id)
1178  ON DELETE CASCADE;
1180
1180  — Reference: Workshop_registration_Workshop_reservations (table: Workshop_registration)
1182  ALTER TABLE Workshop_registration ADD CONSTRAINT Workshop_registration_Workshop_reservations
      FOREIGN KEY (reservation_id)
      REFERENCES Workshop_reservations (reservation_id)
1184  ON DELETE CASCADE;
1186
1186  — Reference: Workshop_reservations_Conference_day_reservations (table: Workshop_reservations)
1188  ALTER TABLE Workshop_reservations ADD CONSTRAINT
      Workshop_reservations_Conference_day_reservations
      FOREIGN KEY (Conference_day_res_id)
1188  REFERENCES Conference_day_reservations (reservation_id)
1190  ON DELETE CASCADE;
1192
1192  — Reference: Workshop_reservations_Workshops (table: Workshop_reservations)
1194  ALTER TABLE Workshop_reservations ADD CONSTRAINT Workshop_reservations_Workshops
      FOREIGN KEY (workshop_id)
      REFERENCES Workshops (workshop_id)
1196  ON DELETE CASCADE;
1198
1198  — Reference: Workshops_Conference_days (table: Workshops)
1200  ALTER TABLE Workshops ADD CONSTRAINT Workshops_Conference_days
      FOREIGN KEY (conference_day_id)
      REFERENCES Conference_days (conference_day_id);
1202
1202  — End of file.

```

../Create.sql

```

1000 CREATE FUNCTION IsValidNip(
1001     @nip nvarchar(15)
1002 )
1003     RETURNS bit
1004 AS
1005 BEGIN
1006     IF ISNUMERIC(@nip) = 0
1007         BEGIN
1008             RETURN 0
1009         END
1010
1011     IF @nip = '0000000000'
1012         BEGIN
1013             RETURN 0
1014         END
1015
1016     IF @nip = '1234567891'
1017         BEGIN
1018             RETURN 0
1019         END
1020
1021     IF @nip = '1111111111'
1022         BEGIN
1023             RETURN 0
1024         END
1025
1026     IF @nip = '1111111112'
1027         BEGIN
1028             RETURN 0
1029         END
1030
1031     IF @nip = '9999999999'
1032         BEGIN
1033             RETURN 0
1034         END
1035
1036     IF @nip = '1111111112'
1037         BEGIN
1038             RETURN 0
1039         END
1040
1041     DECLARE @sum INT;
1042     SET @sum = 6 * CONVERT(INT, SUBSTRING(@nip, 1, 1)) +
1043         5 * CONVERT(INT, SUBSTRING(@nip, 2, 1)) +
1044         7 * CONVERT(INT, SUBSTRING(@nip, 3, 1)) +
1045         2 * CONVERT(INT, SUBSTRING(@nip, 4, 1)) +
1046         3 * CONVERT(INT, SUBSTRING(@nip, 5, 1)) +
1047         4 * CONVERT(INT, SUBSTRING(@nip, 6, 1)) +
1048         5 * CONVERT(INT, SUBSTRING(@nip, 7, 1)) +
1049         6 * CONVERT(INT, SUBSTRING(@nip, 8, 1)) +
1050         7 * CONVERT(INT, SUBSTRING(@nip, 9, 1));
1051
1052     IF CONVERT(TINYINT, SUBSTRING(@nip, 10, 1)) = (@sum % 11)
1053         BEGIN
1054             RETURN 1
1055         END
1056     RETURN 0
1057 END

```

../Functions/IsValidNip.sql

Widoki

```
1000 — Shows sum of payments per reservation
1001 CREATE VIEW PaymentsForReservation
1002 AS
1003 SELECT reservation_id , ISNULL(sum(Payments.value) , 0) as already_paid
1004 FROM Payments
1005 GROUP BY reservation_id
1006 GO

1008 — Show sum of payments per client
1009 CREATE VIEW PaymentsForClients
1010 AS
1011 SELECT clients_id , SUM(value) AS paid
1012 FROM Payments
1013         INNER JOIN Conference_day_reservations Cdr ON Payments.reservation_id = Cdr.
1014         reservation_id
1015 GROUP BY clients_id
1016 GO

1018 — Shows balance of payments per reservation
1019 CREATE VIEW BalanceForReservation
1020 AS
1021 SELECT reservation_id , already_paid - dbo.confReservationPrice(reservation_id) as balance
1022 FROM PaymentsForReservation
1023 GO

1024 — Shows payment balance per client
1025 CREATE VIEW ClientsBalanceView
1026 AS
1027 SELECT id as client_id ,
1028        dbo.clientsBalance(id) as balance
1029 FROM Clients
1030 GO

1032 — Shows clients with unpaid reservations
1033 CREATE VIEW ClientsWithUnpaidReservations
1034 AS
1035 SELECT clients_id ,
1036        reservation_id ,
1037        due_price
1038        as to_pay_until ,
1039        DATEDIFF(DAY, GETDATE() , due_price) as days_left ,
1040        dbo.confReservationPrice(reservation_id) - dbo.confReservationPaidAmount(reservation_id)
1041        as left_to_pay ,
1042        dbo.showClientsName(clients_id)
1043        as clients_name
1044 FROM Conference_day_reservations
1045 WHERE dbo.confReservationPrice(reservation_id) - dbo.confReservationPaidAmount(reservation_id)
1046        > 0.01
1047 and Conference_day_reservations.active = 1
1048 GO

1046 — Same but only for companies
1047 CREATE VIEW CompaniesWithUnpaidReservations
1048 AS
1049 SELECT *
1050 FROM ClientsWithUnpaidReservations
1051 WHERE dbo.isClientCompany(clients_id) = 1
1052 GO

1054 — Same but only for individual clients
1055 CREATE VIEW IndividualClientsWithUnpaidReservations
1056 AS
1057 SELECT *
1058 FROM ClientsWithUnpaidReservations
1059 WHERE dbo.isClientCompany(clients_id) = 0
1060 GO

1062 — Same, but with the earliest payment deadline
1063 CREATE VIEW UnpaidReservationsWithEarliestDeadline
1064 AS
1065 SELECT TOP 10 *
1066 FROM ClientsWithUnpaidReservations
1067 ORDER BY to_pay_until ASC
```

```

GO
1070
1072 — Clients with unpaid reservations who exceeded payment deadline
CREATE VIEW ClientsWithExceededPaymentDeadline
AS
1074     SELECT *
FROM ClientsWithUnpaidReservations
1076     WHERE to_pay_until < GETDATE()
GO
1078
1080 — Workshops with free seats available
CREATE VIEW WorkshopsWithFreeSeats
AS
1082     SELECT workshop_id ,
            dbo.workshopFreeSeats(workshop_id) as free_seats
1084 FROM Workshops
WHERE dbo.workshopFreeSeats(workshop_id) > 0
1086 GO
1088
1088 — Conference days with free seats available
CREATE VIEW ConferenceDaysWithFreeSeats
AS
1090     SELECT conference_day_id ,
            dbo.conferenceFreeSeats(conference_day_id) as free_seats
1092 FROM Conference_days
WHERE dbo.conferenceFreeSeats(conference_day_id) > 0
1094 GO
1096
1098 — Clients who paid the most
CREATE VIEW ClientsWhoPaidMost
AS
1100     SELECT TOP 20 *
from PaymentsForClients
1102     ORDER BY paid DESC
GO
1104
1106 — Clients with the highest count of conference reservations
CREATE VIEW MostActiveClients
AS
1108     SELECT TOP 20 clients_id , COUNT(reservation_id) AS reservation_count
FROM Clients
1110         INNER JOIN Conference_day_reservations Cdr on Clients.id = Cdr.clients_id
GROUP BY clients_id
1112     ORDER BY COUNT(reservation_id) DESC
GO
1114
1116 — Show participants for conference days
CREATE VIEW ParticipantsForConferenceDay
AS
1118     SELECT name, surname, conference_day_id
FROM Participants
1120         INNER JOIN Conference_day_registration Cdr on Participants.participant_id = Cdr.
            Participant_id
            INNER JOIN Conference_day_reservations Cdr on Cdr.reservation_id = Cdr.
            reservation_id
1122
1124 — Show participants for workshops
CREATE VIEW ParticipantsForWorkshop
AS
1126     SELECT name, surname, workshop_id
FROM Participants
1128         INNER JOIN Workshop_registration Wrg on Participants.participant_id = Wrg.
            Participant_id
            INNER JOIN Workshop_reservations Wrs on Wrg.reservation_id = Wrs.reservation_id
1130
1132 — Show cancelled conference reservations
CREATE VIEW CancelledConferenceReservations
AS
1134     SELECT reservation_id ,
            conference_day_id ,
1136            reservation_date ,
            clients_id ,
1138            adult_seats ,
            student_seats ,
1140            dbo.showClientsName(clients_id) as clients_name
FROM Conference_day_reservations

```



```

1142 WHERE active = 0
1144 — Show cancelled workshops reservations
1146 CREATE VIEW CancelledWorkshopsReservations
1148 AS
1150     SELECT Workshop_reservations.reservation_id ,
1151            workshop_id ,
1152            Workshop_reservations.reservation_date ,
1153            nr_of_seats ,
1154            dbo.showClientsName( clients_id ) as clients_name
1155 FROM Workshop_reservations
1156     INNER JOIN Conference_day_reservations Cdr on Workshop_reservations .
1157     Conference_day_res_id = Cdr.reservation_id
1158 WHERE Workshop_reservations.active = 0
1159 GO

```

../Views/Views.sql

Funkcje

```
1000 CREATE FUNCTION isClientCompany(  
      @client_id int  
1002 )  
      RETURNS bit  
1004 AS  
BEGIN  
1006     DECLARE @res bit = ISNULL((SELECT 1 FROM Companies WHERE clients_id=@client_id),0)  
      RETURN @res  
1008 END
```

../Functions/isClientCompany.sql

```
1000 CREATE FUNCTION IsValidNip(  
      @nip nvarchar(15)  
1002 )  
      RETURNS bit  
1004 AS  
BEGIN  
1006     IF ISNUMERIC(@nip) = 0  
          BEGIN  
1008         RETURN 0  
          END  
1010  
      IF @nip = '0000000000'  
          BEGIN  
1012         RETURN 0  
          END  
1014  
      IF @nip = '1234567891'  
          BEGIN  
1016         RETURN 0  
          END  
1018  
      IF @nip = '1111111111'  
          BEGIN  
1020         RETURN 0  
          END  
1022  
      IF @nip = '1111111112'  
          BEGIN  
1024         RETURN 0  
          END  
1026  
      IF @nip = '9999999999'  
          BEGIN  
1028         RETURN 0  
          END  
1030  
      IF @nip = '1111111112'  
          BEGIN  
1032         RETURN 0  
          END  
1034  
      DECLARE @sum INT;  
      SET @sum = 6 * CONVERT(INT, SUBSTRING(@nip, 1, 1)) +  
1038         5 * CONVERT(INT, SUBSTRING(@nip, 2, 1)) +  
         7 * CONVERT(INT, SUBSTRING(@nip, 3, 1)) +  
1040         2 * CONVERT(INT, SUBSTRING(@nip, 4, 1)) +  
         3 * CONVERT(INT, SUBSTRING(@nip, 5, 1)) +  
1042         4 * CONVERT(INT, SUBSTRING(@nip, 6, 1)) +  
         5 * CONVERT(INT, SUBSTRING(@nip, 7, 1)) +  
1044         6 * CONVERT(INT, SUBSTRING(@nip, 8, 1)) +  
         7 * CONVERT(INT, SUBSTRING(@nip, 9, 1));  
1046  
      IF CONVERT(TINYINT, SUBSTRING(@nip, 10, 1)) = (@sum % 11)  
1048         BEGIN  
            RETURN 1  
          END  
1050  
      RETURN 0  
1052 END
```

../Functions/IsValidNip.sql

```
1000 CREATE FUNCTION showClientsName(  
      @client_id int  
1002 )  
      RETURNS varchar(100)  
1004 AS
```

```

BEGIN
1006     DECLARE @name VARCHAR(100) = (SELECT name + ' ' + surname FROM Participants WHERE
        clients_id = @client_id)
        if @name is not null
1008         BEGIN
            RETURN @name
1010         END
        SET @name = (SELECT companyName FROM Companies WHERE clients_id = @client_id)
1012     RETURN @name
END

```

../Functions/showClientsName.sql

```

1000 CREATE FUNCTION conferenceFreeSeats (@conferenceId int)
        RETURNS INT
1002 AS
BEGIN
1004     DECLARE @used INT
        SET @used = ISNULL((SELECT SUM(adult_seats + student_seats)
1006                             FROM Conference_day_reservations
                             WHERE conference_day_id = @conferenceId), 0)

1008     DECLARE @all INT
        SET @all = (SELECT number_of_seats
1010                     FROM Conference_days
                     WHERE conference_day_id = @conferenceId)
1012     RETURN @all - @used
END
1014 GO

```

../Functions/FreeSeats/conferenceFreeSeats.sql

```

1000 CREATE FUNCTION workshopFreeSeats (@workshopId int)
        RETURNS INT
1002 AS
BEGIN
1004     DECLARE @used INT
        SET @used = ISNULL((SELECT SUM(nr_of_seats)
1006                             FROM Workshop_reservations
                             WHERE workshop_id = @workshopId), 0)

1008     DECLARE @all INT
        SET @all = (SELECT number_of_seats
1010                     FROM Workshops
                     WHERE workshop_id = @workshopId)
1012     RETURN @all - @used
END
1014 GO

```

../Functions/FreeSeats/workshopFreeSeats.sql

```

1000 CREATE FUNCTION participantsForGivenConference (
        @conferenceID int
1002 )
        RETURNS table
1004 AS
        RETURN SELECT name, surname
1006                FROM ParticipantsForConferenceDay
                WHERE conference_day_id = @conferenceID

```

../Functions/ParticipantsLists/participantsForGivenConference.sql

```

1000 CREATE FUNCTION participantsForGivenWorkshop (
        @workshopID int
1002 )
        RETURNS table
1004 AS
        RETURN SELECT name, surname
1006                FROM ParticipantsForWorkshop
                WHERE workshop_id = @workshopID

```

../Functions/ParticipantsLists/participantsForGivenWorkshop.sql

```

1000 CREATE FUNCTION clientsBalance (@ClientId int)
        RETURNS MONEY
1002 AS

```

```

BEGIN
1004 DECLARE @paid MONEY = (SELECT SUM(P.VALUE)
                             FROM Payments P
                             inner join Conference_day_reservations Cdr on P.
                             reservation_id = Cdr.reservation_id
                             WHERE Cdr.clients_id = @ClientId and cdr.active = 1)
1006 DECLARE @owed MONEY = (SELECT SUM(dbo.confReservationPrice(cdr.reservation_id))
                             FROM Conference_day_reservations cdr
                             WHERE cdr.clients_id = @ClientId and cdr.active = 1)
1008 DECLARE @res MONEY = ROUND(ISNULL(@paid, 0) - ISNULL(@owed, 0), 2);
1010 IF @res = 0.01
1012 BEGIN
1014     return 0
1016     END
1018 RETURN @res
END

```

../Functions/PaymentsAndPrices/clientsBalance.sql

```

1000 CREATE FUNCTION confDayPrice(@reservationId int)
      RETURNS MONEY
1002 AS
      BEGIN
1004 DECLARE @earlySignupDiscount decimal(4, 4) = ISNULL((Select TOP 1 esd.discount
                                                           from Conference_day_reservations as
                                                           res
                                                           inner join Conference_days
                                                           as day on res.conference_day_id = day.conference_day_id
                                                           inner join
                                                           Early_signup_discounts esd
                                                           on day.
                                                           conference_day_id = esd.conference_day_id
                                                           where reservation_id = @reservationId
                                                           and esd.end_date > res.
                                                           reservation_date
                                                           order by esd.end_date ASC), 0)
1010 DECLARE @nrOfStudents int = (SELECT student_seats
                                 FROM Conference_day_reservations
                                 WHERE reservation_id = @reservationId)
1012 DECLARE @nrOfAdults int = (SELECT adult_seats
                               FROM Conference_day_reservations
                               WHERE reservation_id = @reservationId)
1014 DECLARE @conferenceDayID int = (SELECT conference_day_id
                                   FROM Conference_day_reservations
                                   WHERE reservation_id = @reservationId)
1016 DECLARE @standardPrice money = (SELECT standard_price
                                   FROM Conference_days
                                   WHERE conference_day_id = @conferenceDayID)
1018 DECLARE @studentDiscount decimal(4, 4) = (SELECT student_discount
                                                FROM Conference_days
                                                WHERE conference_day_id = @conferenceDayID)
1020 DECLARE @price money = (@nrOfAdults * @standardPrice) +
1022     (@nrOfStudents * (@standardPrice * (1.0 - @studentDiscount)))
1024 RETURN CONVERT(money, ROUND(@price * (1.0 - @earlySignupDiscount), 2))
1026 END
1028 GO

```

../Functions/PaymentsAndPrices/confDayPrice.sql

```

1000 CREATE FUNCTION confReservationPaidAmount(@reservation_id int)
      RETURNS MONEY
1002 AS
      BEGIN
1004 RETURN ISNULL((SELECT sum(value) FROM Payments WHERE reservation_id = @reservation_id), 0)
1006 END

```

../Functions/PaymentsAndPrices/confReservationPaidAmount.sql

```

1000 CREATE FUNCTION confReservationPrice(@reservation_id int)
      RETURNS MONEY
1002 AS
      BEGIN
1004 DECLARE @dayPrice money = dbo.confDayPrice(@reservation_id);
1006 DECLARE @workshopsPrice money = (select sum(wr.nr_of_seats * W.price)
                                   from Workshop_reservations wr

```

```

1008         workshop_id          inner join Workshops W on wr.workshop_id = W.
1010         where wr.Conference_day_res_id = @reservation_id);

RETURN ROUND(@dayPrice + ISNULL(@workshopsPrice , 0) , 2)
END

```

../Functions/PaymentsAndPrices/confReservationPrice.sql

Generator danych

```
1000 from ParticipantsGenerator import *
1001 from ClientsGenerator import *
1002 from ConfDayResGenerator import *
1003 from ConfDaysGenerator import *
1004 from EsdGenerator import *
1005 from ConferenceGenerator import *
1006 from WorkshopGenerator import *
1007 from WorkshopResGen import *
1008 from ConfRegistrationGen import *
1009 from WorkshopRegistrationGen import *
1010 from PaymentGen import *

1011
1012 from random import Random
1013 from faker import Faker
1014
1015 faker = Faker(['pl_PL'])
1016 rand = Random()
1017
1018 generators = []
1019
1020 part_gen = ParticipantsGenerator(rand)
1021 part_gen.make(None, 4000)
1022 #part_gen.make(None, 5)
1023
1024 clients_gen = ClientsGenerator(part_gen)
1025 generators.append(clients_gen)
1026 clients_gen.make(400)
1027 #clients_gen.make(10)
1028
1029 conf_gen = ConferenceGenerator(rand, faker)
1030 generators.append(conf_gen)
1031 conf_gen.make(72)
1032 #conf_gen.make(3)
1033
1034 day_gen = ConfDaysGenerator(rand, faker)
1035 generators.append(day_gen)
1036 day_gen.make(conf_gen.conferences)
1037
1038 esd_gen = EsdGenerator(rand, faker)
1039 generators.append(esd_gen)
1040 esd_gen.make(day_gen.days)
1041
1042 day_res_gen = ConfDayResGenerator(clients_gen, rand, faker)
1043 generators.append(day_res_gen)
1044 day_res_gen.make(day_gen.days)
1045
1046 wor_gen = WorkshopGenerator(part_gen, rand, faker)
1047 generators.append(wor_gen)
1048 wor_gen.make(day_gen.days)
1049
1050 wor_res_gen = WorkshopResGen(day_res_gen)
1051 generators.append(wor_res_gen)
1052 wor_res_gen.make(wor_gen.workshops)
1053
1054 conf_reg_gen = ConfRegistrationGen(rand, part_gen)
1055 generators.append(conf_reg_gen)
1056 conf_reg_gen.make(day_res_gen.reservations)
1057
1058 wor_reg_gen = WorkshopRegistrationGen(rand, part_gen)
1059 generators.append(wor_reg_gen)
1060 wor_reg_gen.make(wor_res_gen.reservations)
1061
1062 pay_gen = PaymentGen(rand, faker)
1063 generators.append(pay_gen)
1064 pay_gen.make(day_res_gen.reservations)
1065
1066 for g in generators:
1067     print(g.to_sql())
```

../Generator/main.py

```
1000 from datetime import datetime, timedelta, time
```

```

1002 class AbstractClass:
1004     def random_time(self, date):
1006         return datetime.combine(date, time(self.rand.randint(0, 23), self.rand.randint(0, 59))
1008     )

```

../Generator/AbstractClass.py

```

1000 def table_to_sql(table, n_row=True):
1002     res = '\n' if n_row else ''
1004     res += table[0].to_sql()
1006     lid = 0
1008     for v in range(1, len(table)):
1010         if v - lid < 950:
1012             res += ','
1014             res += table[v].to_sql(False)
1016         else:
1018             res += '\n'
1020             res += table[v].to_sql()
1022             lid = v
1024     return res

```

../Generator/AbstractGenerator.py

```

1000 class Client:
1002     def __init__(self, cl_id, faker):
1004         self.cl_id = cl_id
1006         self.faker = faker
1008
1010         add = self.faker.address().split('\n')
1012         self.address = add[0]
1014         self.zip_code = add[-1].split(' ')[0]
1016         self.city = ' '.join(add[-1].split(' ')[1:])
1018
1020     def to_sql(self, start=True):
1022         values = "(" + str(self.cl_id) + ",\'" + self.zip_code + "\',\'" + self.city + "\',\'"
1024         + self.address + "\')'"
1026         return "INSERT INTO CLIENTS (id,zip_code, city, address) " \
1028             "VALUES "+ values if start else values

```

../Generator/Client.py

```

1000 from faker import Faker
1002 import random
1004 from ParticipantsGenerator import *
1006 from Client import *
1008 from Company import *
1010
1012 def table_to_sql(table):
1014     res = '\n'
1016     res += table[0].to_sql()
1018     lid = 0
1020     for v in range(1, len(table)):
1022         if v - lid < 950:
1024             res += ','
1026             res += table[v].to_sql(False)
1028         else:
1030             lid = v
1032             res += '\n'
1034             res += table[v].to_sql()
1036     return res
1038
1040 class ClientsGenerator:
1042     def __init__(self, participants_gen, next_client_id=1):
1044         self.faker = Faker(['pl.PL'])
1046         self.rand = random.Random()
1048
1050         self.next_client_id = next_client_id
1052         self.participants_gen = participants_gen
1054         self.clients = []
1056         self.companies = []
1058
1060     def choice(self):

```

```

1034         return self.rand.choice(self.clients)
1036
1038     def clients_count(self):
1039         return len(self.clients)
1040
1042     def make(self, n=1):
1043         for _ in range(n):
1044             cl = Client(self.next_client_id, self.faker)
1045             if self.rand.randint(0, 1) == 0:
1046                 cm = Company(self.next_client_id, self.faker, self.rand)
1047                 self.companies.append(cm)
1048             else:
1049                 self.participants_gen.make(self.next_client_id)
1050                 self.next_client_id += 1
1051                 self.clients.append(cl)
1052
1054     def to_sql(self):
1055         res = 'SET IDENTITY_INSERT Clients ON'
1056         res += table_to_sql(self.clients)
1057
1058         res += '\nSET IDENTITY_INSERT Clients OFF'
1059         res += table_to_sql(self.companies)
1060         res += '\n'
1061         res += self.participants_gen.to_sql()
1062
1063         self.clients = []
1064         self.companies = []
1065         return res

```

../Generator/ClientsGenerator.py

```

1000 class Company:
1001     def __init__(self, clients_id, faker, rand):
1002         self.faker = faker
1003         self.rand = rand
1004         self.clients_id = clients_id
1005
1006         self.name = self.faker.company()
1007         self.phone = self.faker.phone_number()
1008         self.email = self.faker.email()
1009         self.nip = self.random_nip()
1010
1012     def random_nip(self):
1013         res = ''
1014         sum = 0
1015         weights = [6, 5, 7, 2, 3, 4, 5, 6, 7]
1016         for i in range(8):
1017             k = self.rand.randint(1 if i < 3 else 0, 9)
1018             sum += weights[i] * k
1019             res += str(k)
1020         k = self.rand.randint(0, 9)
1021         if (sum + (k * weights[8])) % 11 == 10:
1022             k += (1 if k + 1 < 10 else -1)
1023         res += str(k)
1024         sum += k * weights[8]
1025         res += str(sum % 11)
1026         return res
1027
1028     def to_sql(self, start=True):
1029         values = "(" + self.name + ", " + self.nip + ", " + self.phone + ", " + str(
1030             self.clients_id) + ", " + self.email + ", " + self.faker
1031         return "INSERT INTO COMPANIES (companyName, nip, phone, clients_id, email) VALUES " +
1032         values if start else values

```

../Generator/Company.py

```

1000 from AbstractClass import *
1001
1002 class ConfDayReservation(AbstractClass):
1003     def __init__(self, res_id, clients_id, day, part_count, faker, rand):
1004         self.faker = faker
1005         self.rand = rand
1006
1007         self.res_id = res_id
1008         self.day_id = day.day_id

```



```

1010         self.clients_id = clients_id

1012         self.date = self.random_time(self.faker.date.between(start_date=datetime.today(),
end_date=day.date))
        self.active = 1 if self.rand.randint(1, 1000) % 8 == 0 else 0
1014         self.due_price = self.date + timedelta(weeks=self.rand.randint(1, 4))
        self.adult_seats = self.rand.randint(1, min(day.free_seats, part_count))
1016         self.student_seats = self.rand.randint(0, max(0, min(day.free_seats, part_count) -
self.adult_seats))

1018         self.workshops_price = 0
        self.day_price = day.price * self.adult_seats
1020         self.day_price += day.price * (1 - day.stud_disc) * self.student_seats
        esds = list(filter(lambda x: x.date > self.date.date(), day.esds))
1022         esds = sorted(esds, key=lambda x: x.date)
        esd = 0 if len(esds) == 0 else esds[0].discount
1024         self.day_price *= (1 - esd)

1026     def to_sql(self, start=True):
        values = "(" + str(
1028             self.res_id) + "," + str(self.day_id) + "," + str(self.clients_id) + "," + str(
self.date) + "\',\'" + str(
            self.active) + "\',\'" + str(self.due_price) + "\',\'" + str(self.adult_seats) + "," +
1030             str(
self.student_seats) + ")"
        return "INSERT INTO Conference_day_reservations (reservation_id, conference_day_id,
clients_id, reservation_date, active, due_price, adult_seats, student_seats) VALUES " +
values if start else values

```

../Generator/ConfDayReservation.py

```

1000 from random import Random
1001 from faker import Faker
1002 from ConfDayReservation import *

1004 class ConfDayResGenerator:
1006     def __init__(self, clients_gen, rand=Random(), faker=Faker(['pl-PL']), next_res_id=1):
        self.faker = faker
1008         self.rand = rand

1010         self.clients_gen = clients_gen
        self.next_res_id = next_res_id
1012         self.reservations = []

1014     def choice(self):
        return self.rand.choice(self.reservations)

1016     def res_count(self):
1018         return len(self.reservations)

1020     def to_sql(self):
        res = 'SET IDENTITY_INSERT Conference_day_reservations ON'
1022         res += '\n'
        res += self.reservations[0].to_sql()
1024         for v in range(1, len(self.reservations)):
            res += ','
1026             res += self.reservations[v].to_sql(False)
        res += '\nSET IDENTITY_INSERT Conference_day_reservations OFF'
1028         self.reservations = []
        return res

1030     def make(self, days):
1032         for day in days:
            n_res = self.rand.randint(2, self.clients_gen.clients_count() / 5)
1034             while day.free_seats > 0 and n_res > 0:
                n_res -= 1
1036                 self.reservations.append(
                    ConfDayReservation(self.next_res_id, self.clients_gen.choice().cl_id, day,
1038                                         len(self.clients_gen.participants_gen.participants),
self.faker, self.rand))
                self.next_res_id += 1
1040                 day.free_seats -= self.reservations[-1].adult_seats
                day.free_seats -= self.reservations[-1].student_seats

```

../Generator/ConfDayResGenerator.py

```

1000 from faker import Faker
1001 from random import Random
1002 from ConferenceDay import *
1003 from datetime import datetime, timedelta, time
1004 from AbstractGenerator import table_to_sql
1005
1006 class ConfDaysGenerator:
1007     def __init__(self, rand=Random(), faker=Faker(['pl_PL']), next_day_id=1):
1008         self.faker = faker
1009         self.rand = rand
1010
1011         self.next_day_id = next_day_id
1012         self.days = []
1013
1014     def make(self, conferences):
1015         for c in conferences:
1016             self.days.append(ConferenceDay(self.next_day_id, c.conf_id, self.faker, self.rand)
1017 )
1018             self.next_day_id += 1
1019             date = self.days[-1].date
1020             n = self.rand.randint(2, 4)
1021             for _ in range(n):
1022                 date += timedelta(days=1)
1023                 self.days.append(ConferenceDay(self.next_day_id, c.conf_id, self.faker, self.
1024 rand, date))
1025                 self.next_day_id += 1
1026
1027     def to_sql(self):
1028         res = 'SET IDENTITY_INSERT Conference_days ON'
1029         res += table_to_sql(self.days)
1030         res += '\nSET IDENTITY_INSERT Conference_days OFF'
1031         self.days = []
1032         return res

```

../Generator/ConfDaysGenerator.py

```

1000 class ConferenceDay:
1001     def __init__(self, day_id, conf_id, faker, rand, day=None):
1002         self.faker = faker
1003         self.rand = rand
1004
1005         self.day_id = day_id
1006         self.conf_id = conf_id
1007         self.price = round(self.rand.uniform(10.0, 1000.0), 2)
1008         self.stud_disc = round(self.rand.uniform(0.0, 0.5), 2)
1009         self.date = (self.faker.date_between(start_date='today', end_date='+5y')) if day is
1010 None else day
1011         self.numb_of_seats = self.rand.randint(150, 250)
1012         self.free_seats = self.numb_of_seats
1013         self.esds = []
1014
1015     def to_sql(self, start=True):
1016         values = "(" + str(self.day_id) + "," + str(self.conf_id) + ",\'" + str(self.date) + "
1017 \',\' + str(
1018         self.price) + "," + str(self.stud_disc) + ',\' + str(self.numb_of_seats) + ")"
1019         return "INSERT INTO Conference_days (conference_day_id, conference_id, date,
1020 standard_price, student_discount, number_of_seats) VALUES " + values if start else values

```

../Generator/ConferenceDay.py

```

1000 from faker import Faker
1001 from random import Random
1002 from Conference import *
1003 from AbstractGenerator import table_to_sql
1004
1005 class ConferenceGenerator:
1006     def __init__(self, rand=Random(), faker=Faker(['pl_PL']), next_conference_id=1):
1007         self.faker = faker
1008         self.rand = rand
1009
1010         self.next_conference_id = next_conference_id
1011         self.conferences = []

```

```

1014     def to_sql(self):
1015         res = 'SET IDENTITY_INSERT Conferences ON'
1016         res += table_to_sql(self.conferences)
1017         res += '\nSET IDENTITY_INSERT Conferences OFF'
1018         self.conferences = []
1019         return res
1020
1021     def make(self, n=1):
1022         for _ in range(n):
1023             self.conferences.append(Conference(self.next_conference_id, self.faker))
1024             self.next_conference_id += 1

```

../Generator/ConferenceGenerator.py

```

1000 class Conference:
1001     def __init__(self, conf_id, faker):
1002         self.faker = faker
1003
1004         self.conf_id = conf_id
1005         self.name = self.faker.bs()
1006         self.description = self.faker.text()
1007
1008     def to_sql(self, start=True):
1009         values = "(" + str(self.conf_id) + ",\'" + self.name + '\',\'" + self.description + "
1010         \'")"
1011         return "INSERT INTO Conferences (Conference_id, name, description) VALUES " + values
1012     if start else values

```

../Generator/Conference.py

```

1000 from ConfRegistration import *
1001 from AbstractGenerator import *
1002
1003 class ConfRegistrationGen:
1004     def __init__(self, rand, part_gen):
1005         self.rand = rand
1006
1007         self.part_gen = part_gen
1008         self.registrations = []
1009
1010     def to_sql(self):
1011         res = table_to_sql(self.registrations, False)
1012         self.registrations = []
1013         return res
1014
1015     def make(self, reservations):
1016         for res in reservations:
1017             if res.active == 0:
1018                 continue
1019             parts = set([p.part_id for p in self.part_gen.participants])
1020
1021             for _ in range(res.adult_seats):
1022                 p = self.rand.sample(parts, 1)
1023                 self.registrations.append(ConfRegistration(res.res_id, p[0], 1, self.rand))
1024                 parts.remove(p[0])
1025
1026             for _ in range(res.student_seats):
1027                 p = self.rand.sample(parts, 1)
1028                 self.registrations.append(ConfRegistration(res.res_id, p[0], 0, self.rand))
1029                 parts.remove(p[0])
1030

```

../Generator/ConfRegistrationGen.py

```

1000 class ConfRegistration:
1001     def __init__(self, res_id, participant_id, student, rand):
1002         self.rand = rand
1003
1004         self.res_id = res_id
1005         self.student = student
1006         self.participant_id = participant_id
1007
1008     def to_sql(self, start=True):
1009         values = "(" + str(self.res_id) + ", " + str(self.participant_id) + ", " + str(self.
1010         student) + ")"

```

```

1010         return "INSERT INTO Conference_day_registration (reservation_id , Participant_id ,
is_student) VALUES " + values if start else values

```

../Generator/ConfRegistration.py

```

1000 from random import Random
1001 from faker import Faker
1002 from Esd import *
1003 from AbstractGenerator import *
1004
1005 class EsdGenerator:
1006     def __init__(self, rand=Random(), faker=Faker(['pl-PL'])):
1007         self.faker = faker
1008         self.rand = rand
1009
1010         self.esds = []
1011
1012     def to_sql(self):
1013         res = table_to_sql(self.esds, False)
1014         self.esds = []
1015         return res
1016
1017     def make(self, days):
1018         for day in days:
1019             for _ in range(self.rand.randint(1, 5)):
1020                 e = Esd(self.faker, self.rand, day)
1021                 self.esds.append(e)
1022                 day.esds.append(e)

```

../Generator/EsdGenerator.py

```

1000 class Esd:
1001     def __init__(self, faker, rand, day):
1002         self.faker = faker
1003         self.rand = rand
1004
1005         self.day_id = day.day_id
1006         self.discount = round(self.rand.uniform(0.0, 0.5), 2)
1007         self.date = self.faker.date_between(start_date='-2y', end_date=day.date)
1008
1009     def to_sql(self, start=True):
1010         values = "(" + str(self.day_id) + ",\'" + str(self.date) + "\', " + str(self.discount)
1011         + ")"
1012         return "INSERT INTO Early_signup_discounts (conference_day_id, end_date, discount)
VALUES " + values if start else values

```

../Generator/Esd.py

```

1000 class Participant:
1001     def __init__(self, part_id, faker, client_id=None):
1002         self.part_id = part_id
1003         self.client_id = client_id
1004         self.faker = faker
1005
1006         n = self.faker.name().split(' ')
1007         if n[0] == 'pani' or n[0] == 'pan' or n[0] == 'Pan' or n[0] == 'Pani':
1008             n = n[1:]
1009         self.name = n[0]
1010         self.surname = ' '.join(n[1:])
1011         self.phone = self.faker.phone_number()
1012         self.email = self.faker.email()
1013
1014     def to_sql(self, start=True):
1015         values = "(" + str(self.part_id) + ", " + (str(
1016             self.client_id if self.client_id is not None else 'null') + ",\'" + self.name + "
\'',\'" + self.surname + "\',\'" + self.email + "\',\'" + self.phone + "\')")
1017         return "INSERT INTO Participants (participant_id, clients_id, name, surname, email,
phone) VALUES " + values if start else values

```

../Generator/Participant.py

```

1000 from faker import Faker
1001 from Participant import *
1002 from AbstractGenerator import table_to_sql

```

```

1004 class ParticipantsGenerator:
1006     def __init__(self, rand, faker=Faker(['pl.PL']), next_participant_id=1):
1008         self.faker = faker
1009         self.rand = rand
1010
1011         self.next_participant_id = next_participant_id
1012         self.participants = []
1013
1014     def choice(self):
1015         return self.rand.choice(self.participants)
1016
1017     def part_count(self):
1018         return len(self.participants)
1019
1020     def make(self, clients_id=None, n=1):
1021         for _ in range(n):
1022             res = Participant(self.next_participant_id, self.faker, clients_id)
1023             self.next_participant_id += 1
1024             self.participants.append(res)
1025
1026     def to_sql(self):
1027         res = 'SET IDENTITY_INSERT Participants ON'
1028         res += table_to_sql(self.participants)
1029         res += '\nSET IDENTITY_INSERT Participants OFF'
1030         self.participants = []
1031         return res

```

../Generator/ParticipantsGenerator.py

```

1000 from Payment import *
1001 from AbstractGenerator import *
1002
1003
1004 class PaymentGen:
1005     def __init__(self, rand, faker):
1006         self.rand = rand
1007         self.faker = faker
1008         self.payments = []
1009
1010     def make(self, reservations):
1011         for res in reservations:
1012             if res.active == 0 and self.rand.randint(1,1000) % 8 != 0:
1013                 continue
1014             price = res.workshops_price + res.day_price
1015             payed = int(price)
1016             if self.rand.randint(1, 1000) % 30 == 0: # nie oplacone
1017                 payed = 0 if self.rand.randint(0, 1000) % 2 == 0 else self.rand.randint(0, int
1018 (price))
1019             if payed == 0:
1020                 continue
1021             n_payments = self.rand.randint(1, 4)
1022             values = [payed // n_payments for _ in range(n_payments)]
1023             i = 0
1024             while sum(values) < payed:
1025                 values[i % n_payments] += 1
1026                 i += 1
1027             i = 0
1028             while i < n_payments:
1029                 p = self.rand.randint(0, values[i])
1030                 values[i] -= p
1031                 values[(i + 1) % n_payments] += p
1032                 i += 1
1033             values[-1] += round(price - int(price), 2)
1034             for value in values:
1035                 self.payments.append(Payment(value, res, self.faker, self.rand))
1036
1037     def to_sql(self):
1038         res = table_to_sql(self.payments, False)
1039         self.payments = []
1040         return res

```

../Generator/PaymentGen.py

```

1000 from AbstractClass import *

```

```

1002 class Payment(AbstractClass):
1004     def __init__(self, value, day_res, faker, rand):
1006         self.faker = faker
1007         self.rand = rand
1008
1009         self.res_id = day_res.res_id
1010         self.date = self.random_time(self.faker.date_between(start_date=day_res.date, end_date
1011 =day_res.due_price))
1012         self.value = value
1013
1014     def to_sql(self, start=True):
1015         values = "(" + str(self.res_id) + ",\'" + str(self.date) + "\'," + str(self.value) + "
1016 )"
1017         return "INSERT INTO Payments (reservation_id, in_date, value) VALUES " + values if
1018 start else values

```

../Generator/Payment.py

```

1000 from random import Random
1001 from faker import Faker
1002 from Workshop import *
1003 from AbstractGenerator import table_to_sql
1004
1005 class WorkshopGenerator:
1006     def __init__(self, part_gen, rand=Random(), faker=Faker(['pl_PL']), next_workshop_id=1):
1007         self.faker = faker
1008         self.rand = rand
1009
1010         self.part_gen = part_gen
1011         self.workshops = []
1012         self.next_workshop_id = next_workshop_id
1013
1014     def to_sql(self):
1015         res = 'SET IDENTITY_INSERT Workshops ON'
1016         res += table_to_sql(self.workshops)
1017         res += '\nSET IDENTITY_INSERT Workshops OFF'
1018         self.workshops = []
1019         return res
1020
1021     def make(self, days):
1022         for day in days:
1023             for _ in range(self.rand.randint(2, 6)):
1024                 self.workshops.append(
1025                     Workshop(self.next_workshop_id, day, self.part_gen.part_count(), self.
1026 faker, self.rand))
1027                 self.next_workshop_id += 1

```

../Generator/WorkshopGenerator.py

```

1000 from datetime import datetime, timedelta, time
1001
1002 class Workshop:
1003     def __init__(self, workshop_id, day, part_count, faker, rand):
1004         self.faker = faker
1005         self.rand = rand
1006
1007         self.workshop_id = workshop_id
1008         self.day_id = day.day_id
1009         self.price = round(self.rand.uniform(10.0, 1000.0), 2)
1010         self.start = self.random_time(day.date)
1011         self.end = self.random_time(day.date)
1012         if self.start > self.end:
1013             self.start, self.end = self.end, self.start
1014         self.topic = self.faker.bs()
1015         self.numb_seats = self.rand.randint(1, min(day.numb_of_seats, part_count))
1016         self.free_seats = self.numb_seats
1017
1018     def random_time(self, date):
1019         return datetime.combine(date, time(self.rand.randint(0, 23), self.rand.randint(0, 59))
1020 )
1021
1022     def to_sql(self, start=True):

```

```

        values = "(" + str(self.workshop_id) + "," + str(self.day_id) + ",\'" + str(self.start
    ) + "\',\'" + str(
1024         self.end) + "\',\'" + self.topic + "\',\'" + str(self.price) + "," + str(self.
        numb_seats) + ")"
        return "INSERT INTO Workshops (workshop_id, conference_day_id, start_time, end_time,
        topic, price, number_of_seats) VALUES " + values if start else values

```

../Generator/Workshop.py

```

1000 from WorkshopRegistration import *
1002 from AbstractGenerator import *

1004 class WorkshopRegistrationGen:
1006     def __init__(self, rand, part_gen):
1008         self.rand = rand
1010         self.part_gen = part_gen
1012         self.registrations = []

1014     def to_sql(self):
1016         res = table_to_sql(self.registrations, False)
1018         self.registrations = []
1020         return res

1022     def make(self, reservations):
1024         for res in reservations:
            if res.active == 0:
                continue
            parts = set([p.part_id for p in self.part_gen.participants])
            for _ in range(res.nr_seats):
                p = self.rand.sample(parts, 1)
                self.registrations.append(WorkshopRegistration(res.res_id, p[0]))
                parts.remove(p[0])

```

../Generator/WorkshopRegistrationGen.py

```

1000 class WorkshopRegistration:
1002     def __init__(self, res_id, participant_id):
1004         self.res_id = res_id
1006         self.participant_id = participant_id

1008     def to_sql(self, start=True):
1010         values = "(" + str(self.res_id) + "," + str(self.participant_id) + ")"
1012         return "INSERT INTO Workshop-registration (reservation_id, Participant_id) VALUES " +
1014         values if start else values

```

../Generator/WorkshopRegistration.py

```

1000 from random import Random
1002 from faker import Faker
1004 from WorkshopRes import *
1006 from AbstractGenerator import table_to_sql

1008 class WorkshopResGen:
1010     def __init__(self, conf_day_res_gen, rand=Random(), faker=Faker(['pl.PL']), next_res_id=1):
1012         self.faker = faker
1014         self.rand = rand

1016         self.conf_day_res_gen = conf_day_res_gen
1018         self.next_res_id = next_res_id
1020         self.reservations = []

1022     def to_sql(self):
1024         res = 'SET IDENTITY_INSERT Workshop-reservations ON'
        res += table_to_sql(self.reservations)
        res += '\nSET IDENTITY_INSERT Workshop-reservations OFF'
        self.reservations = []
        return res

    def make(self, workshops):
        for work in workshops:
            n_res = self.rand.randint(1, self.conf_day_res_gen.res_count() // 4)

```

```

1026         while work.free_seats > 0 and n_res > 0:
1027             n_res -= 1
1028             self.reservations.append(
1029                 WorkshopRes(self.next_res_id, work, self.conf_day_res_gen.choice(), self.
1030 faker, self.rand))
1031             self.next_res_id += 1
1032             work.free_seats -= self.reservations[-1].nr_seats

```

../Generator/WorkshopResGen.py

```

1000 from AbstractClass import *
1001
1002 class WorkshopRes(AbstractClass):
1003     def __init__(self, res_id, workshop, conf_res, faker, rand):
1004         self.faker = faker
1005         self.rand = rand
1006
1007         self.res_id = res_id
1008         self.work_id = workshop.workshop_id
1009         self.date = self.random_time(
1010             self.faker.date_between(start_date=datetime.today(), end_date=workshop.start.date
1011 ()))
1012         self.due_price = self.date + timedelta(weeks=self.rand.randint(1, 4))
1013         self.nr_seats = self.rand.randint(1, workshop.free_seats)
1014         self.conf_res_id = conf_res.res_id
1015         self.active = self.rand.randint(0, 1)
1016
1017         conf_res.workshops_price += self.nr_seats * workshop.price
1018
1019     def to_sql(self, start=True):
1020         values = "(" + str(
1021             self.res_id) + "," + str(self.work_id) + ",\'" + str(self.date) + "\',\'" + str(
1022             self.due_price) + "\',\'" + str(
1023             self.nr_seats) + ',\' + str(self.conf_res_id) + ',\' + str(self.active) + ")"
1024         return "INSERT INTO Workshop_reservations (reservation_id, workshop_id,
1025 reservation_date, due_price, nr_of_seats, Conference_day_res_id, active) VALUES " + values
1026         if start else values

```

../Generator/WorkshopRes.py