

ANIMAL SHELTER DATABASE

Mackenzie O'Brien


Table of Contents

Executive Summary.....	3
E-R Diagram.....	4
Types.....	5
Tables.....	6
Views.....	23
Reports.....	27
Stored Procedures.....	28
Triggers.....	31
Security/Roles.....	32
Implementation Notes.....	33
Known Problems/Future Enhancements.....	34

EXECUTIVE SUMMARY

- The Animal Shelter provides vaccinations for animals as well as a temporary home for them until they are adopted. They require a database to keep track of the animals and the adoptions, as well as the volunteers and shelter staff that have shifts at the shelter. This database must be accurate to ensure the safety of the animals and that the animals are not returned to the shelter, but instead end up in safe and happy homes.
- This is intended to be used by the Animal Shelter to keep track of animals, people, and adoption records. It will allow the agency to ensure all animals are cared for and keep track of adoption histories, as well as things done on a daily basis.
- Events that are kept track of are shifts of employees/volunteers, vaccinations, adoptions, and walks.

E-R Diagram



TYPES

- gen type- refers to gender type male or female
 - CREATE TYPE gen as ENUM('male','female');
- fixed type-refers to whether the animal was neutered or spayed
 - CREATE TYPE fixed as ENUM('yes','no');

ReasonFor

```
CREATE TABLE ReasonFor(  
    RFID int not null,  
    Reason text not null,  
    primary key(RFID)  
);
```

Functional Dependencies:
RFID → Reason

rfid integer	reason text
1	heartworm
2	mange
3	new animal
4	bladder in...
5	ticks
6	nail trim
7	neuter
8	euthaniza...

DogBreed

Lists all dog breeds that the shelter has encountered

```
CREATE TABLE DogBreed (
    DBID int not null,
    Name text not null,
    primary key (DBID)
);
```

Functional Dependencies:

DBID → Name

dbid integer	name text
1	mix
2	golden re...
3	pitbull
4	labrador r...
5	beagle
6	husky
7	german s...
8	rottweiler
9	bulldog
10	pug
11	chihuahua

TABLES

Animals

Lists all animals, both current and adopted

```
CREATE TABLE IF NOT EXISTS Animals(
  AID int not null,
  EstimatedAge int,
  Gender gender not null,
  Name text not null,
  Primary key (AID)
);
```

Functional Dependencies:

AID → Name, Gender, EstimatedAge

aid integer	estimate... integer	gender gender	name text
1	1	female	Fiona
2	3	male	Max
3	2	male	Fish
4	6	female	Carmel
5	8	male	Tank
6	3	female	Bella
7	3	female	Izzy
8	2	male	Rex
9	5	male	Buddy
10	4	female	Abby
11	10	male	Bubba
12	1	female	Gracie
13	1	male	Frank
14	7	female	Rosie

CatBreed

Lists all catBreeds that the shelter has encountered

```
CREATE TABLE CatBreed (  
    CBID int not null,  
    Name text not null,  
    primary key (CBID)  
);
```

Functional Dependencies:

CBID → Name

cbid integer	name text
1	mix
2	domestic ...
3	domestic ...
4	persian
5	maine coon
6	siamese
7	ragdoll
8	burmese

Birds

Is a subtype of Animals, lists all birds in the shelter or that have been in the shelter. Also lists the breed of the bird.

```
CREATE TABLE Birds(  
  AID int not null references Animals(AID),  
  Breed text not null,  
  Primary key (AID)  
);  
Functional Dependencies: AID→Breed
```

aid integer	breed text
19	canary
20	cockatiel
21	parakeet
22	grey parrot

Cats

Is a subtype of Animals, lists out all cats that have been through the shelter or are currently there.

```
CREATE TABLE Cats(  
  AID int not null references Animals(AID),  
  CBID int not null references CatBreed(CBID),  
  Neutered fixed not null,  
  Primary key(AID)  
);  
Functional Dependencies: AID→CBID, Neutered
```

aid integer	cbid integer	neutered fixed
10	4	yes
11	7	yes
12	1	no
13	2	yes
14	5	yes
15	6	yes
16	8	no
17	2	yes
18	3	yes

Dogs

This table is a subtype of Animals and lists out all dogs that have been in the shelter or currently are there.

```
CREATE TABLE Dogs(
    AID int not null references Animals(AID),
    DBID int not null references DogBreed(DBID),
    Fixed fixed not null,
    primary key (AID)
);
```

Functional Dependencies:

$AID \rightarrow DBID, Fixed$

aid integer	dbid integer	fixed fixed
1	1	yes
2	3	yes
3	2	yes
4	6	yes
5	8	no
6	10	yes
7	11	yes
8	9	no
9	7	yes

Other

List of Other Animals, specifies what kind of animal they are

```
CREATE TABLE Other(
    AID int not null references Animals (AID),
    Neutered fixed not null,
    AnimalType text not null,
    primary key (AID)
);
```

aid integer	neutered fixed	animaltype text
23	no	gerbil
24	no	rabbit
25	no	teacup pig

Functional Dependencies:

AID → Neutered, AnimalType,

VetVisit

Lists all visits to the vet for all animals and includes if they got vaccinations

```
CREATE TABLE VetVisit(
    RFID int ReasonFor(RFID),
    ApptDate date not null,
    AID int not null references Animals(AID),
    primary key (AID,ApptDate, RFID)
);
```

No functional dependencies

rfid integer	apptdate date	aid integer
1	2016-10-...	1
1	2016-10-...	2
1	2016-11-...	3
1	2016-11-...	4
1	2016-11-...	5
1	2016-11-...	6
1	2016-12-...	7
1	2016-12-...	8
1	2016-12-...	9
2	2016-10-...	4
3	2016-10-...	1
3	2016-10-...	2
3	2016-10-...	3
3	2016-11-...	4
3	2016-11-...	5

ZipCode- List of all zipcodes that have been used in the system

```
CREATE TABLE Zipcode(  
    Zip int not null,  
    City text not null,  
    State text not null,  
    primary key(Zip)  
);
```

zip integer	city text	state text
12601	Poughkee...	NY
10001	New York...	NY
18092	Zionsville	PA
10597	Katonah	NY
11798	Wheely H...	NY
18094	Macungie	PA

Functional Dependencies:

Zip \rightarrow City, State

People- List of all people in the system

```
CREATE TABLE People(
    PID int not null,
    Zip int not null references ZipCode(Zip),
    FirstName text not null,
    LastName text not null,
    StreetAddress text not null,
    DOB date not null,
    email text not null,
    phoneNum text not null,
    primary key (PID)
);
```

Functional Dependencies:

PID → Zip, FirstName, LastName, StreetAddress, DOB, email, phoneNum

pid integer	zip integer	firstname text	lastname text	streetadd... text	dob text	email text	phonenumber text
1	12601	Mackenzie	O'Brien	3399 Nort...	11/17/19...	m@gmail....	6108230...
2	10001	Tien	LongName	1234 Chi...	12/23/19...	minion@l...	1234567...
3	18092	Rachel	Choi	4359 Joh...	6/9/1997	rachelchoi...	6108495...
4	10597	Blaise	Spinelli	6591 Che...	4/1/1993	blaisesp@...	4843925...
5	11798	Mark	Rajovic	100 Penn...	3/3/1994	mark@m...	1234567...
6	18094	Katie	Bartolotta	5 First Ave	9/30/1960	katieb@a...	5456567...
7	11798	Marcus	Zimmerm...	1 Second ...	4/5/1996	maZ@gm...	3455434...
8	18094	G	Leaden	2 Second ...	3/3/1993	gLeaden...	2223334...
9	10001	Lauren	Waide	5423 Sch...	2/20/1997	lwaide@y...	9876543...
10	12601	Nicole	Deserpa	57489 Ap...	10/28/19...	nikkid@a...	6667879...
11	10597	Stephanie	Stone	9 Pie lane	12/1/1995	stephston...	5498275...
12	10001	Tadd	Bindas	8 Red Fox...	8/4/1996	taddyb@y...	7894032...
13	12601	Rachel	Danko	543 Maris...	9/4/1995	rdanko@...	4848957...
14	10597	Ravmond	Mattinalv	4897 Mcc...	11/4/1993	rmattinal...	5659832...

Staff

```
CREATE TABLE Staff(
    PID int not null references People(PID),
    Title text not null,
    DateStarted date not null,
    primary key(PID)
);
```

Functional Dependencies:

PID → Title, DateStarted

pid integer	title text	datestart.. text
1	founder	10/5/2016
2	head of a...	10/5/2016
3	head of v...	10/5/2016
4	vet	10/5/2016
5	secretary	11/5/2016
6	dog trainer	11/11/20...
7	secretary	12/5/2016
8	Social Me...	1/10/2017

Adopters

```
CREATE TABLE Adopters(  
  PID int not null references People(PID),  
  primary key(PID)  
);
```

Functional Dependencies: None

pid integer
13
14
15
16
17
18
19
20

Adoptions

```
CREATE TABLE Adoptions(
    PID int not null references Adopters(PID),
    AID int not null references Animals(AID),
    Date date not null,
    primary key(PID, AID)
);
```

Functional Dependencies: PID, AID → Date

pid integer	aid integer	date text
13	1	10/20/20...
14	5	10/25/20...
15	7	10/30/20...
16	9	11/6/2016
17	11	11/6/2016
18	13	11/15/20...
19	4	11/20/20...
20	18	12/6/2016
13	23	12/23/20...
15	20	12/24/20...
18	3	12/28/20...

Volunteers

```
CREATE TABLE Volunteers(  
    PID int not null references People(PID),  
    DateStarted date not null,  
    primary key (PID)  
);
```

Functional Dependencies: PID → DateStarted

pid integer	datestart.. text
9	10/20/20...
10	11/5/2016
11	12/20/20...
12	11/5/2016

Shifts

```
CREATE TABLE Shifts(
    SID int not null,
    PID int not null references People(PID),
    TimeIn time not null,
    TimeOut time not null,
    Date date not null,
    primary key(SID)
);
```

Functional Dependencies:
SID, PID → TimeIn, TimeOut, Date

sid integer	pid integer	timeIn text	timeOut text	date text
1	1	8:00	17:00	10/5/2016
2	3	8:00	16:00	11/6/2016
3	2	8:00	18:00	10/25/20...
4	4	12:00	20:00	10/10/20...
5	1	5:00	14:00	11/15/20...
6	2	10:00	18:00	10/20/20...
7	3	9:00	15:00	10/30/20...
8	1	12:00	21:00	10/30/20...
9	5	10:00	14:00	11/6/2016
10	6	9:00	15:00	11/15/20...
11	5	11:00	16:00	11/20/20...
12	7	9:00	14:00	12/6/2016
13	8	8:00	14:00	1/12/2017
14	9	9:00	16:00	10/25/20...

Walks

```

CREATE TABLE Walks(
    PID int not null references Volunteers(PID),
    AID int not null references Dogs(AID),
    Time time not null,
    Date date not null,
    primary key(PID,AID)
);
    
```

Functional Dependencies: PID,AID→ Time, Date

pid integer	aid integer	time text	date text
9	1	9:00	10/26/20...
10	2	10:00	10/30/20...
10	3	11:00	11/5/2016
11	4	9:00	11/5/2016
12	5	11:00	11/11/20...
10	3	10:00	11/12/20...
12	7	17:00	11/21/20...
9	9	16:00	11/22/20...
10	8	15:00	12/5/2016
12	2	16:00	12/12/20...
11	3	14:00	12/28/20...
12	6	13:00	1/5/2017

VIEWS

currentAvailable- Selects the animals that are currently available for adoption at the shelter

```
DROP VIEW IF EXISTS currentAvailable;
```

```
CREATE VIEW currentAvailable as
```

```
    select name, animals.aid
```

```
    from animals
```

```
    where animals.aid not in(select animals.AID
```

```
                            from Animals
```

```
                            inner join Adoptions on Animals.AID=Adoptions.AID
```

```
                            ) and EstimatedAge is not null
```

```
ORDER BY Animals.AID ASC;
```

Screen shot of CurrentAvailable results

name text	aid integer
Max	2
Bella	6
Rex	8
Abby	10
Gracie	12
Rosie	14
Fido	15
Roxy	16
Teddy	17
Charlie	19
Lucy	21
Jake	22
Lola	24
Lucky	25

VIEWS

MostWalks- Selects the names of the volunteers with the most number of walks-used for a rewards program

```
DROP VIEW IF EXISTS mostWalks;
```

```
CREATE VIEW mostWalks as
```

```
    select FirstName , count(FirstName) as numWalks  
    from People
```

```
        inner join Volunteers on People.PID=Volunteers.PID
```

```
        inner join Walks on People.PID=Walks.PID
```

```
group by FirstName
```

```
ORDER BY count(FirstName) DESC
```

```
LIMIT 2;
```

Screenshot from
MostWalks query

firstname text	numwalks bigint
Tadd	4
Nicole	4

REPORTS

Select all adoption records and pull up the names of all parties involved
 select distinct people.firstName as Owner_FirstName,
 people.LastName as Owner_LastName,
 animals.Name as PetName, animals.EstimatedAge, adoptions.date
 from adoptions
 inner join people on people.pid=adoptions.pid
 inner join animals on adoptions.aid=animals.aid

owner_fir... text	owner_la... text	petname text	estimate... integer	date text
Sam	Klamar	Frank	1	11/15/20...
Molly	Smith	Izzy	3	10/30/20...
Carlos	Moreno	Bubba	10	11/6/2016
Lidia	Bayus	Buddy	5	11/6/2016
Molly	Smith	Molly	1	12/24/20...
Raymond	Mattingly	Tank	8	10/25/20...
Alan	Labouseur	Carmel	6	11/20/20...
Taylor	OBrien	Daisy	3	12/6/2016
Rachel	Danko	Sadie	3	12/23/20...
Rachel	Danko	Fiona	1	10/20/20...
Sam	Klamar	Fish	2	12/28/20...

STORED PROCEDURES

Sets the animals age to null if the Animal is put down by the vet (will not appear in available to adopt query anymore) See trigger for results

```
CREATE OR REPLACE FUNCTION euthanized()  
RETURNS TRIGGER AS  
$$  
BEGIN  
    UPDATE Animals  
    SET estimatedAge=null  
    where NEW.RFID=8 and NEW.aid=Animals.aid;  
    RETURN NEW;  
END;  
$$  
language plpgsql;
```

```

CREATE OR REPLACE FUNCTION oldEnough(VolunteerID int)
RETURNS INTERVAL AS
$$
DECLARE
birthday date := (SELECT people.dob
                    from people
                    inner join volunteers on people.pid=volunteers.pid
                    where volunteers.pid=VolunteerID
                    );
BEGIN
    RETURN age(birthday);
END;
$$
language plpgsql

```

```
select oldEnough(9)
```

oldenough interval
20 years 2 mons 9 days


```
select calculateTotalHours('2016-11-6','results');
fetch all from results;
```

```
CREATE OR REPLACE FUNCTION
  calculateTotalHours(date, refcursor)
RETURNS refcursor as
```

```
$$
```

```
DECLARE
```

```
    dayOf date := $1;
```

```
    resultset refcursor:= $2;
```

```
BEGIN
```

```
open resultset for
```

```
    select shifts.pid, sum(timeout-timein) as TotalHours, timein, timeout , people.firstName
```

```
    from shifts
```

```
inner join people on shifts.pid=people.pid
```

```
where shifts.date=dayOf
```

```
group by shifts.pid, people.firstName, timein, timeout
```

```
order by pid ASC;
```

```
return resultset;
```

```
END;$$language plpgsql;
```

pid integer	totalhours interval	timein time with...	timeout time with...	firstname text
3	08:00:00	08:00:00	16:00:00	Rachel
5	04:00:00	10:00:00	14:00:00	Mark
9	10:00:00	11:00:00	21:00:00	Lauren

TRIGGERS

```
CREATE TRIGGER euthanize references Stored Procedure Euthanized
AFTER INSERT ON VetVisit
FOR EACH ROW
EXECUTE PROCEDURE euthanized();
```

before

aid integer	estimate... integer	gender gender	name text
4	6	female	Carmel
5	8	male	Tank
6	3	female	Bella
7	3	female	Izzy
8	2	male	Rex
9	5	male	Buddy
10	4	female	Abby
11	10	male	Bubba
12	1	female	Gracie
13	1	male	Frank
14	7	female	Rosie

after

aid integer	estimate... integer	gender gender	name text
7	3	female	Izzy
8	2	male	Rex
9	5	male	Buddy
10		female	Abby
11	10	male	Bubba
12	1	female	Gracie
13	1	male	Frank
14	7	female	Rosie
15	1	male	Fido

ROLES

- Admin: It is the admin's job to maintain the database, so they have full access
create role admin;
grant all on all tables in schema public to admin;
- Staff: It is the staff's job to update the tables as needed
create role staff;
grant all on all tables in schema public to admin;
- Volunteer: It is the volunteers job to enter their information, as well as info for walks and adoptions
create role volunteer;
revoke all on all tables in schema public from volunteer;
grant select on all tables in schema public to volunteer;
grant insert on Volunteers, People, Shifts, Walks, Adoptions, Dogs, Cats to volunteer;
grant update on Volunteers, People, Shifts, Walks, Adoptions, Dogs, Cats to volunteer;
- Vet: It is the vet's role to take care of all the animals and to update the ReasonsFor table as needed
create role vet;
revoke all on all tables in schema public from vet;
grant select on Animals, ReasonFor, Shifts, People to vet;
grant update on ReasonFor, Shifts, People to vet;
grant delete on ReasonFor to vet;
grant insert on ReasonFor to vet;

IMPLEMENTATION NOTES

When making this database, the Shelter had no data from an old system, as the shelter is a new business and thus had no records to save. Therefore, the only data in the system now is the animals that have arrived since the shelter opened.

Due to the need for record-keeping, any animals that have been put down the estimatedAges are changed to null in order to keep them in the system but not available for adoption.

In order to volunteer to walk the dogs, the volunteer must be 18, which is where the oldEnough() function comes in, as children can still be a volunteer and do other tasks at the shelter.

As an incentive to get more volunteers, the shelter implemented a program that whoever walks the most dogs gets a prize whenever the shelter decides, thus creating the need for the MostWalks function.

To check if payroll/hours are correct, the calculateTotalHours() was created.

KNOWN PROBLEMS/FUTURE ENHANCEMENTS

- Other tables, such as EuthanizedAnimals and returnedAnimals could be added to the database, as sometimes adoptions do not work out or are 'unadoptable'. Other attributes such as height and weight could be added to animal tables
- Adding fostered/fosterer tables would be a good idea, as fostering helps animals adapt to a home environment and gives them extra love and attention that they may need, especially if they react badly to being in the shelter environment.
- There is no way currently to check if the volunteers walking the dogs are actually 18 or are just volunteers in general when entered into the walks table.
- Adopters should also be 18+, but nothing has been implemented to check that.
- There should be a way to add a dog/cat breed if it is not currently in the system when a dog/cat is entered into the system