

Simulation-Reality Comparison Module (SRCM) defines the governance

OOF™ Origin Open Foundation™

Independent Methodological Authority

Architecture Ecosystem: Structured Reality Standards™

Architecture Family: SIMULOS® — Simulation Governance Architecture

Parent Standard: Simulation-to-Reality Correlation Standard (SRCS)

Operational Layer: Simulation-to-Reality Correlation Layer

Category: Governance & Enforcement

Subcategory: Simulation Governance

Type: Parent Standard Module

Governed Space: Simulation-Reality Comparison

Version: 1.0

Status: Canonical · Open Module

Effective Date: 19 August 2026

Compatibility: OOF® Methodology OS™ · GOA™ · ORA™ · VALIDOS® · INTEGROS® · ADIT® · AGA™ · AIG® · ASGA™ · RIS™

AI-Readable: Yes

Authority: OOF®

Protection: MIP® — Methodological Intellectual Property

Canonical Language: English (UCL™)

Governed Space

Simulation-Reality Comparison

Canonical Definition

Simulation-Reality Comparison Module (SRCM) defines the governance conditions under which simulated conditions, states, behaviors, events, relationships, trajectories, and outputs are systematically compared with corresponding observations from Operational Reality so that similarities, differences, missing correspondence, and unavailable comparison evidence remain explicitly identifiable and traceable.

SRCM establishes the first governed comparison layer between:

what occurred in simulation

and:

what occurred in reality.

It does not assume that similarity establishes equivalence, nor does it determine whether the observed level of correlation is sufficient for a

particular reliance or validation purpose.

Operational Role

SRCM serves as the first internal governance space of the Simulation-to-Reality Correlation Standard (SRCS).

The module asks:

What exactly can be compared between the simulation and Operational Reality, and what does that comparison actually show?

The governed progression begins:

Simulation Evidence + Operational Reality Evidence → Comparison Basis → Correspondence Mapping → Difference Identification → Comparison Record

The resulting comparison basis becomes an input to:

SCCM — Simulation Correlation Criteria Module.

Module Operational Space

SRCM governs: simulation-reality comparison objects, comparison purpose, comparison scope, simulation-side evidence, reality-side evidence, comparable variables, comparable states, comparable behaviors, comparable events, comparable trajectories, comparable conditions, comparable outputs, temporal alignment, spatial alignment, state alignment, unit alignment, resolution alignment, abstraction alignment, correspondence mapping, comparison windows, baseline comparison, event comparison, behavioral comparison, trajectory comparison, distributional comparison, sequence comparison, comparison gaps, unavailable reality evidence, unavailable simulation evidence, incomparable elements, observed similarity, observed difference, and complete comparison traceability.

Module Function

SRCM prevents organizations from moving directly from:

“the simulation looks realistic”

to:

“the simulation represents reality.”

Its function is to create an explicit comparison basis before correlation strength, deviations, alignment, or uncertainty are evaluated.

The module separates:

Simulation Evidence

from:

Operational Reality Evidence

and then establishes which elements can legitimately be compared.

Simulation-Reality Comparison Object

Every governed comparison should identify the exact phenomenon being compared.

A Comparison Object may include: system behavior, autonomous decision, physical trajectory, sensor response, thermal behavior, structural response, failure sequence, communication behavior, resource consumption, human-system interaction, environmental response, recovery behavior, or another materially relevant phenomenon.

Comparison Pair

SRCM establishes a basic relationship:

Simulation Observation

↑

Corresponding Reality Observation

A comparison is meaningful only where the relationship between the two sides is sufficiently defined.

Comparison Identity

A materially relevant comparison should be distinguishable through a stable Comparison ID or equivalent mechanism.

Conceptually:

Comparison ID

↓

Simulation Execution

↓

Simulation Observation / Output

↓

Reality Observation

↓

Comparison Object

↓

Comparison Conditions

↓

Comparison Result

This preserves the provenance of the comparison.

Comparison Purpose

Before comparison, the organization should establish why the comparison is being performed.

Examples include: behavioral correspondence, model calibration support, mission reconstruction, failure investigation, autonomous-system assessment, performance comparison, environmental correspondence, or post-deployment simulation review.

Different purposes may require different comparison depth.

Comparison Scope

SRCM requires the comparison boundary to remain explicit.

The comparison may concern:

Entire System

Subsystem

Specific Behavior

Specific Scenario

Specific Operating Region

Specific Failure Mode

Specific Time Window

or another bounded domain.

No Whole-Simulation Inference from Partial Comparison

SIMULOS® establishes:

Correlation observed within one bounded comparison region must not automatically be represented as correlation across the entire simulation.

A simulation may correspond strongly to reality in one region and poorly in

another.

Simulation-Side Basis

The simulation side of the comparison should remain connected to the governed execution that produced it.

Where material, this may include: Simulation Execution ID, model version, environment version, scenario, inputs, parameters, assumptions, runtime conditions, observations, and Simulation Outputs.

Reality-Side Basis

The reality side should identify the Operational Reality evidence against which simulation is compared.

This may include: physical measurements, sensor records, operational telemetry, observed system behavior, incident records, mission data, environmental observations, human observations, field-test results, production-system records, or another sufficiently identifiable reality source.

ORA™ Relationship

ORA™ governs Operational Reality itself.

SRCM does not redefine Operational Reality.

SRCM consumes or references sufficiently governed reality observations and governs the comparison relationship between those observations and the simulation.

Therefore:

ORA™ → Operational Reality

SIMULOS® SRCM → Simulation ↔ Reality Comparison Comparison Correspondence Mapping

Before numerical or qualitative comparison occurs, SRCM should establish which simulation element corresponds to which reality element.

Conceptually:

Simulation Variable A ↔ Reality Variable A

Simulation Event B ↔ Reality Event B

Simulation State C ↔ Reality State C

Simulation Trajectory D ↔ Reality Trajectory D

This prevents comparison between superficially similar but materially different phenomena.

Semantic Correspondence

Two variables carrying similar names may not represent the same underlying phenomenon.

SRCM therefore distinguishes:

Label Similarity

from:

Semantic Correspondence.

Unit Alignment

Where quantitative comparison is performed, units must be sufficiently aligned.

For example:

meters ↔ meters

seconds ↔ seconds

degrees Celsius ↔ degrees Celsius

or converted through an explicit transformation.

Temporal Alignment

Simulation time and Operational Reality time may not correspond directly.

SRCM may require alignment of: timestamps, event sequence, elapsed time, phase, cycle, mission stage, or relative temporal position.

Temporal Distortion

A simulation may reproduce the correct event sequence but at materially different timing.

That difference should remain visible.

For example:

Simulation failure occurs after 120 seconds

while:

Operational failure occurs after 37 seconds.

The presence of the same failure does not establish temporal correspondence.

Spatial Alignment

Physical and spatial simulations may require alignment of: position, coordinate system, orientation, altitude, distance, geometry, or reference frame.

Resolution Alignment

Reality observations and simulation observations may exist at different resolutions.

For example:

Simulation sampling: 1 millisecond

Reality telemetry: 1 second

A direct point-by-point comparison may therefore be misleading.

SRCM requires resolution differences to remain explicit.

Abstraction Alignment

Simulation may represent reality at a higher abstraction level.

For example:

Operational Reality may contain:

hundreds of interacting physical components

while simulation represents them as:

one aggregated subsystem.

SRCM does not prohibit this abstraction.

It requires the comparison to recognize it.

Condition Alignment

Simulation and reality should not be treated as directly comparable merely because they concern the same system.

Relevant conditions may include: environment, load, temperature, velocity, system configuration, software version, hardware version, autonomy state, population, external actors, weather, communication state, or mission phase.

Comparable Condition Set

SRCM may establish a:

Comparable Condition Set

representing the conditions sufficiently aligned for comparison.

Condition Mismatch

Where material conditions differ, the comparison should preserve the mismatch.

A condition mismatch does not necessarily make comparison useless.

It limits what may legitimately be inferred from it.

Behavioral Comparison

SRCM may compare how a simulated system behaves relative to the real system.

Examples include: decision sequence, control response, navigation behavior, obstacle avoidance, recovery behavior, failure response, resource allocation, or human interaction.

Event Comparison

Events may be compared according to:

Occurrence

Non-Occurrence

Timing

Order

Frequency

Duration

Magnitude

and:

Context.

Trajectory Comparison

Trajectory comparison may apply to: spacecraft, aircraft, robots, vehicles, physical processes, economic states, system states, or other evolving phenomena.

A trajectory should not be reduced to final-state similarity where the path itself is materially relevant.

Sequence Comparison

Some simulations must reproduce not merely events but their ordering.

For example:

Sensor degradation → Navigation error → Recovery attempt → Safe-state transition

may differ materially from:

Navigation error → Sensor degradation → System shutdown.

Even if both end in a safe state, the underlying behavior is different.

Distributional Comparison

For stochastic systems, individual-run comparison may be insufficient.

SRCM may compare:

Simulation Distribution

with:

Observed Reality Distribution.

This can include: frequency, variance, tails, rare events, failure rates, response ranges, or other statistical characteristics.

Population Comparison

Where simulation represents populations, SRCM may govern comparison across: demographic groups, system fleets, agent populations, operating environments, geographic regions, or other relevant populations.

Baseline Comparison

A baseline may be established to determine whether later simulation versions move:

closer to

or:

further from

observed reality.

Observed Similarity

SRCM may record areas where simulation and reality correspond.

However:

Observed Similarity is an observation, not a declaration of reality equivalence.

Observed Difference

Differences should be preserved even where overall correspondence appears strong.

Differences may concern: magnitude, timing, sequence, frequency, direction, state, behavior, distribution, or occurrence.

No Selective Similarity Principle

SIMULOS® establishes:

A Simulation-Reality Comparison must not preserve only the dimensions in which simulation performs well while silently excluding materially relevant dimensions in which correspondence is weak.

Comparison Gap

A Comparison Gap exists where a materially relevant simulation phenomenon cannot currently be compared with Operational Reality.

Reasons may include: reality has not yet occurred, measurement is unavailable, telemetry is missing, the phenomenon cannot be safely tested, reality evidence is inaccessible, the simulation contains an abstract construct with no direct physical equivalent, or the comparison method is insufficient.

No Reality Evidence ≠ Simulation Confirmation

A foundational SRCM rule is:

The absence of contradictory reality evidence does not establish that the simulation corresponds to reality.

Where Operational Reality evidence does not exist, the comparison status should remain appropriately bounded.

Comparison Availability States

SRCM may classify comparison availability as:

Directly Comparable

Conditionally Comparable

Partially Comparable

Indirectly Comparable

Not Currently Comparable

or:

Comparability Undetermined.

Incomparable Elements

Some simulation elements may legitimately have no direct reality counterpart.

These should remain identifiable rather than being forced into artificial comparison.

Comparison Evidence Quality

SRCM does not own general validation of evidence quality.

However, it should preserve whether the comparison basis depends upon: incomplete measurements, sparse observations, uncertain telemetry, transformed data, indirect observations, or another material limitation.

These limitations propagate downstream.

Point-in-Time Comparison

SRCM may support reconstruction of questions such as:

Which simulation version was compared?

Which real system version was observed?

Which scenario was used?

Which operational conditions existed?

Which variables were compared?

Which variables were unavailable?

Which transformations were applied?

Which differences were observed?

Comparison Matrix

A practical SRCM implementation may establish a Simulation-Reality Comparison Matrix.

Example structure:

Phenomenon → Simulation Representation → Reality Observation → Alignment
Conditions → Comparison Availability → Observed Relationship → Limitation

This creates a structured basis for downstream correlation assessment.

Space and Mission Simulation

For space missions, direct Operational Reality evidence may be expensive, sparse, delayed, or available only after deployment.

SRCM can compare: simulated trajectories with mission trajectories, predicted thermal states with flight telemetry, simulated communication loss with actual communication behavior, simulated navigation uncertainty with observed navigation error, simulated subsystem failures with mission anomalies, and simulated autonomous recovery with actual recovery behavior.

This allows every mission to become a potential source of evidence for improving the simulation-reality relationship.

Autonomous Systems

For autonomous systems, comparison may extend beyond final performance.

SRCM can compare: decisions, action sequences, recovery paths, timing, interaction patterns, environmental responses, failure behavior, and emergent system behavior.

This matters because two systems may achieve the same final outcome through materially different behavioral paths.

Digital Twins

A digital twin may appear visually or numerically close to its physical counterpart while diverging in specific operational regions.

SRCM provides a structured basis for comparing:

Digital Representation

against:

Physical Operational Reality

without presuming that the existence of the digital twin establishes correspondence.

Comparison at Scale

Organizations may possess millions of simulation runs but only limited Operational Reality observations.

SRCM allows reality evidence to be mapped against relevant subsets of the simulation population rather than treating the complete simulation corpus as equally correlated.

Reality Evidence Accumulation

Simulation-to-Reality Comparison may improve over time as Operational Reality produces additional evidence.

The comparison relationship is therefore potentially dynamic.

A previously:

Not Currently Comparable

simulation phenomenon may later become:

Directly Comparable

when operational evidence becomes available.

Historical Comparison Preservation

New Operational Reality evidence should not erase earlier comparison states.

Historical comparison records may reveal whether simulation correspondence is: improving, degrading, stable, condition-dependent, or previously misunderstood.

Comparison Does Not Equal Correlation Determination

SRCM establishes the comparison basis.

It does not determine:

how much similarity is sufficient.

That question moves to:

SCCM — Simulation Correlation Criteria Module.

Comparison Does Not Equal Deviation Governance

SRCM identifies observed differences.

Detailed governance of material simulation-reality deviations belongs to:

SDMM — Simulation-Reality Deviation Module.

Comparison Does Not Equal Reality Alignment

SRCM identifies correspondence and difference.

Governance of how the simulation may be brought into better alignment with reality belongs to:

SRAM — Reality Alignment Module.

Comparison Does Not Resolve Correlation Uncertainty

Uncertainty surrounding the simulation-reality relationship belongs to:

SCUM — Correlation Uncertainty Module.

Internal SRCS Flow

SRCM — Simulation-Reality Comparison

↓

SCCM — Simulation Correlation Criteria

↓

SDMM — Simulation-Reality Deviation

↓

SRAM — Reality Alignment

↓

SCUM — Correlation Uncertainty

SRCM therefore creates the empirical comparison foundation upon which the remainder of SRCS operates.

Minimum Implementation Framework

1. Define the Comparison Object

Identify exactly which simulated and real phenomenon is being compared. 2. Establish Comparison Purpose

Define why the comparison is required. 3.

Establish Comparison Scope

Identify included and excluded regions, conditions, variables, behaviors, and time periods. 4. Bind Simulation Evidence

Connect the comparison to the applicable Simulation Execution and outputs. 5. Bind Operational Reality Evidence

Identify the corresponding real-world observations. 6. Establish Correspondence Mapping

Map simulation variables, states, events, behaviors, and outputs to their reality counterparts. 7. Align Comparison Conditions

Assess temporal, spatial, unit, resolution, abstraction, state, and environmental alignment. 8. Perform the Comparison

Compare the materially relevant phenomena. 9. Preserve Similarities and Differences

Do not selectively retain favorable correspondence. 10. Identify Comparison Gaps

Record unavailable, incomplete, indirect, or incomparable elements. 11. Establish Comparison Availability Status

Classify the degree to which meaningful comparison is currently possible. 12. Produce the Simulation-Reality Comparison Record

Create the governed comparison basis for downstream correlation criteria and deviation governance.

Governance Outputs

SRCM may produce: Simulation-Reality Comparison ID, Comparison Object Record, Comparison Purpose Record, Comparison Scope Record, Simulation Evidence Binding, Operational Reality Evidence Binding, Correspondence Map, Comparable Variable Set, Comparable State Set, Comparable Event Set, Comparable Behavior Set, Comparable Condition Set, Temporal Alignment Record, Spatial Alignment Record, Unit Alignment Record, Resolution Alignment Record, Abstraction Alignment Record, Condition Mismatch Record, Behavioral Comparison Record, Event Comparison Record, Trajectory Comparison Record, Sequence Comparison Record, Distributional Comparison Record, Population Comparison Record, Observed Similarity Record, Observed Difference Record, Comparison Gap Record, Incomparable Element Record, Comparison Availability Status, Simulation-Reality Comparison Matrix, and Governed Simulation-Reality Comparison Record.

Use Case 1 — Spacecraft Mission Simulation vs Flight Reality

A space agency executes extensive pre-mission simulations covering trajectory, thermal behavior, navigation, communication, subsystem failure, and autonomous recovery.

After launch, SRCM maps actual mission telemetry against the corresponding simulation conditions.

The comparison reveals that trajectory and thermal behavior correspond closely within tested regions, while communication degradation begins materially earlier in Operational Reality than in simulation.

SRCM does not declare the simulation valid or invalid.

It establishes exactly:

where correspondence exists, where difference exists, under which conditions, and where reality evidence remains insufficient.

The resulting comparison record provides the basis for correlation criteria, deviation analysis, and future reality alignment. Use Case 2 — Autonomous Robot Simulation vs Deployment Behavior

An autonomous mobile robot performs reliably across millions of simulated

warehouse scenarios.

After deployment, operational records show that its obstacle-avoidance behavior differs when reflective surfaces, human movement, and temporary sensor degradation occur simultaneously.

SRCM compares the relevant simulated behaviors with the corresponding Operational Reality observations across: decision sequence, sensor state, response timing, trajectory, recovery behavior, and environmental conditions.

The organization can then distinguish between simulation regions that correspond strongly to deployment reality and regions where the simulation-reality relationship remains weak or insufficiently observed.

Architectural Position

SRCM is the first module of the Simulation-to-Reality Correlation Standard (SRCS).

It transforms:

Simulation Evidence + Operational Reality Evidence

into:

Governed Simulation-Reality Comparison Record.

That record becomes the foundation for determining correlation criteria, identifying deviations, governing reality alignment, and expressing correlation uncertainty.

Foundational Principle

Simulation similarity is not reality equivalence.

Canonical Closing Statement

Simulation-Reality Comparison Module establishes the governed empirical bridge between simulation and Operational Reality by identifying what can legitimately be compared, binding simulation evidence to corresponding reality observations, aligning materially relevant conditions, preserving both similarities and differences, exposing comparison gaps, and maintaining complete comparison traceability. SRCM prevents visual similarity, isolated matching outcomes, or the absence of contradictory evidence from being transformed into unsupported claims of reality correspondence. By establishing a structured Simulation-Reality Comparison Record before correlation is judged, deviation is interpreted, alignment is attempted, or uncertainty is bounded, SRCM provides the foundational comparison layer through which SIMULOS® can determine what simulation actually demonstrates about the reality it claims to represent.

OOF® MIP® Protection Notice

OOF® · Protected under MIP® — Methodological Intellectual Property

Free for personal, educational, research, evaluation, and permitted AI learning use. Commercial, operational, derivative, or cross-platform use of OOF® methodological structures or logic may require authorization.

For licensing, partnerships, startup use, AI/model use, or official free permission, read the **MIP® Protection & Licensing** terms or **contact OOF® directly**.

Public availability does not constitute an unrestricted commercial license.

Active Protection & Compatibility Detection applies.

Canonical Source

<https://originopenfoundation.org/>